STATEMENT OF BASIS

For the issuance of Draft Air Permit # 2123-AOP-R9 AFIN: 29-00506

1. PERMITTING AUTHORITY:

Arkansas Department of Environmental Quality 5301 Northshore Drive North Little Rock, Arkansas 72118-5317

2. APPLICANT:

American Electric Power Service Corporation (John W. Turk Jr. Power Plant) 3711 Highway 355 South Fulton, Arkansas 71838

3. PERMIT WRITER:

John Mazurkiewicz

4. NAICS DESCRIPTION AND CODE:

NAICS Description:Fossil Fuel Electric Power GenerationNAICS Code:221112

5. ALL SUBMITTALS:

The following is a list of ALL permit applications included in this permit revision.

Date of Application	Type of Application (New, Renewal, Modification, Deminimis/Minor Mod, or Administrative Amendment)	Short Description of Any Changes That Would Be Considered New or Modified Emissions
11/12/2019	Renewal	None

6. **REVIEWER'S NOTES**:

- Various formatting corrections were made throughout the permit.
- Regulatory citations have been updated.
- Sources (SN-TP-11, SN-TP-19, and SN-TP-21), which were never installed and are not permitted to emit air pollutants, have been removed.
- The fee calculation spreadsheet has been amended to include ammonia emissions and to indicate that emissions of sulfuric acid and mercury are chargeable.

7. COMPLIANCE STATUS:

The following summarizes the current compliance of the facility including active/pending enforcement actions and recent compliance activities and issues.

Inspections were conducted on November 27, 2017, and on September 25, 2018. The following areas of concern/noncompliance were identified.

- The facility performed NO_X testing at the Auxilary Boiler (SN-02) on June 28, 2017. Plantwide Condition #3 requires the permittee to submit compliance test results to the Department within sixty (60) calendar days; however, the full report was not submitted until November 27, 2017.
- The facility reported an upset condition on June 19, 2018 in which opacity at the main boiler (SN-01) exceeded the limits established in Specific Condition #4 and #12.

There are no active or pending CAOs. A review of ECHO indicated no CAA violations in the last twelve quarters.

8. PSD/GHG APPLICABILITY:

a) Did the facility undergo PSD review in this permit (i.e., BACT, Modeling, etc.)? No. If yes, were GHG emission increases significant? N/A.

- b) Is the facility categorized as a major source for PSD? Yes.
- Single pollutant ≥ 100 tpy and on the list of 28 or single pollutant ≥ 250 tpy and not on list

If yes for 8(b), explain why this permit modification is not PSD.

This revision does not include any major modification as defined in 40 C.F.R. § 52.21.

9. SOURCE AND POLLUTANT SPECIFIC REGULATORY APPLICABILITY:

Source	Pollutant	Regulation (NSPS, NESHAP or PSD)	
	all	PSD	
01	HAPs	40 C.F.R. Part 63, Subpart UUUUU	
	PM, SO ₂ , NO _x	40 C.F.R. Part 60, Subpart Da	
	all	PSD	
02	HAPs	40 C.F.R. Part 63, Subpart DDDDD	
	NO _x	40 C.F.R. 60, Subpart Db	
03	all	PSD	
	PM, fuel specifications	40 C.F.R. 60, Subpart IIII	

Source	Pollutant	Regulation (NSPS, NESHAP or PSD)
	N/A	40 C.F.R. 63, Subpart ZZZZ
04 & 05	PM, NO _x , fuel specifications	40 C.F.R. 60, Subpart IIII
EP-01 through EP-10, EP-12, TP-16 and TP-20	opacity	40 C.F.R. 60, Subpart Y

10. PERMIT SHIELD – TITLE V PERMITS ONLY:

Did the facility request a permit shield in this application? No. (Note - permit shields are not allowed to be added, but existing ones can remain, for minor modification applications or any Regulation 18 requirement.)

If yes, are applicable requirements included and specifically identified in the permit? If not, explain why. N/A.

11. EMISSION CHANGES AND FEE CALCULATION:

See emission change and fee calculation spreadsheet in Appendix A.

12. AMBIENT AIR EVALUATIONS:

The following are results for ambient air evaluations or modeling.

a) NAAQS

A NAAQS evaluation is not required under the Arkansas State Implementation Plan, National Ambient Air Quality Standards, Infrastructure SIPs and NAAQS SIP per Ark. Code Ann. § 8-4-318, dated March 2017 and the ADEQ Air Permit Screening Modeling Instructions.

b) Non-Criteria Pollutants:

The non-criteria pollutants listed below were evaluated. Based on Department procedures for review of non-criteria pollutants, emissions of all other non-criteria pollutants are below thresholds of concern.

1st Tier Screening (PAER)

Estimated hourly emissions from the following sources were compared to the Presumptively Acceptable Emission Rate (PAER) for each compound. The Department has deemed the PAER to be the product, in lb/hr, of 0.11 and the Threshold Limit Value (mg/m³), as listed by the American Conference of Governmental Industrial Hygienists (ACGIH).

Permit #: 2123-AOP-R9 AFIN: 29-00506 Page 4 of 12

Pollutant	TLV (mg/m ³)	$PAER (lb/hr) = 0.11 \times TLV$	Proposed lb/hr	Pass?
Acrolein	0.229	0.025	0.14	Ν
Antimony	0.5	0.055	0.15	Ν
Arsenic	0.01	0.001	0.52	Ν
Benzyl Chloride	5.177	0.569	0.27	Ν
Beryllium	0.002	0.00022	0.02	Ν
Cadmium	0.01	0.001	0.03	Ν
Carbon Disulfide	31.141	3.426	0.05	Y
Chloroform	48.826	5.371	0.03	Y
Chromium	0.5	0.055	0.19	Ν
Chromium VI	0.05	0.006	0.06	Ν
Cobalt	0.2	0.002	0.04	Ν
Cyanide	5.19	0.571	0.94	Ν
Dichlorobenzene	60.127	6.614	0.01	Y
Dimethyl Sulfate	0.516	0.057	0.02	Y
Dioxins & Furans	0.001	0.0001	0.01	Ν
Hydrogen Chloride	2.983	0.328	12.00	Ν
Hydrogen Fluoride	0.409	0.045	1.20	Ν
Lead	0.05	0.006	0.1603	Ν
Manganese	0.2	0.022	1.12	Ν
Mercury	0.025	0.003	7.34E-03	Ν
Methyl Hydrazine	0.019	0.002	0.07	Ν
Nickel	0.1	0.011	0.12	Ν
Phenol	19.245	2.117	0.01	Y
Phosphorous	0.1	0.011	2.40	N
РОМ	0.2	0.022	0.05	N
Propionaldehyde	47.526	5.228	0.15	Y

Pollutant	TLV (mg/m ³)	$PAER (lb/hr) = 0.11 \times TLV$	Proposed lb/hr	Pass?
Selenium	0.2	0.022	0.25	Ν
Sulfuric Acid	0.2	0.022	25.20	Ν
Ammonia	17.413	1.91	37.50	Ν

2nd Tier Screening (PAIL)

AERMOD air dispersion modeling was performed on the estimated hourly emissions from the following sources, in order to predict ambient concentrations beyond the property boundary. The Presumptively Acceptable Impact Level (PAIL) for each compound has been deemed by the Department to be one one-hundredth of the Threshold Limit Value as listed by the ACGIH.

Pollutant	PAIL $(\mu g/m^3) = 1/100$ of Threshold Limit Value	Modeled Concentration $(\mu g/m^3)$	Pass?
Acrolein	2.3	5.38E-04	Y
Antimony	5	7.43E-04	Y
Arsenic	0.1	0.001	Y
Benzyl Chloride	16	1.3E-03	Y
Beryllium	0.02	3.9E-05	Y
Cadmium	0.02	9.02E-05	Y
Chromium	5	8.58E-04	Y
Chromium VI	0.5	2.49E-04	Y
Cobalt	0.2	1.26E-04	Y
Cyanide	51.9	4.64E-03	Y
Dioxins & Furans	0.01	5E-05	Y
Hydrogen Chloride	29.8	0.06823	Y
Hydrogen Fluoride	24.6	0.0267	Y
Lead	0.5	0.00091	Y
Manganese	2.0	5.5E-03	Y
Mercury	0.1	1.97E-04	Y
Methyl hydrazine	0.19	3.16E-04	Y

Pollutant	PAIL $(\mu g/m^3) = 1/100$ of Threshold Limit Value	Modeled Concentration $(\mu g/m^3)$	Pass?
Nickel	1.0	5.25E-04	Y
Phosphorous	1.0	1.19E-02	Y
РОМ	0.02	8.0E-05	Y
Sulfuric Acid	2.0	1.19E-01	Y
Selenium	2.0	1.19E-03	Y
Ammonia	174	0.18575	Y

* Modeling does not include intermittent emissions from emergency engines.

** Permitted emissions of non-criteria pollutants have not been revised in this revision. Modeled concentrations are the result of modeling that was performed for previous permit revisions.

c) H₂S Modeling:

A.C.A. §8-3-103 requires hydrogen sulfide emissions to meet specific ambient standards. Many sources are exempt from this regulation, refer to the Arkansas Code for details.

Is the facility exempt from the H₂S Standards Y If exempt, explain: No H₂S emissions

13. CALCULATIONS:

SN	Emission Factor Source	Pollutant	Emission Factor	Control Equipment	Control Equipment Efficiency	Comments
		PM/PM ₁₀ (filterable)	0.012 lb/MMBtu	Baghouse	99.9	
		PM/PM ₁₀ (total)	0.025 lb/MMBtu	Baghouse	99.9	
		SO_2	0.065 lb/MMBTU	Dry Flue Gas Desulfurization	80-90+	
01	BACT	VOC	0.0036 lb/MMBtu	Proper Design/Operation		
		СО	0.15 lb/MMBtu	Proper Design/Operation		
		NO _x	0.067 lb/MMBTU/0.05 lb/MMBTU annual	SCR	70-90	
01	BACT	Pb	2.6E-05 lb/MMBtu	Baghouse	99.9	

Permit #: 2123-AOP-R9 AFIN: 29-00506 Page 7 of 12

SN	Emission Factor Source	Pollutant	Emission Factor	Control Equipment	Control Equipment Efficiency	Comments
		H_2SO_4	0.0042	DFGD with		
		PM (total)	0.0076 lb/MMBTU	Natural Gas Combustion		
		SO_2	0.0006 lb/MMBtu	Natural Gas Combustion		
		VOC	0.0055 lb/MMBtu	Proper Design/Operation		
02	BACT	СО	0.30 lb/MMBTU	Proper Design/Operation		
		NO _x	0.11 lb/MMBtu	Low NO _x Burner and Flue Gas Recirculation		
		Pb	N/A	Natural Gas combustion		
		NO _x + NMHC	6.4 g/kWh	Proper		
03 and 04	BACT	SO_2	0.007 g/kWh	Low Sulfur		
		PM	0.2 g/kWh	Diesel		
		СО	3.5 g/kWh	100 hrs/yr		
EP-01 – EP-10, TP- 16, TP-20	AP-42	PM/PM ₁₀	various	Water and Surfactant Spray		
EP-12	Design	PM/PM ₁₀	0.01 gr/dscf	filter		
TP-22 TP-23	design	PM/PM ₁₀	9.4E-05 lb/ton	None		
EP-15 - EP-18 EP-21 - EP-25	Design	PM/PM ₁₀	0.01 gr/dscf	filter		
F-01 – F- 03, F-05, F-06	EPA Guidance	PM/PM ₁₀	3.9 lb/day/acre	None	N/A	
F-04	AP-42	PM/PM ₁₀	lb/day/acre 1.0 PM 0.5 PM ₁₀	Water Spray	75%	Maximum of 26 acres
CT-01	BACT	Drift rate	0.0005%	Drift Eliminators	N/A	

Permit #: 2123-AOP-R9 AFIN: 29-00506 Page 8 of 12

SN	Emission Factor Source	Pollutant	Emission Factor	Control Equipment	Control Equipment Efficiency	Comments
RD-01	AP-42	PM/PM ₁₀	1.07 lb/VMT	Watering and chemical suppression	90	
TK-01	TANKS	VOC	Varies	N/A	N/A	Based on 25,000 gallons of gasoline per year.
		NO _x	4.0 g/kW-hr			
	Manufacturer's specs	CO	3.5 g/kW-hr	Oxidation Catalyst		
05		VOC	0.19 g/kW-hr			Annual emissions
		PM/PM ₁₀	0.2 g/kW-hr		Not specified	are based on
	ULSD	SO_2	0.007 g/kW-hr		1	100 hours per year
	AP-42 Chapter 3.3, Table 3.3- 2	HAPs	Varies			

14. TESTING REQUIREMENTS:

The permit requires testing of the following sources.

SN	Pollutants	Test Method	Test Interval	Justification
01	VOC PM/PM ₁₀ HF HCl H ₂ SO ₄ Ammonia Lead (Pb)	various	annual	BACT/NSPS/MACT Verify Emission Rates
01	Other Non- Criteria	TBD	Once	Verify Emission Rates/MACT
02	PM CO	various	Once	NSPS/MACT
02	NO _x	7E	Initial and once every five years.	Verify emission rates
EP-01 through EP-10, and EP- 12	Opacity	Method 9	Initial	NSPS

15. MONITORING OR CEMS:

The permittee must monitor the following parameters with CEMS or other monitoring equipment (temperature, pressure differential, etc.)

SN	Parameter or Pollutant to be Monitored	Method (CEM, Pressure Gauge, etc.)	Frequency	Report (Y/N)
01	Opacity CO NO _x SO ₂ CO ₂ Mercury	COMS CEMS	Continuous	Y
01	Bag Leaks	Bag Leak Detector	Continuous	Y

16. RECORDKEEPING REQUIREMENTS:

The following are items (such as throughput, fuel usage, VOC content, etc.) that must be tracked and recorded.

SN	Recorded Item	Permit Limit	Frequency	Report (Y/N)	
01	Mercury	1.7 lb/TBtu per	Monthly	V	
01	Emissions	12-month period	Monuny	I	
	Bag Leak				
01	Detector	None specified	Monthly	Y	
	Readings				
01	BTI input	6000 MMBtu/hr	Continuous	v	
01	DTO input	24-hour average	Continuous	1	
		0.065 lb/MMBtu			
		(30-day rolling	Monthly	Y	
01	SO ₂ emissions	average)			
01		480.0 lb/hr			
		(24-hr rolling	Monthly	Y	
		average)			
		0.067 lb/MMBtu			
		(24-hr rolling	Monthly	Y	
		average normal	Wientiny	1	
01	NO _x emissions	operations)			
		420.0 lb/hr			
		(24-hr rolling	Monthly	Y	
		average)			
		0.05 lb/MMBtu			
01	NO _x emissions	(12-month	Monthly	Y	
		rolling average)			
01	CO	0.15 lb/MMBtu	Monthly	Y	

SN	Recorded Item	Permit Limit	Frequency	Report (Y/N)
		(30-day rolling		
		average)		
02	Fuel Used	272.1 MMscf/12 month	Monthly	Y
03	Hours of operation	500 per year	Monthly	Y
04	Hours of operation	100 per year	Monthly	Y
F-04	Maximum area of the inactive coal piles	26 acres	Semi-annually	Y
F-06	Maximum area of the solid waste disposal area	50 acres	Semi-annually	Y
CT-01	Total Dissolved Solids (TDS)	7,500 ppm	Weekly	Y
TK-01	Gasoline throughput	25,000 gallons per 12-month	Monthly	Y
05	Hours of operation	100 hours per calendar year	Monthly	Y
Welsh Unit 2	SO ₂ emissions	2,165 lb/hr (24-hr rolling average)	Semi-annually	Y

17. OPACITY:

SN	Opacity	Justification for limit	Compliance Mechanism
01	10	Good Operations	COM
02	10	Good Operations	СОМ
03	20% in acceleration mode 15% in Lugging mode 50% during peaks (as measured according to 40 C.F.R. 86, Subpart I)	Good Operations	Method 9
04 & 05	20	Dept. Guidance	One time visible observation
SN-EP-01 through EP-10, EP-12, TP-16, and TP-20	20	NSPS	Method 9
SN-TP-22	20	Dept. Guidance	Daily Observations

SN	Opacity	Justification for limit	Compliance Mechanism
EP-15 through EP-25	10	Dept. Guidance	Weekly observations
SN-F-01 through F-06	10	Dept. Guidance	Weekly observations

18. DELETED CONDITIONS:

Former SC	Justification for removal
	None

19. GROUP A INSIGNIFICANT ACTIVITIES:

The following is a list of Insignificant Activities including revisions by this permit.

				Emiss	ions (tp	y)		
Source Name	Group A		<u> </u>	NO	HA	APs		
	Category	PM/PM_{10}	50_2	VUC	CO	NO _x	Single	Total
Diesel or Propane Space Heaters (20 Total)	A-1	0.002	1.1E- 05	0.0036	0.025	0.09	0.0036	0.0036
10,000 gallon Diesel Storage Tanks (3 Total)	A-3			0.005			0.005	0.005
700 gallon Diesel Storage Tank	A-3			0.0001			0.0001	0.0001
572 gallon Diesel Storage Tank	A-3			0.0002			0.0002	0.0002
Boiler Feed Pump Lube Oil Reservoir (2,906 gal)	A-3			0.0008			0.0008	0.0008
550 gallon Diesel Storage Tank	A-3			0.0001			0.0001	0.0001
10,000 gallon Construction fuel storage tank (diesel)	A-3			0.0128			0.0128	0.0128
10,000 gallon Sulfuric Acid Tanks (2 total)	A-4							
4,800 gallon Sulfuric Acid Tank	A-4							
10,000 gallon Sodium Hypochlorite Tank	A-4							
5,000 gallon	A-4							

Permit #: 2123-AOP-R9 AFIN: 29-00506 Page 12 of 12

	C			Emiss	ions (tp	y)		
Source Name	Group A		50	VOC	CO	NO	HA	APs
	Category	PM/PM_{10}	50_2	VUC	CO	NO _x	Single	Total
Sodium								
Hypochlorite Tank								
1,500 gallon								
Sodium Bromide	A-4							
Tank								
11,100 gallon	Λ /							
Coagulant Tank	A-4							
1,500 gallon								
Corrosion	A 1							
Inhibitor/Phosphoric	A-4							
Acid Tank								
30,000 gallon								
Anhydrous	A-4							
Ammonia Tank								
Emissions from								
laboratory	A-5	N	o VOCs	are used i	n the pla	int's lab	oratory.	
equipment & vents								
Water washing								
activities of empty	A-6							
55 gallon drums								
5 gallon Gasoline	Δ_8							
Containers (15 total)	A-0							
Turbine Lube Oil								
Storage Tank	A-13			0.007			0.007	0.007
(16,800 gal)								
Turbine Lube Oil								
Reservoir and	A_13			0.03			0.003	0.003
Storage Tank	A-13			0.05			0.005	0.005
(11,624 gal)								

20. VOIDED, SUPERSEDED, OR SUBSUMED PERMITS:

The following is a list of all active permits voided/superseded/subsumed by the issuance of this permit.

Permit #
2123-AOP-R8

APPENDIX A – EMISSION CHANGES AND FEE CALCULATION

Fee Calculation for Major Source

Facility Name: American Electric Power Service Corporation (John W. Turk Jr. Power Plant) Permit Number: 2123-AOP-R9 AFIN: 29-00506

\$/ton factor Permit Type	23.93 Renewal No Changes	Annual Chargeable Emissions (tpy) Permit Fee \$	4611.8717
Minor Modification Fee \$	500		
Minimum Modification Fee \$	1000		
Renewal with Minor Modification \$	500		
Check if Facility Holds an Active Minor Source or Mino Source General Permit	r		
If Hold Active Permit, Amt of Last Annual Air Permit Invoice \$	0		
Total Permit Fee Chargeable Emissions (tpy) Initial Title V Permit Fee Chargeable Emissions (tpy)	0		

HAPs not included in VOC or PM:

Chlorine, Hydrazine, HCl, HF, Methyl Chloroform, Methylene Chloride, Phosphine, Tetrachloroethylene, Titanium Tetrachloride

Air Contaminants:

All air contaminants are chargeable unless they are included in other totals (e.g., H2SO4 in condensible PM, H2S in TRS, etc.)

Revised 03-11-16

Pollutant (tpy)	Check if Chargeable Emission	Old Permit	New Permit	Change in Emissions	Permit Fee Chargeable Emissions	Annual Chargeable Emissions
РМ		468.5	468.5	0		
PM ₁₀		744	744	0	0	744
PM _{2.5}		0	0	0		
SO ₂		2102.8	2102.8	0	0	2102.8
VOC		96.71	96.71	0	0	96.71
со		3986.7	3986.7	0		
NO _X		1334.5	1334.5	0	0	1334.5

Dollutant (tax)	Check if Chargeable	Old Permit	New Permit	Change in Emissions	Permit Fee Chargeable	Annual Chargeable
A cataldabyda*		0.03			Emissions	LIIIISSIOIIS
Acrolein*		0.03	0.03	0		
Benzene*		0.05	0.05	0		
1,3-Butadiene*		0.04	0.04	0		
Formaldehyde*		0.03	0.03	0		
Hexane*		0.01	0.01	0		
Hydrogen Chloride		52.56	52.56	0	0	52.56
Hydrogen Fluoride	•	5.26	5.26	0	0	5.26
Lead**		0.6801	0.6801	0		
Mercury	v	0.0317	0.0317	0	0	0.0317
POM*		0.03	0.03	0		
Sulfuric Acid	•	110.38	110.38	0	0	110.38
Toluene*		0.05	0.05	0		
2,2,4-Trimethylpentane*		0.01	0.01	0		
Xylene*		0.04	0.04	0		
Total Other HAPs		35.15	35.15	0		
Total Other Chargeable HAPs	•	0.55	0.55	0	0	0.55
Ammonia		164.4	164.4	0	0	164.4
Total Other Air Contaminants	v	0.68	0.68	0	0	0.68