# ADEQ MINOR SOURCE AIR PERMIT

Permit No.: 0791-AR-8

IS ISSUED TO:

Kohler Co. 415 South Oklahoma Street Sheridan, AR 72150 Grant County AFIN: 27-00004

THIS PERMIT IS THE ABOVE REFERENCED PERMITTEE'S AUTHORITY TO CONSTRUCT, MODIFY, OPERATE, AND/OR MAINTAIN THE EQUIPMENT AND/OR FACILITY IN THE MANNER AS SET FORTH IN THE DEPARTMENT'S MINOR SOURCE AIR PERMIT AND THE APPLICATION. THIS PERMIT IS ISSUED PURSUANT TO THE PROVISIONS OF THE ARKANSAS WATER AND AIR POLLUTION CONTROL ACT (ARK. CODE ANN. SEC. 8-4-101 *ET SEQ*.) AND THE REGULATIONS PROMULGATED THEREUNDER, AND IS SUBJECT TO ALL LIMITS AND CONDITIONS CONTAINED HEREIN.

Signed:

Mike Bates Chief, Air Division Date

# **Table of Contents**

Section I: FACILITY INFORMATION	.4
Section II: INTRODUCTION	. 5
Summary of Permit Activity	. 5
Process Description	. 5
Regulations	
Total Allowable Emissions	. 8
Section III: PERMIT HISTORY	. 9
Section IV: EMISSION UNIT INFORMATION	10
Section V: INSIGNIFICANT ACTIVITIES	14
Section VI: GENERAL CONDITIONS	15
Appendix A	

# List of Acronyms and Abbreviations

A.C.A.	Arkansas Code Annotated
AFIN	ADEQ Facility Identification Number
CFR	Code of Federal Regulations
CO	Carbon Monoxide
HAP	Hazardous Air Pollutant
lb/hr	Pound Per Hour
No.	Number
NO <sub>x</sub>	Nitrogen Oxide
PM	Particulate Matter
$PM_{10}$	Particulate Matter Smaller Than Ten Microns
$SO_2$	Sulfur Dioxide
tpy	Tons Per Year
UTM	Universal Transverse Mercator
VOC	Volatile Organic Compound

# Section I: FACILITY INFORMATION

PERMITTEE:	Kohler Co.
AFIN:	27-00004
PERMIT NUMBER:	0791-AR-8
FACILITY ADDRESS: MAILING ADDRESS:	<ul><li>415 South Oklahoma Street Sheridan, AR 72150</li><li>415 South Oklahoma Street Sheridan, AR 72150</li></ul>
COUNTY:	Grant
COUNTY: CONTACT POSITION:	Grant Randy Kuykendall - Safety and Environmental Specialist
	Randy Kuykendall - Safety and Environmental Specialist
CONTACT POSITION:	Randy Kuykendall - Safety and Environmental Specialist 870-942-2111
CONTACT POSITION: TELEPHONE NUMBER:	Randy Kuykendall - Safety and Environmental Specialist 870-942-2111

#### Section II: INTRODUCTION

#### **Summary of Permit Activity**

Kohler Co. operates a facility for the fabrication, plating, and assembly of faucets located at 415 South Oklahoma in Sheridan, AR. This permit modification removes SN-23 and SN-24 from the permit because they are no longer in operation, moves SN-25 and SN-30 to the insignificant activities list because they are no longer vented to the atmosphere, and removes Cu from the non-criteria pollutants tables because it is already included in the PM emissions. The proposed modifications result in no permitted emission changes.

#### **Process Description**

The predominant industrial activities are brazing, buffing and plating, with metal and plastic as the main raw materials. Raw materials such as screws, washers, etc. are used only in final assembly, and do not substantially contribute to the industrial processes. Completed faucets are distributed nationally, and may be shipped using various modes of transportation.

#### Machining

Brass barstock and tube stock are machined to produce faucet components. No air emission sources are associated with this process. Some faucet components are also received from Sheridan's sister facility in Malvern, AR.

#### Brazing

At the brazing machines, faucet components are placed into fixtures mounted on a rotary table. The table is rotated through various stations within the machine, to accommodate proper heating of each component. Heating is accomplished using several propane burners, with flames similar in appearance to those of small hand-held torches. Burner flames are directed to sufficiently heat the brass and allow brazing material to glow evenly within the appropriate joints. Fumes produced by brazing and burner exhausts are captured by a fume hood and vented outside the facility.

#### **Bright Dip (Bernite 45)**

After brazing, faucets are submerged in a "Bright Dip" wash solution to remove oxidized material from the faucets' components. This is an aqueous dip that contains no VOCs. Heat and non-HAP emissions are captured by a hood and vented to the atmosphere. There are two Bright Dip units at the Kohler Sheridan facility.

#### Polishing

A fraction of the faucets' components require polishing before buffing. Up to six hand and semiautomatic polishing stations make up the polishing operation. The primary emissions from this process are brass fines. To control particulate emissions, all polishing equipment is vented through a cartridge dust collector (SN-30).

# Buffing

The majority of faucet components which require buffing are received from the brazing machine. The Hammond rotary buffer, Harper buffing machines #1, #2, and #3, the Fairfax auto-buffer and six spot buffing machines make up the buffing operations. The primary emission from this process is lint from the cloth buffing wheels. To control particulate emissions, all buffing machines vent through a wet dust collector (SN-12).

#### Plating (Ni/Cr Line)

There are three plating lines, the nickel-chrome (Ni/Cr) line, the udylite bright acid copper (UBAC) line, and the barrel plating line. The Ni/Cr plating operation is listed as SN-17, 18, and 19, and a Superior brand 4.2 million BTU gas-fired boiler (SN-01) is used to heat the plating tanks. The barrel plating is listed as SN-25.

#### Plating (UABC)

Nearly all plated parts eventually go through the Ni/Cr line, however only twenty-five to fifty percent of plated faucet components go through the copper line. If copper plating is required, a component will proceed through the first half of the Ni/Cr plating sequence; transfer to the copper line and complete the copper plating sequence; then return to complete the remaining Ni/Cr plating cycle.

#### **Plastic Pre-Plating**

Unplated plastic components are used only in final assembly, while those requiring plating must go through the plastic pre-plate system. The objective of pre-plating is to prepare the surface of plastic components, then apply a thin layer of electroless nickel. This forms a conductive surface on the plastic part. To insure an acceptable metal coating on the plastic components from a conductivity, strength, and product quality perspective, the electroless nickel film is plated again with an acid copper strike. After final rinsing with de-ionized water, these components are transferred to the Ni/Cr plating line.

Exhaust from chromic acid etching tanks used in the process is controlled by a packed bed scrubber with a mist eliminator (SN-20). Plating tanks used in this process exhaust through a single stack (SN-21).

## Nickel Barrel Plating

Some faucet components are too small to hang on racks for plating. These are plated in a barrelstyle plater (SN-25). The components are placed inside a small drum made of sturdy plastic mesh. This barrel is then immersed in the various plating solutions while being rotated to tumble the small parts within.

#### **Rack Stripping**

All plating racks used in the Ni/Cr plating process must have their contacts stripped clean of plated metals to prevent contamination in the tanks. This is an electrolytic process requiring a reduced concentration of nitric acid in a bath. Rack stripping tanks used in this process exhaust through a single stack (SN-22).

#### Assembly

Various faucet components are assembled to produce finished products. Faucets are packaged and sent to the warehouse. No air emission sources are associated with the assembly process.

#### Warehouse and Distribution

After the completed faucets have been packaged, they are delivered directly to the loading docks for shipment or transferred to rack storage.

#### Regulations

The following table contains the regulations applicable to this permit.

Regulations
Arkansas Air Pollution Control Code, Regulation 18, effective February 15, 1999
Regulations of the Arkansas Plan of Implementation for Air Pollution Control, Regulation 19, effective May 28, 2006
40 CFR Part 63, Subpart N – Standards for Chromium Emissions from Hard and Decorative Chromium Electroplating and Chromium Anodizing Tanks

The following table is a summary of emissions from the facility. This table, in itself, is not an enforceable condition of the permit.

TOTAL ALLOWABLE EMISSIONS		
Pollutant	Emission Rates	
Fonutant	lb/hr	tpy
PM	2.0	7.3
PM <sub>10</sub>	2.0	7.3
CrO <sub>3</sub>	0.10	0.32
F (as HF)	0.01	0.05
HCl	0.15	0.67
$H_2SO_4*$	0.58	2.40
NH <sub>3</sub> *	0.07	0.31
Ni	0.02	0.09

# **Total Allowable Emissions**

\*Air Contaminants such as ammonia, acetone, and certain halogenated solvents are not VOCs or HAPs.

#### Section III: PERMIT HISTORY

Permit number 791-A, issued on June 9, 1986, was the initial permit for this facility.

Permit number 791-AR-1 was issued on June 6, 1991. It allowed the permittee to install a new plastic pre-plate and rack stripping line. Also, this permit showed the elimination of existing equipment listed 791-A.

Permit number 791-AR-2 was issued on March 21, 1994. It replaced an electroless copper bath with an electroless nickel bath.

Permit Number 791-AR-3 was issued on October 22, 1996. It allowed the permittee to install a nickel barrel plater, a parts stripper, an electric annealing oven, a rotary buffer, and two in-line buffers.

Permit Number 791-AR-4 was issued on August 6, 1997 and revised on January 5, 1999. It allowed emissions to be routed from a barrel plater through a scrubber.

Permit Number 791-AR-5 was issued on May 8, 2001. It allowed the addition of two new brazing machines. Also, the permit recognized the relocation of one brazing machine to a different location in the plant. Lastly, the permit authorized the addition of the following insignificant activities: one new brass buffing lint dust collector, one new polishing dust collector, and a Bright Dip wash station.

Permit number 791-AR-6 was issued on November 8, 2001. This permit modification allowed the Harper Buffer #3 and one new auto-buffer (Fairfax Buffer) to be connected to the SN-12 dust collector. This action eliminated one buffing dust collector at SN-15. Also, a rotary table auto buffer and six small hand buffing stations were connected to the SN-12 dust collector. The polishing dust collector located at SN-28 was also eliminated and one new polishing dust collector emission point (SN-30) was created. Two insignificant "Bright Dip" wash stations and up to eight insignificant aqueous ultrasonic cleaning stations were installed. This modification increased particulate matter emission by 3.36 tons per year. An administrative amendment to this permit issued on February 7, 2003 allowed the rack stripping operation (SN-22), the Superior Boiler (SN-01), the cleaner baths at the plater (SN-17), and a new PVD Process to be listed as insignificant activities. An administrative amendment issued on February 5, 2004 also eliminated the wash tank and annealer (SN-27), and Specific Conditions #6 and #7, and the record keeping requirements for natural gas and propane for SN-01 and SN-09.

Permit number 791-AR-7 was issued on July 19, 2005. This de minimis permit modification allowed the addition of a decorative chromium plating line (SN-32) which was routed to SN-20 and the correction of PM and  $PM_{10}$  emissions. The proposed change resulted in an increase of 5.6 tpy of  $PM_{10}$  and PM and 0.01 tpy of  $CrO_3$ .

## Section IV: EMISSION UNIT INFORMATION

#### **Specific Conditions**

1. The permittee shall not exceed the emission rates set forth in the following table. [§19.501 *et seq.* of the Regulations of the Arkansas Plan of Implementation for Air Pollution Control, effective May 28, 2006, (Regulation 19) and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]

SN	Description	Pollutant	lb/hr	tpy
12	Harper #1 In-Line Buffer	$PM_{10}$	0.6	2.5
18	Bright Acid Copper Plate	$PM_{10}$	0.4	1.6
19	Chrome Plating Line	$PM_{10}$	0.1	0.2
20	Chrome Etch Bath Plater	$PM_{10}$	0.3	0.7
21	Nickel/Copper Pre- Plater	$PM_{10}$	0.6	2.3
32	Offline Brushed Chrome Plating Line	Routed to SN-20		

2. The permittee shall not exceed the emission rates set forth in the following table. [§18.801 of the Arkansas Air Pollution Control Code, effective February 15, 1999 (Regulation 18) and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

SN	Description	Pollutant	lb/hr	tpy
12	Harper #1 In-Line Buffer	РМ	0.6	2.5
		PM	0.4	1.6
18	Bright Acid Copper Plate	HCl	0.01	0.05
		$H_2SO_4$	0.05	0.22
		PM	0.1	0.2
19	Chrome Disting Line	CrO <sub>3</sub>	0.01	0.05
19	Chrome Plating Line	HF	0.01	0.05
		$H_2SO_4$	0.01	0.05
20	Chrome Etch Bath Plater	PM	0.3	0.7
	i latel	CrO <sub>3</sub>	0.09	0.27

SN	Description	Pollutant	lb/hr	tpy
		$H_2SO_4$	0.13	0.42
		PM	0.6	2.3
	Nickel/Copper Pre- Plater	HCl	0.14	0.62
21		$H_2SO_4$	0.39	1.71
		NH <sub>3</sub>	0.07	0.31
		Ni	0.02	0.09
32	Offline Brushed Chrome Plating Line	Routed to SN-20		

3. Visible emissions may not exceed the limits specified in the following table of this permit as measured by EPA Reference Method 9. [A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]

SN	Limit	Regulatory Citation
12	5%	§18.501
18	5%	§18.501
19	5%	§18.501
20	5%	§18.501
21	5%	§18.501

- 4. The permittee shall not cause or permit the emission of air contaminants, including odors or water vapor and including an air contaminant whose emission is not otherwise prohibited by Regulation #18, if the emission of the air contaminant constitutes air pollution within the meaning of A.C.A. §8-4-303. [§18.801 of Regulation 18 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 5. The permittee shall not conduct operations in such a manner as to unnecessarily cause air contaminants and other pollutants to become airborne. [§18.901 of Regulation 18 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 6. The permittee shall comply with all applicable provisions of 40 CFR Part 63, Subpart N National Emission Standards for Chromium Emissions from Hard and Decorative Chromium Electroplating and Chromium Anodizing Tanks at all times. See Attachment A. [§19.304 of Regulation 19 and 40 CFR Part 63, Subpart N National Emission Standards for Chromium Emissions from Hard and Decorative Chromium Electroplating and Chromium Emissions from Hard and Decorative Chromium Electroplating and Chromium Emissions from Hard and Decorative Chromium Electroplating and Chromium Emissions from Hard and Decorative Chromium Electroplating and Chromium Emissions from Hard and Decorative Chromium Electroplating and Chromium Anodizing Tanks]

- 7. The permittee shall continuously measure the chrome plate bath surface tension (SN-19 and SN-32) using method 306B. Measurements of the bath surface tension must be made every 4 hours of tank operation for the first 40 hours of tank operation after the compliance date. Once there are no exceedances during 40 hours of tank operation, measurements may be conducted once every 8 hours of tank operation. Once there are no exceedances during 40 hours of tank operation on an on-going basis, until an exceedance occurs. If the surface tension of the bath exceeds 45 dynes per centimeter limit, the time interval reverts back to the original monitoring schedule of once every 4 hours. The maximum time interval for measurements is once every 40 hours of tank operation. These records shall be kept on site and shall be made available to Department personnel upon request. [§19.304 of Regulation 19 and 40 CFR Part 63, Subpart N -- National Emission Standards for Chromium Emissions From Hard and Decorative Chromium Electroplating and Chromium Anodizing Tanks]
- 8. The permittee shall label any additional sources resulting from this permit modification within (30) days of the issuance of Permit #791-AR-8. [A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
- 9. The permittee shall not exceed the usage and content limits set forth in the following table which demonstrates compliance with Specific Conditions No. 1 and 2. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]

Compound	Annual Limit	Maximum Content Limit
Activator	300 gal/yr	7.42 lb/gal of HCl
Ammonia	16,000 lb/yr	30% NH <sub>3</sub>
Chrome Catalyst	1,200 lb/yr	15% Sodium Silicofluoride
Copper (Solid)	32,000 lb/yr	100% Cu
Copper Maintenance	2400 gal/yr	1.32 lb/gal of H <sub>2</sub> SO <sub>4</sub>
Copper Make-up	300 gal/yr	1.29 lb/gal of H <sub>2</sub> SO <sub>4</sub>
Copper Sulfate Snowform	6000 lb/yr	20% Cu
Hydrochloric Acid Reagent	18,100 lb/yr	38% HCl
Replenisher	1,200 gal/yr	4.725 lb/gal of NiCl <sub>2</sub>
Sulfuric Acid	36,650 lb/yr	93.2% H <sub>2</sub> SO <sub>4</sub>

- 10. The permittee shall maintain monthly records which demonstrate compliance with Specific Condition #9. The permittee will update the records by the fifteenth day of the month following the month to which the records pertain. The permittee will keep the records onsite, and make the records available to Department personnel upon request. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 11. The permittee shall test SN-21 for NH<sub>3</sub> emissions. This test shall be conducted within 120 days of 791-AR-8 being issued using test method CTM-027 with the source operating at 90% capacity or greater, and in accordance with General Condition 7. Test results will be maintained on-site, made available to Department personnel upon request, and will be submitted to the Department in accordance with General Condition 7. [§19.702 of Regulation 19 and 40 CFR Part 52, Subpart E]
- 12. The permittee shall submit a permit modification within 120 days of 791-AR-8 being issued. This permit application will include stack testing information for SN-21 for H<sub>2</sub>SO<sub>4</sub>, Ni, Cu, and HCl emissions. This testing shall be conducted with the source operating at 90% capacity or greater, and in accordance with General Condition 7. [§19.702 of Regulation 19 and 40 CFR Part 52, Subpart E]

## Section V: INSIGNIFICANT ACTIVITIES

The Department deems the following types of activities or emissions as insignificant on the basis of size, emission rate, production rate, or activity in accordance with Group A of the Insignificant Activities list found in Regulation 18 and 19 Appendix A. Insignificant activity emission determinations rely upon the information submitted by the permittee in an application dated April 27, 2000 and July 9, 2002.

Source No.	Description	Category
01	Superior Boiler Natural Gas (4.2 MMBtu/hr)	A-1
09 and 29	Two Brazing Machines No.2 Propane - (1.386 MMBtu/hr)	A-13
17	Cleaner Baths for Brass Plater	A-9
22	Rack Stripping	A-9
30	One Polishing Dust Collector	A-13
	Eight Ultrasonic Cleaning Stations	A-13
31	PVD Process	A-13
37	Nitric Acid Stripping Tank	A-13
25	Nickel Barrel Plating	A-13

#### Section VI: GENERAL CONDITIONS

- 1. Any terms or conditions included in this permit that specify and reference Arkansas Pollution Control & Ecology Commission Regulation 18 or the Arkansas Water and Air Pollution Control Act (A.C.A. §8-4-101 et seq.) as the sole origin of and authority for the terms or conditions are not required under the Clean Air Act or any of its applicable requirements, and are not federally enforceable under the Clean Air Act. Arkansas Pollution Control & Ecology Commission Regulation 18 was adopted pursuant to the Arkansas Water and Air Pollution Control Act (A.C.A. §8-4-101 et seq.). Any terms or conditions included in this permit that specify and reference Arkansas Pollution Control & Ecology Commission Regulation 18 or the Arkansas Water and Air Pollution Control Act (A.C.A. §8-4-101 *et seq.*) as the origin of and authority for the terms or conditions are enforceable under this Arkansas statute.
- 2. This permit does not relieve the owner or operator of the equipment and/or the facility from compliance with all applicable provisions of the Arkansas Water and Air Pollution Control Act and the regulations promulgated under the Act. [A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 3. The permittee will notify the Department in writing within thirty (30) days after commencement of construction, completion of construction, first operation of equipment and/or facility, and first attainment of the equipment and/or facility target production rate. [Regulation 19, §19.704 and/or A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 4. Construction or modification must commence within eighteen (18) months from the date of permit issuance. [Regulation 19, §19.410(B) and/or Regulation 18, §18.309(B) and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 5. The permittee must keep records for five years to enable the Department to determine compliance with the terms of this permit such as hours of operation, throughput, upset conditions, and continuous monitoring data. The Department may use the records, at the discretion of the Department, to determine compliance with the conditions of the permit. [Regulation 19, §19.705 and/or Regulation 18, §18.1004 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 6. A responsible official must certify any reports required by any condition contained in this permit and submit any reports to the Department at the address below. [Regulation 19, \$19.705 and/or Regulation 18, \$18.1004 and A.C.A. \$8-4-203 as referenced by A.C.A. \$8-4-304 and \$8-4-311]

Arkansas Department of Environmental Quality Air Division ATTN: Compliance Inspector Supervisor Post Office Box 8913 Little Rock, AR 72219

- 7. The permittee will test any equipment scheduled for testing, unless stated in the Specific Conditions of this permit or by any federally regulated requirements, within the following time frames: (1) newly constructed or modified equipment within sixty (60) days of achieving the maximum production rate, but no later than 180 days after initial start up of the permitted source or (2) existing equipment already operating according to the time frames set forth by the Department. The permittee must notify the Department of the scheduled date of compliance testing at least fifteen (15) days in advance of such test. The permittee must submit compliance test results to the Department within thirty (30) days after the completion of testing. [Regulation 19, §19.702 and/or Regulation 18, §18.1002 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 8. The permittee will provide: [Regulation 19, §19.702 and/or Regulation 18, §18.1002 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
  - a. Sampling ports adequate for applicable test methods
  - b. Safe sampling platforms
  - c. Safe access to sampling platforms
  - d. Utilities for sampling and testing equipment
- 9. The permittee will operate equipment, control apparatus and emission monitoring equipment within their design limitations. The permittee will maintain in good condition at all times equipment, control apparatus and emission monitoring equipment. [Regulation 19, §19.303 and/or Regulation 18, §18.1104 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- If the permittee exceeds an emission limit established by this permit, the permittee will be deemed in violation of said permit and will be subject to enforcement action. The Department may forego enforcement action for emissions exceeding any limits established by this permit provided the following requirements are met: [Regulation 19, §19.601 and/or Regulation 18, §18.1101 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
  - a. The permittee demonstrates to the satisfaction of the Department that the emissions resulted from an equipment malfunction or upset and are not the result of negligence or improper maintenance, and the permittee took all reasonable measures to immediately minimize or eliminate the excess emissions.
  - b. The permittee reports the occurrence or upset or breakdown of equipment (by telephone, facsimile, or overnight delivery) to the Department by the end of the next business day after the occurrence or the discovery of the occurrence.
  - c. The permittee must submit to the Department, within five business days after the occurrence or the discovery of the occurrence, a full, written report of such occurrence, including a statement of all known causes and of the scheduling and nature of the actions to be taken to minimize or eliminate future occurrences, including, but not limited to, action to reduce the frequency of occurrence of such conditions, to minimize the amount by which said limits are exceeded, and to

reduce the length of time for which said limits are exceeded. If the information is included in the initial report, the information need not be submitted again.

- 11. The permittee shall allow representatives of the Department upon the presentation of credentials: [A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
  - a. To enter upon the permittee's premises, or other premises under the control of the permittee, where an air pollutant source is located or in which any records are required to be kept under the terms and conditions of this permit;
  - b. To have access to and copy any records required to be kept under the terms and conditions of this permit, or the Act;
  - c. To inspect any monitoring equipment or monitoring method required in this permit;
  - d. To sample any emission of pollutants; and
  - e. To perform an operation and maintenance inspection of the permitted source.
- 12. The Department issued this permit in reliance upon the statements and presentations made in the permit application. The Department has no responsibility for the adequacy or proper functioning of the equipment or control apparatus. [A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 13. The Department may revoke or modify this permit when, in the judgment of the Department, such revocation or modification is necessary to comply with the applicable provisions of the Arkansas Water and Air Pollution Control Act and the regulations promulgated the Arkansas Water and Air Pollution Control Act. [Regulation 19, §19.410(A) and/or Regulation 18, §18.309(A) and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 14. This permit may be transferred. An applicant for a transfer must submit a written request for transfer of the permit on a form provided by the Department and submit the disclosure statement required by Arkansas Code Annotated §8-1-106 at least thirty (30) days in advance of the proposed transfer date. The permit will be automatically transferred to the new permittee unless the Department denies the request to transfer within thirty (30) days of the receipt of the disclosure statement. The Department may deny a transfer on the basis of the information revealed in the disclosure statement or other investigation or, deliberate falsification or omission of relevant information. [Regulation 19, §19.407(B) and/or Regulation 18, §18.307(B) and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 15. This permit shall be available for inspection on the premises where the control apparatus is located. [A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 16. This permit authorizes only those pollutant emitting activities addressed herein. [A.C.A. \$8-4-203 as referenced by A.C.A. \$8-4-304 and \$8-4-311]

- This permit supersedes and voids all previously issued air permits for this facility.
  [Regulation 18 and 19 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
- 18. The permittee must pay all permit fees in accordance with the procedures established in Regulation No. 9. [A.C.A §8-1-105(c)]

APPENDIX A