



Source Point

Operations Areas

Map Date: 10/10/2013

Sources: Esri, DeLorme,
NAVTEQ, TomTom, Intermap,
increment P Corp., GEBCO,


MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SITE LOCATION MAP



FIGURE

1-1



B Background Sediment Sample



Approximate Surface Water Flow Direction



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

BACKGROUND SOIL AND SEDIMENT SAMPLE LOCATIONS IN LAKE CONWAY AND DRAINAGE WAYS



FIGURE

Map Date: 10/10/2013





Sediment Sample Soil Sample

Drainage Path

Operations Areas

NOTE:

1. Surface soil samples were collected as five-point composite samples at locations shown. Example composite grid layout shown for illustrative purposes only; see Table 2-1 for actual sample grid dimensions at each location.


Map Date: 10/10/2013



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SOIL AND SEDIMENT SAMPLE LOCATIONS IN A-MAIN





Sediment Sample

Soil Sample

Drainage Path

Operations Areas NOTE:

1. Surface soil samples were collected as five-point composite samples at locations shown. Example composite grid layout shown for illustrative purposes only; see Table 2-1 for actual sample grid dimensions


Map Date: 10/10/2013




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

> SOIL AND SEDIMENT SAMPLE **LOCATIONS IN A-365E & A-365W**





2-3



Sediment Sample Location

Re-sampled Sediment Location

Approximate location of containment boom during sampling activities

Approximate locations of turbidity curtain during sampling activities

Operations Areas


Map Date: 1/3/2014



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SEDIMENT SAMPLE LOCATIONS IN LAKE CONWAY





B Background Sediment Sample

Background Soil Sample

Approximate Surface Water Flow Direction

Map Date: 10/10/2013



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

BACKGROUND SOIL AND SEDIMENT SAMPLE LOCATIONS IN LAKE CONWAY



FIGURE

2-5



B Background Sediment Sample

-- · Drainage Path

Operations Areas




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

BACKGROUND SEDIMENT SAMPLE LOCATIONS UPSTREAM OF DRAINAGE WAY



FIGURE

Map Date: 10/10/2013



Surface Water Sample Location WS-001 Daily Sampling Location ID



Parcel Boundary

Stream/River: Intermittent

Stream/River: Perennial

Approximate Surface Water Flow Direction


Map date: 1/3/2014



MAYFLOWER PIPELINE INCIDENT RESPONSE **EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY** DOWNSTREAM AREAS DATA ASSESSMENT REPORT

HISTORICAL AND DAILY SURFACE WATER SAMPLE LOCATIONS





Surface Water Sample
Locations Accessed by Foot

Surface Water Sample
Locations Accessed by Boat

Source Point

- Parcel Boundary

Approximate Surface Water Flow Direction

Stream/River: Intermittent

Stream/River: Perennial


Map date: 1/17/2014



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

WEEKLY SURFACE WATER SAMPLE LOCATIONS





One-time Surface Water Sample

Drainage Path

Approximate location of containment boom during sampling activities

Operations Areas


Map Date: 1/7/2014




MAYFLOWER PIPELINE INCIDENT RESPONSE **EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT**

DARSP SURFACE WATER SAMPLE LOCATIONS





Depositional Layer Assessment Locations



Approximate Surface
Water Flow Direction

Map Date: 1/3/2014




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

LAKE CONWAY DEPOSITIONAL LAYER ASSESSMENT LOCATIONS



FIGURE 2-10





Survey Point Used In Interpolation Survey Point

Drainage Path

Study Area

1. Survey data collected during field activities interpolated by the Inverse Distance Weighting (IDW) method using an optimized power term to develop a digital elevation model (DEM) for the area shown.

Map Date: 10/10/2013

279.6


257.9



MAYFLOWER PIPELINE INCIDENT RESPONSE **EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT**

SITE LOCATION TOPOGRAPHIC SURVEY








1. Topographic data from LiDAR dataset obtained from the United States Department of Agriculture (USDA) and supplemented by field survey information.


Map Date: 10/10/2013



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

LIDAR DATA IN DAWSON COVE AREA





Outlet Culvert
Staff Gauge

- Drainage Path

Study Area

261 ft
262.2 ft
262.87 ft
263 ft
264 ft
265 ft


Map Date: 10/10/2013



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

TOPOGRAPHIC MAP OF DAWSON COVE AREA





Notes:

- 1. Water elevation data are available from February 18, 2008 through September 16, 2013. The data are provided by Lake Manager, Mr. Matthew Horton (Arkansas Game and Fish Commission [AGFC], District 10 Lake Manager).
- 2. Water surface elevations are recorded at the gauge located near the AGFC Mayflower Enforcement Training Center.
- 3. Lake Conway levels on April 9 and 10, 2008 were reported as 236.12 feet and 236.02 feet (NAVD88). No additional information related to this data point is available at this time.


MAYFLOWER PIPELINE INCIDENT RESPONSE
EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY
DOWNSTREAM AREAS DATA ASSESSMENT REPORT


Lake Conway Peak Daily Water Elevation Data




FIGURE

3-4







B Background Sediment Sample

Map Date: 10/11/2013

Background Soil Sample


Approximate Surface
Water Flow Direction

MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SOIL BACKGROUND SAMPLING RESULTS: PAHS



FIGURE 5_2 1



B Background Sediment Sample

Map Date: 10/10/2013

B Background Soil Sample


Approximate Surface
Water Flow Direction



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SOIL BACKGROUND SAMPLING RESULTS: METALS





B Background Sediment Sample

Drainage Path

Operations Areas

NOTES:

1. All background data are from surface samples that were collected at depths of 0-0.5 foot below sediment surface. 2. Polycyclic Aromatic Hydrocarbon (PAH) concentrations

are presented in micrograms per kilogram (µg/kg). 3. PAH summations are based on the Priority+2 List and the Long List of PAHs (Table 5-3).


Map Date: 10/11/2013



MAYFLOWER PIPELINE INCIDENT RESPONSE **EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT**

DRAINAGE WAY SEDIMENT BACKGROUND SAMPLING RESULTS: PAHS





B Background Sediment Sample

-- Drainage Path

Operations Areas




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

DRAINAGE WAY SEDIMENT BACKGROUND SAMPLING RESULTS: METALS



FIGURE

Map Date: 10/10/2013 increment P Corp., GEBCO,



B Background Sediment Sample

Map Date: 10/11/2013


B Background Soil Sample



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

LAKE CONWAY SEDIMENT BACKGROUND SAMPLING RESULTS: PAHS





B Background Sediment Sample

Map Date: 10/11/2013


B Background Soil Sample



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

LAKE CONWAY SEDIMENT BACKGROUND SAMPLING RESULTS: METALS








- Sediment Sample
- Soil Sample
- Drainage Path
- Operations Areas

NOTES

- 1. Data boxes present maximum detections for each analyte at each location, and the associated sample depth interval at which the maximum detection was recorded (i.e., 0-0.5 foot, 0.5-1.0 foot, or 1.0-1.5 feet).
- 2. Polycyclic Aromatic Hydrocarbon concentrations are presented in micrograms per kilogram (µg/kg).
- 3. Yellow highlighted cells identify concentrations above the Ecological Screening Values.
- 4. PAH summations are based on the Long List of PAHs (Table 5-3).




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SOIL SAMPLING RESULTS IN DRAINAGE WAYS: PAHS



FIGURE **6-1.1**






- Sediment Sample
- Soil Sample
- ••• Drainage Path
- Operations Areas

NOTE:

- 1. Metals were analyzed in cores collected from 0-1.5 feet bgs; data boxes present maximum detections for each analyte at each location, and the associated sample depth interval at which the maximum detection was recorded (i.e., 0-0.5 foot, 0.5-1.0 foot, or 1.0-1.5 feet).
- Only detected concentrations of nickel, selenium, and silver are shown.
- 3. Metals concentrations are presented in milligrams per kilogram.
- 4. Yellow highlighted cells identify concentrations above the Arkansas Background and Ecological Screening Values.




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SOIL SAMPLING RESULTS IN DRAINAGE WAYS: METALS



6-1.2





- Sediment Sample
- Soil Sample
- Dart Sample Location
- O Deep Core Sample Location
- Operations Areas
- Approximate Oil Extent
- Drainage Path
 - Approximate location of containment boom during sampling activities


Contour Elevation

- -- 262.2 ft
- -- 262.87 ft

NOTES:

- 1. Data boxes present maximum detections for each analyte at each location, and the associated sample depth interval at which the maximum detection was recorded (i.e., 0-0.5 foot, 0.5-1.0 foot, or 1.0-1.5 feet).


 2. Polycyclic Aromatic Hydrocarbon concentrations
- are presented in micrograms per kilogram (µg/kg). 3. Yellow highlighted cells identify concentrations above the Ecological Screening Values.
- 4. PAH summations are based on the Long List of PAHs (Table 5-3).



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SOIL SAMPLING RESULTS IN DAWSON COVE: PAHS







Sediment Sample

Soil Sample

Dart Sample Location

Deep Core Sample Location

Operations Areas

Approximate Oil Extent (Source: ARCADIS, May 2013)

Drainage Path

Approximate location of containment boom during sampling activities


Contour Elevation

-- 262.2 ft

--- 262.87 ft

NOTE:

- 1. Metals were analyzed in cores collected from 0-1.5 feet bgs; data boxes present maximum detections for each analyte at each location, and the associated sample depth interval at which the maximum detection was recorded (i.e., 0-0.5 foot, 0.5-1.0 foot, or 1.0-1.5 feet).
- 2. Metals concentrations are presented in milligrams per kilogram.
- 3. Yellow highlighted cells identify concentrations above the Arkansas Background and Ecological Screening Values.
- 4. Only detected concentrations of nickel, selenium, and silver are shown.




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SOIL SAMPLING RESULTS IN DAWSON COVE: METALS



FIGURE **6-2.2**






- Sediment Sample
- Soil Sample
- Drainage Path
- Operations Areas

NOTES:

- 1. Data boxes present maximum detections for each analyte at each location, and the associated sample depth interval at which the maximum detection was recorded (i.e., 0-0.5 foot, 0.5-1.0 foot, or 1.0-1.5 feet).
- 2. Polycyclic Aromatic Hydrocarbon concentrations are presented in micrograms per kilogram ($\mu g/kg$).
- 3. Yellow highlighted cells identify concentrations above the Ecological Screening Values.
- 4. PAH summations are based on the Priority+2 List and the Long List of PAHs (Table 5-3).




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SEDIMENT SAMPLING RESULTS IN DRAINAGE WAYS: PAHS



FIGURE **7-1.1**






- Sediment Sample
- Soil Sample
- Drainage Path
- Operations Areas

NOTES

- 1. Total Polycyclic Aromatic Hydrocarbon Toxic Unit values are unitless.
- 2. All data are from surface samples that were collected at depths of 0-0.5 foot below sediment surface.




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SEDIMENT SAMPLING RESULTS IN DRAINAGE WAYS: TOXIC UNIT



FIGURE **7-1.2**






- Sediment Sample
- Soil Sample
- Drainage Path
- Operations Areas

NOTES

- 1. Metals were analyzed in cores collected from 0-1.5 feet bgs; data boxes present maximum detections for each analyte at each location, and the associated sample depth interval at which the maximum detection was recorded (i.e.,0-0.5 foot, 0.5-1.0 foot, or 1.0-1.5 feet).
- 2. Metals concentrations are presented inmilligrams per kilogram.
- 3. Yellow highlighted cells identify concentrations above the Arkansas Background and Ecological Screening Values.
- 4. Only detected concentrations of nickel, selenium, silver, and vanadium are shown.




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SEDIMENT SAMPLING RESULTS IN DRAINAGE WAYS: METALS



FIGURE **7-1.3**





- Sediment Sample
- Soil Sample
- Dart Sample Location
- Deep Core Sample Location
- Operations Areas
- Approximate Oil Extent
- Drainage Path
- Approximate location of containment boom during sampling activities

Contour Elevation

- 262.2 ft
- -- 262.87 ft

NOTES:


- 1. Data boxes present maximum detections for each analyte at each location, and the associated sample depth interval at which the maximum detection was recorded (i.e., 0-0.5 foot, 0.5-1.0 foot, or 1.0-1.5 feet).
- 2. Polycyclic Aromatic Hydrocarbon concentrations are presented in micrograms per kilogram (µg/kg).
- 3. Yellow highlighted cells identify concentrations above the Ecological Screening Values.
- 4. PAH summations are based on the Priority+2 List and the Long List of PAHs (Table 5-3).



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT


SEDIMENT SAMPLING RESULTS IN DAWSON COVE: PAHS








- 1. Total Polycyclic Aromatic Hydrocarbon Toxic
- collected at depths of 0-0.5 foot below sediment



MAYFLOWER PIPELINE INCIDENT RESPONSE **EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT**

> **SEDIMENT SAMPLING RESULTS IN DAWSON COVE: TOXIC UNIT**








- Sediment Sample
- Soil Sample
- Dart Sample Location
- Deep Core Sample Location
- Operations Areas
- Approximate Oil Extent (Source: ARCADIS, May 2013)
- Drainage Path
- Approximate location of containment boom during sampling activities

Contour Elevation

- -- 262.2 ft
- -- 262.87 ft

NOTES:


- 1. Metals were analyzed in cores collected from 0-1.5 feet bgs; data boxes present maximum detections for each analyte at each location, and the associated sample depth interval at which the maximum detection was recorded (i.e., 0-0.5 foot, 0.5-1.0 foot, or 1.0-1.5 feet).
- 2. Metals concentrations are presented in milligrams per kilogram.
- 3. Yellow highlighted cells identify concentrations above the Arkansas Background and Ecological Screening Values.
- 4. Only detected concentrations of nickel, selenium, silver, and vanadium are shown.



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SEDIMENT SAMPLING RESULTS IN DAWSON COVE: METALS





- Sediment Sample Location
- Re-sampled Sediment Location Approximate location of
- containment boom during sampling activities
- Turbidity Curtain
- Operations Areas


Map Date: 1/6/2014



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SEDIMENT SAMPLING RESULTS IN LAKE CONWAY: PAHS





Sediment Sample Location

Re-sampled Sediment Location
 Approximate location of
 containment boom during
 sampling activities

--- Turbidity Curtain

Operations Areas

Map Date: 1/8/2014




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SEDIMENT SAMPLING RESULTS IN LAKE CONWAY: TOXIC UNIT



FIGURE

7-3.2



LEGEND

- Sediment Sample Location
- Re-sampled Sediment Location Approximate location of containment boom during
- sampling activities --- Turbidity Curtain
- Operations Areas


Map Date: 1/3/2014



MAYFLOWER PIPELINE INCIDENT RESPONSE **EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT**

> SEDIMENT SAMPLING RESULTS IN LAKE CONWAY: METALS





USCS Soil Group Symbol: CL = Inorganic clay of low plasticity, lean clay ML = Inorganic silt SM = Silty sand = Subsurface Observation of Gray Sediment (Silty Sand) = Subsurface Observation of Brown Sediment (Silty Sand) = Subsurface Observation of Brown Sediment (Clay) = Subsurface Observation of Brown Sediment (Silty Sand)

Notes:

- 1. All sediments described in the field using the Unified Soil Classification System (USCS).
- 2. All sediment colors depicted are approximate representations of colors observed during field sampling.


MAYFLOWER PIPELINE INCIDENT RESPONSE

EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

LAKE CONWAY
DEPOSITIONAL LAYER ASSESSMENT:
CORE PROFILES WITH SURFACE BROWN LAYER



7-4.1



USCS Soil Group Symbol:

CL = Inorganic clay of low plasticity, lean clay

ML = Inorganic silt

SM = Silty sand

Color Legend:

= Surface Sediment Layer (Silt)

= Subsurface Observation of Gray Sediment (Silt, Clay or Silty Sand)

= Subsurface Observation of Brown Sediment (Silty Sand)

= Subsurface Observation of Brown Sediment (Clay)

= Subsurface Observation of Brown Sediment (Silt)

Notes:

- 1. All sediments described in the field using the Unified Soil Classification System (USCS).
- 2. All sediment colors depicted are approximate representations of colors observed during field sampling.


MAYFLOWER PIPELINE INCIDENT RESPONSE

EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

LAKE CONWAY
DEPOSITIONAL LAYER ASSESSMENT:
CORE PROFILES WITHOUT SURFACE
BROWN LAYER



7-4.2



▲ Surface Water Sample Location WS-001 VOC Above Ecological Screening Value (ESV) (4/2/2013) Most Recent Date Above ESV

Source Point

Stream/River: Intermittent

Stream/River: Perennial

Approximate Surface Water Flow Direction

VOC Volatile Organic Compounds

*Evaluation based on the data collected between March 29 and October 31, 2013. No VOC exceedances above ESV at any sample location since April 13, 2013.



MAYFLOWER PIPELINE INCIDENT RESPONSE **EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY** DOWNSTREAM AREAS DATA ASSESSMENT REPORT

DAILY SURFACE WATER SAMPLE LOCATIONS WITH **VOC CONCENTRATION ABOVE ESV**



FIGURE

VOCs D	etected < 1%	of Samples		
Analyte shading = not detected in crude oil	Total Samples	Total Detections	Detection Frequency (%)	Last Date Detected
1,1-Dichloroethene	1864	11	0.6%	10/15/13
1,2,4-Trimethylbenzene	1864	15	0.8%	10/28/13
1,2-Dichloroethane	1864	1	0.1%	10/23/13
1,3,5-Trimethylbenzene	1864	5	0.3%	10/28/13
2-Butanone	1864	1	0.1%	07/08/13
Benzene	1864	6	0.3%	10/28/13
Bromoform (Tribromomethane)	1864	1	0.1%	10/23/13
Diethyl Ether (Ethyl ether)	1842	1	0.1%	05/08/13
Ethylbenzene	1864	6	0.3%	10/28/13
Methylene Chloride (Dichloromethane)	1864	2	0.1%	08/20/13
n-Propylbenzene	1864	1	0.1%	05/08/13
Tetrahydrofuran	1842	3	0.2%	06/19/13
Trichloroethene	1864	5	0.3%	10/23/13

	VOCs	Detected ≥ 1%	of Samples		
Analyte shading = not detected in crude oil	Total Samples	Total Detections	Detection Frequency (%)	Detected Concentration Range (µg/L)	Ecological Screening Value (ESV) (μg/L)
Acetone	1864	82	4%	3.0 - 16.0	1500
p-Isopropyltoluene (Cymene)	1864	31	2%	0.1 - 22.0	85
Toluene	1864	131	7%	0.1 - 15.0	175
Total Xylenes	1864	46	2%	0.1 - 6.8	13

 μ g/L = micrograms per liter

RL = reporting limit

USEPA = U.S. Environmental Protection Agency


VOC = volatile organic compound


WS-001D = deep sample

WS-001S = shallow sample

No detected VOC concentrations above ESV at any location within Lake Conway.

The graphs below show benzene and total xylenes concentrations with time for the locations that had at least one detection.





- 1. Evaluation based on the following locations in Lake Conway: WS-001S, WS-001D, WS-002, WS-003, WS-006S, WS-006D, WS-009, WS-010S, WS-011D, WS-012S, WS-012D, WS-018S, WS-018D, and WS-021.
- 2. No benzene detections above RLs at locations WS-001D, WS-002, WS-006S, WS-006D, WS-009, WS-010S, WS-010D, WS-011D, WS-011D, WS-012D, WS-018D, and WS-021. The reporting limit was 1.0 μ g/L from March 29 to April 4, 2013 and has been 0.5 μ g/L since April 5, 2013.
- 3. No total xylene detections above RLs at locations WS-006S, WS-006D, WS-010S, WS-010D, WS-011D, WS-012S, WS-018S, WS-018D, and WS-021. The reporting limit was 3.0 µg/L from March 29 to April 4, 2013 and has been 0.5 µg/L since April 5, 2013.
- 4. Naphthalene was not detected when analyzed with VOCs (USEPA 8260) and therefore was not reported in this figure; naphthalene was analyzed with the polycyclic aromatic hydrocarbons (USEPA 8270 selective ion monitoring) and is reported with Figures 8-4 through 8-8.
- 5. Sampling at WS-001S and WS-006S was discontinued on July 14, 2013. Sampling at WS-009 and WS-021 was discontinued in April 2013.
- 6. VOC analyses were discontinued on October 31, 2013.

MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

EVALUATION OF VOCs IN LAKE CONWAY SURFACE WATER (MARCH 29 - OCTOBER 31, 2013)



FIGURE


VOCs I	Detected < 1%	of Samples		
Analyte	Total	Total	Detection	Last Date
shading = not detected in crude oil	Samples	Detections	Frequency (%)	Detected
1,2,3-Trichlorobenzene	523	2	0.4%	6/14/2013
2-Phenylbutane	514	1	0.2%	9/9/2013
Chloromethane	523	1	0.2%	6/19/2013
Tetrahydrofuran	514	1	0.2%	6/19/2013


<u>Benzene and Total Xylenes</u> are the only VOCs that have been detected at concentrations above the associated ecological screening values.

- o *Benzene* has only been detected above the ESV in 2 of the 523 samples analyzed through October 31, 2013 [see graph below]. Benzene has not been detected in any Dawson Cove samples since May 6, 2013.
- o *Total Xylenes* has been detected above the ESV in 5 of the 523 samples analyzed through October 31, 2013 [see graph below]. Total xylenes has not been detected in any Dawson Cove samples since June 1, 2013.

The graphs below show benzene and total xylenes concentrations with time for the locations that had at least one detection.

	VOCs	Detected ≥ 1%	of Samples		
Analyte shading = not detected in crude oil	Total Samples	Total Detections	Detection Frequency (%)	Detected Concentration Range (µg/L)	Ecological Screening Value (ESV) (μg/L)
1,2,4-Trimethylbenzene	523	40	8%	0.1 - 5.9	33
1,3,5-Trimethylbenzene	523	78	15%	0.1 - 4.2	71
2-Butanone (MEK)	523	42	8%	1.0 - 6.1	14000
Acetone	523	376	72%	3.0 - 24	1500
Benzene	523	39	7%	0.1 - 102	53
Ethylbenzene	523	18	3%	0.1 - 6.0	453
Isopropylbenzene (Cumene)	523	12	2%	0.1 - 1.1	2.6
n-Propylbenzene	523	9	2%	0.1 - 0.3	128
p-Isopropyltoluene (Cymene)	523	24	5%	0.1 - 0.2	85
Toluene	523	324	62%	0.1 - 77.7	175
Xylene (Total)	523	84	16%	0.1 - 59.2	13





Notes:

μg/L = micrograms per liter

USEPA = U.S. Environmental Protection Agency

WS-004D = deep sample

RL = reporting limit VOC = volatile organic compound

WS-004S = shallow sample


- 1. Evaluation based on the following locations in Dawson Cove: WS-004S, WS-004D, WS-007S, WS-007D, and WS-020.
- 2. No benzene detections above RLs at location WS-020. The reporting limit was 1.0 µg/L from March 29 to April 4, 2013 and has been 0.5 µg/L since April 5, 2013.
- 3. No total xylene detections above RLs at location WS-020. The reporting limit was 3.0 µg/L from March 29 to April 4, 2013 and has been 0.5 µg/L since April 5, 2013.
- 4. Naphthalene was not detected when analyzed with VOCs (USEPA 8260) and therefore was not reported in this figure; naphthalene was analyzed with the polycyclic aromatic hydrocarbons (USEPA 8270 selective ion monitoring) and is reported with Figures 8-4 through 8-8.
- 5. Sampling at WS-004S, WS-004D, and WS-007S was discontinued on July 14, 2013.
- 6. VOC analyses were discontinued on October 31, 2013.

MAYFLOWER PIPELINE INCIDENT RESPONSE
EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY
DOWNSTREAM AREAS DATA ASSESSMENT REPORT

EVALUATION OF VOCs IN DAWSON COVE SURFACE WATER (MARCH 29 - OCTOBER 31, 2013)



FIGURE 8-3



Surface Water Sample Location
WS-001
PAH Above Environmental
Screening Value (ESV)

(8/4/2013) Most Recent Date Above ESV

Source Point

Parcel Boundary

~ - Stream/River: Intermittent

Stream/River: Perennial

between March 29 and October 31, 2013.

Approximate Surface Water Flow Direction PAH Polycyclic aromatic hydrocarbon *Evaluation based on the data collected




MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

DAILY SURFACE WATER SAMPLE LOCATIONS WITH PAH CONCENTRATION ABOVE ESV



FIGURE



Surface Water Sample Location
WS-010 PAH Above Ecological
Screening Value (ESV)

(12/26/2013) Most Recent Date Above ESV



--- Parcel Boundary

--- Stream/River: Intermittent

Stream/River: Perennial

Approximate Surface Water Flow Direction

PÅH Polycyclic aromatic hydrocarbon *Evaluation based on the data collected between November 1 and December 31, 2013.



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

WEEKLY SURFACE WATER SAMPLE LOCATIONS WITH PAH CONCENTRATION ABOVE ESV (NOVEMBER 1-DECEMBER 31,2013)




FIGURE


		PAHs with	No Detection	s Above ESV			
				All Sampling (3/30/2013 - 12			
	ESV	Total	Total	Detection	Maximum	Maximum	Maximum
Analyte	(µg/L)	Samples	Detections	Frequency (%)	(µg/L)	Location	Date
1-Methylnaphthalene	2.1	470	0	0%			
2-Methylnaphthalene	4.7	470	3	0.6%	0.012	WS-014S	7/21/2013
Acenaphthene	17	474	1	0.2%	0.16	WS-005	7/4/2013
Acenaphthylene	4840	474	0	0%			
Anthracene	0.012	474	0	0%			
Benzo(a)Anthracene	0.018	474	2	0.4%	0.016	WS-014S	12/12/2013
Benzo(b)Fluoranthene	9.07	474	9	2%	0.079	WS-014S	12/12/2013
Benzo(g,h,i)Perylene	7.64	474	7	1%	0.14	WS-014S	12/12/2013
Benzo(k)Fluoranthene		474	3	0.6%	0.08	WS-014S	12/12/2013
Chrysene		474	4	0.8%	0.022	WS-005	5/17/2013
Dibenz(a,h)Anthracene		474	4	0.8%	0.13	WS-014S	12/12/2013
Fluoranthene	39.8	474	6	1%	0.060	WS-005	5/17/2013
Fluorene	3	474	0	0%			
Indeno[1,2,3-cd]Pyrene	4.31	474	6	1%	0.13	WS-014S	12/12/2013
Naphthalene	62	474	45	9%	0.17	WS-005	7/11/2013
Phenanthrene	0.4	474	0	0%			

Notes:

- -- = no criteria available or not applicable
- ESV = Ecological screening value
- μg/L = micrograms per liter
- PAH = polycyclic aromatic hydrocarbon
- RL = reporting limit
- RCRA = Resource Conservation and Recovery Act
- USEPA = U.S. Environmental Protection Agency
- WS-014D = deep sample
- WS-014S = shallow sample
- 1. Evaluation based on the following background locations in Lake Conway: WS-005, WS-014S, WS-14D, WS-015S, and
- 2. Sampling at WS-005 was discontinued on October 31, 2013.
- 3. Weekly surface water sampling started from November 1, 2013.

					PAHs with Dete	ections Above	ESV in Daily	/ Samples bu	ıt, No Detecti	ons Above ESV i	n Weekly Saı	mples					
				All	Sampling Resu	lts			Recent	Daily Sampling R	esults			Week	ly Sampling I	Results	
				(3/3	0/2013 - 12/31/20	013)		(10/1/2013 - 10/31/2013)						(11/1	/2013 - 12/31	/2013)	
		ESV	Total	Total	Detection		Above	Total	Total	Detection	Range	Above	Total	Total	Maximum	Maximum	Maximum
	Analyte	(µg/L)	Samples						Detections	Frequency (%)	(µg/L)	ESV	Samples	Detections	(µg/L)	Location	Date
Р	Pyrene	0.025	474	22	5%	0.011-1.5	14	93	4	4%	0.02-0.086	3	32	0			





- samples collected since December 12, 2013.
- o *Pyrene*: For the entire monitoring period, there were fourteen detected concentrations above the ESV. The ESV of 0.025 µg/L is from Region 3 and is based on a value identified in 1999 by the Canadian Council of Ministers of the Environment (CCME). There was one detected concentration of pyrene on August 22, 2013 above the alternate ESV of 0.39 µg/L established by USEPA Region 5 as a RCRA Interim Criterion (USEPA 2003). There are no detected concentrations in weekly samples.
 - = Approximate timeframe with no flow through Dawson Cove culverts to Lake Conway

MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

EVALUATION OF PAHS IN BACKGROUND SURFACE WATER (MARCH 30 - DECEMBER 31, 2013)



FIGURE 8-6

		PAHs	with No Detect	tions Above ESV			
				All Sampling (3/29/2013 - 1	•		
	ESV	Total	Total	Detection	Maximum	Maximum	Maximum
Analyte	(µg/L)	Samples	Detections	Frequency (%)	(µg/L)	Location	Date
1-Methylnaphthalene	2.1	1920	19	1%	0.069	WS-003	5/8/2013
2-Methylnaphthalene	4.7	1920	34	2%	0.13	WS-003	5/8/2013
Acenaphthene	17	1942	4	0.2%	0.083	WS-002	7/4/2013
Acenaphthylene	4840	1942	6	0.3%	0.054	WS-012D	9/27/2013
Benzo(b)Fluoranthene	9.07	1942	73	4%	0.91	WS-006S	7/8/2013
Benzo(g,h,i)Perylene	7.64	1942	27	1%	0.27	WS-006S	7/8/2013
Benzo(k)Fluoranthene	-	1942	28	1%	0.48	WS-006S	7/8/2013
Chrysene		1942	66	3%	0.60	WS-006S	7/8/2013
Dibenz(a,h)Anthracene		1942	13	0.7%	0.23	WS-006S	7/8/2013
Fluoranthene	39.8	1942	78	4%	0.64	WS-006S	7/8/2013
Fluorene	3	1942	4	0.2%	0.22	WS-006S	7/8/2013
Indeno[1,2,3-cd]Pyrene	4.31	1942	30	2%	0.33	WS-006S	7/8/2013
Naphthalene	62	1942	311	16%	0.56	WS-003	7/17/2013
Phenanthrene	0.4	1942	4	0.2%	0.071	WS-001D	9/5/2013

Notes:

-- = no criteria available ESV = Ecological screening value

μg/L = micrograms per liter PAH = polycyclic aromatic hydrocarbon RL = reporting limit

RCRA = Resource Conservation and Recovery Act
USEPA = U.S. Environmental Protection Agency

WS-001D = deep sample

1. Evaluation based on the following locations in Lake Conway: WS-001S, WS-001D, WS-002, WS-003, WS-006S, WS-006D, WS-009, WS-010S, WS-010D, WS-011S, WS-011D, WS-012S, WS-012D, WS-018S, WS-018D, and WS-021.


- 2. No pyrene detections in weekly samples collected from WS-010S, WS-011S, and WS-012S.
- 3. Sampling at WS-001S and WS-006S was discontinued on July 14, 2013. Sampling at WS-009 and WS-021 was discontinued from April through October 2013. Sampling at WS-002, WS-003, WS-018S, and WS-018D was discontinued on October 31, 2013.
- 4. Weekly surface water sampling started from November 1, 2013.

Anthracene and Benzo(a)Anthracene were detected with concentrations above the ESV in daily samples.

- o *Anthracene*: There was only one detected concentration above the ESV in a daily sample collected at WS-010S (0.014 μg/L) on October 23, 2013. There are no detected concentrations in weekly samples.
- o *Benzo(a)Anthracene*: There were ten detected concentrations above ESV until September 30, 2013. There are no detected concentrations in recent daily samples. There is one detected concentration of 0.017 μg/L (WS-011D) in weekly samples.

				PAHs	with Detection	ns Above ESV	in Daily San	nples but, No	Detections Abov	ve ESV in Weekl	y Samples						
			Α	II Sampling Resu	lts			Recer	nt Daily Sampling	g Results			Wee	kly Sampling R	esults		
			(3/	30/2013 - 12/31/20)13)			(1	0/1/2013 - 10/31/2	2013)		(11/1/2013 - 12/31/2013)					
	ESV Total Total Detection Range							Total	Detection			Total	Total	Maximum	Maximum	Maximum	
Analyte	(µg/L)	Samples	Detections	Frequency (%)	(µg/L)	Above ESV	Samples	Detections	Frequency (%)	Range (µg/L)	Above ESV	Samples	Detections	(µg/L)	Location	Date	
Anthracene	0.012	1942	9	0.5%	0.013-0.23	8	338	1	0.3%	0.014	1	80	0				
Benzo(a)Anthracene	0.018	1942	31	2%	0.011-0.51	10	338	0	0%			80	4	0.017	WS-011D	11/13/2013	

						P/	AHs with Dete	ections Above	ESV in Weekly	Samples							
			Α	II Sampling Resu	lts			Recer	nt Daily Sampling	g Results				Weekly Samp	oling Results		
			(3/	30/2013 - 12/31/20)13)			(1	0/1/2013 - 10/31/	2013)				(11/1/2013 -	12/31/2013)		
	ESV	Total	Total	Detection	Range		Total	Total	Detection			Total	Total		Maximum	Maximum	Maximum
Analyte	(µg/L)	Samples	Detections	Frequency (%)	(µg/L)	Above ESV	Samples	Detections	Frequency (%)	Range (µg/L)	Above ESV	Samples	Detections	Above ESV	(µg/L)	Location	Date
Benzo(a)Pyrene	0.015	1942	23	1%	0.011-0.51	15	338	0	0%			80	4	3	0.021	WS-009	12/11/2013
Pyrene	0.025	1942	135	7%	0.011-1.0	55	338	4	1%	0.012-0.031	2	80	14	5	0.11	WS-021	11/13/2013



Benzo(a)Pyrene and Pyrene had detected concentrations above the ESV in weekly samples collected between November 1 and December 31, 2013.

WS-001S = shallow sample

- o **Benzo(a)Pyrene**: There were three detected concentrations above the ESV in a weekly sample collected at WS-009 (0.021 μ g/L) on December 11, 2013 and samples collected at WS-006D (0.017 μ g/L) and WS-010D (0.019 μ g/L) on December 26, 2013.
- o *Pyrene*: For the weekly samples, there were five detected concentration above the ESV of 0.025 μg/L. For the entire monitoring period, there were 54 detected concentrations (50 daily and 5 weekly samples) above the ESV. The maximum detected pyrene concentration of 1.0 μg/L in Lake Conway samples is less than the maximum of 1.5 μg/L detected pyrene concentration in a background sample. The ESV of 0.025 μg/L is from Region 3 and is based on a value identified in 1999 by the Canadian Council of Ministers of the Environment (CCME). There were three detected concentrations of pyrene above the alternate ESV of 0.39 μg/L established by USEPA Region 5 as a RCRA Interim Criterion (USEPA 2003). Locations WS-002, WS-003, WS-011, and WS-012 are not located adjacent to the Dawson Cove outlet.
 - = Approximate timeframe with no flow through Dawson Cove culverts to Lake Conway

MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

EVALUATION OF PAHS IN LAKE CONWAY SURFACE WATER (MARCH 29 - DECEMBER 31, 2013)



FIGURE

		PAHs w	ith No Detectio	ns Above ESV			
				All Samplir	_		
				(3/29/2013 -			
	ESV		Total	Detection	Maximum	Maximum	Maximum
Analyte	(µg/L)	Total Samples	Detections	Frequency (%)	(µg/L)	Location	Date
1-Methylnaphthalene	2.1	536	264	49%	0.50	WS-007D	4/5/2013
2-Methylnaphthalene	4.7	536	251	47%	0.47	WS-004S	5/5/2013
Acenaphthene	17	545	128	23%	0.76	WS-007D	7/20/2013
Acenaphthylene	4840	545	118	22%	2.7	WS-007D	7/20/2013
Benzo(g,h,i)Perylene	7.64	545	217	40%	6.1	WS-007D	6/26/2013
Benzo(k)Fluoranthene		545	215	39%	9.6	WS-007D	6/26/2013
Chrysene		545	313	57%	33	WS-007D	6/26/2013
Dibenz(a,h)Anthracene		545	105	19%	1.9	WS-007D	7/20/2013
Fluorene	3	545	185	34%	1.0	WS-007D	7/22/2013
Naphthalene	62	545	162	30%	0.93	WS-004S	4/2/2013

Notes:

-- = no criteria available ESV = Ecological screening value

µg/L = micrograms per liter

PAH = polycyclic aromatic hydrocarbon

RL = reporting limit


RCRA = Resource Conservation and Recovery Act USEPA = U.S. Environmental Protection Agency

WS-004D = deep sample WS-004S = shallow sample

- 1. Evaluation based on the following locations in Dawson Cove: WS-004S, WS-004D, WS-007S, WS-007D, and WS-020.
- 2. No pyrene detections above RLs at location WS-020. The reporting limit was 0.1 μg/L from March 29 to April 4, 2013 and has been 0.05 μg/L since April 5, 2013.
- 3. Sampling at WS-004S and WS-007S was discontinued on July 14, 2013. Sampling at WS-004D was discontinued from July 15 through October 31, 2013. Sampling at WS-020 was discontinued from April through October 2013.
- 4. Weekly surface water sampling started from November 1, 2013.

				PAHs with Detec	ctions Above	e ESV in Dai	ly Samples	but, No Dete	ctions Above ES	V in Weekly Sa	nples					
				mpling Results 013 - 12/31/2013)					ent Daily Samplin (10/1/2013 - 10/31	_				dy Sampling 1/2013 - 12/31		
Analyte	ESV (μg/L)	Total Samples	Total Detections	Detection Frequency (%)	Range (µg/L)	Above ESV	Total Samples	Total Detections	Detection Frequency (%)	Range (µg/L)	Above ESV	Total Samples	Total Detections	Maximum (μg/L)	Maximum Location	Maximum Date
Anthracene	0.012	545	193	36%	0.011-3.4	181	31	0	0%			24	0		-	
Benzo(b)Fluoranthene	9.07	545	304	56%	0.011-31	6	31	4	13%	0.015-0.023	0	24	8	0.035	WS-007D	11/13/2013
Fluoranthene	39.8	545	329	60%	0.011-47	1	31	5	16%	0.011-0.022	0	24	8	0.031	WS-007D	12/11/2013
Indeno[1,2,3-cd]Pyrene	4.31	545	208	38%	0.011-6.7	3	31	2	6%	0.011-0.012	0	24	2	0.019	WS-020	12/18/2013
Phenanthrene	0.4	545	178	34%	0.031-8.7	34	31	0	0%			24	1	0.033	WS-020	11/13/2013

						PAHs wit	h Detectio	ns Above ES	/ in Weekly Sam	oles							
			All Sa	mpling Results				Rec	ent Daily Samplin	g Results				Weekly San	pling Results		
			(3/30/20	013 - 12/31/2013)			(10/1/2013 - 10/31/2013)							(11/1/2013	- 12/31/2013)		
	ESV		Total	Detection	Range		Total	Total Total Detection					Total		Maximum	Maximum	Maximum
Analyte	(µg/L)	Total Samples	Detections	Frequency (%)	(µg/L)	Above ESV	Samples	Detections	Frequency (%)	Range (µg/L)	Above ESV	Samples	Detections	Above ESV	(µg/L)	Location	Date
Benzo(a)Anthracene	0.018	545	229	42%	0.011-10	168	31	0	0%			24	1	1	0.019	WS-007D	11/13/2013
Benzo(a)Pyrene	0.015	545	207	39%	0.011-9.0	173	31	0	0%	==		24	2	1	0.016	WS-007D	11/13/2013
Pyrene	0.025	545	365	68%	0.011-38	249	31	5	16%	0.011-0.02	0	24	9	1	0.038	WS-004D	11/20/2013



Anthracene, benzo(b)fluroanthene, fluoranthene, indeno(1,2,3-cd)pyrene, and phenanthrene were detected above their respective ESVs in past daily samples but, have not been detected at concentrations above ESVs in recent daily samples collected in October 2013 or in weekly samples collected between November 1 and December 31, 2013.

o *Anthracene* was detected above the ESV of 0.012 μg/L in 181 daily samples with a maximum concentration of 3.4 μg/L in a sample collected at WS-007D on September 28, 2013. Anthracene has not been detected in samples collected since September 29, 2013.

o Benzo(b)fluroanthene was detected above the ESV of 9.07 μ g/L in six daily samples with a maximum concentration of 31 μ g/L in a sample collected at WS-007D on June 26, 2013. Benzo(b)fluoranthene has not been detected above the ESV in samples collected since July 23, 2013.

o *Fluoranthene* was detected above the ESV of 39.8 μg/L in only one sample (47 μg/L) collected at WS-007D on June 26, 2013. Fluoranthene has not been detected above the ESV in samples collected since June 26, 2013.

o *Indeno[1,2,3-cd]pyrene* was detected above the ESV of 4.31 μg/L in three daily samples with a maximum concentration of 6.7 μg/L in a sample collected at WS-007D on June 26, 2013. Indeno[1,2,3-cd]pyrene has not been detected above the ESV in samples collected since July 23, 2013.

o **Phenanthrene** was detected above the ESV of 0.4 μ g/L in 34 daily samples with a maximum concentration of 8.7 μ g/L in a sample collected at WS-007D on June 26, 2013. Phenanthrene has not been detected above the ESV in samples collected since July 30, 2013.

Benzo(a)anthracene, benzo(a)pyrene, and pyrene were detected above their respective ESVs in weekly samples collected between November 1 and December 31, 2013.

o *Benzo(a)anthracene*: There was one detected concentration (0.019 μg/L) above the ESV of 0.018 μg/L on November 13, 2013.

o *Benzo(a)pyrene*: There was one detected concentration (0.016 μg/L) above the ESV of 0.015 μg/L on November 13, 2013.

o *Pyrene*: For the weekly samples, there was one detected concentraion (0.038 μ g/L) above the Region 3 ESV of 0.025 μ g/L. For the entire monitoring period, there were 249 detected concentrations (248 daily and 1 weekly samples) above the Region 3 ESV (0.025 μ g/L) which is based on a value identified in 1999 by the Canadian Council of Ministers of the Environment (CCME). Since September 14, 2013, there were no detected concentrations of pyrene above the alternate ESV of 0.39 μ g/L established by USEPA Region 5 as a RCRA Interim Criterion (USEPA 2003).

MAYFLOWER PIPELINE INCIDENT RESPONSE
EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY
DOWNSTREAM AREAS DATA ASSESSMENT REPORT

EVALUATION OF PAHs IN DAWSON COVE SURFACE WATER (MARCH 29 - DECEMBER 31, 2013)

ARCADIS

FIGURE 8-8


15


Pyrene and phenanthrene shown for illustration purposes. Similar trends observed for anthrancene, benzo(a)anthracene, benzo(a)pyrene, benzo(b)fluoranthene, fluoranthene, and indeno(1,2,3-cd)pyrene.

= Approximate timeframe with no flow through Dawson Cove culverts to Lake Conway

			Summary of Oil & Gro	ease Data							
				Sampling Results 2013 - 10/31/2013)							
			Detection Frequency	Detection Range	Maximum Detected	Maximum	Maximum				
Analyte	Total Samples Total Detections (%) (mg/L) Concentration (mg/L) Location Date										
Oil & Grease	1788	415	23%	1.4 - 10.1	10.1	WS-008	5/29/2013				

There has been only one Oil & Grease concentration above the Guideline Average Concentration of 10 mg/L at WS-008 (10.1 mg/L) on May 29, 2013 (location in the drainage way along Main St, not graphed below). There have been no recent detected concentrations above the Guideline Average or Maximum Concentrations.





Notes:

mg/L = milligrams per liter RL = reporting limit WS-001D = deep sample WS-001S = shallow sample

- 1. Graphs show Oil & Grease concentrations with time for locations that had more than one detection of Oil & Grease.
- 2. Lake Conway evaluation based on the locations WS-001S, WS-001D, WS-002, WS-003, WS-006S, WS-006D, WS-009, WS-010S, WS-010D, WS-011S, WS-011D, WS-012S, WS-012D, WS-018, and WS-021. Samples from WS-009 and WS-021 were not analyzed for Oil & Grease.
- 3. Dawson Cove evaluation based on the locations WS-004S, WS-004D, WS-007S, WS-007D, and WS-020. Samples from WS-020 were not analyzed for Oil & Grease.
- 4. No Oil & Grease detections above the RL of 5 mg/L at locations WS-BKG-001 and WS-BKG-002.
- 5. Evaluation based on data for surface water samples collected from April 9 through October 31, 2013.
- 6. Average and Maximum Guideline Concentrations are based on Arkansas Pollution Control and Ecology Commission Regulation No. 2.
- 7. Sampling at WS-001S, WS-004S, WS-004D, WS-006S, and WS-007S was discontinued on July 14, 2013. Sampling at WS-009 and WS-021 was discontinued in April 2013. There was no flow in WS-008 between June 19 and August 11, 2013, and therefore, the location was not sampled.
- 8. Oil & Grease analyses were discontinued on October 31, 2013.

MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

EVALUATION OF OIL & GREASE IN SURFACE WATER (APRIL 9 - OCTOBER 31, 2013)




FIGURE

					Metals with I	No Dissolved	Concentrations I	Detected Above	ESV					
Analyte				ved Metals Samp /15/2013 - 10/31/2	•				To	otal Metals Sampling R (7/15/2013 - 10/31/20				
shading = not detected in	ESV*	Dissolved	Dissolved	Detection	Range	Average		Total	Detection	Minimum Detected	Average	Maximum	Maximum	Maximum
crude oil	(mg/L)	Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	Total Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	(mg/L)	Location	Date
Arsenic	0.15	315	16	5%	0.0068-0.0103	0.0078	315	45	14%	0.0069	0.0084	0.017	WS-005	9/17/2013
Cadmium	0.00037	315	0	0%			315	1	0.3%		0.0048		WS-014S	9/13/2013
Calcium	116						315	315	100%	3.9	6.21	18.3	WS-005	10/5/2013
Chromium	0.0572	315	1	0.3%		0.0038	315	34	11%	0.0016	0.0025	0.067	WS-014S	10/11/2013
Magnesium	82						315	315	100%	2.00	2.81	6.62	WS-005	10/5/2013
Mercury	0.00077	315	1	0.3%		0.00077	315	4	1%	0.000067	0.00007	0.000079	WS-014S	9/28/2013
Nickel	0.049	314	14	4%	0.0015-0.0026	0.0017	315	77	24%	0.0015	0.0023	0.011	WS-014S	7/20/2013
Selenium	0.005	315	0	0%			315	0	0%		-			
Silver	0.0003	315	0	0%			315	0	0%					
Vanadium	0.02	315	0	0%			315	12	4%	0.0021	0.0027	0.005	WS-005	9/17/2013

^{*}All ESVs are for dissolved metals, except for arsenic and mercury. ESVs for arsenic and mercury are for total metals.

					Metal with	Dissolved Co	ncentrations De	tected Above ES	V					
			Recent Diss	solved Metals San	npling Results				Recen	t Total Metals Samplir	ng Results			
Analyte			(1	(10/1/2013 - 10/31/2013) (10/1/2013 - 10/31/2013)										
shading = not detected in	ESV	Dissolved	Dissolved	issolved Detection Range Average Total Detection Minimum Detected Average Maximum Maximum Maximum										
crude oil	(mg/L)	Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	Total Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	(mg/L)	Location	Date
Barium	0.004	93	93	100%	0.012-0.11	0.020	93	93	100%	0.019	0.037	0.139	WS-005	10/5/2013
Lead	0.00054	93	1 1% 0.0049 93 2 2% 0.0055 0.0055 WS-005; WS-014S 10/31/2013											



Between July 15 and October 31, 2013, dissolved barium concentrations in background surface water samples ranged from 0.0051 to 0.011 mg/L, above the ESV of 0.004 mg/L.

The Barium ESV is a secondary chronic value developed by the USEPA for the Great Lakes Water Quality Initiative, as cited in Suter and Tsao (1996). Suter and Tsao (1996) include a comment about this ESV: "Background water concentrations should be used as a check for these benchmarks [i.e., ESVs]. That is, because some of these benchmarks are quite conservative and because the measured concentrations in ambient water may include forms that are not bioavailable, benchmark concentrations may be lower than background water concentrations. If the background concentrations are valid and represent an uncontaminated state and if exposed site does not contain forms of the chemicals that are more bioavailable or toxic than the forms at background sites, then screening benchmarks lower than the background concentration should not be used."

Notes:

-- = no criterion available or not applicable

ESV = Ecological screening value

mg/L = milligrams per liter

USEPA = U.S. Environmental Protection Agency

WS-014D = deep sample

WS-014S = shallow sample

- 1. Evaluation based on the following background locations in Lake Conway: WS-005, WS-014S, and WS-14D.
- 2. Metals analyses were discontinued on October 31, 2013.

EXXONMOBIL PIPELINE COMPANY
MAYFLOWER PIPELINE INCIDENT RESPONSE
MAYFLOWER, ARKANSAS
SURFACE WATER DATA EVALUATION

EVALUATION OF METALS IN BACKGROUND
SURFACE WATER (JULY 15 - OCTOBER 31, 2013)

FIGURE
ARCADIS


8-10

				Metals N	Not Detected in Crud	le Oil or with	No Dissolved Cor	ncentrations De	tected Above ES\	I				
Analyte				olved Metals Samp 7/15/2013 - 10/31/2					Т	otal Metals Sampling (7/15/2013 - 10/31/20				
shading = not detected in	ESV*	Dissolved	Dissolved	Detection	Range	Average		Total	Detection	Minimum Detected	Áverage	Maximum	Maximum	Maximum
crude oil	(mg/L)	Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	Total Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	(mg/L)	Location	Date
Arsenic	0.15	1159	59	5%	0.0068-0.0102	0.0077	1159	196	17%	0.0069	8800.0	0.0316	WS-006D	7/21/2013
Calcium	116						1159	1159	100%	4.03	6.1	11.5	WS-006D	7/21/2013
Chromium	0.0572	1159	6	0.5%	0.0017-0.0091	0.0030	1159	72	6%	0.0016	0.048	0.0357	WS-006D	7/27/2013
Magnesium	82						1159	1159	100%	1.91	2.87	8.14	WS-006D	7/21/2013
Mercury	0.00077	1159	10	1%	0.000061-0.0011	0.00025	1159	24	2%	0.000062	0.000093	0.0002	WS-018S	7/23/2013
Nickel	0.049	1159	26	2%	0.0015-0.0078	0.0020	1159	215	19%	0.0015	0.0026	0.0216	WS-006D	7/27/2013
Selenium	0.005	1159	0	0%			1159	0	0%		==			
Silver	0.0003	1159	0	0%			1159	5	0.4%	0.0021	0.0022	0.0024	WS-018S	7/25/2013
Vanadium	0.02	1159	1	0.1%		0.0073	1159	43	4%	0.002	0.012	0.0867	WS-006D	7/21/2013

^{*}All ESVs are for dissolved metals, except for arsenic and mercury. ESVs for arsenic and mercury are for total metals.

					Metals with No	Recent Dissolv	ed Concentration	s Detected Abo	ve ESV						
			Recent Dis	solved Metals San	npling Results				Rece	nt Total Metals Sampl	ing Results				
Analyte			('	10/1/2013 - 10/31/2	013)		(10/1/2013 - 10/31/2013)								
shading = not detected in	ESV	Dissolved	Dissolved	Detection	Range	Average		Total	Detection	Minimum Detected	Average	Maximum	Maximum	Maximum	
crude oil	(mg/L)	Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	Total Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	(mg/L)	Location	Date	
Cadmium	0.00037	338	0	0%			338	0	0%	-	1		1		

					Metals with	n Dissolved C	oncentrations Det	ected Above ES	SV					
			Recent Dis	solved Metals Sar	npling Results				Rece	nt Total Metals Sampl	ing Results			
Analyte			(10/1/2013 - 10/31/2013) (10/1/2013 - 10/31/2013)											
shading = not detected in	ESV	Dissolved	d Dissolved Detection Range Average Total Detection Minimum Detected Áverage Maximum Maximum Maximum											
crude oil	(mg/L)	Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	Total Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	(mg/L)	Location	Date
Barium	0.004	338	8 338 100% 0.015-0.056 0.020 338 338 100% 0.0229 0.038 0.118 WS-018S 10/13/2013											
Lead	0.00054	338	38 5 1% 0.0048-0.0066 0.0056 338 13 4% 0.0047 0.0051 0.0058 WS-012S 10/31/2013											



Barium, cadmium, and lead are the only metals that have dissolved concentrations above the ESV in Lake Conway samples.

- o *Barium* concentrations in the Lake Conway samples ranged from 0.0027 to 0.194 mg/L which is slightly higher than the range of dissolved barium, 0.0051 to 0.11 mg/L, detected in background surface water sample. Average barium concentrations in Lake Conway (0.020 mg/L) samples collected between October 1 and 31, 2013 is same as the background samples (0.020 mg/L) [see graph to left].
- o *Cadmium* was detected at a concentration of 0.0026 mg/L above the ESV of 0.00037 mg/L in one Lake Conway sample collected at WS-002 on August 11, 2013. Cadmium was not detected in any Lake Conway dissolved metal samples collected since August 11, 2013.
- o *Lead* was detected at concentrations above the ESV of 0.00054 mg/L in five Lake Conway dissolved samples collected on October 24, 2013. Lead was not detected in any Lake Conway dissolved metal samples collected since October 24, 2013.

Notes:

--= no criterion available or not applicable WS-001D = deep sample ESV = Ecological screening value WS-001S = shallow sample mg/L = milligrams per liter

- 1. Evaluation based on the following locations in Lake Conway: WS-001S, WS-001D, WS-002, WS-003, WS-006S, WS-006D, WS-010S, WS-010D, WS-011S, WS-011D, WS-012S, WS-012D, and WS-018S.
- 2. Sampling at WS-001S and WS-006S was discontinued on July 14, 2013.

3. Metals analyses were discontinued on October 31, 2013.

MAYFLOWER PIPELINE INCIDENT RESPONSE
EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY
DOWNSTREAM AREAS DATA ASSESSMENT REPORT

EVALUATION OF METALS IN LAKE CONWAY SURFACE WATER (JULY 15 - OCTOBER 31, 2013)

ARCADIS


FIGURE

					Metal	s with No Dis	ssolved Detection	ns Above ESV						
Analyte				ved Metals Sampl 15/2013 - 10/31/2	_					Total Metals Sampling (7/15/2013 - 10/31/2				
shading = not detected in	ESV*	Dissolved	Dissolved	Detection	Range	Average	I	Total	Detection	Minimum Detected	Average	Maximum	Maximum	Maximum
crude oil	(mg/L)	Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	Total Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	(mg/L)	Location	Date
Arsenic	0.15	109	12	11%	0.0068-0.0092	0.0074	109	69	63%	0.0068	0.016	0.113	WS-007D	7/26/2013
Cadmium	0.00037	109	0	0%			109	18	17%	0.0009	0.0023	0.0097	WS-007D	7/26/2013
Calcium	116						109	109	100%	2.17	6.20	43.6	WS-007D	7/26/2013
Chromium	0.0572	109	0	0%			109	54	50%	0.0016	0.028	0.259	WS-007D	7/26/2013
Magnesium	82						109	109	100%	1.0	3.6	36.1	WS-007D	7/26/2013
Mercury	0.00077	109	2	2%	0.000063	0.000063	109	19	17%	0.000061	0.00017	0.00044	WS-007D	8/31/2013
Nickel	0.049	109	33	30%	0.0015-0.0029	0.0020	109	83	76%	0.0015	0.021	0.279	WS-007D	7/26/2013
Selenium	0.005	109	0	0%			109	2	2%	0.0139	0.0175	0.0211	WS-007D	9/28/2013
Vanadium	0.02	109	0	0%			109	67	61%	0.0021	0.035	0.38	WS-007D	7/26/2013

^{*}All ESVs are for dissolved metals, except for arsenic and mercury. ESVs for arsenic and mercury are for total metals.

					Metals with No F	Recent Disso	ved Concentration	ons Detected Al	bove ESV					
			Recent Diss	olved Metals Sam	pling Results				Rece	ent Total Metals Sampl	ing Results			
			(10	0/1/2013 - 10/31/20)13)					(10/1/2013 - 10/31/2	013)			
Analyte	ESV	Dissolved	Dissolved	Detection	Range	Average		Total	Detection	Minimum Detected	Average	Maximum	Maximum	Maximum
	(mg/L)	Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	Total Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	(µg/L)	Location	Date
Silver	0.0003 31 0 0% 31 0 0%													

					Metals with	n Dissolved C	Concentrations D	etected Above I	ESV					
			Recent Diss	olved Metals Sam	pling Results				Rec	ent Total Metals Sampl	ing Results			
			(10/1/2013 - 10/31/2013) (10/1/2013 - 10/31/2013)											
Analyte	ESV	Dissolved												
	(mg/L)	Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	Total Samples	Detections	Frequency (%)	(mg/L)	(mg/L)	(µg/L)	Location	Date
Barium	0.004	31	1 31 100% 0.0047-0.0381 0.023 31 31 100% 0.0143 0.055 0.22 WS-007D 10/10/2013											
Lead	0.00054	31	31 1 3% 0.0057 31 14 45% 0.005 0.010 0.0336 WS-007D 10/13/2013											



Barium, Lead, and Silver are the only metals that have dissolved concentrations above the screening levels in Dawson Cove since July 15, 2013.

- o *Barium* concentrations in Dawson Cove dissolved samples ranged from 0.0047 to 0.0381 mg/L, which are less than the range of dissolved barium detected in background samples (0.0051 to 0.11 mg/L) and within the range of dissolved barium detected in the Lake Conway samples (0.0027 to 0.194 mg/L) [see graph to left].
- o *Lead* was detected at a concentration of 0.0057 mg/L, above the ESV of 0.00054 mg/L, in one dissolved samples collected at WS-007D on October 24, 2013. Lead was not detected in any Dawson Cove dissolved metal samples collected between October 24 and 31, 2013.
- o *Silver* was detected at a concentration of 0.0024 mg/L, above the ESV of 0.0003 mg/L, in one dissolved sample collected at WS-007D on July 26, 2013. Silver was not detected in recent Dawson Cove dissolved metal samples.

Notes

-- = no criterion available or not applicable

mg/L = milligrams per liter S = shallow sample

D = deep sample

ESV = Ecological screening value

lue


- 1. Evaluation based on the following location in Dawson Cove: WS-007D.
- 2. Weekly surface water sampling started from November 1, 2013. Metals analyses were discontinued on October 31, 2013.

MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

EVALUATION OF METALS IN DAWSON COVE SURFACE WATER (JULY 15 - OCTOBER 31, 2013)

ARCADIS

FIGURE



Legend:

- Drainage Path
- Brittle Sheen
- Non-Brittle Sheen
- Non-Brittle Sheen with Oil Spot
- Sheen Sample Location

Notes:


- Location of sheens observed during daily sheen monitoring activities conducted from October 21, 2013 through January 5, 2014. Approximate locations are shown on this figure.
- Locations of sheen sampling conducted on November 4, 2013. Type of sheen based on field characterization. Sampling results based on data analysis presented in Appendix M.

MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SUMMARY OF SHEEN OBSERVATIONS AND SAMPLING IN DRAINAGE WAY



FIGURE 11-1



Legend:

- Drainage Path
- Brittle Sheen
- Brittle Sheen with Oil Spot
- Non-Brittle Sheen
- Non-Brittle Sheen with Oil Spot
- Sheen Sample Location
- **OW-1** Staked Locations for Daily Observations (See Note 3)

Notes:

- 1. Location of sheens observed during daily sheen monitoring activities conducted from October 21, 2013 through January 5, 2014. Approximate locations are shown on this figure.
- 2. Locations of sheen sampling conducted on November 4, 2013. Type of sheen based on field characterization. Sampling results based on data analysis presented in Appendix M.
- 3. Brittle and non-brittle sheens observed at the staked locations are summarized in the table below.


Staked Location	Brittle Sheens	Brittle Sheens with Oil Spots	Non- Brittle Sheens	Non-Brittle Sheens with Oil Spots	Total Sheens Observed
OW-1	2	-	3	1	5
OW-2	4		4	3	11
OW-3		3	14	37	54
OW-4		1	5	2	8
OW-5	1		5	7	13
OW-6	3		5	17	25

MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

SUMMARY OF SHEEN OBSERVATIONS AND SAMPLING IN DAWSON COVE



FIGURE **11-2**





Legend

Approximate Areas for Sheen Mitigation


Drainage Path

--- Water's Edge

Containment Boom

Operations Areas


1. Areas for mitigation are approximate, and based on daily sheen monitoring activities initiated on October 21, 2013 and results from 10 sheen samples collected on November 4, 2013. Pre-design study will be conducted to confirm and refine the mitigation area.



MAYFLOWER PIPELINE INCIDENT RESPONSE **EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY** DOWNSTREAM AREAS DATA ASSESSMENT REPORT

APPROXIMATE AREAS FOR SHEEN MITIGATION







Legend

Pre-Design Study Activities to Refine Proposed Mitigation Area

Field Probing to Confirm Delineation of Mitigation Area

Areas with Heavy Vegetation

Drainage Path


--- Water's Edge

Containment Boom

Operations Areas

NOTE:


1. Details regarding proposed pre-design activities are described in Appendix O.



MAYFLOWER PIPELINE INCIDENT RESPONSE EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT

PRE-DESIGN STUDY AREAS





REGIONAL MAP NAVTEQ, TomTom, Intermap, increment P Corp., GEBCO,

Approximate Inlet Channel Targeted Removal Area Approximate Open Water Cap Placement Area


Areas with Heavy Vegetation

--- Water's Edge

Containment Boom

Operations Areas

1. Potential targeted removal area and cap placement areas are approximate, and based on daily sheen monitoring activities initiated on October 21, 2013 and results from 10 sheen samples collected on November 4, 2013. Pre-design study will be conducted to confirm the



MAYFLOWER PIPELINE INCIDENT RESPONSE **EXXONMOBIL ENVIRONMENTAL SERVICES COMPANY DOWNSTREAM AREAS DATA ASSESSMENT REPORT**

ALTERNATIVE 4 - TARGETED REMOVAL IN THE INLET CHANNEL AND REACTIVE **CAPPING IN THE OPEN WATER AREA**

