

ADEQ MINOR SOURCE AIR PERMIT

Permit #: 511-AR-5

IS ISSUED TO:

Amercable, Inc.
350 Bailey Road
El Dorado, AR 71730
Union County
AFIN: 70-00103

THIS PERMIT IS Amercable, Inc.'s AUTHORITY TO CONSTRUCT, MODIFY, OPERATE, AND/OR MAINTAIN THE EQUIPMENT AND/OR FACILITY IN THE MANNER AS SET FORTH IN THE DEPARTMENT'S MINOR SOURCE AIR PERMIT AND THE APPLICATION. THIS PERMIT IS ISSUED PURSUANT TO THE PROVISIONS OF THE ARKANSAS WATER AND AIR POLLUTION CONTROL ACT (ARK. CODE ANN. SEC. 8-4-101 ET SEQ.) AND THE REGULATIONS PROMULGATED THEREUNDER, AND IS SUBJECT TO ALL LIMITS AND CONDITIONS CONTAINED HEREIN.

Signed:

Michael Bonds
Chief, Air Division

Date

Table of Contents

Section I: FACILITY INFORMATION 3

Section II: INTRODUCTION 4

Section III: PERMIT HISTORY 8

Section IV: EMISSION UNIT INFORMATION 9

 SN-01, SN-02, SN-03, and SN-04 Specific Conditions 12

 SN-05 Specific Conditions 12

 SN-06 and SN-08 Specific Conditions 12

 SN-07 Specific Conditions 14

 SN-09 Specific Conditions 15

 Plantwide Conditions 16

Section V: INSIGNIFICANT ACTIVITIES 17

Section VI: GENERAL CONDITIONS 18

Amercable, Inc.
Permit #: 511-AR-5
AFIN: 70-00103

Section I: FACILITY INFORMATION

PERMITTEE: Americable, Inc.

AFIN: 70-00103

PERMIT NUMBER: 511-AR-5

FACILITY ADDRESS: 350 Bailey Road
El Dorado, AR 71730

COUNTY: Union

CONTACT POSITION: Harry Beemer, Safety and Environmental Specialist

TELEPHONE NUMBER: (870) 309-3326

REVIEWING ENGINEER: Ann Sudmeyer

UTM North-South (Y): Zone 15 3550.0

UTM East-West (X): Zone 15 732.5



Section II: INTRODUCTION

Summary

Amercable, Inc. is a manufacturer of industrial cable. This facility is located in El Dorado, Union County, Arkansas. This de minimis modification is necessary to:

1. Correct the hourly throughput of inks and extenders;
2. Increase the annual ink and extender usage limit to 1,000 gallons per year;
3. Increase the VOC content limit of the inks and extenders from 6.9 lb/gal to 9.84 lb/gal;
4. Permit the inks and extenders for a maximum methyl isobutyl ketone content of 3.75 lb/gal;
5. Permit inks and extenders for a maximum toluene content of 4.97 lb/gal; and
6. Increase the acetone content limit of the inks and extenders from 0.6 lb/gal to 4.02 lb/gal.

This will result in permitted emission rate increases of 4.7 tpy VOC, 3.25 tpy methyl ethyl ketone, 1.28 tpy methyl isobutyl ketone, and 2.07 tpy acetone.

In addition, the permit was corrected to include the toluene emission limits for SN-08. The Lacquer (Telecom Cable) used at SN-08 was permitted for a toluene content of 5% by weight, but the emission rate limits did not reflect this.

Process Description

Emissions from the Americable plant result from several processes involved in the development and production of commercial cable. These emissions include the combustion of natural gas, application of coatings, furnaces, and solvent cleaning.

Raw materials are brought in for storage in the warehouse. This can include spools, pellets for compounding, drums of solvent, and other miscellaneous items.

Heat is supplied to various processing operations through the use of four (4) boilers located at the facility (SN-01, SN-02, SN-03, and SN-04). Each of these boilers is natural gas fired.

RESIN LINES

The two (2) Resin Lines (SN-05) at Americable are used to produce cables up to 2.5" and 4.5", respectively. Strand enters an electrically heated extruder where compound is introduced and extruded to produce a coated strand. The coated strand is cooled in a water bath before being wound onto a reel. The Resin Lines are similar to the Continuous Vulcanization (CV) lines, except there is no steam tube.

FLAT ASSEMBLY

The Flat Assembly Line (SN-06) mechanically combines conductors which are held in place with string and tape to form a flat cable, which is then dipped into a vat of Chemlok adhesive for

Amercable, Inc.
Permit #: 511-AR-5
AFIN: 70-00103

bonding. Toluene is added to the Chemlok as an extender. The cable is then heat dried and wound on a reel.

CONTINUOUS VULCANIZATION LINES

There are four (4) vulcanization lines and four (4) tuber lines (SN-07) located at Americable. There are eleven (11) extruders associated with the CV lines and eight (8) extruders associated with the tuber lines. These lines extrude thermoset/rubber compounds. Vegetable oil is used in small quantities on the "A-Line" as a lubricant. Strand enters the electrically heated extruder where compound is introduced and extruded to produce a coated strand. The coated strand travels through a steam traced tube, then is cooled in a water bath before being wound onto a reel. Acetophenone (a known HAP) is produced during the extrusion process.

MISCELLANEOUS SPECIALTY OPERATIONS

Miscellaneous specialty operations (SN-08) at Americable include the Trace and Spool processing area, the Cable Reprint Line, Solvent Cleaning, and Stencil operations.

The Trace and Spool operation consists of running cable through a process that prints a stencil on the cable for marking and/or other purposes. The inks and solvents used in the application can contain VOC and HAP constituents. Stenciling is also applied to finished cable on four (4) CV lines.

The Cable Reprint Line involved a rub down of the cable with a solvent to remove the existing ink or stencil print. The stencil is then reapplied prior to the cable being rewound.

Solvent cleaning is used throughout the facility. The most common solvents are methylene chloride and a cyclohexanone/methyl isobutyl ketone mixture. Solvent is used in closed containers referred to as "soak cans" in the facility. There is also a small parts washer located in the maintenance area.

The Telecom Cable Operation involves pumping a heated saturant material over a cable jacketed with a fiber braid, using a small amount of acetone as an extender. The saturant is then coated with a lacquer which contains 25% acetone and 20% methanol (small amounts of additional acetone are added as an extender.) The lacquered cable then passes through a short tube where it is subjected to heated air and then wound onto a reel.

LEAD JACKETING OPERATIONS

To produce lead cured cable, a lead jacket is extruded over the uncured cable coating. The purpose of the lead jacket is to act as a mold (maintaining cable diameter) and to equalize heating and cooling during the curing (vulcanizing) process. After curing, the lead jacket is normally mechanically removed and the lead reused. Only a small percent of cable is sold with the lead jacket installed.

Calcium Stearate is applied to the cable as a lead release agent, as the cable is pulled through a water cooling trough. The cable is then pulled through extruders. The extruders coat the cable with molten lead from a 10-ton kettle. A 20-ton kettle feeds the 10-ton kettle. The kettles are

Amercable, Inc.
Permit #: 511-AR-5
AFIN: 70-00103

filled with either virgin lead which is added by hand or with recycled lead which is added by conveyor from one of the hoppers.

The molten lead flows from the 10-ton kettle through pipes to the extruder, as the cable is pulled through the extruder by the take-up reel machine. When the reel has the desired amount of cable, the cable is cut and the reel is ready for curing.

The loaded reels are moved into the autoclave (vulcanizer) by hand truck. The autoclave is sealed and flooded with carbon dioxide to reduce oxidation of the lead during curing. The autoclave is then heated with steam to provide heat which cures the cable. The temperature and duration cycle varies according to the coating being cured. After this cycle is completed, the cable reel is removed from the autoclave and allowed to cool.

The cooled reel of cable is moved to the stripper payoff reeling machine. The cable is then pulled through the stripper where the lead jacket is mechanically peeled off and cut into chips. These chips are placed in a return hopper to be reused. The finished cable moves to quality assurance prior to being shipped.

All of the lead dust produced from the lead jacketing operations is handled by a baghouse (SN-09)

Regulations

This facility is subject to regulation under the *Arkansas Air Pollution Control Code* (Regulation 18) and the *Regulations of the Arkansas Plan of Implementation for Air Pollution Control* (Regulation 19).



The following table is a summary of the facility's total emissions.

Table 1 - Total Allowable Emissions

Amercable, Inc.
 Permit #: 511-AR-5
 AFIN: 70-00103

Total Allowable Emissions		
Pollutant	Emission Rates	
	lb/hr	tpy
PM	0.8	1.4
PM ₁₀	0.8	1.4
SO ₂	0.4	0.4
VOC	43.2	42.3
CO	2.0	8.0
NO _x	2.4	9.6
Lead ^{HAP}	0.3	0.3
Acetophenone ^{HAP}	11.2	7.50
Di (2-ethylhexyl) phthalate ^{HAP}	0.94	1.48
Ethyl Benzene ^{HAP}	0.24	0.86
Methanol ^{HAP}	3.0	6.00
Methylene Chloride ^{HAP}	5.5	9.5
Methyl Ethyl Ketone ^{HAP}	7.0	3.5
Methyl Isobutyl Ketone ^{HAP}	5.9	9.5
Toluene ^{HAP}	9.4	9.5
Xylene ^{HAP}	0.86	3.77
Total HAP	---	23.75
Acetone	15.5	19.7

Amercable, Inc.
Permit #: 511-AR-5
AFIN: 70-00103

Section III: PERMIT HISTORY

511-A was issued to United States Steel Corporation for the installation of two fuel oil fired boilers. The maximum emissions were 0.7 pounds of particulate per hour and 2.3 pounds of SO₂ per hour.

511-A (Modification) was issued to United States Steel Corporation to allow firing of residual oil up to 6% sulfur content in its boiler, in the event of unavailability of low sulfur oil or natural gas. The maximum predicted SO₂ emissions were 30.6 pounds per hour, or 99.4 tons per year.

511-AR-2 was approved on May 25, 1984. Americable, a Division of Associated Materials, purchased the United States Steel Corporation cable plant. This modification requested that the existing permit (511-A mod.) be issued to Americable. The allowable particulate emission rate was 0.7 pounds per hour per boiler, and the allowable SO₂ emission rate was 2.3 pounds per hour per boiler.

511-AR-3 was issued on July 6, 1990. This modification added a 4.2 MMBTU/hr natural gas fired steam generator (SN-03) and a flame testing booth (SN-04) to the facility's air permit. Total allowable emissions were 1.72 pounds of NO_x per hour and 7.54 tons of NO_x per year.

The facility's permit #511-AR-3 was voided due to emissions less than 10 tpy. An authorization to operate was given on January 3, 1994. This authorization allowed the facility to operate in the manner described in the application. The authorization also set operating conditions as follows: (1) set maximum firing rates for the boilers (SN-01, SN-02, and SN-03) and authorized natural gas usage only; (2) authorized the flame test chamber (SN-04) to use only liquefied petroleum gas; (3) install, operate, and maintain the fabric filter (SN-05) per manufacturer's specifications; (4) submit an annual VOC usage report; (5) submit a complete permit application for review and possible permitting activities prior to the installation, modification, or operation of additional processes, equipment, or emission sources; and (6) set visible emission limits for SN-01 through SN-07.

511-AR-4 was issued on November 26, 2003. This permitting action was necessary to formally permit operations at the facility as a synthetic minor source. This permit modification also incorporated a de minimis change to replace the existing two 5-ton lead kettles with a 10-ton kettle and to add one 20-ton lead kettle to SN-09. The total permitted emission rates were 1.4 tons per year (tpy) PM/PM₁₀, 0.4 tpy SO₂, 37.6 tpy VOC, 8.0 tpy CO, 9.6 tpy NO_x, 17.63 tpy acetone, 9.5 tpy or less for each individual hazardous air pollutant (HAP), and 23.75 tpy of any combination of HAPs.

Section IV: EMISSION UNIT INFORMATION

Specific Conditions

1. The permittee will not exceed the emission rates set forth in the following table.
 [§19.501 *et seq.* of the Regulations of the Arkansas Plan of Implementation for Air Pollution Control]

Table 2 - Criteria Pollutants

SN	Description	Pollutant	lb/hr	tpy
SN-01	Cleaver-Brooks Boiler (6.5 MMBTU/hr)	PM ₁₀	0.1	0.3
		SO ₂	0.1	0.1
		VOC	0.1	0.2
		CO	0.6	2.4
		NO _x	0.7	2.9
SN-02	Cleaver-Brooks Boiler (6.5 MMBTU/hr)	PM ₁₀	0.1	0.3
		SO ₂	0.1	0.1
		VOC	0.1	0.2
		CO	0.6	2.4
		NO _x	0.7	2.9
SN-03	Kewanee Boiler (4.2 MMBTU/hr)	PM ₁₀	0.1	0.2
		SO ₂	0.1	0.1
		VOC	0.1	0.2
		CO	0.4	1.6
		NO _x	0.5	1.9
SN-04	Superior Boiler (4.2 MMBTU/hr)	PM ₁₀	0.1	0.2
		SO ₂	0.1	0.1
		VOC	0.1	0.2
		CO	0.4	1.6
		NO _x	0.5	1.9
SN-05	Resin Lines	PM ₁₀	0.1	0.1
		VOC	0.2	0.2
SN-06	Flat Assembly	VOC	4.3	30.4*
SN-08	Miscellaneous Specialty Operations	VOC	23.9	

Amercable, Inc.
 Permit #: 511-AR-5
 AFIN: 70-00103

SN	Description	Pollutant	lb/hr	tpy
SN-07	Continuous Vulcanization Lines	VOC	13.6	9.5
SN-09	Lead Jacketing Operations	PM ₁₀	0.3	0.3
		VOC	0.8	1.4
		Lead	0.3	0.3**

*Denotes combined total annual VOC emissions for SN-06 and SN-08.

**Denotes a plantwide limit of 23.75 tons of any combination of HAPs per year.

- The permittee will not exceed the emission rates set forth in the following table.
 [§18.801 of the Arkansas Air Pollution Control Code, effective February 15, 1999
 (Regulation 18) and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

Table 3 - Non-Criteria Pollutants

SN	Description	Pollutant	lb/hr	tpy
SN-01	Cleaver-Brooks Boiler (6.5 MMBTU/hr)	PM	0.1	0.3
SN-02	Cleaver-Brooks Boiler (6.5 MMBTU/hr)	PM	0.1	0.3
SN-03	Kewanee Boiler (4.2 MMBTU/hr)	PM	0.1	0.2
SN-04	Superior Boiler (4.2 MMBTU/hr)	PM	0.1	0.2
SN-05	Resin Lines	PM	0.1	0.1
SN-06	Flat Assembly	Ethyl Benzene	0.2	0.68*
		Toluene	3.6	**
		Xylene	0.54	2.36*
SN-07	Continuous Vulcanization Lines	Acetophenone	11.2	7.50*
		Di (2-ethylhexyl) phthalate	0.94	1.48*

SN	Description	Pollutant	lb/hr	tpy
SN-08	Miscellaneous Specialty Operations	Acetone	15.5	19.7
		Ethyl Benzene	0.04	0.18*
		Methanol	3.0	6.00*
		Methylene Chloride	5.5	9.5*
		Methyl Ethyl Ketone	7.0	3.5*
		Methyl Isobutyl Ketone	5.9	9.5*
		Toluene	5.8	**
		Xylene	0.32	1.41*
SN-09	Lead Jacketing Operations	PM	0.3	0.3

* Denotes a plantwide limit of 23.75 tons of any combination of HAPs per year.

**Denotes a plantwide limit of 9.5 tons of the individual HAP per year and a plantwide limit of 23.75 tons of any combination of HAPs per year.

- Visible emissions will not exceed the limits specified in the following table of this permit as measured by EPA Reference Method 9. [A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

Table 4 - Visible Emissions

SN	Limit	Regulatory Citation
SN-01	5%	§18.501 and A.C.A.
SN-02	5%	§18.501 and A.C.A.
SN-03	5%	§18.501 and A.C.A.
SN-04	5%	§18.501 and A.C.A.
SN-05	5%	§18.501 and A.C.A.
SN-09	5%	§18.501 and A.C.A.

- The permittee will not cause or permit the emission of air contaminants, including odors or water vapor and including an air contaminant whose emission is not otherwise prohibited by Regulation #18, if the emission of the air contaminant constitutes air pollution within the meaning of A.C.A. §8-4-303. [§18.801 of Regulation 18, and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
- The permittee will not conduct operations in such a manner as to unnecessarily cause air contaminants and other pollutants to become airborne. [§18.801 of Regulation 18, and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

SN-01, SN-02, SN-03, and SN-04 Specific Condition

6. The permittee shall burn only pipeline quality natural gas at SN-01, SN-02, SN-03, and SN-04. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

SN-05 Specific Conditions

7. The permittee shall not use more than 2,500,000 pounds of thermoplastic compounds per consecutive twelve (12) month period at SN-05. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
8. The permittee shall maintain monthly records which demonstrate compliance with Specific Condition #7. These records shall be updated by the fifteenth day of the month following the month to which the records pertain. A twelve month rolling total and each individual month's data shall be maintained on site, and made available to Department personnel upon request. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

SN-06 and SN-08 Specific Conditions

9. The permittee shall not exceed 30.4 tons of VOC per year at SN-06 and SN-08 combined. The permittee shall maintain monthly records to demonstrate compliance with this specific condition. These records shall be updated by the fifteenth day of the month following the month to which the records pertain. A twelve month rolling total and each individual month's data shall be maintained on site, and made available to Department personnel upon request. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
10. The permittee shall not exceed the following VOC content limits at SN-06. Material Safety Data Sheets or equivalent documentation shall be maintained on-site to demonstrate compliance with this specific condition. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

Material	VOC Content Limit
Chemlok	6.903 lb/gal
Toluene Extender	7.18 lb/gal

11. The permittee shall not exceed the following pollutant content limits at SN-06. Material Safety Data Sheets or equivalent documentation shall be maintained on-site to demonstrate compliance with this specific condition. [§18.1004 of Regulation 18 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

Material	Pollutant	Pollutant Content Limit
-----------------	------------------	--------------------------------

Material	Pollutant	Pollutant Content Limit
Chemlok	Ethyl Benzene	1.534 lb/gal
	Xylene	5.369 lb/gal
Toluene Extender	Toluene	7.18 lb/gal

12. The permittee shall not exceed the following throughputs at SN-08. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

Material	Throughput
Acetone	3,000 gallons/year
Lacquer (Telecom Cable)	60,000 pounds/year
Ink/Extender (combined)	1,000 gallons/year

13. The permittee shall maintain monthly records which demonstrate compliance with Specific Condition #12. These records shall be updated by the fifteenth day of the month following the month to which the records pertain. A twelve month rolling total and each individual month's data shall be maintained on site, and made available to Department personnel upon request. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

14. The permittee shall not exceed the following VOC content limits at SN-08. Material Safety Data Sheets or equivalent documentation shall be maintained on-site to demonstrate compliance with this specific condition. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

Material	VOC Content Limits
M-1055 Solvent	7.5 lb/gal
Lacquer (Telecom Cable)	25% by weight
Varsol	6.34 lb/gal
Ink/Extender	9.84 lb/gal

15. The permittee shall not exceed the following pollutant content limits at SN-08. Material Safety Data Sheets or equivalent documentation shall be maintained on-site to demonstrate compliance with this specific condition. [§18.1004 of Regulation 18 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

Material	Pollutant	Pollutant Content Limits
Methylene Chloride Solvent	Methylene Chloride	11.0 lb/gal
M-1055 Solvent	Methyl Isobutyl Ketone	3.75 lb/gal
Lacquer (Telecom Cable)	Acetone	25% by weight
	Methanol	20% by weight
	Toluene	5% by weight
Varsol	Ethylbenzene	0.04 lb/gal
	Xylene	0.32 lb/gal
Ink/Extender	Acetone	4.02 lb/gal
	Methyl Ethyl Ketone	6.9 lb/gal
	Methyl Isobutyl Ketone	3.75 lb/gal
	Toluene	4.97 lb/gal

SN-07 Specific Conditions

16. The permittee shall not use more than 1,500,000 pounds of acetophenone-producing thermoset compounds per consecutive twelve (12) month period at SN-07. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
17. The permittee shall maintain monthly records which demonstrate compliance with Specific Condition #16. These records shall be updated by the fifteenth day of the month following the month to which the records pertain. A twelve month rolling total and each individual month's data shall be maintained on site, and made available to Department personnel upon request. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

Amercable, Inc.
Permit #: 511-AR-5
AFIN: 70-00103

18. The permittee shall not use more than 12,000,000 pounds of total thermoset compounds per consecutive twelve (12) month period at SN-07. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
19. The permittee shall maintain monthly records which demonstrate compliance with Specific Condition #18. These records shall be updated by the fifteenth day of the month following the month to which the records pertain. A twelve month rolling total and each individual month's data shall be maintained on site, and made available to Department personnel upon request. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
20. The acetophenone produced from the decomposition of cumene peroxide shall not exceed 1% by weight at SN-07. Material Safety Data Sheets or equivalent documentation shall be maintained on-site to demonstrate compliance with this specific condition. [§18.1004 of Regulation 18 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
21. The permittee shall not exceed 360 gallons of Adhesive (DOP) per consecutive twelve (12) month period at SN-07.
22. The permittee shall maintain monthly records which demonstrate compliance with Specific Condition #21. These records shall be updated by the fifteenth day of the month following the month to which the records pertain. A twelve month rolling total and each individual month's data shall be maintained on site, and made available to Department personnel upon request. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
23. The VOC content of the Adhesive (DOP) used at SN-07 shall not exceed 8.2 lb/gal. Material Safety Data Sheets or equivalent documentation shall be maintained on-site to demonstrate compliance with this specific condition. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
24. The di (2-ethylhexyl) phthalate content of the Adhesive (DOP) used at SN-07 shall not exceed 8.2 lb/gal. Material Safety Data Sheets or equivalent documentation shall be maintained on-site to demonstrate compliance with this specific condition. [§18.1004 of Regulation 18 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

SN-09 Specific Conditions

25. The permittee shall not exceed 1.4 tons of VOC per year at SN-09. The permittee shall maintain monthly records to demonstrate compliance with this specific condition. These records shall be updated by the fifteenth day of the month following the month to which the records pertain. A twelve month rolling total and each individual month's data shall be maintained on site, and made available to Department personnel upon request. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
26. The VOC content of the Quikkote Lead Release Agent used at SN-09 shall not exceed 15% by weight. Material Safety Data Sheets or equivalent documentation shall be

Amercable, Inc.
Permit #: 511-AR-5
AFIN: 70-00103

maintained on-site to demonstrate compliance with this specific condition. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

27. The lead dust produced from the lead jacketing operations at SN-09 shall not exceed 15,000 pounds per year. The permittee shall maintain monthly records which demonstrate compliance with this condition. These records shall be updated by the fifteenth day of the month following the month to which the records pertain. A twelve month rolling total and each individual month's data shall be maintained on site, and made available to Department personnel upon request. [§19.705 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
28. The permittee shall operate the baghouse at SN-09 at all times during lead jacketing operations, and shall maintain the baghouse in good operating condition. The permittee shall conduct weekly maintenance inspections on the baghouse. A log of these inspections shall be kept on site, and made available to Department personnel upon request. [§19.303 of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]

Plantwide Conditions

29. The permittee shall not emit more than 9.5 tons of a single hazardous air pollutant (HAP) or 23.75 tons of any combination of HAPs from the facility in any consecutive 12 month period. [§19.405(B) of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
30. The permittee shall maintain monthly records of the HAP emissions from the facility. These records shall be updated by the fifteenth day of the month following the month to which the records pertain. These records shall be kept on-site, and made available to Department personnel upon request. [§19.405(B) of Regulation 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311] These records shall include the following:
 - a. the total monthly emissions for each HAP;
 - b. the consecutive 12 month total emissions for each HAP; and
 - c. the consecutive 12 month total emissions for all HAPs combined.



Section V: INSIGNIFICANT ACTIVITIES

The Department deems the following types of activities or emissions as insignificant on the basis of size, emission rate, production rate, or activity in accordance with Group A of the Insignificant Activities list found in Regulation 18 and 19 Appendix A. Insignificant activity emission determinations rely upon the information submitted by the permittee in an application dated February 5, 2003 and correspondence dated April 16, 2003.

Table 5 - Insignificant Activities

Description	Category
One 1.75 MMBTU/hr Oven	A-1
Caustic storage tanks that contain no VOCs	A-4
Burn treater/cable burn facility for research and development – aggregate pollutant specific emissions do not exceed 5 tpy of any combination of HAPs and 10 tpy of any other pollutant (less than 1,000 pounds of cable burned per year)	A-5
Equipment used for surface coating, painting, dipping, or spraying operations, provided the material used contains no more than 0.4 lb/gal VOCs, no hexavalent chromium, and no more than 0.1 tpy of all other HAPs.	A-9

Section VI: GENERAL CONDITIONS

1. Any terms or conditions included in this permit that specify and reference Arkansas Pollution Control & Ecology Commission Regulation 18 or the Arkansas Water and Air Pollution Control Act (A.C.A. §8-4-101 *et seq.*) as the sole origin of and authority for the terms or conditions are not required under the Clean Air Act or any of its applicable requirements, and are not federally enforceable under the Clean Air Act. Arkansas Pollution Control & Ecology Commission Regulation 18 was adopted pursuant to the Arkansas Water and Air Pollution Control Act (A.C.A. §8-4-101 *et seq.*). Any terms or conditions included in this permit that specify and reference Arkansas Pollution Control & Ecology Commission Regulation 18 or the Arkansas Water and Air Pollution Control Act (A.C.A. §8-4-101 *et seq.*) as the origin of and authority for the terms or conditions are enforceable under this Arkansas statute.
2. This permit does not relieve the owner or operator of the equipment and/or the facility from compliance with all applicable provisions of the Arkansas Water and Air Pollution Control Act and the regulations promulgated under the Act. [A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
3. The permittee will notify the Department in writing within thirty (30) days after commencement of construction, completion of construction, first operation of equipment and/or facility, and first attainment of the equipment and/or facility target production rate. [§19.704 of the Regulations of the Arkansas Plan of Implementation for Air Pollution Control (Regulation 19) and/or A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
4. Construction or modification must commence within eighteen (18) months from the date of permit issuance. [§19.410(B) of Regulation 19 and/or §18.309(B) of the Arkansas Air Pollution Control Code (Regulation 18) and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
5. The permittee must keep records for five years to enable the Department to determine compliance with the terms of this permit--such as hours of operation, throughput, upset conditions, and continuous monitoring data. The Department may use the records, at the discretion of the Department, to determine compliance with the conditions of the permit. [§19.705 of Regulation 19 and/or §18.1004 of Regulation 18 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
6. A responsible official must certify any reports required by any condition contained in this permit and submit any reports to the Department at the address below. [§19.705 of Regulation 19 and/or §18.1004 of Regulation 18 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]

Amercable, Inc.
Permit #: 511-AR-5
AFIN: 70-00103

Arkansas Department of Environmental
Quality
Air Division
ATTN: Compliance Inspector Supervisor
Post Office Box 8913
Little Rock, AR 72219

7. The permittee will test any equipment scheduled for testing, unless stated in the Specific Conditions of this permit or by any federally regulated requirements, within the following time frames: (1) newly constructed or modified equipment within sixty (60) days of achieving the maximum production rate, but no later than 180 days after initial start-up of the permitted source or (2) existing equipment already operating according to the time frames set forth by the Department. The permittee must notify the Department of the scheduled date of compliance testing at least fifteen (15) days in advance of such test. The permittee must submit compliance test results to the Department within thirty (30) days after the completion of testing. [§19.702 of Regulation 19 and/or §18.1002 of Regulation 18 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
8. The permittee will provide: [§19.702 of Regulation 19 and/or §18.1002 of Regulation 18 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
 - a. Sampling ports adequate for applicable test methods;
 - b. Safe sampling platforms;
 - c. Safe access to sampling platforms;
 - d. Utilities for sampling and testing equipment.
9. The permittee will operate equipment, control apparatus and emission monitoring equipment within their design limitations. The permittee will maintain in good condition at all times equipment, control apparatus and emission monitoring equipment. [§19.303 of Regulation 19 and/or §18.1104 of Regulation 18 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
10. Pursuant to, if the permittee exceeds an emission limit established by this permit, the permittee will be deemed in violation of said permit and will be subject to enforcement action. The Department may forego enforcement action for emissions exceeding any limits established by this permit provided the following requirements are met: [§19.601 of Regulation 19 and/or §18.1101 of Regulation 18 and A.C.A. §8-4-203 as referenced by A.C.A. §8-4-304 and §8-4-311]
 - e. The permittee demonstrates to the satisfaction of the Department that the emissions resulted from an equipment malfunction or upset and are not the result of negligence or improper maintenance, and the permittee took all reasonable measures to immediately minimize or eliminate the excess emissions.
 - f. The permittee reports the occurrence or upset or breakdown of equipment (by telephone, facsimile, or overnight delivery) to the Department by the end of the next business day after the occurrence or the discovery of the occurrence.

Amercable, Inc.
Permit #: 511-AR-5
AFIN: 70-00103

16. This permit authorizes only those pollutant emitting activities addressed herein.
[A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
17. This permit supersedes and voids all previously issued air permits for this facility.
[Regulation 18 and 19 and A.C.A. §8-4-203 as referenced by §8-4-304 and §8-4-311]
18. The permittee must pay all permit fees in accordance with the procedures established in Regulation No. 9. [A.C.A §8-1-105(c)]