

STATEMENT OF BASIS

For the issuance of Draft Air Permit # 0996-AOP-R32 AFIN: 66-00041

1. PERMITTING AUTHORITY:

Division of Environmental Quality  
5301 Northshore Drive  
North Little Rock, Arkansas 72118-5317

2. APPLICANT:

ABB Motors and Mechanical Inc.  
5711 R.S. Boreham Jr. Street  
Fort Smith, Arkansas 72901

3. PERMIT WRITER:

Jacob Allen

4. NAICS DESCRIPTION AND CODE:

NAICS Description: Motor and Generator Manufacturing  
NAICS Code: 335312

5. ALL SUBMITTALS:

The following is a list of ALL permit applications included in this permit revision.

Date of Application	Type of Application (New, Renewal, Modification, Deminimis/Minor Mod, or Administrative Amendment)	Short Description of Any Changes That Would Be Considered New or Modified Emissions
2/10/2025	Renewal	Decrease in the SN-A VOC bubble limit, lower emissions for SN-33, SN- 35 and SN-40.

6. REVIEWER'S NOTES:

ABB Motors and Mechanical Inc. (AFIN: 66-00041), located at 5711 R. S. Boreham Jr. St. in Fort Smith, AR, manufacturers electric motors for industrial use. This is a renewal of the existing permit. The facility also wished to lower the SN-A VOC annual bubble limit as well as lower the emission rates for SN-33, SN-35, and SN-40. Insignificant activities will be updated. Permitted emissions will decrease by 0.6 tpy in PM/PM<sub>10</sub>, 0.9 tpy in SO<sub>2</sub>, 75.9 tpy in VOC, 0.3 tpy in CO, and 4.2 tpy in NO<sub>x</sub>.

7. COMPLIANCE STATUS:

The following summarizes the current compliance of the facility including active/pending enforcement actions and recent compliance activities and issues.

The facility was last inspected on June 24, 2025 there were no violations noted at this time. There were no violations listed in ECHO.

8. PSD/GHG APPLICABILITY:

a) Did the facility undergo PSD review in this permit (i.e., BACT, Modeling, etc.)? N

b) Is the facility categorized as a major source for PSD? N

- *Single pollutant  $\geq 100$  tpy and on the list of 28 or single pollutant  $\geq 250$  tpy and not on list*

9. SOURCE AND POLLUTANT SPECIFIC REGULATORY APPLICABILITY:

Source	Pollutant	Regulation (NSPS, NESHAP or PSD)
All Diesel Generators (SN-33, SN-34, SN-35, SN-36, SN-40, SN-46 and SN-49)	HAPs	40 CFR 63 Subpart ZZZZ
New Diesel Generators (SN-33, SN-34, SN-35, SN-40, SN-46 and SN-49)	HAPs	40 CFR Part 60, Subpart IIII
Welding (SN-C) and Machining (SN-E)	N/A	40 CFR 63 Subpart XXXXXX
When complying with the HAP limits in this permit the facility will not be subject to Subpart MMMM.		

10. UNCONSTRUCTED SOURCES:

Unconstructed Source	Permit Approval Date	Extension Requested Date	Extension Approval Date	If Greater than 18 Months without Approval, List Reason for Continued Inclusion in Permit
N/A				

11. PERMIT SHIELD – TITLE V PERMITS ONLY:

Did the facility request a permit shield in this application? Y

(Note - permit shields are not allowed to be added, but existing ones can remain, for minor modification applications or any Rule 18 requirement.)

If yes, are applicable requirements included and specifically identified in the permit? Y

Source	Regulation	Description
SN-33, SN-34, SN35, SN-36, SN- 40, SN-46 and SN-49	40 CFR Subpart ZZZZ	National Emission Standards for Hazardous Air Pollutant for Stationary Reciprocating Internal Combustion Engines
SN-C and SN-E	40 CFR 63 Subpart XXXXXX	National Emission Standards for Hazardous Air Pollutants Area Source Standards for Nine Metal Fabrication and Finishing Source
SN-33, SN-34, SN-35, SN-40, SN-46 and SN-49	40 CFR Part 60, Subpart III	Standards of Performance for Stationary Compression Ignition Internal Combustion Engines

12. COMPLIANCE ASSURANCE MONITORING (CAM) – TITLE V PERMITS ONLY:

List sources potentially subject to CAM because they use a control device to achieve compliance and have pre-control emissions of at least 100 percent of the major source level. List the pollutant of concern and a brief summary of the CAM plan (temperature monitoring, CEMs, opacity monitoring, etc.) and frequency requirements of § 64.

Source	Pollutant Controlled	Cite Exemption or CAM Plan Monitoring and Frequency
N/A		

13. EMISSION CHANGES AND FEE CALCULATION:

See emission change and fee calculation spreadsheet in Appendix A.

14. AMBIENT AIR EVALUATIONS:

The following are results for ambient air evaluations or modeling.

a) NAAQS

A NAAQS evaluation is not required under the Arkansas State Implementation Plan, National Ambient Air Quality Standards, Infrastructure SIPs and NAAQS SIP per Ark. Code Ann. § 8-4-318, dated March 2017 and the DEQ Air Permit Screening Modeling Instructions.

b) Non-Criteria Pollutants:

The non-criteria pollutants listed below were evaluated. Based on Department procedures for review of non-criteria pollutants, emissions of all other non-criteria pollutants are below thresholds of concern.

#### 1<sup>st</sup> Tier Screening (PAER)

Estimated hourly emissions from the following sources were compared to the Presumptively Acceptable Emission Rate (PAER) for each compound. The Department has deemed the PAER to be the product, in lb/hr, of 0.11 and the Threshold Limit Value ( $\text{mg}/\text{m}^3$ ), as listed by the American Conference of Governmental Industrial Hygienists (ACGIH).

Pollutant	TLV ( $\text{mg}/\text{m}^3$ )	PAER (lb/hr) = $0.11 \times \text{TLV}$	Proposed lb/hr	Pass?
Acrolein	0.2	0.022	4.6E-04	Yes
Acetone	593.865	65.325	108.57	No
Arsenic	0.01	0.0011	1.14E-06	Yes
Benzene	0.0639	0.00703	0.0066	Yes
Beryllium	5E-05	5.5E-06	6.82E-08	Yes
Cadmium	0.002	2.2E-04	6.25E-06	Yes
Chromium	0.5	0.055	7.96E-06	Yes
Cobalt	0.02	0.0022	4.78E-07	Yes
Lead	0.05	0.0055	2.84E-06	Yes
Manganese	0.1	0.011	2.79E-03	Yes
Mercury	0.03	0.0033	1.48E-06	Yes
Selenium	0.2	0.022	1.36E-07	Yes
POMs	0.2	0.022	3.67E-03	Yes

#### 2<sup>nd</sup> Tier Screening (PAIL)

AERMOD air dispersion modeling was performed on the estimated hourly emissions from the following sources, in order to predict ambient concentrations beyond the property boundary. The Presumptively Acceptable Impact Level (PAIL) for each compound has been deemed by the Department to be one one-hundredth of the Threshold Limit Value as listed by the ACGIH.

Pollutant	PAIL ( $\mu\text{g}/\text{m}^3$ ) = 1/100 of Threshold Limit Value	Modeled Concentration ( $\mu\text{g}/\text{m}^3$ )	Pass?
Acetone	59386.5	1219.95	Yes

15. CALCULATIONS:

SN	Emission Factor Source (AP-42, testing, etc.)	Emission Factor (lb/ton, lb/hr, etc.)	Control Equipment	Control Equipment Efficiency	Comments
SN-01a	Mass Balance	0.0484 gal/motor 1.3 lb VOC/gal	None	N/A	167 s/cycle 6 motors/cycle
SN-01b			None	N/A	
SN-01c	AP-42 1.4-3	<u>Units in lb/MMscf</u> PM/PM <sub>10</sub> : 7.6 SO <sub>2</sub> : 0.6 VOC: 5.5 CO: 84.0 NOx: 100.0	None	N/A	4.0 MMBtu/hr
SN-02	Mass Balance/Testing	7.0 lb VOC/gal	None	N/A	0.017 gal/Motor 88.5 Motors/hr
SN-03			None	N/A	0.017 gal/Motor 88.5 Motors/hr
SN-05			None	N/A	0.022 gal/Motor 82.6 Motors/hr
SN-06			None	N/A	0.028 gal/Motor 77.5 Motors/hr
SN-07	Equipment capacity	7.0 lb VOC/gal	None	N/A	0.63 gal/hr
SN-11	Mass Balance/Testing	7.0 lb VOC/gal	None	N/A	0.017 gal/Motor 62.5 Motors/hr
SN-12			None	N/A	0.017 gal/Motor 62.5 Motors/hr
SN-31b	AP-42 1.4-3	<u>Units in lb/MMscf</u> PM/PM <sub>10</sub> : 7.6 SO <sub>2</sub> : 0.6 VOC: 5.5 CO: 84.0 NOx: 100.0	None	N/A	1.8 MMBtu/hr (combined)
	Mass Balance	0.0484 gal/motor 1.3 lb VOC/gal			167 s/cycle 6 motors/cycle
SN-33	AP-42 Table 3.4-1		None	N/A	685 HP, 500 hours/yr

SN	Emission Factor Source (AP-42, testing, etc.)	Emission Factor (lb/ton, lb/hr, etc.)	Control Equipment	Control Equipment Efficiency	Comments
SN-34	AP-42 Table 3.3-1	Units in lb/MMBtu, Table 3.3 or Table 3.4: PM/PM10: 0.31 or 0.1 SO2: 0.29 or 1.01*0.0015 VOC: 0.36 or 0.09 CO: 0.95 or 0.85 NOx: 4.41 or 3.2	None	N/A	237 HP, 500 hours/yr
SN-35	AP-42 Table 3.4-1		None	N/A	685 HP, 500 hours/yr
SN-36	AP-42 Table 3.3-1		None	N/A	85 HP, 500 hours/yr
SN-39	Mass Balance/Testing	7.0 lb VOC/gal	None	N/A	0.017 gal/rotor 40 rotors/hr
SN-40	AP-42 Table 3.3-1	<u>Units in lb/MMBtu</u> PM/PM10: 0.1 SO2: 1.01*0.0015 VOC: 0.09 CO: 0.85 NOx: 3.2	None	N/A	685 HP, 500 hours/yr
SN-41	Mass Balance/Testing	7.0 lb VOC/gal	None	N/A	77.5 motors/hr 0.028 gal/motor
SN-42			None	N/A	77.5 motors/hr 0.028 gal/motor
SN-44a&b	Mass Balance/Testing	0.0484 gal/motor 1.3 lb/gal VOC	None	N/A	158 cycles/hr 6 motors/cycle
SN-C	MSDS	HAP content: 7.5% Manganese: 7.5% PM: 5.2 lb/10 <sup>3</sup> electrode	None	N/A	35,000 lbs electrode/yr; 7.14 lbs electrodes/hr GMAW – ER70S
SN-E	N/A	Estimate based upon nature of process	Enclosed within building	N/A	
SN-46	AP-42 Table 3.3-1	<u>Units in lb/MMBtu</u> PM/PM10: 0.31 SO2: 0.29 VOC: 0.36 CO: 0.95 NOx: 4.41	None	N/A	80 HP, 500 hours/yr
SN-48	Mass Balance/Testing	7.0 lb VOC/gal	None	N/A	0.007 gal/Motor 5.5 Motors/hr

SN	Emission Factor Source (AP-42, testing, etc.)	Emission Factor (lb/ton, lb/hr, etc.)	Control Equipment	Control Equipment Efficiency	Comments
SN-49	AP-42 Table 3.3-1 (for SO <sub>2</sub> only) & Exhaust Emission Data (EPA Certificate Data)	SO <sub>2</sub> : 2.05 E-03 lb/Hp-Hr PM/PM <sub>10</sub> : 0.17 g/kW-Hr VOC: 0.15 g/kW-Hr CO: 1.3 g/kW-Hr NOx: 3.4 g/kW-Hr	None	N/A	134.1 Hp, 100 kW, 500 hours/years
SN-50	MSDS	7.0 lb VOC/gal	None	N/A	0.028 gal/Motor 30 Motors/hr

16. TESTING REQUIREMENTS:

The permit requires testing of the following sources.

SN	Pollutants	Test Method	Test Interval	Justification
N/A				

17. MONITORING OR CEMS:

The permittee must monitor the following parameters with CEMS or other monitoring equipment (temperature, pressure differential, etc.)

SN	Parameter or Pollutant to be Monitored	Method (CEM, Pressure Gauge, etc.)	Frequency	Report (Y/N)
N/A				

18. RECORDKEEPING REQUIREMENTS:

The following are items (such as throughput, fuel usage, VOC content, etc.) that must be tracked and recorded.

SN	Recorded Item	Permit Limit	Frequency	Report (Y/N)
A	VOC Content	7.0 lb/gal	As needed	N
A	VOC Emissions	185.0 tpy	Monthly	Y
A	HAP Content	TLV > 1.0 µg/m <sup>3</sup>	As received	N
B	VOC Content	1.3 lb/gal	As needed	N
B	VOC Emissions	50.0 tpy	Monthly	Y
Facility	HAP Emissions	Single HAP: 9.84 tpy	Monthly	Y

SN	Recorded Item	Permit Limit	Frequency	Report (Y/N)
		Total HAPs: 23.94 tpy		
C	Welding Wire HAP content	7.5% HAPs 7.5% Manganese	Continuous	N
C	Welding Wire Used	35,000 lb/yr	Monthly	N
C	Manufacturer's Instructions	N/A	Continuous	N
C	Management Practices	Minimum one from listed in SC#24	Continuous	N
C	Corrective action if visible emissions detected	See SC #25	As Needed	Y
C	All visual determination of opacity	No visible fugitive emissions	See SC #27	N
E	Manufacturer's Instructions	Operate according to instructions	Continuous	N
SN-33, SN-34, SN-35, SN-40, & SN-46	Fuel Type Used	Non-road Diesel only	As needed	N
SN-33, SN-34, SN-35, SN-40, SN-46, & SN-36	Maintenance Record & Manufacturer approved instructions	Changes must be permitted by manufacturer and engine must be maintained according to instructions	Continuous	N
SN-33, SN-34, SN-35, SN-40, & SN-46	If engine has a diesel particulate filter: Action taken if backpressure monitor alarm	N/A	As needed	N
SN-33, SN-34, SN-35, SN-40, SN-46, & SN-36	Hours of Operation and Description of Use	500 hr/ calendar yr total 100 hr/yr maintenance 50 hr/yr non-emergency	Each use	N
SN-36	Maintenance	Oil and Filter: 500 hours or annual  Air Cleaner: 1000 hours or annual	As needed	N

SN	Recorded Item	Permit Limit	Frequency	Report (Y/N)
		Hoses and belts: 500 Hours or annual		
SN-33, SN-34, SN-35, SN-40, SN-46, and SN-36	Opacity Observation data and corrective actions	20% Opacity	Daily	N
SN-49	Hours of Operation	500 hrs	12-month period	N
SN-49	Opacity Observation data and corrective actions	20% during the acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or lugging modes	Daily	N

19. OPACITY:

SN	Opacity	Justification for limit	Compliance Mechanism
B	5%	Reg.18.501	Use of Natural Gas
C	5%	Reg.18.501	Compliance with NESHAP XXXXXX
C	Any Visual Emissions	NESHAP XXXXXX	SC# 24 through #28
E	5%	Reg.18.501	Work Practices
SN-33, SN-34, SN-35, SN-40, SN-46, SN-36, & SN-49	20%	Reg.19.503	Daily observation when operating more than 24 hours

20. DELETED CONDITIONS:

Former SC	Justification for removal
	N/A

## 21. GROUP A INSIGNIFICANT ACTIVITIES:

The following is a list of Insignificant Activities including revisions by this permit.

Source Name	Group A Category	Emissions (tpy)						
		PM/PM <sub>10</sub>	SO <sub>2</sub>	VOC	CO	NO <sub>x</sub>	HAPs	
							Single	Total
Wastewater Evaporator (natural gas-fired, 0.22 MMBtu/hr) @ Bay.#9	A-1	0.01	0.01	0.01	0.08	0.10	0.01	0.01
Wastewater Evaporator, 210 Area (natural gas-fired, 0.65 MMBtu/hr) @ Bldg.#9	A-1	0.03	0.01	0.02	0.24	0.28	0.01	0.01
Three (3) Natural Gas Ovens (combined: 0.3 MMBtu/hr) @ Bldg. #3	A-1	0.01	0.01	0.01	0.11	0.13	0.01	0.01
Curing Oven (natural gas-fired, 0.5 MMBtu/hr) @ Bldg. #7	A-1	0.02	0.01	0.02	0.18	0.22	0.01	0.01
Epoxy Encapsulation Curing Oven (Electric Oven) @ Bldg. #2	A-1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Electric Spray Washer with Natural Gas Burner (natural gas-fired, 0.44 MMBtu/hr) @ Bay #3	A-1	0.02	0.01	0.01	0.16	0.19	0.01	0.01
TTX Oven in 210 Area (natural gas-fired, 2.5 MMBtu/hr) @ Bldg. #2	A-1	0.09	0.01	0.06	0.91	1.08	0.03	0.03
TTX Oven (natural gas-fired, 2.5 MMBtu/hr) @ Bldg. #6	A-1	0.09	0.01	0.06	0.91	1.08	0.03	0.03
Burn Off Oven for Varnish Hooks (natural gas-fired,	A-1	0.02	0.001	0.02	0.18	0.21	0.004	0.004

0.475 MMBtu/hr) @ Bldg. #9								
EPIKURE Curing Oven (electric) @ Bay #3	A-1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Master Ring Heater @ Bldg. #2 (electric)	A-1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
A-1 Total		0.29	0.071	0.22	2.89	3.31	0.114	0.114
Seven (7) 250-gallon Diesel Tanks for Emergency Generators	A-2	0	0	0.003	0	0	0	0
A-2 Total		0	0	0.003	0	0	0	0
Endplate Washer @ Bldg.#2 and Bay #3 (water vapor only)	A-13	Electric, water vapor only. No emissions						
Varnish Line Cooling Tunnel (TTX) @ Bldg. #2 and #6	A-13	Cooling Tunnel emissions are accounted for in painting operations						
Forty-nine (49) Mist Eliminators @ Bldg. #2, #3, #7, and Bay #3	A-13	0.1	-	-	-	-	-	-
Four (4) Laser Engravers @ Bldg. #2 and Two (2) @ Bay #3	A-13	0.1	-	-	-	-	-	-
Soldering Station @ Bldg. #2	A-13	0.04	-	-	-	-	0.04	0.04
Mold release usage @ Bldg. #2	A-13	0	0	1.0	0	0	0	0
Paint kitchen @ Bay #3 (accounted in SN- 11 and SN-12)	A-13	Emissions accounted in SN-11 and SN-12						
Paint kitchen @ Bldg. #2 (accounted in SN- 02, 03 and 05)	A-13	Emissions accounted in SN-02, 03 and 05						
Paint kitchen @ Bldg. #7 (account in SN-41, 42, 48 and 51)	A-13	Emissions accounted in SN-41, 42, 48 and 51						
Three (3) Electric Curing Ovens @ Bldg. #2 (accounted in SN-A)	A-13	Emissions accounted in SN-A						

Permit #: 0996-AOP-R32

AFIN: 66-00041

Page 12 of 12

Two (2) Parts Washers @ Bldg. #2	A-13	0	0	2.19	0	0	0	0
Electric Parts Washer @ Bldg. #3 (water vapor only)	A-13	0	0	0	0	0	0	0
A-13 Total		0.39	0	3.19	0	0	0.04	0.04

22. VOIDED, SUPERSEDED, OR SUBSUMED PERMITS:

The following is a list of all active permits voided/superseded/subsumed by the issuance of this permit.

Permit #
0996-AOP-R31

## APPENDIX A – EMISSION CHANGES AND FEE CALCULATION

## Fee Calculation for Major Source

Revised 03-11-16

Facility Name: ABB Motors and Mechanical Inc.  
 Permit Number: 0996-AOP-R32  
 AFIN: 66-00041

\$/ton factor	28.14	Annual Chargeable Emissions (tpy)	181.9
Permit Type	Minor Mod	Permit Fee \$	500

Minor Modification Fee \$	500
Minimum Modification Fee \$	1000
Renewal with Minor Modification \$	500
Check if Facility Holds an Active Minor Source or Minor Source General Permit	<input type="checkbox"/>
If Hold Active Permit, Amt of Last Annual Air Permit Invoice \$	0
Total Permit Fee Chargeable Emissions (tpy)	-81.6
Initial Title V Permit Fee Chargeable Emissions (tpy)	

*HAPs not included in VOC or PM:*

*Chlorine, Hydrazine, HCl, HF, Methyl Chloroform, Methylene Chloride, Phosphine, Tetrachloroethylene, Titanium Tetrachloride*

*Air Contaminants:*

*All air contaminants are chargeable unless they are included in other totals (e.g., H2SO4 in condensable PM, H2S in TRS, etc.)*

Pollutant (tpy)	Check if Chargeable Emission	Old Permit	New Permit	Change in Emissions	Permit Fee Chargeable Emissions	Annual Chargeable Emissions
PM		2.6	2	-0.6		
PM <sub>10</sub>		2.6	2	-0.6	-0.6	2
PM <sub>2.5</sub>		0	0	0		
SO <sub>2</sub>		1.9	1	-0.9	-0.9	1
VOC		237	161.1	-75.9	-75.9	161.1
CO		6.7	6.4	-0.3		
NO <sub>x</sub>		22	17.8	-4.2	-4.2	17.8
Manganese	<input type="checkbox"/>	0.01	0.01	0		

