



**DIVISION OF ENVIRONMENTAL QUALITY**

**DRAFT OPERATING AIR PERMIT**

**PERMIT NUMBER:** 1855-AOP-R7

**IS ISSUED TO:**

BFI-Waste System of Arkansas, LLC  
18511 West Sardis Road  
Bauxite, AR 72011  
Saline County  
**AFIN:** 63-00155

PURSUANT TO THE RULES OF THE ARKANSAS OPERATING AIR PERMIT PROGRAM, RULE 26: THIS PERMIT AUTHORIZES THE ABOVE REFERENCED PERMITTEE TO INSTALL, OPERATE, AND MAINTAIN THE EQUIPMENT AND EMISSION UNITS DESCRIBED IN THE PERMIT APPLICATION AND ON THE FOLLOWING PAGES. THIS PERMIT IS VALID BETWEEN:

AND

THE PERMITTEE IS SUBJECT TO ALL LIMITS AND CONDITIONS CONTAINED HEREIN.

**Signed:**

---

Demetria Kimbrough  
Deputy Director, Office of Air Quality  
Division of Environmental Quality

---

Date

Table of Contents

<b>SECTION I: FACILITY INFORMATION .....</b>	<b>4</b>
<b>SECTION II: INTRODUCTION .....</b>	<b>5</b>
<b>Summary of Permit Activity .....</b>	<b>5</b>
<b>Process Description .....</b>	<b>5</b>
<b>Rules and Regulations .....</b>	<b>6</b>
<b>Emission Summary .....</b>	<b>6</b>
<b>SECTION III: PERMIT HISTORY .....</b>	<b>8</b>
<b>SECTION IV: SPECIFIC CONDITIONS .....</b>	<b>10</b>
SN-01 .....	10
SN-02 .....	11
SN-03 .....	13
SN-04 .....	15
<b>SECTION V: COMPLIANCE PLAN AND SCHEDULE .....</b>	<b>17</b>
<b>SECTION VI: PLANTWIDE CONDITIONS .....</b>	<b>18</b>
Regulation 21—Asbestos Abatement .....	21
Title VI Provisions .....	23
<b>SECTION VII: INSIGNIFICANT ACTIVITIES .....</b>	<b>26</b>
<b>SECTION VIII: GENERAL PROVISIONS .....</b>	<b>27</b>

Appendix A - 40 C.F.R. Part 60, Subpart XXX – *Standards of Performance for Municipal Solid Waste Landfills That Commenced Construction, Reconstruction, or Modification After July 17, 2014*

Appendix B – 40 C.F.R. Part 63 Subpart AAAA – *National Emission Standards for Hazardous Air Pollutants: Municipal Solid Waste Landfills*

Appendix C – 40 C.F.R. Part 63 Subpart CCCCCC – *National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Dispensing Facilities*

BFI-Waste System of Arkansas, LLC

Permit #: 1855-AOP-R7

AFIN: 63-00155

#### List of Acronyms and Abbreviations

Ark. Code Ann.	Arkansas Code Annotated
AFIN	Arkansas DEQ Facility Identification Number
C.F.R.	Code of Federal Regulations
CO	Carbon Monoxide
COMS	Continuous Opacity Monitoring System
HAP	Hazardous Air Pollutant
Hp	Horsepower
lb/hr	Pound Per Hour
NESHAP	National Emission Standards (for) Hazardous Air Pollutants
MVAC	Motor Vehicle Air Conditioner
No.	Number
NO <sub>x</sub>	Nitrogen Oxide
NSPS	New Source Performance Standards
PM	Particulate Matter
PM <sub>10</sub>	Particulate Matter Equal To Or Smaller Than Ten Microns
PM <sub>2.5</sub>	Particulate Matter Equal To Or Smaller Than 2.5 Microns
SNAP	Significant New Alternatives Program (SNAP)
SO <sub>2</sub>	Sulfur Dioxide
SSM	Startup, Shutdown, and Malfunction Plan
Tpy	Tons Per Year
UTM	Universal Transverse Mercator
VOC	Volatile Organic Compound

BFI-Waste System of Arkansas, LLC

Permit #: 1855-AOP-R7

AFIN: 63-00155

## **SECTION I: FACILITY INFORMATION**

PERMITTEE: BFI-Waste System of Arkansas, LLC

AFIN: 63-00155

PERMIT NUMBER: 1855-AOP-R7

FACILITY ADDRESS: 18511 West Sardis Road  
Bauxite, AR 72011

MAILING ADDRESS: 5605 Moreau River Access Rd  
Jefferson City, MO 65101

COUNTY: Saline County

CONTACT NAME: Brad Zimmerman

CONTACT POSITION: Environmental Manager

TELEPHONE NUMBER: (573) 636-1144

REVIEWING ENGINEER: Jesse Smith

UTM North South (Y): Zone 15: 3824495.02 m

UTM East West (X): Zone 15: 547541.58 m

## **SECTION II: INTRODUCTION**

### **Summary of Permit Activity**

BFI Waste Systems of Arkansas operates a solid waste landfill located at 18511 West Sardis Road, Bauxite, AR. This permit is a renewal of their previous Title V permit. During this permitting action, the facility added a Gasoline Storage Tank to the permit and applicable conditions for NESHAP Subpart CCCCCC have also been added. The facility has also completed the expansion referenced in the previous renewal, and NSPS Subpart WWW has been removed as it is no longer applicable. Conditions relating to requirements from NSPS Subpart XXX and NESHAP Subpart AAAA have been added and updated as the facility exceeds the 50 Mg/yr threshold. Emission increases as a result of this permitting action are as follows: 0.5 tpy VOC and 0.07 tpy single HAP, 2.09 tpy total HAP, and 0.24 tpy H<sub>2</sub>S.

### **Process Description**

The BFI Waste Systems of Arkansas Saline County Solid Waste Landfill (Landfill) is a solid waste disposal facility that occupies approximately 129 acres consisting of a Class 1 landfill area, a Class 4 landfill area, and ancillary facilities including a building, a scale house, and administrative offices. The permitted disposal area encompasses approximately 108 acres of which 81 acres are devoted to the Class 1 landfill area.

Solid waste decomposition is initiated by aerobic bacteria present within the waste at the time of disposal. The primary gas produced during this phase of decomposition is carbon dioxide. As the oxygen supply is depleted facultative bacteria continue the decomposition process. Ultimately anaerobic bacteria become the predominant means of waste decomposition. Methane and carbon dioxide are produced at about a 50-50 ratio as the decomposition process proceeds in the facultative and anaerobic stages. Other components present in the gas include hydrogen sulfide and non-methane organic compounds (NMOC). Some NMOC are volatile organic compounds (VOCs) and/or hazardous air pollutants (HAPs).

Emissions result from four sources: (1) uncontrolled emissions and earthmoving operations from the landfill (SN-01); (2) emissions from vehicles traveling over paved and unpaved roads (SN-02); emissions from the flare unit (SN-03); and emissions from a gasoline storage tank (SN-04).

BFI Waste Systems of Arkansas operates a Landfill Gas (LFG) Collection and Control System (GCCS) at the Landfill. The purpose of the system is to provide a safe, manageable, and efficient system for the combustion of landfill gas. The system captures and destroys methane otherwise allowed to be emitted. LFG collection systems are relatively simple in design and principle. Blowers provide a negative pressure that pulls LFG through a header system and toward the control device. The blower/flare station unit consists of 2,200 scfm blowers that supply the “vacuum” to transport the LFG to the flare unit (SN-03).

Insignificant activities include two diesel storage tanks, a used oil tank, two leachate tanks, solidification basins, and a torit dust collector.

BFI-Waste System of Arkansas, LLC  
 Permit #: 1855-AOP-R7  
 AFIN: 63-00155

The Landfill accepts asbestos containing waste, which is accepted and handled in accordance with Regulation 21, *Arkansas Asbestos Abatement Regulation*.

### Rules and Regulations

The following table contains the rules and regulations applicable to this permit.

Rules and Regulations
Arkansas Air Pollution Control Code, Rule 18, effective March 14, 2016
Rules of the Arkansas Plan of Implementation for Air Pollution Control, Rule 19, effective May 6, 2022
Rules of the Arkansas Operating Air Permit Program, Rule 26, effective March 14, 2016
Arkansas Asbestos Abatement Regulation, Rule 21, effective September 11, 2015
40 C.F.R. Part 60 Subpart XXX – <i>Standards of Performance for Municipal Solid Waste Landfills That Commenced Construction, Reconstruction, or Modification After July 17, 2014</i>
40 C.F.R. Part 63 Subpart AAAA – <i>National Emission Standards for Hazardous Air Pollutants: Municipal Solid Waste Landfills</i>
40 C.F.R. Part 63 Subpart CCCCCC – <i>National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Dispensing Facilities</i>

### Emission Summary

The following table is a summary of emissions from the facility. This table, in itself, is not an enforceable condition of the permit.

EMISSION SUMMARY				
Source Number	Description	Pollutant	Emission Rates	
			lb/hr	tpy
Total Allowable Emissions		PM	96.2	232.9
		PM <sub>10</sub>	23.9	59.3
		PM <sub>2.5</sub>	See Note*	
		SO <sub>2</sub>	8.7	37.8
		VOC	2.5	10.3
		CO	24.5	107.0

EMISSION SUMMARY				
Source Number	Description	Pollutant	Emission Rates	
			lb/hr	tpy
		NO <sub>x</sub>	4.5	19.7
	HAPs	Single HAP	1.02	4.39
		Total HAPs**	2.22	10.49
	Air Contaminants ***	Hydrogen Sulfide	1.86	8.15
		Acetone	0.07	0.25
01	Landfill and Earthmoving Emissions	PM	15.1	103.2
		PM <sub>10</sub>	5.0	26.6
		VOC	2.2	9.6
		Single HAP	0.49	2.16
		Total HAPs	1.38	6.04
		Hydrogen Sulfide	1.86	8.15
		Acetone	0.06	0.24
02	Traffic Emissions	PM	80.0	124.8
		PM <sub>10</sub>	17.8	27.8
03	Open Flare	PM	1.1	4.9
		PM <sub>10</sub>	1.1	4.9
		SO <sub>2</sub>	8.7	37.8
		VOC	0.2	0.5
		CO	24.5	107.0
		NO <sub>x</sub>	4.5	19.7
		Single HAP	0.52	2.22
		Total HAPs	0.83	3.65
		Acetone	0.01	0.01
04	Gasoline Storage Tank	VOC	0.1	0.2
		Single HAP	0.01	0.01
		Total HAPs	0.01	0.01

\*PM<sub>2.5</sub> limits are source specific, if required. Not all sources have PM<sub>2.5</sub> limits.

\*\*HAPs included in the VOC totals. Other HAPs are not included in any other totals unless specifically stated.

\*\*\*Air Contaminants such as ammonia, acetone, and certain halogenated solvents are not VOCs or HAPs.

### SECTION III: PERMIT HISTORY

Permit 1855-A was issued to Saline County Regional Solid Waste District Landfill on October 18, 1999. Uncontrolled emissions from the decomposition of the enclosed municipal solid waste were the only source listed. The facility was listed as subject to 40 CFR 60, Subpart WWW — Standards of Performance for Municipal Solid Waste Landfills. Emission limits for the permit were: VOC—2.3 tpy; Toluene—2.04 tpy; 1,1,2,2-Tetrachlorethane—0.11 tpy; Acrylonitrile—0.04 tpy, Vinyl Chloride—0.26 tpy; 1,1-Dichloroethane—0.13 tpy; and Mercury 0.02 tpy.

Permit 1855-AOP-R0 was issued to BFI-Waste System of Arkansas, LLC on August 11, 2010. This facility, which previously operated under a Minor Source air permit (1855-A), was required to obtain a Title V Operating Air Permit under the provisions of 40 CFR Part 60 Subpart WWW — *Standards of Performance for Municipal Solid Waste Landfills* due to the Landfill design capacity, and the fact that construction commenced after May 30, 1991. Pursuant to 40 CFR 60, Subpart WWW the landfill is required to submit Part 70 (Title V) permit application when the landfill design capacity is greater than 3.27 million cubic yards. There was no increase in landfill design capacity with this modification

This permitting action issued a Title V permit and allowed installation of a landfill gas collection system and an associated flare (SN-03). Permitted emissions were: 111.8 tpy PM; 30.1 tpy PM<sub>10</sub>; 4.4 tpy SO<sub>2</sub>; 55.8 tpy VOC; 103.4 tpy CO; 19.0 tpy I; 0.25 tpy 1,1,2,2-Tetrachloroethane; 0.30 tpy 1,1-Dichloroethane; 0.44 tpy Acrylonitrile; 4.69 tpy Toluene; 1.56 tpy Dichloromethane; 1.67 tpy Xylenes; 2.19 tpy Hydrochloric Acid; 1.23 tpy Hydrogen Sulfide; 0.53 tpy Acetone, and 0.6 tpy Vinyl Chloride.

Permit 1855-AOP-R1 was issued on June 18, 2012. With this Administrative Amendment, the facility installed a 10,000 gallon horizontal diesel tank (Diesel-1) as a category A-3 Insignificant Activity. As well, Plantwide Conditions and General Provisions were updated to reflect those in the current templates. Permitted emissions were unchanged with this action.

Permit 1855-AOP-R2 was issued on July 9, 2012. With this Administrative Amendment, the facility added a dust collector to an existing lime-containing tank as a category A-13 Insignificant Activity. Permitted emissions are unchanged.

Permit 1855-AOP-R3 was issued on August 7, 2013. This permit modification is for the addition of 12 solar powered flares to be installed around the southern edge of the facility. Each of the flares is 3 MMBTU/hr.

Permit 1855-AOP-R4 was issued on October 1, 2013. With this Administrative Amendment, the facility added a 225,000 gallon leachate tank to the insignificant activities list.

Permit 1855-AOP-R5 was issued on June 15, 2015. This permit was a renewal of the Title V permit. The emissions from the landfill (SN-01) were updated due to the recent 2012 LandGEM modeling results for the landfill. The traffic emissions (SN-02) were also modified due to active watering of the unpaved roads and the distance travelled on these roads was doubled to account



BFI-Waste System of Arkansas, LLC  
Permit #: 1855-AOP-R7  
AFIN: 63-00155

for traveling to and from the work face of the landfill. The Open Flare (SN-03) was modified from 2100 cfm to 2200 cfm, resulting in slightly increased emissions. Modified emissions were as follows: +36.9 tpy PM, +9.1 tpy PM<sub>10</sub>, +0.2 tpy SO<sub>2</sub>, +4.9 tpy CO, +0.9 tpy NO<sub>x</sub>, and +1.86 tpy H<sub>2</sub>S. The HAP emissions are 11.06 tpy Single HAP and 30.3 tpy Total HAPs.

Permit 1855-AOP-R6 was issued on August 5, 2020. This was a renewal of the Title V permit. During this permitting action, emissions for SN-01 were updated to include earthmoving activities and update the landfill fugitive emissions. SN-02 was updated to account for the planned amount of truck traffic, SN-03's emissions were updated due to emission factor updates, and SN-05 was removed from the permit. After the landfills currently planned expansion, the facility will be subject to NSPS Subpart XXX and applicable conditions have been added to the permit. Emission changes as a result of this permitting action were as follows: Increase of 83.5 tpy PM, increase of 19.4 tpy PM<sub>10</sub>, decrease of 46.5 tpy VOC, decrease of 8.6 tpy CO, decrease of 8.9 tpy NO<sub>x</sub>, decrease of 6.74 tpy Single HAP, decrease of 21.9 tpy Total HAPs, increase of 4.85 tpy H<sub>2</sub>S, and a decrease of 0.29 tpy Acetone.

#### SECTION IV: SPECIFIC CONDITIONS

##### SN-01

##### Landfill Surface Gas and Earthmoving Emissions

##### Source Description

Uncontrolled emissions arising from the surface of the landfill (without the gas gathering system operating) and emissions from earthmoving operations are designated as SN-01. Per AP-42 Section 2.4.4.2, 25% of the LFG generated is released as landfill fugitive emissions (SN-01). The Landfill has an active landfill GCCS required under 40 CFR 60 Subpart XXX and 40 CFR 63 Subpart AAAA since NMOC greater than 50 Mg/yr.

##### Specific Conditions

1. The permittee shall not exceed the emission rates set forth in the following table. The permittee shall demonstrate compliance with this condition by compliance with Plantwide Conditions 7 and 13. [Rule 19.501 *et seq.*, 40 C.F.R. Part 60 Subpart XXX, and 40 C.F.R. Part 52, Subpart E]

SN	Description	Pollutant	lb/hr	tpy
01	Landfill and Earthmoving Emissions	PM <sub>10</sub> VOC	5.0 2.2	26.6 9.6

2. The permittee shall not exceed the emission rates set forth in the following table. The permittee shall demonstrate compliance with this condition by compliance with Plantwide Condition 7 and 13. [Rule 18.801 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]

SN	Description	Pollutant	lb/hr	tpy
01	Landfill and Earthmoving Emissions	PM	15.1	103.2
		Single HAP	0.49	2.16
		Total HAPs	1.38	6.04
		Hydrogen Sulfide	1.86	8.15
		Acetone	0.06	0.24

SN-02  
Traffic Emissions  
Paved and Unpaved Roads and Aggregate handling

Source Description

Particulates (road emissions) are emitted from the operation of vehicles and equipment over the paved and unpaved roads, aggregate handling, and wind erosion of storage piles and from the placing of soil cover material on the landfill surface. These activities are collectively referred to as Traffic Emissions (SN-02). Dust controls may include water dispersion equipment, sweeping, and other techniques.

Specific Conditions

3. The permittee shall not exceed the emission rates set forth in the following table. The permittee shall demonstrate compliance with this condition by compliance with Specific Conditions 6 and 8. [Rule 19.501 *et seq.* and 40 C.F.R. Part 52, Subpart E]

SN	Pollutant	lb/hr	tpy
02	PM <sub>10</sub>	17.8	27.8

4. The permittee shall not exceed the emission rates set forth in the following table. The permittee shall demonstrate compliance with this condition by compliance with Specific Conditions 6 and 8. [Rule 18.801 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]

SN	Pollutant	lb/hr	tpy
02	PM	80.0	124.8

5. Visible emissions may not exceed the limits specified in the following table of this permit. The permittee shall demonstrate compliance with this condition by compliance with Specific Condition 8.

SN	Limit	Regulatory Citation
Facility-wide	5%	[Rule 18.501 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]

6. The permittee shall not operate in a manner such that emissions from the storage piles, aggregate handling, earthmoving operations (SN-01), and paved and unpaved roads (SN-

BFI-Waste System of Arkansas, LLC

Permit #: 1855-AOP-R7

AFIN: 63-00155

- 02) would cause a nuisance off-site or allow visible emissions to extend beyond the property boundary. Under normal conditions, off-site opacity less than or equal to 5% shall not be considered a nuisance provided that there are no complaints received by the Division regarding dust from the facility. The permittee shall use water sprays, sweeping, or other techniques as necessary to control fugitive emissions that migrate off-site. [Rule 18.501 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]
7. Nothing in this permit shall be construed to authorize a violation of the Arkansas Water and Air Pollution Control Act or the federal National Pollutant Discharge Elimination System (NPDES). [Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]
  8. The permittee shall conduct weekly observations of the opacity from earthmoving operations, SN-01, and traffic emissions, SN-02, and keep a record of these observations. If the permittee detects visible emissions, the permittee must immediately take action to identify and correct the cause of the visible emissions. After implementing the corrective action, the permittee must document that the source complies with the visible emissions requirements. The permittee shall maintain records of the cause of any visible emissions and the corrective action taken. The permittee must keep these records onsite and make them available to Division personnel upon request. [Rule 18.501 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]

SN-03  
 Landfill Gas Open Flare Emissions

Source Description

The landfill gas (LFG) collection and control system (GCCS), SN-03, collects and routes the gases generated by the landfill to an LFG Specialties Model CF103418 “candle type” flare and blower, with 10” diameter tip and 34’ overall flare height. Design LFG flow range is 210 scfm to 2200 scfm.

The Landfill’s GCCS will not be subject to 40 C.F.R. Part 60, Subpart XXX and 40 C.F.R. 63 Subpart AAAA since the site specific NMOC emissions are determined to be  $\geq 50$  Mg per year. The flare generates combustion by-product emissions, mainly CO, NO<sub>x</sub>, SO<sub>2</sub>, and hydrogen chloride (HCl).

Specific Conditions

9. The permittee shall not exceed the emission rates set forth in the following table. The permittee shall demonstrate compliance with this condition by compliance with Specific Conditions 11, 14, and 15. [Rule 19.501 *et seq.* and 40 C.F.R. Part 52, Subpart E]

SN	Pollutant	lb/hr	tpy
03	PM <sub>10</sub>	1.1	4.9
	SO <sub>2</sub>	8.7	37.8
	VOC	0.2	0.5
	CO	24.5	107.0
	NO <sub>x</sub>	4.5	19.7

10. The permittee shall not exceed the emission rates set forth in the following table. The permittee shall demonstrate compliance with this condition by compliance with Specific Conditions 11, 14, and 14. [Rule 18.801 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]

SN	Pollutant	lb/hr	tpy
03	PM	1.1	4.9
	Single HAP	0.52	2.22
	Total HAPs	0.83	3.65
	Acetone	0.01	0.01

11. The permittee shall maintain records of gas flow to the flare in standard cubic feet per minute (scfm). Electronic or paper hourly records shall be maintained of the flow rate to the flare. The permittee shall update these records by the fifteenth day of the month following the month to which the records pertain, shall be maintained on site and made

available to Division personnel upon request. [Rule 18.1004, Rule 19.705, 40 C.F.R. Part 52, Subpart E and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]

12. Visible emissions may not exceed the limits specified in the table below. Compliance with this condition shall be demonstrated through the use of landfill gas as the only fuel combusted. [Rule 18.501, 40 C.F.R. § 60.181(1) and (f) and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311].

SN	Limit	Regulatory Citation
03	0%	[Rule 18.501, § 60.18(f)(1), Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311], § 60.18(f)(1)

13. The permittee shall conduct monthly observations of the opacity from SN-03 and keep a record of these observations. If the permittee detects visible emissions, the permittee must immediately take action to identify and correct the cause of the visible emissions. After implementing the corrective action, the permittee must document that the source complies with the visible emissions requirements. The permittee shall maintain records of all observations, the cause of any visible emissions, and the corrective action taken. The permittee must keep these records onsite and make them available to Division personnel upon request. [Rule 18.501 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]
14. The permittee must operate SN-03's pilot flame within the design limitations and manufacturer's specifications. The pilot flames may be lit by landfill gas, natural gas, or propane. [Rule 19.303 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]
15. The flare, SN-03, must have a flame present at all times of operation or if no flame is present, the flare orifice must be closed and the GCCS piping to the unlit flare must be closed to prevent venting of uncontrolled gases. The presence of a flame shall be monitored by an ultraviolet sensor or thermocouple or any other equivalent device. In the event of a flame failure the extraction system directed to the flare must automatically shut down to prevent passive venting of landfill gas. [Rule 19.303, Rule 19.304 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]

SN-04  
Gasoline Storage Tank

Source Description

The gasoline storage tank is a repurposed 2,000 gallon diesel tank used to store gasoline for site usage. The tank is estimated to have three turnovers a year, resulting in a throughput of 6,000 gallons of gasoline per rolling twelve months.

Specific Conditions

16. The permittee shall not exceed the emission rates set forth in the following table. The permittee shall demonstrate compliance with this condition by compliance with Specific Condition #18. [Rule 19.501 *et seq.* and 40 C.F.R. § 52 Subpart E]

SN	Pollutant	lb/hr	tpy
04	VOC	0.1	0.2

17. The permittee shall not exceed the emission rates set forth in the following table. The permittee shall demonstrate compliance with this condition by compliance with Specific Condition #18. [Rule 18.801 and Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311]

SN	Pollutant	lb/hr	tpy
04	Single HAP	0.01	0.01
	Total HAP	0.01	0.01

18. The permittee shall not exceed a throughput of 6,000 gallons of gasoline at SN-04 per rolling 12 month period. [Rule 18.1004, Rule 19.705, 40 C.F.R. Part 52, Subpart E and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]
19. The permittee shall maintain monthly records to demonstrate compliance with Specific Condition #18. The permittee shall update these records by the fifteenth day of the month following the month to which the records pertain. The twelve month rolling totals and each individual month's data shall be maintained on-site, made available to Division of Environmental Quality personnel upon request, and submitted in accordance with General Provision #7. [Rule 18.1004, Rule 19.705, 40 C.F.R. Part 52, Subpart E and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]
20. SN-04 is subject to the requirements of 40 C.F.R. § 63 Subpart CCCCCC – *National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Dispensing Facilities*. As gasoline throughput is less than 10,000 gallons per month, the permittee must not allow gasoline to be handled in a manner that would result in vapor

BFI-Waste System of Arkansas, LLC

Permit #: 1855-AOP-R7

AFIN: 63-00155

releases to the atmosphere for an extended period of time. Measures to be taken include, but are not limited to minimizing gasoline spills, cleaning up spills as expeditiously as practicable, cover all open gasoline containers and all gasoline storage tank fill-pipes with a gasketed seal when not in use, and minimizing gasoline sent to open waste collection systems that collect and transport gasoline to reclamation and recycling devices, such as oil/water separators. [Rule 19.304 and 40 C.F.R. 63.11116]



BFI-Waste System of Arkansas, LLC

Permit #: 1855-AOP-R7

AFIN: 63-00155

## **SECTION V: COMPLIANCE PLAN AND SCHEDULE**

BFI-Waste System of Arkansas, LLC will continue to operate in compliance with those identified regulatory provisions. The facility will examine and analyze future rules and regulations that may apply and determine their applicability with any necessary action taken on a timely basis.

## SECTION VI: PLANTWIDE CONDITIONS

1. The permittee shall notify the Director in writing within thirty (30) days after commencing construction, completing construction, first placing the equipment and/or facility in operation, and reaching the equipment and/or facility target production rate. [Rule 19.704, 40 C.F.R. § 52 Subpart E, and Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311]
2. If the permittee fails to start construction within eighteen months or suspends construction for eighteen months or more, the Director may cancel all or part of this permit. [Rule 19.410(B) and 40 C.F.R. § 52 Subpart E]
3. The permittee must test any equipment scheduled for testing, unless otherwise stated in the Specific Conditions of this permit or by any federally regulated requirements, within the following time frames: (1) new equipment or newly modified equipment within sixty (60) days of achieving the maximum production rate, but no later than 180 days after initial start up of the permitted source or (2) operating equipment according to the time frames set forth by the Division or within 180 days of permit issuance if no date is specified. The permittee must notify the Division of the scheduled date of compliance testing at least fifteen (15) business days in advance of such test. The permittee shall submit the compliance test results to the Division within sixty (60) calendar days after completing the testing. [Rule 19.702 and/or Rule 18.1002 and Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311]
4. The permittee must provide:
  - a. Sampling ports adequate for applicable test methods;
  - b. Safe sampling platforms;
  - c. Safe access to sampling platforms; and
  - d. Utilities for sampling and testing equipment.

[Rule 19.702 and/or Rule 18.1002 and Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311]
5. The permittee must operate the equipment, control apparatus and emission monitoring equipment within the design limitations. The permittee shall maintain the equipment in good condition at all times. [Rule 19.303 and Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311]
6. This permit subsumes and incorporates all previously issued air permits for this facility. [Rule 26 and Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311]
7. The facility's current Solid Waste Permit 261-S1-R3, issued April 3, 2018, permitted a maximum design capacity of 14,444,615 cubic yards. The permittee shall weigh every

incoming load of waste accepted by the facility on its truck scale. The permittee shall update its' air permit to reflect the new capacity in the event that a new Solid Waste Permit is issued that allows an increase in the total capacity of the landfill. [Rule 19.705, 40 C.F.R. § 70.6 and/or Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]

8. The permittee shall maintain monthly records to demonstrate compliance with Plantwide Condition 7. The permittee shall update the records by the fifteenth day of the month following the month to which the records pertain. The permittee shall maintain a lifetime in-place total, a twelve month rolling total, and each individual month's data on site, made available to the Division upon request and submitted semi-annually in accordance with General Provision 7 of this permit. Any density conversions shall be documented and maintained with these records. These records shall be retained at least 5 years. [Rule 19.705 and 40 C.F.R. Part 52 Subpart E and/or Rule 18.1004, and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311, and 40 C.F.R. § 60.768]
9. The permittee shall limit all landfill operation hours to 12 hours per day, Monday through Saturday. [Rule 18.1004 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]
10. The permittee will maintain monthly records of hours of operation which demonstrate compliance with Plantwide Condition 9. The permittee will maintain a twelve month rolling total and each individual month's data on site and make these records available to Division personnel upon request. The permittee will update the records by the fifteenth day of the month following the month to which the records pertain. [Rule 19.705, Rule 18.1004, and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311].
11. The permittee shall be required to modify this permit before starting any modification, construction, or reconstruction at the facility not described in this permit. The permittee is allowed to install additional gas extraction wells and remove and/or replace existing gas extraction wells; any such modifications shall be documented and a record maintained on site and made available to Division personnel upon request. [Rule 19.304 and Ark. Code Ann. § 8-4-203 as referenced by §§ 8-4-304 and 8-4-311]

#### *NSPS Requirements*

12. As estimated uncontrolled NMOC emissions equal or exceed 50 Mg/yr as calculated in accordance with 40 C.F.R. 60.754 or 40 C.F.R. 60.764, the facility is subject to and the permittee shall comply with 40 C.F.R. Part 63 Subpart AAAA – *National Emission Standards for Hazardous Air Pollutants – Municipal Solid Waste Landfills*. [Rule 19.304 and 40 C.F.R. § 63.1935]
13. The permittee must operate the collection system such that gas is collected from each area, cell, or group of cells in the MSW landfill in which solid waste has been in place for

- 5 years or more if active or 2 years or more if closed or at final grade. The permittee must operate the collection system with negative pressure at each wellhead except under the conditions outlined in § 63.1958(b). [Rule 19.304 and 40 C.F.R. § 63.1958(a) and (b)]
14. The permittee must operate each interior wellhead in the collection system as specified in § 60.763(c) until the permittee elects to meet the operational standard temperature of landfill gas less than 62.8 degrees Celsius (145 degrees Fahrenheit). [Rule 19.304 and 40 C.F.R. § 63.1958(c)]
  15. The permittee must operate the collection system so that methane concentration is less than 500 parts per million above background at the surface of the landfill. The permittee must conduct surface testing using an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications provided in § 63.1960(d). The permittee must conduct surface testing at all cover penetrations. Thus, the permittee must monitor any cover penetrations that are within an area of the landfill where waste has been placed and a gas collection system is required. The permittee must determine the latitude and longitude coordinates of each exceedance using an instrument with an accuracy of at least 4 meters. The coordinates must be in decimal degrees with at least five decimal places. [Rule 19.304 and 40 C.F.R. § 63.1958(d)]
  16. The permittee must operate the control system at all times when the collected gas is routed to the system. In the event the collection or control system is not operating the gas mover system must be shut down and all valves in the collection and control system contributing to venting of the gas to the atmosphere must be closed within 1 hour of the collection or control system not operating, and efforts to repair the collection or control system must be initiated and completed in a manner such that downtime is kept to a minimum, and the collection and control system must be returned to operation. [Rule 19.304 and 40 C.F.R. § 63.1958(e) and (f)]
  17. The permittee must submit a collection and control system design to the Division for approval according to § 63.1981 (d). The collection and control system design plan must be prepared and approved by a professional engineer. [Rule 19.304 and 40 C.F.R. § 63.1981(d)]
  18. The permittee must submit to the division semi-annual reports. The permittee must submit the report as specified in § 63.1981(l). The initial report must be submitted within 180 days of installation and startup of the collection and control system and must include the initial performance test report required under § 63.7 of subpart A, as applicable. The semi-annual reports must contain all the information listed in § 63.1981(h)(1) through (8). [Rule 19.304 and 40 C.F.R. § 63.1981(h)]
  19. Except as provided in § 63.1981(d)(2), the permittee must keep for at least 5 years up-to-date, readily accessible, on-site records of the design capacity report that triggered § 63.1959(b), the current amount of solid waste in-place, and the year-by-year waste

acceptance rate. Off-site records may be maintained if they are retrievable within 4 hours. Either paper or electronic formats are acceptable. The permittee must also keep up-to-date, readily accessible records for the life of the control system equipment of the data listed through § 63.1983(b)(1) through (5) as measured during the initial performance or compliance determination. Records of subsequent tests or monitoring must be maintained for a minimum of 5 years. Records of control device vendor specifications must be maintained until removal. [Rule 19.304 and 40 C.F.R. § 63.1983(a) and (b)]

20. The facility is subject to and the permittee shall comply with 40 C.F.R. Part 60, Subpart XXX – *Standards of Performance for Municipal Solid Waste Landfills That Commenced Construction, Reconstruction, or Modification After July 17, 2014*. [Rule 19.705 and 40 C.F.R. Part 60, Subpart XXX]
21. If the facility emits less than 34 megagrams per year of NMOCs, the permittee must submit an annual NMOC emission rate report to the Division, except as provided in § 60.767(b)(1)(ii) or (b)(3), and recalculate the NMOC rate annually using the procedures specified in § 60.764(a)(1) until such time as the calculated NMOC emission rate is equal to or greater than 34 megagrams per year, or the landfill is closed. As the calculated NMOC emission rate is determined to be equal to or greater than 34 megagrams per year, the permittee must either comply with § 60.762(b)(2), calculate NMOC emissions using the next higher tier in § 60.764, or conduct a surface emission monitoring demonstration using the procedures specified in § 60.764(a)(6). [Rule 19.705 and § 60.762(b)(1)]
22. The permittee shall maintain records of the following on-site and make available to Division personnel upon request:
  - a. Submit a collection and control system design plan prepared by a professional engineer to the Division within 1 year, as required by 40 C.F.R. § 60.762(b)(2) and
  - b. Install a collection and control system that captures the gas generated within the landfill areas required paragraphs by 40 C.F.R. § 60.762(b)(2)(ii)(A) or (B) and (b)(2)(iii) within 30 months after the first annual report in which the emission rate equals or exceeds 50 Mg/yr. [40 C.F.R. § 60.762(b)]

#### Regulation 21—Asbestos Abatement

23. The permittee is subject to and shall comply with Regulation 21, *Arkansas Asbestos Abatement Regulation*, §11.2 Standards for Waste Disposal Sites. [Regulation 21, § 11.2(A-D), and 40 C.F.R. § 60.752]
25. The permittee of an active waste disposal site that received asbestos-containing waste material from a source covered by Regulation 21 shall meet the following requirements: [Regulation 21, § 11.2(A)(i-ii)]
  - a. At the end of each operating day, or at least once every 24-hour period while the site is in continuous operation, the asbestos-containing waste material that has

been deposited at the site during the operating day or previous 24-hour period shall:

- i. Be covered with at least 6 inches of compacted nonasbestos-containing material; or
    - ii. Be covered with a resinous or petroleum-based dust suppression agent that effectively binds dust and controls wind erosion. Such an agent shall be used in the manner and frequency recommended for the particulate dust by the dust suppression agent manufacturers to achieve and maintain dust control. Other equally effective dust suppression agents may be used upon prior approval by the Director. For purposes of this paragraph, any used, spent, or other waste oil is not considered a dust suppression agent.
  - b. Use an alternative emissions control method that has received prior written approval by the Director demonstrating the following criteria:
    - i. The alternative method will control asbestos emissions equivalent to currently required methods;
    - ii. The suitability of the alternative method for the intended application;
    - iii. The alternative method will not violate other regulations; and
    - iv. The alternative method will not result in increased water pollution, land pollution, or occupational hazards.
26. The permittee shall maintain waste shipment records (WSR) of all asbestos-containing waste material received: [Rule 19.705 and Regulation 21, § 11.2(B)(i-vii)]
- a. Maintain waste shipment records (WSR), using a form with the following information:
    - i. The name, address, and telephone number of the waste generator;
    - ii. The name, address, and telephone number of the transporter(s);
    - iii. The quantity of the asbestos-containing waste material in tons;
    - iv. The presence of improperly enclosed or uncovered waste, or any asbestos-containing waste material not sealed in leak-tight containers. Report in writing to the Division Official responsible for administering the Asbestos program for the waste generator (identified in the WSR, and, if different the local, State, or EPA regional office responsible for administering the asbestos NESHAP program for the disposal site, by the following working day, the presence of a significant amount of improperly enclosed or uncovered waste. Submit a copy of the WSR along with the report; and
    - v. The date of the receipt.
  - b. The permittee shall as soon as possible and no longer than 30 days after receipt of the asbestos-containing waste, send a copy of the signed WSR to the waste generator. [Regulation 21, § 11.2(B)(ii)]
  - c. The permittee shall check the WSR that accompanies each asbestos-containing waste shipment that arrives at the waste disposal site for accuracy of the quantity of waste designated and attempt to reconcile any discrepancy with the waste generator. If the discrepancy is not resolved within 15 days after receiving the waste, the permittee will immediately report in writing to the specific agency responsible for administering the NESHAP program for the waste generator.

- Describe the discrepancy and attempts to reconcile it, and submit a copy of the WSR along with the report. [Rule 19.705 and Regulation 21, § 11.2(B)(iii)]
- d. Furnish upon request and make available during normal business hours for inspection by the Division, all records required under Regulation 21, § 11.2. [Regulation 21, § 21.11.2(B)(iv)]
  - e. The permittee shall maintain a copy of all records and reports required by Regulation 21, § 11.2 on-site for at least 2 years. [Regulation 21, § 11.2(B)(v)]
  - f. Maintain until landfill closure, records of the location, depth and area, and quantity in tons of asbestos-containing waste material within the disposal site on a map or diagram of the disposal area. [Regulation 21, § 11.2(B)(vi)]
  - g. Submit to the Director, upon closure of the facility, a copy of records of asbestos waste disposal locations and quantities. [Regulation 21, § 11.2(B)(vii)]
27. The permittee shall notify the Division in writing at least 45 days prior to excavating or otherwise disturbing any asbestos-containing waste material that has been deposited at the waste disposal site and is covered. If the excavation will begin on a date other than the one contained in the original notice, notice of the new start date must be provided to the Division at least 10 working days before excavation begins and in no event shall excavation begin earlier than the date specified in the original notification. The following information shall be included in the notice: [Regulation 21, § 11.2I(i-iv)]
- a. Schedule starting and completion dates;
  - b. Reason for disturbing the waste;
  - c. Procedures to be used to control emissions during the excavation, storage, transport, and ultimate disposal of the excavated asbestos-containing waste material (if deemed necessary, the Division may require changes in the emission control procedures to be used); and
  - d. Location of any temporary storage site and the final disposal site.
28. Within 60 days of a site becoming inactive, the permittee shall record a notation, in accordance with Arkansas State law, on the deed to the facility property and on any other instrument that would normally be examined during a title search. This notation will in perpetuity notify any potential purchaser of the property that: [Regulation 21, § 11.2(D)(i-ii)]
- a. The land has been used for the disposal of asbestos-containing waste material; and
  - b. The survey plot and record of the location and quantity of asbestos-containing waste disposed of within the disposal site required in Regulation 21, § 11.2(B)(vi) have been filed with the Division.

#### Title VI Provisions

29. The permittee must comply with the standards for labeling of products using ozone-depleting substances. [40 C.F.R. § 82 Subpart E]

- a. All containers containing a class I or class II substance stored or transported, all products containing a class I substance, and all products directly manufactured with a class I substance must bear the required warning statement if it is being introduced to interstate commerce pursuant to § 82.106.
  - b. The placement of the required warning statement must comply with the requirements pursuant to § 82.108.
  - c. The form of the label bearing the required warning must comply with the requirements pursuant to § 82.110.
  - d. No person may modify, remove, or interfere with the required warning statement except as described in § 82.112.
30. The permittee must comply with the standards for recycling and emissions reduction, except as provided for MVACs in Subpart B. [40 C.F.R. § 82 Subpart F]
  - a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to § 82.156.
  - b. Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to § 82.158.
  - c. Persons performing maintenance, service repair, or disposal of appliances must be certified by an approved technician certification program pursuant to § 82.161.
  - d. Persons disposing of small appliances, MVACs, and MVAC like appliances must comply with record keeping requirements pursuant to § 82.166. (“MVAC like appliance” as defined at § 82.152)
  - e. Persons owning commercial or industrial process refrigeration equipment must comply with leak repair requirements pursuant to § 82.156.
  - f. Owners/operators of appliances normally containing 50 or more pounds of refrigerant must keep records of refrigerant purchased and added to such appliances pursuant to § 82.166.
31. If the permittee manufactures, transforms, destroys, imports, or exports a class I or class II substance, the permittee is subject to all requirements as specified in 40 C.F.R. § 82 Subpart A, Production and Consumption Controls.
32. If the permittee performs a service on motor (fleet) vehicles when this service involves ozone depleting substance refrigerant (or regulated substitute substance) in the motor vehicle air conditioner (MVAC), the permittee is subject to all the applicable requirements as specified in 40 C.F.R. § 82 Subpart B, Servicing of Motor Vehicle Air Conditioners.

The term “motor vehicle” as used in Subpart B does not include a vehicle in which final assembly of the vehicle has not been completed. The term “MVAC” as used in Subpart B does not include the air tight sealed refrigeration system used as refrigerated cargo, or the system used on passenger buses using HCFC 22 refrigerant.



BFI-Waste System of Arkansas, LLC

Permit #: 1855-AOP-R7

AFIN: 63-00155

33. The permittee can switch from any ozone depleting substance to any alternative listed in the Significant New Alternatives Program (SNAP) promulgated pursuant to 40 C.F.R. § 82 Subpart G.

BFI-Waste System of Arkansas, LLC  
Permit #: 1855-AOP-R7  
AFIN: 63-00155

## SECTION VII: INSIGNIFICANT ACTIVITIES

The Division of Environmental Quality deems the following types of activities or emissions as insignificant on the basis of size, emission rate, production rate, or activity in accordance with Group A of the Insignificant Activities list found in Rule 18 and Rule 19 Appendix A. Group B insignificant activities may be listed but are not required to be listed in permits. Insignificant activity emission determinations rely upon the information submitted by the permittee in an application dated January 28, 2025. [Rule 26.304 and Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311]

Description	Category
Tank 001—500 gallon diesel storage tank	A-3
Diesel-1—10,000 gallon horizontal diesel storage tank	A-3
700 Gallon Used Oil Tank	A-3
Solidification Basins	A-13
Torit Dust Collector Model 90-3	A-13
LEACH 1 – 225,000 Gallon Leachate Tank	A-13
LEACH 2 – 225,000 Gallon Leachate Tank	A-13

## SECTION VIII: GENERAL PROVISIONS

1. Any terms or conditions included in this permit which specify and reference Arkansas Pollution Control & Ecology Commission Rule 18 or the Arkansas Water and Air Pollution Control Act (Ark. Code Ann. § 8-4-101 *et seq.*) as the sole origin of and authority for the terms or conditions are not required under the Clean Air Act or any of its applicable requirements, and are not federally enforceable under the Clean Air Act. Arkansas Pollution Control & Ecology Commission Rule 18 was adopted pursuant to the Arkansas Water and Air Pollution Control Act (Ark. Code Ann. § 8-4-101 *et seq.*). Any terms or conditions included in this permit which specify and reference Arkansas Pollution Control & Ecology Commission Rule 18 or the Arkansas Water and Air Pollution Control Act (Ark. Code Ann. § 8-4-101 *et seq.*) as the origin of and authority for the terms or conditions are enforceable under this Arkansas statute. [40 C.F.R. § 70.6(b)(2)]
2. This permit shall be valid for a period of five (5) years beginning on the date this permit becomes effective and ending five (5) years later. [40 C.F.R. § 70.6(a)(2) and Rule 26.701(B)]
3. The permittee must submit a complete application for permit renewal at least six (6) months before permit expiration. Permit expiration terminates the permittee's right to operate unless the permittee submitted a complete renewal application at least six (6) months before permit expiration. If the permittee submits a complete application, the existing permit will remain in effect until the Division of Environmental Quality takes final action on the renewal application. The Division of Environmental Quality will not necessarily notify the permittee when the permit renewal application is due. [Rule 26.406]
4. Where an applicable requirement of the Clean Air Act, as amended, 42 U.S.C. 7401, *et seq.* (Act) is more stringent than an applicable requirement of regulations promulgated under Title IV of the Act, the permit incorporates both provisions into the permit, and the Director or the Administrator can enforce both provisions. [40 C.F.R. § 70.6(a)(1)(ii) and Rule 26.701(A)(2)]
5. The permittee must maintain the following records of monitoring information as required by this permit.
  - a. The date, place as defined in this permit, and time of sampling or measurements;
  - b. The date(s) analyses performed;
  - c. The company or entity performing the analyses;
  - d. The analytical techniques or methods used;
  - e. The results of such analyses; and
  - f. The operating conditions existing at the time of sampling or measurement.

[40 C.F.R. § 70.6(a)(3)(ii)(A) and Rule 26.701(C)(2)]

6. The permittee must retain the records of all required monitoring data and support information for at least five (5) years from the date of the monitoring sample, measurement, report, or application. Support information includes all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. [40 C.F.R. § 70.6(a)(3)(ii)(B) and Rule 26.701(C)(2)(b)]
7. The permittee must submit reports of all required monitoring every six (6) months. If the permit establishes no other reporting period, the reporting period shall end on the last day of the month six months after the issuance of the initial Title V permit and every six months thereafter. The report is due on the first day of the second month after the end of the reporting period. The first report due after issuance of the initial Title V permit shall contain six months of data and each report thereafter shall contain 12 months of data. The report shall contain data for all monitoring requirements in effect during the reporting period. If a monitoring requirement is not in effect for the entire reporting period, only those months of data in which the monitoring requirement was in effect are required to be reported. The report must clearly identify all instances of deviations from permit requirements. A responsible official as defined in Rule 26.2 must certify all required reports. The permittee will send the reports electronically using <https://portal.adeq.state.ar.us> or mail them to the address below:

Division of Environmental Quality  
Office of Air Quality  
ATTN: Compliance Inspector Supervisor  
5301 Northshore Drive  
North Little Rock, AR 72118-5317

[40 C.F.R. § 70.6(a)(3)(iii)(A) and Rule 26.701(C)(3)(a)]

8. The permittee shall report to the Division of Environmental Quality all deviations from permit requirements, including those attributable to upset conditions as defined in the permit.
  - a. For all upset conditions (as defined in Rule 19.601), the permittee will make an initial report to the Division of Environmental Quality by the next business day after the discovery of the occurrence. The initial report may be made by telephone and shall include:
    - i. The facility name and location;
    - ii. The process unit or emission source deviating from the permit limit;
    - iii. The permit limit, including the identification of pollutants, from which deviation occurs;
    - iv. The date and time the deviation started;
    - v. The duration of the deviation;

- vi. The emissions during the deviation;
- vii. The probable cause of such deviations;
- viii. Any corrective actions or preventive measures taken or being taken to prevent such deviations in the future; and
- ix. The name of the person submitting the report.

The permittee shall make a full report in writing to the Division of Environmental Quality within five (5) business days of discovery of the occurrence. The report must include, in addition to the information required by the initial report, a schedule of actions taken or planned to eliminate future occurrences and/or to minimize the amount the permit's limits were exceeded and to reduce the length of time the limits were exceeded. The permittee may submit a full report in writing (by facsimile, overnight courier, or other means) by the next business day after discovery of the occurrence, and the report will serve as both the initial report and full report.

- b. For all deviations, the permittee shall report such events in semi-annual reporting and annual certifications required in this permit. This includes all upset conditions reported in 8a above. The semi-annual report must include all the information as required by the initial and full reports required in 8a.

[Rule 19.601, Rule 19.602, Rule 26.701(C)(3)(b), and 40 C.F.R. § 70.6(a)(3)(iii)(B)]

- 9. If any provision of the permit or the application thereof to any person or circumstance is held invalid, such invalidity will not affect other provisions or applications hereof which can be given effect without the invalid provision or application, and to this end, provisions of this Rule are declared to be separable and severable. [40 C.F.R. § 70.6(a)(5), Rule 26.701(E), and Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311]
- 10. The permittee must comply with all conditions of this Part 70 permit. Any permit noncompliance with applicable requirements as defined in Rule 26 constitutes a violation of the Clean Air Act, as amended, 42 U.S.C. § 7401, *et seq.* and is grounds for enforcement action; for permit termination, revocation and reissuance, for permit modification; or for denial of a permit renewal application. [40 C.F.R. § 70.6(a)(6)(i) and Rule 26.701(F)(1)]
- 11. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity to maintain compliance with the conditions of this permit. [40 C.F.R. § 70.6(a)(6)(ii) and Rule 26.701(F)(2)]
- 12. The Division of Environmental Quality may modify, revoke, reopen and reissue the permit or terminate the permit for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. [40 C.F.R. § 70.6(a)(6)(iii) and Rule 26.701(F)(3)]

13. This permit does not convey any property rights of any sort, or any exclusive privilege. [40 C.F.R. § 70.6(a)(6)(iv) and Rule 26.701(F)(4)]
14. The permittee must furnish to the Director, within the time specified by the Director, any information that the Director may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee must also furnish to the Director copies of records required by the permit. For information the permittee claims confidentiality, the Division of Environmental Quality may require the permittee to furnish such records directly to the Director along with a claim of confidentiality. [40 C.F.R. § 70.6(a)(6)(v) and Rule 26.701(F)(5)]
15. The permittee must pay all permit fees in accordance with the procedures established in Rule 9. [40 C.F.R. § 70.6(a)(7) and Rule 26.701(G)]
16. No permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes for changes provided for elsewhere in this permit. [40 C.F.R. § 70.6(a)(8) and Rule 26.701(H)]
17. If the permit allows different operating scenarios, the permittee shall, contemporaneously with making a change from one operating scenario to another, record in a log at the permitted facility a record of the operational scenario. [40 C.F.R. § 70.6(a)(9)(i) and Rule 26.701(I)(1)]
18. The Administrator and citizens may enforce under the Act all terms and conditions in this permit, including any provisions designed to limit a source's potential to emit, unless the Division of Environmental Quality specifically designates terms and conditions of the permit as being federally unenforceable under the Act or under any of its applicable requirements. [40 C.F.R. § 70.6(b) and Rule 26.702(A) and (B)]
19. Any document (including reports) required by this permit pursuant to 40 C.F.R. § 70 must contain a certification by a responsible official as defined in Rule 26.2. [40 C.F.R. § 70.6(c)(1) and Rule 26.703(A)]
20. The permittee must allow an authorized representative of the Division of Environmental Quality, upon presentation of credentials, to perform the following: [40 C.F.R. § 70.6(c)(2) and Rule 26.703(B)]
  - a. Enter upon the permittee's premises where the permitted source is located or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
  - b. Have access to and copy, at reasonable times, any records required under the conditions of this permit;

- c. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit; and
  - d. As authorized by the Act, sample or monitor at reasonable times substances or parameters for assuring compliance with this permit or applicable requirements.
- 21. The permittee shall submit a compliance certification with the terms and conditions contained in the permit, including emission limitations, standards, or work practices. The permittee must submit the compliance certification annually. If the permit establishes no other reporting period, the reporting period shall end on the last day of the anniversary month of the initial Title V permit. The report is due on the first day of the second month after the end of the reporting period. The permittee must also submit the compliance certification to the Administrator as well as to the Division of Environmental Quality. All compliance certifications required by this permit must include the following: [40 C.F.R. § 70.6(c)(5) and Rule 26.703(E)(3)]
  - a. The identification of each term or condition of the permit that is the basis of the certification;
  - b. The compliance status;
  - c. Whether compliance was continuous or intermittent;
  - d. The method(s) used for determining the compliance status of the source, currently and over the reporting period established by the monitoring requirements of this permit; and
  - e. Such other facts as the Division of Environmental Quality may require elsewhere in this permit or by § 114(a)(3) and § 504(b) of the Act.
- 22. Nothing in this permit will alter or affect the following: [Rule 26.704(C)]
  - a. The provisions of Section 303 of the Act (emergency orders), including the authority of the Administrator under that section;
  - b. The liability of the permittee for any violation of applicable requirements prior to or at the time of permit issuance;
  - c. The applicable requirements of the acid rain program, consistent with § 408(a) of the Act; or
  - d. The ability of EPA to obtain information from a source pursuant to § 114 of the Act.
- 23. This permit authorizes only those pollutant emitting activities addressed in this permit. [Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311]
- 24. The permittee may request in writing and at least 15 days in advance of the deadline, an extension to any testing, compliance or other dates in this permit. No such extensions are authorized until the permittee receives written Division of Environmental Quality approval. The Division of Environmental Quality may grant such a request, at its discretion in the following circumstances:

- a. Such an extension does not violate a federal requirement;
- b. The permittee demonstrates the need for the extension; and
- c. The permittee documents that all reasonable measures have been taken to meet the current deadline and documents reasons it cannot be met.

[Rule 18.314(A), Rule 19.416(A), Rule 26.1013(A), Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311, and 40 C.F.R. § 52 Subpart E]

25. The permittee may request in writing and at least 30 days in advance, temporary emissions and/or testing that would otherwise exceed an emission rate, throughput requirement, or other limit in this permit. No such activities are authorized until the permittee receives written Division of Environmental Quality approval. Any such emissions shall be included in the facility's total emissions and reported as such. The Division of Environmental Quality may grant such a request, at its discretion under the following conditions:

- a. Such a request does not violate a federal requirement;
- b. Such a request is temporary in nature;
- c. Such a request will not result in a condition of air pollution;
- d. The request contains such information necessary for the Division of Environmental Quality to evaluate the request, including but not limited to, quantification of such emissions and the date/time such emission will occur;
- e. Such a request will result in increased emissions less than five tons of any individual criteria pollutant, one ton of any single HAP and 2.5 tons of total HAPs; and
- f. The permittee maintains records of the dates and results of such temporary emissions/testing.

[Rule 18.314(B), Rule 19.416(B), Rule 26.1013(B), Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311, and 40 C.F.R. § 52 Subpart E]

26. The permittee may request in writing and at least 30 days in advance, an alternative to the specified monitoring in this permit. No such alternatives are authorized until the permittee receives written Division of Environmental Quality approval. The Division of Environmental Quality may grant such a request, at its discretion under the following conditions:

- a. The request does not violate a federal requirement;
- b. The request provides an equivalent or greater degree of actual monitoring to the current requirements; and
- c. Any such request, if approved, is incorporated in the next permit modification application by the permittee.



BFI-Waste System of Arkansas, LLC

Permit #: 1855-AOP-R7

AFIN: 63-00155

[Rule 18.314(C), Rule 19.416(C), Rule 26.1013(C), Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311, and 40 C.F.R. § 52 Subpart E]

27. Any credible evidence based on sampling, monitoring, and reporting may be used to determine violations of applicable emission limitations. [Rule 18.1001, Rule 19.701, Ark. Code Ann. § 8-4-203 as referenced by Ark. Code Ann. §§ 8-4-304 and 8-4-311, and 40 C.F.R. § 52 Subpart E]

**Appendix A**

**40 C.F.R. Part 60 Subpart XXX**

***Standards of Performance for Municipal Solid Waste Landfills That Commenced  
Construction, Reconstruction, or Modification After July 17, 2014***

## **Subpart XXX—Standards of Performance for Municipal Solid Waste Landfills That Commenced Construction, Reconstruction, or Modification After July 17, 2014**

**Source:**[81 FR 59368](#), Aug. 29, 2016, unless otherwise noted.

### **§ 60.760 Applicability, designation of affected source, and delegation of authority.**

(a) The provisions of this subpart apply to each municipal solid waste landfill that commenced construction, reconstruction, or modification after July 17, 2014. Physical or operational changes made to an MSW landfill solely to comply with [subparts Cc, Cf](#), or [WWW of this part](#) are not considered construction, reconstruction, or modification for the purposes of this section.

(b) The following authorities are retained by the Administrator and are not transferred to the state: [§ 60.764\(a\)\(5\)](#).

(c) Activities required by or conducted pursuant to a Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA), Resource Conservation and Recovery Act (RCRA), or state remedial action are not considered construction, reconstruction, or modification for purposes of this subpart.

### **§ 60.761 Definitions.**

As used in this subpart, all terms not defined herein have the meaning given them in the Act or in [subpart A of this part](#).

*Active collection system* means a gas collection system that uses gas mover equipment.

*Active landfill* means a landfill in which solid waste is being placed or a landfill that is planned to accept waste in the future.

*Closed area* means a separately lined area of an MSW landfill in which solid waste is no longer being placed. If additional solid waste is placed in that area of the landfill, that landfill area is no longer closed. The area must be separately lined to ensure that the landfill gas does not migrate between open and closed areas.

*Closed landfill* means a landfill in which solid waste is no longer being placed, and in which no additional solid wastes will be placed without first filing a notification of modification as prescribed under [§ 60.7\(a\)\(4\)](#). Once a notification of modification has been filed, and additional solid waste is placed in the landfill, the landfill is no longer closed.

*Closure* means that point in time when a landfill becomes a closed landfill.

*Commercial solid waste* means all types of solid waste generated by stores, offices, restaurants, warehouses, and other nonmanufacturing activities, excluding residential and industrial wastes.

*Controlled landfill* means any landfill at which collection and control systems are required under this subpart as a result of the nonmethane organic compounds emission rate. The landfill is considered controlled at the time a collection and control system design plan is submitted in compliance with either [§ 60.762\(b\)\(2\)\(i\)](#), [40 CFR part 60, subpart WWW](#), or a Federal plan or EPA approved and effective state plan or tribal plan that implements either [40 CFR part 60, subparts Cc](#) or [Cf](#), whichever regulation first required submission of a collection and control system design plan for the landfill.

*Corrective action analysis* means a description of all reasonable interim and long-term measures, if any, that are available, and an explanation of why the selected corrective action(s) is/are the best alternative(s), including, but not limited to, considerations of cost effectiveness, technical feasibility, safety, and secondary impacts.

*Design capacity* means the maximum amount of solid waste a landfill can accept, as indicated in terms of volume or mass in the most recent permit issued by the state, local, or tribal agency responsible for regulating the landfill, plus any in-place waste not accounted for in the most recent permit. If the owner or operator chooses to convert the design capacity from volume to mass or from mass to volume to demonstrate its design capacity is less than 2.5 million megagrams or 2.5 million cubic meters, the calculation must include a site-specific density, which must be recalculated annually.

*Disposal facility* means all contiguous land and structures, other appurtenances, and improvements on the land used for the disposal of solid waste.

*Emission rate cutoff* means the threshold annual emission rate to which a landfill compares its estimated emission rate to determine if control under the regulation is required.

*Enclosed combustor* means an enclosed firebox which maintains a relatively constant limited peak temperature generally using a limited supply of combustion air. An enclosed flare is considered an enclosed combustor.

*Flare* means an open combustor without enclosure or shroud.

*Gas mover equipment* means the equipment (*i.e.*, fan, blower, compressor) used to transport landfill gas through the header system.

*Gust* means the highest instantaneous wind speed that occurs over a 3-second running average.

*Household waste* means any solid waste (including garbage, trash, and sanitary waste in septic tanks) derived from households (including, but not limited to, single and multiple residences, hotels and motels, bunkhouses, ranger stations, crew quarters, campgrounds, picnic grounds, and day-use recreation areas). Household waste does not include fully segregated yard waste. Segregated yard waste means vegetative matter resulting exclusively from the cutting of grass, the pruning and/or removal of bushes, shrubs, and trees, the weeding of gardens, and other

landscaping maintenance activities. Household waste does not include construction, renovation, or demolition wastes, even if originating from a household.

*Industrial solid waste* means solid waste generated by manufacturing or industrial processes that is not a hazardous waste regulated under Subtitle C of the Resource Conservation and Recovery Act, [parts 264](#) and [265 of this chapter](#). Such waste may include, but is not limited to, waste resulting from the following manufacturing processes: Electric power generation; fertilizer/agricultural chemicals; food and related products/by-products; inorganic chemicals; iron and steel manufacturing; leather and leather products; nonferrous metals manufacturing/foundries; organic chemicals; plastics and resins manufacturing; pulp and paper industry; rubber and miscellaneous plastic products; stone, glass, clay, and concrete products; textile manufacturing; transportation equipment; and water treatment. This term does not include mining waste or oil and gas waste.

*Interior well* means any well or similar collection component located inside the perimeter of the landfill waste. A perimeter well located outside the landfilled waste is not an interior well.

*Landfill* means an area of land or an excavation in which wastes are placed for permanent disposal, and that is not a land application unit, surface impoundment, injection well, or waste pile as those terms are defined under [§ 257.2 of this title](#).

*Lateral expansion* means a horizontal expansion of the waste boundaries of an existing MSW landfill. A lateral expansion is not a modification unless it results in an increase in the design capacity of the landfill.

*Leachate recirculation* means the practice of taking the leachate collected from the landfill and reapplying it to the landfill by any of one of a variety of methods, including pre-wetting of the waste, direct discharge into the working face, spraying, infiltration ponds, vertical injection wells, horizontal gravity distribution systems, and pressure distribution systems.

*Modification* means an increase in the permitted volume design capacity of the landfill by either lateral or vertical expansion based on its permitted design capacity as of July 17, 2014. Modification does not occur until the owner or operator commences construction on the lateral or vertical expansion.

*Municipal solid waste landfill* or *MSW landfill* means an entire disposal facility in a contiguous geographical space where household waste is placed in or on land. An MSW landfill may also receive other types of RCRA Subtitle D wastes ([§ 257.2 of this title](#)) such as commercial solid waste, nonhazardous sludge, conditionally exempt small quantity generator waste, and industrial solid waste. Portions of an MSW landfill may be separated by access roads. An MSW landfill may be publicly or privately owned. An MSW landfill may be a new MSW landfill, an existing MSW landfill, or a lateral expansion.

*Municipal solid waste landfill emissions* or *MSW landfill emissions* means gas generated by the decomposition of organic waste deposited in an MSW landfill or derived from the evolution of organic compounds in the waste.

*NMOC* means nonmethane organic compounds, as measured according to the provisions of [§ 60.764](#).

*Nondegradable waste* means any waste that does not decompose through chemical breakdown or microbiological activity. Examples are, but are not limited to, concrete, municipal waste combustor ash, and metals.

*Passive collection system* means a gas collection system that solely uses positive pressure within the landfill to move the gas rather than using gas mover equipment.

*Root cause analysis* means an assessment conducted through a process of investigation to determine the primary cause, and any other contributing causes, of positive pressure at a wellhead.

*Segregated yard waste* means vegetative matter resulting exclusively from the cutting of grass, the pruning and/or removal of bushes, shrubs, and trees, the weeding of gardens, and other landscaping maintenance activities.

*Sludge* means the term sludge as defined in [40 CFR 258.2](#).

*Solid waste* means the term solid waste as defined in [40 CFR 258.2](#).

*Sufficient density* means any number, spacing, and combination of collection system components, including vertical wells, horizontal collectors, and surface collectors, necessary to maintain emission and migration control as determined by measures of performance set forth in this part.

*Sufficient extraction rate* means a rate sufficient to maintain a negative pressure at all wellheads in the collection system without causing air infiltration, including any wellheads connected to the system as a result of expansion or excess surface emissions, for the life of the blower.

*Treated landfill gas* means landfill gas processed in a treatment system as defined in this subpart.

*Treatment system* means a system that filters, de-waters, and compresses landfill gas for sale or beneficial use.

*Untreated landfill gas* means any landfill gas that is not treated landfill gas.

[[81 FR 59368](#), Aug. 29, 2016, as amended at [87 FR 8202](#), Feb. 14, 2022]

## **§ 60.762 Standards for air emissions from municipal solid waste landfills.**

(a) Each owner or operator of an MSW landfill having a design capacity less than 2.5 million megagrams by mass or 2.5 million cubic meters by volume must submit an initial design capacity report to the Administrator as provided in [§ 60.767\(a\)](#). The landfill may calculate design capacity in either megagrams or cubic meters for comparison with the exemption values. Any density conversions must be documented and submitted with the report. Submittal of the initial design capacity report fulfills the requirements of this subpart except as provided for in [paragraphs \(a\)\(1\)](#) and [\(2\)](#) of this section.

(1) The owner or operator must submit to the Administrator an amended design capacity report, as provided for in [§ 60.767\(a\)\(3\)](#).

(2) When an increase in the maximum design capacity of a landfill exempted from the provisions of [§§ 60.762\(b\)](#) through [60.769](#) on the basis of the design capacity exemption in [paragraph \(a\)](#) of this section results in a revised maximum design capacity equal to or greater than 2.5 million megagrams and 2.5 million cubic meters, the owner or operator must comply with the provisions of [paragraph \(b\)](#) of this section.

(b) Each owner or operator of an MSW landfill having a design capacity equal to or greater than 2.5 million megagrams and 2.5 million cubic meters, must either comply with [paragraph \(b\)\(2\)](#) of this section or calculate an NMOC emission rate for the landfill using the procedures specified in [§ 60.764](#). The NMOC emission rate must be recalculated annually, except as provided in [§ 60.767\(b\)\(1\)\(ii\)](#). The owner or operator of an MSW landfill subject to this subpart with a design capacity greater than or equal to 2.5 million megagrams and 2.5 million cubic meters is subject to part 70 or 71 permitting requirements.

(1) If the calculated NMOC emission rate is less than 34 megagrams per year, the owner or operator must:

(i) Submit an annual NMOC emission rate emission report to the Administrator, except as provided for in [§ 60.767\(b\)\(1\)\(ii\)](#); and

(ii) Recalculate the NMOC emission rate annually using the procedures specified in [§ 60.764\(a\)\(1\)](#) until such time as the calculated NMOC emission rate is equal to or greater than 34 megagrams per year, or the landfill is closed.

(A) If the calculated NMOC emission rate, upon initial calculation or annual recalculation required in [paragraph \(b\)](#) of this section, is equal to or greater than 34 megagrams per year, the owner or operator must either: Comply with [paragraph \(b\)\(2\)](#) of this section; calculate NMOC emissions using the next higher tier in [§ 60.764](#); or conduct a surface emission monitoring demonstration using the procedures specified in [§ 60.764\(a\)\(6\)](#).

(B) If the landfill is permanently closed, a closure report must be submitted to the Administrator as provided for in [§ 60.767\(e\)](#).

(2) If the calculated NMOC emission rate is equal to or greater than 34 megagrams per year using Tier 1, 2, or 3 procedures, the owner or operator must either:

(i) **Calculated NMOC Emission Rate.** Submit an initial or revised collection and control system design plan prepared by a professional engineer to the Administrator as specified in [§ 60.767\(c\)](#) or [\(d\)](#); calculate NMOC emissions using the next higher tier in [§ 60.764](#); or conduct a surface emission monitoring demonstration using the procedures specified in [§ 60.764\(a\)\(6\)](#). The collection and control system must meet the requirements in [paragraphs \(b\)\(2\)\(ii\)](#) and [\(iii\)](#) of this section.

(ii) **Collection system.** Install and start up a collection and control system that captures the gas generated within the landfill as required by [paragraphs \(b\)\(2\)\(ii\)\(C\)](#) or [\(D\)](#) and [\(b\)\(2\)\(iii\)](#) of this section within 30 months after:

(A) The first annual report submitted under this sub[part or part 62 of this subchapter](#) in which the NMOC emission rate equals or exceeds 34 megagrams per year, unless Tier 2 or Tier 3 sampling demonstrates that the NMOC emission rate is less than 34 megagrams per year, as specified in [§ 60.767\(c\)\(4\)](#); or

(B) The most recent NMOC emission rate report in which the NMOC emission rate equals or exceeds 34 megagrams per year based on Tier 2, if the Tier 4 surface emissions monitoring shows a surface methane emission concentration of 500 parts per million methane or greater as specified in [§ 60.767\(c\)\(4\)\(iii\)](#).

(C) An active collection system must:

(1) Be designed to handle the maximum expected gas flow rate from the entire area of the landfill that warrants control over the intended use period of the gas control system equipment;

(2) Collect gas from each area, cell, or group of cells in the landfill in which the initial solid waste has been placed for a period of 5 years or more if active; or 2 years or more if closed or at final grade.

(3) Collect gas at a sufficient extraction rate;

(4) Be designed to minimize off-site migration of subsurface gas.

(D) A passive collection system must:

(1) Comply with the provisions specified in [paragraphs \(b\)\(2\)\(ii\)\(C\)\(1\)](#), [\(2\)](#), and [\(3\)](#) of this section.

(2) Be installed with liners on the bottom and all sides in all areas in which gas is to be collected. The liners must be installed as required under [40 CFR 258.40](#).



(iii) **Control system.** Route all the collected gas to a control system that complies with the requirements in either [paragraph \(b\)\(2\)\(iii\)\(A\)](#), [\(B\)](#), or [\(C\)](#) of this section.

(A) A non-enclosed flare designed and operated in accordance with the parameters established in [§ 60.18](#) except as noted in [§ 60.764\(e\)](#); or

(B) A control system designed and operated to reduce NMOC by 98 weight-percent, or, when an enclosed combustion device is used for control, to either reduce NMOC by 98 weight percent or reduce the outlet NMOC concentration to less than 20 parts per million by volume, dry basis as hexane at 3 percent oxygen. The reduction efficiency or parts per million by volume must be established by an initial performance test to be completed no later than 180 days after the initial startup of the approved control system using the test methods specified in [§ 60.764\(d\)](#). The performance test is not required for boilers and process heaters with design heat input capacities equal to or greater than 44 megawatts that burn landfill gas for compliance with this subpart.

(1) If a boiler or process heater is used as the control device, the landfill gas stream must be introduced into the flame zone.

(2) The control device must be operated within the parameter ranges established during the initial or most recent performance test. The operating parameters to be monitored are specified in [§ 60.766](#);

(C) Route the collected gas to a treatment system that processes the collected gas for subsequent sale or beneficial use such as fuel for combustion, production of vehicle fuel, production of high-Btu gas for pipeline injection, or use as a raw material in a chemical manufacturing process. Venting of treated landfill gas to the ambient air is not allowed. If the treated landfill gas cannot be routed for subsequent sale or beneficial use, then the treated landfill gas must be controlled according to either [paragraph \(b\)\(2\)\(iii\)\(A\)](#) or [\(B\)](#) of this section.

(D) All emissions from any atmospheric vent from the gas treatment system are subject to the requirements of [paragraph \(b\)\(2\)\(iii\)\(A\)](#) or [\(B\)](#) of this section. For purposes of this subpart, atmospheric vents located on the condensate storage tank are not part of the treatment system and are exempt from the requirements of [paragraph \(b\)\(2\)\(iii\)\(A\)](#) or [\(B\)](#) of this section.

(iv) **Operation.** Operate the collection and control device installed to comply with this subpart in accordance with the provisions of [§§ 60.763](#), [60.765](#), and [60.766](#); or the provisions of [§§ 63.1958](#), [63.1960](#), and [63.1961 of this chapter](#). Once the owner or operator begins to comply with the provisions of [§§ 63.1958](#), [63.1960](#), and [63.1961 of this chapter](#), the owner or operator must continue to operate the collection and control device according to those provisions and cannot return to the provisions of [§§ 60.763](#), [60.765](#), and [60.766](#).

(v) **Removal criteria.** The collection and control system may be capped, removed, or decommissioned if the following criteria are met:

(A) The landfill is a closed landfill (as defined in [§ 60.761](#)). A closure report must be submitted to the Administrator as provided in [§ 60.767\(e\)](#).

(B) The collection and control system has been in operation a minimum of 15 years or the landfill owner or operator demonstrates that the GCCS will be unable to operate for 15 years due to declining gas flow.

(C) Following the procedures specified in [§ 60.764\(b\)](#), the calculated NMOC emission rate at the landfill is less than 34 megagrams per year on three successive test dates. The test dates must be no less than 90 days apart, and no more than 180 days apart.

(c) For purposes of obtaining an operating permit under title V of the Clean Air Act, the owner or operator of an MSW landfill subject to this subpart with a design capacity less than 2.5 million megagrams or 2.5 million cubic meters is not subject to the requirement to obtain an operating permit for the landfill under [part 70](#) or [71 of this chapter](#), unless the landfill is otherwise subject to either part 70 or 71. For purposes of submitting a timely application for an operating permit under part 70 or 71, the owner or operator of an MSW landfill subject to this subpart with a design capacity greater than or equal to 2.5 million megagrams and 2.5 million cubic meters, and not otherwise subject to either part 70 or 71, becomes subject to the requirements of [§ 70.5\(a\)\(1\)\(i\)](#) or [§ 71.5\(a\)\(1\)\(i\) of this chapter](#), regardless of when the design capacity report is actually submitted, no later than:

(1) November 28, 2016 for MSW landfills that commenced construction, modification, or reconstruction after July 17, 2014 but before August 29, 2016;

(2) Ninety days after the date of commenced construction, modification, or reconstruction for MSW landfills that commence construction, modification, or reconstruction after August 29, 2016.

(d) When an MSW landfill subject to this subpart is closed as defined in this subpart, the owner or operator is no longer subject to the requirement to maintain an operating permit under [part 70](#) or [71 of this chapter](#) for the landfill if the landfill is not otherwise subject to the requirements of either part 70 or 71 and if either of the following conditions are met:

(1) The landfill was never subject to the requirement for a control system under [paragraph \(b\)\(2\)](#) of this section; or

(2) The owner or operator meets the conditions for control system removal specified in [paragraph \(b\)\(2\)\(v\)](#) of this section.

[[81 FR 59368](#), Aug. 29, 2016, as amended at [85 FR 17261](#), Mar. 26, 2020; [87 FR 8203](#), Feb. 14, 2022]

#### **§ 60.763 Operational standards for collection and control systems.**

Each owner or operator of an MSW landfill with a gas collection and control system used to comply with the provisions of [§ 60.762\(b\)\(2\)](#) must:

(a) Operate the collection system such that gas is collected from each area, cell, or group of cells in the MSW landfill in which solid waste has been in place for:

(1) 5 years or more if active; or

(2) 2 years or more if closed or at final grade;

(b) Operate the collection system with negative pressure at each wellhead except under the following conditions:

(1) A fire or increased well temperature. The owner or operator must record instances when positive pressure occurs in efforts to avoid a fire. These records must be submitted with the annual reports as provided in [§ 60.767\(g\)\(1\)](#);

(2) Use of a geomembrane or synthetic cover. The owner or operator must develop acceptable pressure limits in the design plan;

(3) A decommissioned well. A well may experience a static positive pressure after shut down to accommodate for declining flows. All design changes must be approved by the Administrator as specified in [§ 60.767\(c\)](#);

(c) Operate each interior wellhead in the collection system with a landfill gas temperature less than 55 degrees Celsius (131 degrees Fahrenheit). The owner or operator may establish a higher operating temperature value at a particular well. A higher operating value demonstration must be submitted to the Administrator for approval and must include supporting data demonstrating that the elevated parameter neither causes fires nor significantly inhibits anaerobic decomposition by killing methanogens. The demonstration must satisfy both criteria in order to be approved (*i.e.*, neither causing fires nor killing methanogens is acceptable).

(d) Operate the collection system so that the methane concentration is less than 500 parts per million above background at the surface of the landfill. To determine if this level is exceeded, the owner or operator must conduct surface testing using an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications provided in [§ 60.765\(d\)](#). The owner or operator must conduct surface testing around the perimeter of the collection area and along a pattern that traverses the landfill at no more than 30-meter intervals and where visual observations indicate elevated concentrations of landfill gas, such as distressed vegetation and cracks or seeps in the cover and all cover penetrations. Thus, the owner or operator must monitor any openings that are within an area of the landfill where waste has been placed and a gas collection system is required. The owner or operator may establish an alternative traversing pattern that ensures equivalent coverage. A surface monitoring design plan must be developed that includes a topographical map with the monitoring route and the rationale for any site-

specific deviations from the 30-meter intervals. Areas with steep slopes or other dangerous areas may be excluded from the surface testing.

(e) Operate the system such that all collected gases are vented to a control system designed and operated in compliance with [§ 60.762\(b\)\(2\)\(iii\)](#). In the event the collection or control system is not operating, the gas mover system must be shut down and all valves in the collection and control system contributing to venting of the gas to the atmosphere must be closed within 1 hour of the collection or control system not operating; and

(f) Operate the control system at all times when the collected gas is routed to the system.

(g) If monitoring demonstrates that the operational requirements in [paragraphs \(b\), \(c\), or \(d\)](#) of this section are not met, corrective action must be taken as specified in [§ 60.765\(a\)\(3\)](#) and [\(5\)](#) or [\(c\)](#). If corrective actions are taken as specified in [§ 60.765](#), the monitored exceedance is not a violation of the operational requirements in this section.

#### **§ 60.764 Test methods and procedures.**

(a)

(1) **NMOC emission rate.** The landfill owner or operator must calculate the NMOC emission rate using either Equation 1 provided in [paragraph \(a\)\(1\)\(i\)](#) of this section or Equation 2 provided in [paragraph \(a\)\(1\)\(ii\)](#) of this section. Both Equation 1 and Equation 2 may be used if the actual year-to-year solid waste acceptance rate is known, as specified in [paragraph \(a\)\(1\)\(i\)](#) of this section, for part of the life of the landfill and the actual year-to-year solid waste acceptance rate is unknown, as specified in [paragraph \(a\)\(1\)\(ii\)](#) of this section, for part of the life of the landfill. The values to be used in both Equation 1 and Equation 2 are 0.05 per year for  $k$ , 170 cubic meters per megagram for  $L_o$ , and 4,000 parts per million by volume as hexane for the  $C_{NMOC}$ . For landfills located in geographical areas with a 30-year annual average precipitation of less than 25 inches, as measured at the nearest representative official meteorologic site, the  $k$  value to be used is 0.02 per year.

(i)

(A) Equation 1 must be used if the actual year-to-year solid waste acceptance rate is known.

$$M_{NMOC} = \sum_{i=1}^n 2 k L_o M_i (e^{-k t_i}) (C_{NMOC}) (3.6 \times 10^{-9}) \quad (\text{Eq. 1})$$

Where:

$M_{NMOC}$  = Total NMOC emission rate from the landfill, megagrams per year.

$k$  = Methane generation rate constant,  $\text{year}^{-1}$ .

$L_o$  = Methane generation potential, cubic meters per megagram solid waste.

$M_i$  = Mass of solid waste in the  $i^{th}$  section, megagrams.

$t_i$  = Age of the  $i^{th}$  section, years.

$C_{NMOC}$  = Concentration of NMOC, parts per million by volume as hexane.

$3.6 \times 10^{-9}$  = Conversion factor.

(B) The mass of nondegradable solid waste may be subtracted from the total mass of solid waste in a particular section of the landfill when calculating the value for  $M_i$  if documentation of the nature and amount of such wastes is maintained.

(ii)

(A) Equation 2 must be used if the actual year-to-year solid waste acceptance rate is unknown.

$$M_{NMOC} = 2L_oR (e^{-kc} - e^{-kt}) C_{NMOC} (3.6 \times 10^{-9}) \quad (\text{Eq. 2})$$

Where:

$M_{NMOC}$  = Mass emission rate of NMOC, megagrams per year.

$L_o$  = Methane generation potential, cubic meters per megagram solid waste.

$R$  = Average annual acceptance rate, megagrams per year.

$k$  = Methane generation rate constant,  $\text{year}^{-1}$ .

$t$  = Age of landfill, years.

$C_{NMOC}$  = Concentration of NMOC, parts per million by volume as hexane.

$c$  = Time since closure, years; for active landfill  $c = 0$  and  $e^{-kc} = 1$ .

$3.6 \times 10^{-9}$  = Conversion factor.

(B) The mass of nondegradable solid waste may be subtracted from the total mass of solid waste in a particular section of the landfill when calculating the value of  $R$ , if documentation of the nature and amount of such wastes is maintained.

(2) **Tier 1.** The owner or operator must compare the calculated NMOC mass emission rate to the standard of 34 megagrams per year.

(i) If the NMOC emission rate calculated in [paragraph \(a\)\(1\)](#) of this section is less than 34 megagrams per year, then the landfill owner or operator must submit an NMOC emission rate

report according to [§ 60.767\(b\)](#), and must recalculate the NMOC mass emission rate annually as required under [§ 60.762\(b\)](#).

(ii) If the calculated NMOC emission rate as calculated in [paragraph \(a\)\(1\)](#) of this section is equal to or greater than 34 megagrams per year, then the landfill owner must either:

(A) Submit a gas collection and control system design plan within 1 year as specified in [§ 60.767\(c\)](#) and install and operate a gas collection and control system within 30 months according to [§ 60.762\(b\)\(2\)\(ii\)](#) and [\(iii\)](#);

(B) Determine a site-specific NMOC concentration and recalculate the NMOC emission rate using the Tier 2 procedures provided in [paragraph \(a\)\(3\)](#) of this section; or

(C) Determine a site-specific methane generation rate constant and recalculate the NMOC emission rate using the Tier 3 procedures provided in [paragraph \(a\)\(4\)](#) of this section.

(3) **Tier 2.** The landfill owner or operator must determine the site-specific NMOC concentration using the following sampling procedure. The landfill owner or operator must install at least two sample probes per hectare, evenly distributed over the landfill surface that has retained waste for at least 2 years. If the landfill is larger than 25 hectares in area, only 50 samples are required. The probes should be evenly distributed across the sample area. The sample probes should be located to avoid known areas of nondegradable solid waste. The owner or operator must collect and analyze one sample of landfill gas from each probe to determine the NMOC concentration using Method 25 or 25C of [appendix A of this part](#). Taking composite samples from different probes into a single cylinder is allowed; however, equal sample volumes must be taken from each probe. For each composite, the sampling rate, collection times, beginning and ending cylinder vacuums, or alternative volume measurements must be recorded to verify that composite volumes are equal. Composite sample volumes should not be less than one liter unless evidence can be provided to substantiate the accuracy of smaller volumes. Terminate compositing before the cylinder approaches ambient pressure where measurement accuracy diminishes. If more than the required number of samples are taken, all samples must be used in the analysis. The landfill owner or operator must divide the NMOC concentration from Method 25 or 25C of [appendix A of this part](#) by six to convert from  $C_{\text{NMOC}}$  as carbon to  $C_{\text{NMOC}}$  as hexane. If the landfill has an active or passive gas removal system in place, Method 25 or 25C samples may be collected from these systems instead of surface probes provided the removal system can be shown to provide sampling as representative as the two sampling probe per hectare requirement. For active collection systems, samples may be collected from the common header pipe. The sample location on the common header pipe must be before any gas moving, condensate removal, or treatment system equipment. For active collection systems, a minimum of three samples must be collected from the header pipe.

(i) Within 60 days after the date of completing each performance test (as defined in [§ 60.8](#)), the owner or operator must submit the results according to [§ 60.767\(i\)\(1\)](#).

(ii) The landfill owner or operator must recalculate the NMOC mass emission rate using Equation 1 or Equation 2 provided in [paragraph \(a\)\(1\)\(i\)](#) or [\(a\)\(1\)\(ii\)](#) of this section and using the average site-specific NMOC concentration from the collected samples instead of the default value provided in [paragraph \(a\)\(1\)](#) of this section.

(iii) If the resulting NMOC mass emission rate is less than 34 megagrams per year, then the owner or operator must submit a periodic estimate of NMOC emissions in an NMOC emission rate report according to [§ 60.767\(b\)\(1\)](#), and must recalculate the NMOC mass emission rate annually as required under [§ 60.762\(b\)](#). The site-specific NMOC concentration must be retested every 5 years using the methods specified in this section.

(iv) If the NMOC mass emission rate as calculated using the Tier 2 site-specific NMOC concentration is equal to or greater than 34 megagrams per year, the landfill owner or operator must either:

(A) Submit a gas collection and control system design plan within 1 year as specified in [§ 60.767\(c\)](#) and install and operate a gas collection and control system within 30 months according to [§ 60.762\(b\)\(2\)\(ii\)](#) and [\(iii\)](#);

(B) Determine a site-specific methane generation rate constant and recalculate the NMOC emission rate using the site-specific methane generation rate using the Tier 3 procedures specified in [paragraph \(a\)\(4\)](#) of this section; or

(C) Conduct a surface emission monitoring demonstration using the Tier 4 procedures specified in [paragraph \(a\)\(6\)](#) of this section.

(4) **Tier 3.** The site-specific methane generation rate constant must be determined using the procedures provided in Method 2E of [appendix A of this part](#). The landfill owner or operator must estimate the NMOC mass emission rate using Equation 1 or Equation 2 in [paragraph \(a\)\(1\)\(i\)](#) or [\(ii\)](#) of this section and using a site-specific methane generation rate constant, and the site-specific NMOC concentration as determined in [paragraph \(a\)\(3\)](#) of this section instead of the default values provided in [paragraph \(a\)\(1\)](#) of this section. The landfill owner or operator must compare the resulting NMOC mass emission rate to the standard of 34 megagrams per year.

(i) If the NMOC mass emission rate as calculated using the Tier 2 site-specific NMOC concentration and Tier 3 site-specific methane generation rate is equal to or greater than 34 megagrams per year, the owner or operator must either:

(A) Submit a gas collection and control system design plan within 1 year as specified in [§ 60.767\(c\)](#) and install and operate a gas collection and control system within 30 months according to [§ 60.762\(b\)\(2\)\(ii\)](#) and [\(iii\)](#); or

(B) Conduct a surface emission monitoring demonstration using the Tier 4 procedures specified in [paragraph \(a\)\(6\)](#) of this section.



(ii) If the NMOC mass emission rate is less than 34 megagrams per year, then the owner or operator must recalculate the NMOC mass emission rate annually using Equation 1 or Equation 2 in [paragraph \(a\)\(1\)](#) of this section and using the site-specific Tier 2 NMOC concentration and Tier 3 methane generation rate constant and submit a periodic NMOC emission rate report as provided in [§ 60.767\(b\)\(1\)](#). The calculation of the methane generation rate constant is performed only once, and the value obtained from this test must be used in all subsequent annual NMOC emission rate calculations.

(5) **Other methods.** The owner or operator may use other methods to determine the NMOC concentration or a site-specific methane generation rate constant as an alternative to the methods required in [paragraphs \(a\)\(3\)](#) and [\(4\)](#) of this section if the method has been approved by the Administrator.

(6) **Tier 4.** The landfill owner or operator must demonstrate that surface methane emissions are below 500 parts per million. Surface emission monitoring must be conducted on a quarterly basis using the following procedures. Tier 4 is allowed only if the landfill owner or operator can demonstrate that NMOC emissions are greater than or equal to 34 Mg/yr but less than 50 Mg/yr using Tier 1 or Tier 2. If both Tier 1 and Tier 2 indicate NMOC emissions are 50 Mg/yr or greater, then Tier 4 cannot be used. In addition, the landfill must meet the criteria in [paragraph \(a\)\(6\)\(viii\)](#) of this section.

(i) The owner or operator must measure surface concentrations of methane along the entire perimeter of the landfill and along a pattern that traverses the landfill at no more than 30-meter intervals using an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications provided in [§ 60.765\(d\)](#).

(ii) The background concentration must be determined by moving the probe inlet upwind and downwind at least 30 meters from the waste mass boundary of the landfill.

(iii) Surface emission monitoring must be performed in accordance with [section 8.3.1](#) of Method 21 of [appendix A of this part](#), except that the probe inlet must be placed no more than 5 centimeters above the landfill surface; the constant measurement of distance above the surface should be based on a mechanical device such as with a wheel on a pole, except as described in [paragraph \(a\)\(6\)\(iii\)\(A\)](#) of this section.

(A) The owner or operator must use a wind barrier, similar to a funnel, when onsite average wind speed exceeds 4 miles per hour or 2 meters per second or gust exceeding 10 miles per hour. Average on-site wind speed must also be determined in an open area at 5-minute intervals using an on-site anemometer with a continuous recorder and data logger for the entire duration of the monitoring event. The wind barrier must surround the SEM monitor, and must be placed on the ground, to ensure wind turbulence is blocked. SEM cannot be conducted if average wind speed exceeds 25 miles per hour.



(B) Landfill surface areas where visual observations indicate elevated concentrations of landfill gas, such as distressed vegetation and cracks or seeps in the cover, and all cover penetrations must also be monitored using a device meeting the specifications provided in [§ 60.765\(d\)](#).

(iv) Each owner or operator seeking to comply with the Tier 4 provisions in [paragraph \(a\)\(6\)](#) of this section must maintain records of surface emission monitoring as provided in [§ 60.768\(g\)](#) and submit a Tier 4 surface emissions report as provided in [§ 60.767\(c\)\(4\)\(iii\)](#).

(v) If there is any measured concentration of methane of 500 parts per million or greater from the surface of the landfill, the owner or operator must submit a gas collection and control system design plan within 1 year of the first measured concentration of methane of 500 parts per million or greater from the surface of the landfill according to [§ 60.767\(c\)](#) and install and operate a gas collection and control system according to [§ 60.762\(b\)\(2\)\(ii\)](#) and [\(iii\)](#) within 30 months of the most recent NMOC emission rate report in which the NMOC emission rate equals or exceeds 34 megagrams per year based on Tier 2.

(vi) If after four consecutive quarterly monitoring periods at a landfill, other than a closed landfill, there is no measured concentration of methane of 500 parts per million or greater from the surface of the landfill, the owner or operator must continue quarterly surface emission monitoring using the methods specified in this section.

(vii) If after four consecutive quarterly monitoring periods at a closed landfill there is no measured concentration of methane of 500 parts per million or greater from the surface of the landfill, the owner or operator must conduct annual surface emission monitoring using the methods specified in this section.

(viii) If a landfill has installed and operates a collection and control system that is not required by this subpart, then the collection and control system must meet the following criteria:

(A) The gas collection and control system must have operated for 6,570 out of 8,760 hours preceding the Tier 4 surface emissions monitoring demonstration.

(B) During the Tier 4 surface emissions monitoring demonstration, the gas collection and control system must operate as it normally would to collect and control as much landfill gas as possible.

(b) After the installation and startup of a collection and control system in compliance with this subpart, the owner or operator must calculate the NMOC emission rate for purposes of determining when the system can be capped, removed or decommissioned as provided in [§ 60.762\(b\)\(2\)\(v\)](#), using Equation 3:

$$M_{\text{NMOC}} = 1.89 \times 10^{-3} Q_{\text{LFG}} C_{\text{NMOC}} \quad (\text{Eq. 3})$$

Where:

$M_{\text{NMOC}}$  = Mass emission rate of NMOC, megagrams per year.

$Q_{\text{LFG}}$  = Flow rate of landfill gas, cubic meters per minute.

$C_{\text{NMOC}}$  = NMOC concentration, parts per million by volume as hexane.

(1) The flow rate of landfill gas,  $Q_{\text{LFG}}$ , must be determined by measuring the total landfill gas flow rate at the common header pipe that leads to the control system using a gas flow measuring device calibrated according to the provisions of section 10 of Method 2E of [appendix A of this part](#).

(2) The average NMOC concentration,  $C_{\text{NMOC}}$ , must be determined by collecting and analyzing landfill gas sampled from the common header pipe before the gas moving or condensate removal equipment using the procedures in Method 25 or Method 25C. The sample location on the common header pipe must be before any condensate removal or other gas refining units. The landfill owner or operator must divide the NMOC concentration from Method 25 or Method 25C of [appendix A of this part](#) by six to convert from  $C_{\text{NMOC}}$  as carbon to  $C_{\text{NMOC}}$  as hexane.

(3) The owner or operator may use another method to determine landfill gas flow rate and NMOC concentration if the method has been approved by the Administrator.

(i) Within 60 days after the date of completing each performance test (as defined in [§ 60.8](#)), the owner or operator must submit the results of the performance test, including any associated fuel analyses, according to [§ 60.767\(i\)\(1\)](#).

(ii) [Reserved]

(c) When calculating emissions for Prevention of Significant Deterioration purposes, the owner or operator of each MSW landfill subject to the provisions of this subpart must estimate the NMOC emission rate for comparison to the Prevention of Significant Deterioration major source and significance levels in [§§ 51.166](#) or [52.21 of this chapter](#) using Compilation of Air Pollutant Emission Factors, Volume I: Stationary Point and Area Sources (AP-42) or other approved measurement procedures.

(d) For the performance test required in [§ 60.762\(b\)\(2\)\(iii\)\(B\)](#), Method 25 or 25C (Method 25C may be used at the inlet only) of [appendix A of this part](#) must be used to determine compliance with the 98 weight-percent efficiency or the 20 parts per million by volume outlet concentration level, unless another method to demonstrate compliance has been approved by the Administrator as provided by [§ 60.767\(c\)\(2\)](#). Method 3, 3A, or 3C must be used to determine oxygen for correcting the NMOC concentration as hexane to 3 percent. In cases where the outlet concentration is less than 50 ppm NMOC as carbon (8 ppm NMOC as hexane), Method 25A should be used in place of Method 25. Method 18 may be used in conjunction with Method 25A on a limited basis (compound specific, *e.g.*, methane) or Method 3C may be used to determine methane. The methane as carbon should be subtracted from the Method 25A total hydrocarbon

value as carbon to give NMOC concentration as carbon. The landowner or operator must divide the NMOC concentration as carbon by 6 to convert from the CNMOC as carbon to CNMOC as hexane. Equation 4 must be used to calculate efficiency:

$$\text{Control Efficiency} = (\text{NMOC}_{\text{in}} - \text{NMOC}_{\text{out}}) / (\text{NMOC}_{\text{in}}) \quad (\text{Eq. 4})$$

Where:

$\text{NMOC}_{\text{in}}$  = Mass of NMOC entering control device.

$\text{NMOC}_{\text{out}}$  = Mass of NMOC exiting control device.

(e) For the performance test required in [§ 60.762\(b\)\(2\)\(iii\)\(A\)](#), the net heating value of the combusted landfill gas as determined in [§ 60.18\(f\)\(3\)](#) is calculated from the concentration of methane in the landfill gas as measured by Method 3C. A minimum of three 30-minute Method 3C samples are determined. The measurement of other organic components, hydrogen, and carbon monoxide is not applicable. Method 3C may be used to determine the landfill gas molecular weight for calculating the flare gas exit velocity under [§ 60.18\(f\)\(4\)](#).

(1) Within 60 days after the date of completing each performance test (as defined in [§ 60.8](#)), the owner or operator must submit the results of the performance tests, including any associated fuel analyses, required by [§ 60.764\(b\)](#) or [\(d\)](#) according to [§ 60.767\(i\)\(1\)](#).

(2) [Reserved]

### **§ 60.765 Compliance provisions.**

(a) Except as provided in [§ 60.767\(c\)\(2\)](#), the specified methods in [paragraphs \(a\)\(1\)](#) through [\(6\)](#) of this section must be used to determine whether the gas collection system is in compliance with [§ 60.762\(b\)\(2\)\(ii\)](#).

(1) For the purposes of calculating the maximum expected gas generation flow rate from the landfill to determine compliance with [§ 60.762\(b\)\(2\)\(ii\)\(C\)\(I\)](#), either Equation 5 or Equation 6 must be used. The methane generation rate constant (k) and methane generation potential ( $L_0$ ) kinetic factors should be those published in the most recent Compilation of Air Pollutant Emission Factors (AP-42) or other site specific values demonstrated to be appropriate and approved by the Administrator. If k has been determined as specified in [§ 60.764\(a\)\(4\)](#), the value of k determined from the test must be used. A value of no more than 15 years must be used for the intended use period of the gas mover equipment. The active life of the landfill is the age of the landfill plus the estimated number of years until closure.

(i) For sites with unknown year-to-year solid waste acceptance rate:

$$Q_m = 2L_0R (e^{-kc} - e^{-kt}) \quad (\text{Eq. 5})$$

Where:

$Q_m$  = Maximum expected gas generation flow rate, cubic meters per year.

$L_o$  = Methane generation potential, cubic meters per megagram solid waste.

$R$  = Average annual acceptance rate, megagrams per year.

$k$  = Methane generation rate constant, year<sup>-1</sup>.

$t$  = Age of the landfill at equipment installation plus the time the owner or operator intends to use the gas mover equipment or active life of the landfill, whichever is less. If the equipment is installed after closure,  $t$  is the age of the landfill at installation, years.

$c$  = Time since closure, years (for an active landfill  $c = 0$  and  $e^{-kc} = 1$ ).

(ii) For sites with known year-to-year solid waste acceptance rate:

$$Q_M = \sum_{i=1}^n 2kL_o M_i (e^{-kt_i}) \quad (\text{Eq. 6})$$

Where:

$Q_M$  = Maximum expected gas generation flow rate, cubic meters per year.

$k$  = Methane generation rate constant, year<sup>-1</sup>.

$L_o$  = Methane generation potential, cubic meters per megagram solid waste.

$M_i$  = Mass of solid waste in the  $i^{\text{th}}$  section, megagrams.

$t_i$  = Age of the  $i^{\text{th}}$  section, years.

(iii) If a collection and control system has been installed, actual flow data may be used to project the maximum expected gas generation flow rate instead of, or in conjunction with, Equation 5 or Equation 6 in [paragraphs \(a\)\(1\)\(i\)](#) and [\(ii\)](#) of this section. If the landfill is still accepting waste, the actual measured flow data will not equal the maximum expected gas generation rate, so calculations using Equation 5 or Equation 6 in [paragraphs \(a\)\(1\)\(i\)](#) or [\(ii\)](#) of this section or other methods must be used to predict the maximum expected gas generation rate over the intended period of use of the gas control system equipment.

(2) For the purposes of determining sufficient density of gas collectors for compliance with [§ 60.762\(b\)\(2\)\(ii\)\(C\)\(2\)](#), the owner or operator must design a system of vertical wells, horizontal collectors, or other collection devices, satisfactory to the Administrator, capable of controlling and extracting gas from all portions of the landfill sufficient to meet all operational and performance standards.

(3) For the purpose of demonstrating whether the gas collection system flow rate is sufficient to determine compliance with [§ 60.762\(b\)\(2\)\(ii\)\(C\)\(3\)](#), the owner or operator must measure gauge pressure in the gas collection header applied to each individual well, monthly. If a positive pressure exists, action must be initiated to correct the exceedance within 5 calendar days, except for the three conditions allowed under [§ 60.763\(b\)](#). Any attempted corrective measure must not cause exceedances of other operational or performance standards.

(i) If negative pressure cannot be achieved without excess air infiltration within 15 calendar days of the first measurement of positive pressure, the owner or operator must conduct a root cause analysis and correct the exceedance as soon as practicable, but no later than 60 days after positive pressure was first measured. The owner or operator must keep records according to [§ 60.768\(e\)\(3\)](#).

(ii) If corrective actions cannot be fully implemented within 60 days following the positive pressure measurement for which the root cause analysis was required, the owner or operator must also conduct a corrective action analysis and develop an implementation schedule to complete the corrective action(s) as soon as practicable, but no more than 120 days following the positive pressure measurement. The owner or operator must submit the items listed in [§ 60.767\(g\)\(7\)](#) as part of the next annual report. The owner or operator must keep records according to [§ 60.768\(e\)\(4\)](#).

(iii) If corrective action is expected to take longer than 120 days to complete after the initial exceedance, the owner or operator must submit the root cause analysis, corrective action analysis, and corresponding implementation timeline to the Administrator, according to [§ 60.767\(g\)\(7\)](#) and [§ 60.767\(j\)](#). The owner or operator must keep records according to [§ 60.768\(e\)\(5\)](#).

(4) [Reserved]

(5) For the purpose of identifying whether excess air infiltration into the landfill is occurring, the owner or operator must monitor each well monthly for temperature as provided in [§ 60.763\(c\)](#). If a well exceeds the operating parameter for temperature, action must be initiated to correct the exceedance within 5 calendar days. Any attempted corrective measure must not cause exceedances of other operational or performance standards.

(i) If a landfill gas temperature less than 55 degrees Celsius (131 degrees Fahrenheit) cannot be achieved within 15 calendar days of the first measurement of landfill gas temperature greater than 55 degrees Celsius (131 degrees Fahrenheit), the owner or operator must conduct a root cause analysis and correct the exceedance as soon as practicable, but no later than 60 days after a landfill gas temperature greater than 55 degrees Celsius (131 degrees Fahrenheit) was first measured. The owner or operator must keep records according to [§ 60.768\(e\)\(3\)](#).

(ii) If corrective actions cannot be fully implemented within 60 days following the positive pressure or elevated temperature measurement for which the root cause analysis was required, the owner or operator must also conduct a corrective action analysis and develop an implementation schedule to complete the corrective action(s) as soon as practicable, but no more than 120 days following the measurement of landfill gas temperature greater than 55 degrees Celsius (131 degrees Fahrenheit) or positive pressure. The owner or operator must submit the items listed in [§ 60.767\(g\)\(7\)](#) as part of the next annual report. The owner or operator must keep records according to [§ 60.768\(e\)\(4\)](#).

(iii) If corrective action is expected to take longer than 120 days to complete after the initial exceedance, the owner or operator must submit the root cause analysis, corrective action analysis, and corresponding implementation timeline to the Administrator, according to [§ 60.767\(g\)\(7\)](#) and [§ 60.767\(j\)](#). The owner or operator must keep records according to [§ 60.768\(e\)\(5\)](#).

(6) An owner or operator seeking to demonstrate compliance with [§ 60.762\(b\)\(2\)\(ii\)\(C\)\(4\)](#) through the use of a collection system not conforming to the specifications provided in [§ 60.769](#) must provide information satisfactory to the Administrator as specified in [§ 60.767\(c\)\(3\)](#) demonstrating that off-site migration is being controlled.

(b) For purposes of compliance with [§ 60.763\(a\)](#), each owner or operator of a controlled landfill must place each well or design component as specified in the approved design plan as provided in [§ 60.767\(c\)](#). Each well must be installed no later than 60 days after the date on which the initial solid waste has been in place for a period of:

(1) Five (5) years or more if active; or

(2) Two (2) years or more if closed or at final grade.

(c) The following procedures must be used for compliance with the surface methane operational standard as provided in [§ 60.763\(d\)](#).

(1) After installation and startup of the gas collection system, the owner or operator must monitor surface concentrations of methane along the entire perimeter of the collection area and along a pattern that traverses the landfill at 30 meter intervals (or a site-specific established spacing) for each collection area on a quarterly basis using an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications provided in [paragraph \(d\)](#) of this section.

(2) The background concentration must be determined by moving the probe inlet upwind and downwind outside the boundary of the landfill at a distance of at least 30 meters from the perimeter wells.

(3) Surface emission monitoring must be performed in accordance with [section 8.3.1](#) of Method 21 of [appendix A of this part](#), except that the probe inlet must be placed within 5 to 10 centimeters of the ground. Monitoring must be performed during typical meteorological conditions.

(4) Any reading of 500 parts per million or more above background at any location must be recorded as a monitored exceedance and the actions specified in [paragraphs \(c\)\(4\)\(i\) through \(v\)](#) of this section must be taken. As long as the specified actions are taken, the exceedance is not a violation of the operational requirements of [§ 60.763\(d\)](#).

(i) The location of each monitored exceedance must be marked and the location and concentration recorded.

(ii) Cover maintenance or adjustments to the vacuum of the adjacent wells to increase the gas collection in the vicinity of each exceedance must be made and the location must be re-monitored within 10 calendar days of detecting the exceedance.

(iii) If the re-monitoring of the location shows a second exceedance, additional corrective action must be taken and the location must be monitored again within 10 days of the second exceedance. If the re-monitoring shows a third exceedance for the same location, the action specified in [paragraph \(c\)\(4\)\(v\)](#) of this section must be taken, and no further monitoring of that location is required until the action specified in [paragraph \(c\)\(4\)\(v\)](#) of this section has been taken.

(iv) Any location that initially showed an exceedance but has a methane concentration less than 500 ppm methane above background at the 10-day re-monitoring specified in [paragraph \(c\)\(4\)\(ii\)](#) or [\(iii\)](#) of this section must be re-monitored 1 month from the initial exceedance. If the 1-month re-monitoring shows a concentration less than 500 parts per million above background, no further monitoring of that location is required until the next quarterly monitoring period. If the 1-month re-monitoring shows an exceedance, the actions specified in [paragraph \(c\)\(4\)\(iii\)](#) or [\(v\)](#) of this section must be taken.

(v) For any location where monitored methane concentration equals or exceeds 500 parts per million above background three times within a quarterly period, a new well or other collection device must be installed within 120 calendar days of the initial exceedance. An alternative remedy to the exceedance, such as upgrading the blower, header pipes or control device, and a corresponding timeline for installation may be submitted to the Administrator for approval.

(5) The owner or operator must implement a program to monitor for cover integrity and implement cover repairs as necessary on a monthly basis.



(d) Each owner or operator seeking to comply with the provisions in [paragraph \(c\)](#) of this section or [§ 60.764\(a\)\(6\)](#) must comply with the following instrumentation specifications and procedures for surface emission monitoring devices:

(1) The portable analyzer must meet the instrument specifications provided in section 6 of Method 21 of [appendix A of this part](#), except that “methane” replaces all references to “VOC”.

(2) The calibration gas must be methane, diluted to a nominal concentration of 500 parts per million in air.

(3) To meet the performance evaluation requirements in [section 8.1](#) of Method 21 of [appendix A of this part](#), the instrument evaluation procedures of [section 8.1](#) of Method 21 of [appendix A of this part](#) must be used.

(4) The calibration procedures provided in sections 8 and 10 of Method 21 of [appendix A of this part](#) must be followed immediately before commencing a surface monitoring survey.

(e) The provisions of this subpart apply at all times, including periods of startup, shutdown or malfunction. During periods of startup, shutdown, and malfunction, you must comply with the work practice specified in [§ 60.763\(e\)](#) in lieu of the compliance provisions in [§ 60.765](#).

[[81 FR 59368](#), Aug. 29, 2016, as amended at [85 FR 17261](#), Mar. 26, 2020]

#### **§ 60.766 Monitoring of operations.**

Except as provided in [§ 60.767\(c\)\(2\)](#):

(a) Each owner or operator seeking to comply with [§ 60.762\(b\)\(2\)\(ii\)\(C\)](#) for an active gas collection system must install a sampling port and a thermometer, other temperature measuring device, or an access port for temperature measurements at each wellhead and:

(1) Measure the gauge pressure in the gas collection header on a monthly basis as provided in [§ 60.765\(a\)\(3\)](#); and

(2) Monitor nitrogen or oxygen concentration in the landfill gas on a monthly basis as follows:

(i) The nitrogen level must be determined using Method 3C, unless an alternative test method is established as allowed by [§ 60.767\(c\)\(2\)](#).

(ii) Unless an alternative test method is established as allowed by [§ 60.767\(c\)\(2\)](#), the oxygen level must be determined by an oxygen meter using Method 3A, 3C, or ASTM D6522-11 (incorporated by reference, see [§ 60.17](#)). Determine the oxygen level by an oxygen meter using Method 3A, 3C, or ASTM D6522-11 (if sample location is prior to combustion) except that:

(A) The span must be set between 10 and 12 percent oxygen;



- (B) A data recorder is not required;
  - (C) Only two calibration gases are required, a zero and span;
  - (D) A calibration error check is not required;
  - (E) The allowable sample bias, zero drift, and calibration drift are  $\pm 10$  percent.
- (iii) A portable gas composition analyzer may be used to monitor the oxygen levels provided:
- (A) The analyzer is calibrated; and
  - (B) The analyzer meets all quality assurance and quality control requirements for Method 3A or ASTM D6522-11 (incorporated by reference, see [§ 60.17](#)).
- (3) Monitor temperature of the landfill gas on a monthly basis as provided in 60.765(a)(5). The temperature measuring device must be calibrated annually using the procedure in [40 CFR part 60, appendix A-1](#), Method 2, [section 10.3](#) such that a minimum of two temperature points, bracket within 10 percent of all landfill absolute temperature measurements or two fixed points of ice bath and boiling water, corrected for barometric pressure, are used.
- (b) Each owner or operator seeking to comply with [§ 60.762\(b\)\(2\)\(iii\)](#) using an enclosed combustor must calibrate, maintain, and operate according to the manufacturer's specifications, the following equipment:
- (1) A temperature monitoring device equipped with a continuous recorder and having a minimum accuracy of  $\pm 1$  percent of the temperature being measured expressed in degrees Celsius or  $\pm 0.5$  degrees Celsius, whichever is greater. A temperature monitoring device is not required for boilers or process heaters with design heat input capacity equal to or greater than 44 megawatts.
  - (2) A device that records flow to the control device and bypass of the control device (if applicable). The owner or operator must:
    - (i) Install, calibrate, and maintain a gas flow rate measuring device that must record the flow to the control device at least every 15 minutes; and
    - (ii) Secure the bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. A visual inspection of the seal or closure mechanism must be performed at least once every month to ensure that the valve is maintained in the closed position and that the gas flow is not diverted through the bypass line.
  - (c) Each owner or operator seeking to comply with [§ 60.762\(b\)\(2\)\(iii\)](#) using a non-enclosed flare must install, calibrate, maintain, and operate according to the manufacturer's specifications the following equipment:

- (1) A heat sensing device, such as an ultraviolet beam sensor or thermocouple, at the pilot light or the flame itself to indicate the continuous presence of a flame.
- (2) A device that records flow to the flare and bypass of the flare (if applicable). The owner or operator must:
- (i) Install, calibrate, and maintain a gas flow rate measuring device that records the flow to the control device at least every 15 minutes; and
  - (ii) Secure the bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. A visual inspection of the seal or closure mechanism must be performed at least once every month to ensure that the valve is maintained in the closed position and that the gas flow is not diverted through the bypass line.
- (d) Each owner or operator seeking to demonstrate compliance with [§ 60.762\(b\)\(2\)\(iii\)](#) using a device other than a non-enclosed flare or an enclosed combustor or a treatment system must provide information satisfactory to the Administrator as provided in [§ 60.767\(c\)\(2\)](#) describing the operation of the control device, the operating parameters that would indicate proper performance, and appropriate monitoring procedures. The Administrator must review the information and either approve it, or request that additional information be submitted. The Administrator may specify additional appropriate monitoring procedures.
- (e) Each owner or operator seeking to install a collection system that does not meet the specifications in [§ 60.769](#) or seeking to monitor alternative parameters to those required by [§§ 60.763](#) through [60.766](#) must provide information satisfactory to the Administrator as provided in [§ 60.767\(c\)\(2\)](#) and [\(3\)](#) describing the design and operation of the collection system, the operating parameters that would indicate proper performance, and appropriate monitoring procedures. The Administrator may specify additional appropriate monitoring procedures.
- (f) Each owner or operator seeking to demonstrate compliance with the 500 parts per million surface methane operational standard in [§ 60.763\(d\)](#) must monitor surface concentrations of methane according to the procedures in [§ 60.765\(c\)](#) and the instrument specifications in [§ 60.765\(d\)](#). Any closed landfill that has no monitored exceedances of the operational standard in three consecutive quarterly monitoring periods may skip to annual monitoring. Any methane reading of 500 ppm or more above background detected during the annual monitoring returns the frequency for that landfill to quarterly monitoring.
- (g) Each owner or operator seeking to demonstrate compliance with [§ 60.762\(b\)\(2\)\(iii\)](#) using a landfill gas treatment system must maintain and operate all monitoring systems associated with the treatment system in accordance with the site-specific treatment system monitoring plan required in [§ 60.768\(b\)\(5\)\(ii\)](#) and must calibrate, maintain, and operate according to the manufacturer's specifications a device that records flow to the treatment system and bypass of the treatment system (if applicable). The owner or operator must:

(1) Install, calibrate, and maintain a gas flow rate measuring device that records the flow to the treatment system at least every 15 minutes; and

(2) Secure the bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. A visual inspection of the seal or closure mechanism must be performed at least once every month to ensure that the valve is maintained in the closed position and that the gas flow is not diverted through the bypass line.

(h) The monitoring requirements of [paragraphs \(b\), \(c\) \(d\) and \(g\)](#) of this section apply at all times the affected source is operating, except for periods of monitoring system malfunctions, repairs associated with monitoring system malfunctions, and required monitoring system quality assurance or quality control activities. A monitoring system malfunction is any sudden, infrequent, not reasonably preventable failure of the monitoring system to provide valid data. Monitoring system failures that are caused in part by poor maintenance or careless operation are not malfunctions. You are required to complete monitoring system repairs in response to monitoring system malfunctions and to return the monitoring system to operation as expeditiously as practicable.

[[81 FR 59368](#), Aug. 29, 2016, as amended at [85 FR 63403](#), Oct. 7, 2020]

#### **§ 60.767 Reporting requirements.**

(a) ***Design capacity report.*** Each owner or operator subject to the requirements of this subpart must submit an initial design capacity report to the Administrator.

(1) ***Submission.*** The initial design capacity report fulfills the requirements of the notification of the date construction is commenced as required by [§ 60.7\(a\)\(1\)](#) and must be submitted no later than:

(i) November 28, 2016, for landfills that commenced construction, modification, or reconstruction after July 17, 2014 but before August 29, 2016; or

(ii) Ninety days after the date of commenced construction, modification, or reconstruction for landfills that commence construction, modification, or reconstruction after August 29, 2016.

(2) ***Initial design capacity report.*** The initial design capacity report must contain the following information:

(i) A map or plot of the landfill, providing the size and location of the landfill, and identifying all areas where solid waste may be landfilled according to the permit issued by the state, local, or tribal agency responsible for regulating the landfill.

(ii) The maximum design capacity of the landfill. Where the maximum design capacity is specified in the permit issued by the state, local, or tribal agency responsible for regulating the landfill, a copy of the permit specifying the maximum design capacity may be submitted as part

of the report. If the maximum design capacity of the landfill is not specified in the permit, the maximum design capacity must be calculated using good engineering practices. The calculations must be provided, along with the relevant parameters as part of the report. The landfill may calculate design capacity in either megagrams or cubic meters for comparison with the exemption values. If the owner or operator chooses to convert the design capacity from volume to mass or from mass to volume to demonstrate its design capacity is less than 2.5 million megagrams or 2.5 million cubic meters, the calculation must include a site-specific density, which must be recalculated annually. Any density conversions must be documented and submitted with the design capacity report. The state, tribal, local agency or Administrator may request other reasonable information as may be necessary to verify the maximum design capacity of the landfill.

(3) ***Amended design capacity report.*** An amended design capacity report must be submitted to the Administrator providing notification of an increase in the design capacity of the landfill, within 90 days of an increase in the maximum design capacity of the landfill to meet or exceed 2.5 million megagrams and 2.5 million cubic meters. This increase in design capacity may result from an increase in the permitted volume of the landfill or an increase in the density as documented in the annual recalculation required in [§ 60.768\(f\)](#).

(b) ***NMOC emission rate report.*** Each owner or operator subject to the requirements of this subpart must submit an NMOC emission rate report following the procedure specified in [paragraph \(i\)\(2\)](#) of this section to the Administrator initially and annually thereafter, except as provided for in [paragraph \(b\)\(1\)\(ii\)](#) of this section. The Administrator may request such additional information as may be necessary to verify the reported NMOC emission rate.

(1) The NMOC emission rate report must contain an annual or 5-year estimate of the NMOC emission rate calculated using the formula and procedures provided in [§ 60.764\(a\)](#) or [\(b\)](#), as applicable.

(i) The initial NMOC emission rate report may be combined with the initial design capacity report required in [paragraph \(a\)](#) of this section and must be submitted no later than indicated in [paragraphs \(b\)\(1\)\(i\)\(A\)](#) and [\(B\)](#) of this section. Subsequent NMOC emission rate reports must be submitted annually thereafter, except as provided for in [paragraph \(b\)\(1\)\(ii\)](#) of this section.

(A) November 28, 2016, for landfills that commenced construction, modification, or reconstruction after July 17, 2014, but before August 29, 2016, or

(B) Ninety days after the date of commenced construction, modification, or reconstruction for landfills that commence construction, modification, or reconstruction after August 29, 2016.

(ii) If the estimated NMOC emission rate as reported in the annual report to the Administrator is less than 34 megagrams per year in each of the next 5 consecutive years, the owner or operator may elect to submit, following the procedure specified in [paragraph \(i\)\(2\)](#) of this section, an

estimate of the NMOC emission rate for the next 5-year period in lieu of the annual report. This estimate must include the current amount of solid waste-in-place and the estimated waste acceptance rate for each year of the 5 years for which an NMOC emission rate is estimated. All data and calculations upon which this estimate is based must be provided to the Administrator. This estimate must be revised at least once every 5 years. If the actual waste acceptance rate exceeds the estimated waste acceptance rate in any year reported in the 5-year estimate, a revised 5-year estimate must be submitted to the Administrator. The revised estimate must cover the 5-year period beginning with the year in which the actual waste acceptance rate exceeded the estimated waste acceptance rate.

(2) The NMOC emission rate report must include all the data, calculations, sample reports and measurements used to estimate the annual or 5-year emissions.

(3) Each owner or operator subject to the requirements of this subpart is exempted from the requirements to submit an NMOC emission rate report, after installing a collection and control system that complies with [§ 60.762\(b\)\(2\)](#), during such time as the collection and control system is in operation and in compliance with [§§ 60.763](#) and [60.765](#).

(c) ***Collection and control system design plan.*** Each owner or operator subject to the provisions of [§ 60.762\(b\)\(2\)](#) must submit a collection and control system design plan to the Administrator for approval according to the schedule in [paragraph \(c\)\(4\)](#) of this section. The collection and control system design plan must be prepared and approved by a professional engineer and must meet the following requirements:

(1) The collection and control system as described in the design plan must meet the design requirements in [§ 60.762\(b\)\(2\)](#).

(2) The collection and control system design plan must include any alternatives to the operational standards, test methods, procedures, compliance measures, monitoring, recordkeeping or reporting provisions of [§§ 60.763](#) through [60.768](#) proposed by the owner or operator.

(3) The collection and control system design plan must either conform with specifications for active collection systems in [§ 60.769](#) or include a demonstration to the Administrator's satisfaction of the sufficiency of the alternative provisions to [§ 60.769](#).

(4) Each owner or operator of an MSW landfill having a design capacity equal to or greater than 2.5 million megagrams and 2.5 million cubic meters must submit a collection and control system design plan to the Administrator for approval within 1 year of the first NMOC emission rate report in which the NMOC emission rate equals or exceeds 34 megagrams per year, except as follows:

(i) If the owner or operator elects to recalculate the NMOC emission rate after Tier 2 NMOC sampling and analysis as provided in [§ 60.764\(a\)\(3\)](#) and the resulting rate is less than 34

megagrams per year, annual periodic reporting must be resumed, using the Tier 2 determined site-specific NMOC concentration, until the calculated emission rate is equal to or greater than 34 megagrams per year or the landfill is closed. The revised NMOC emission rate report, with the recalculated emission rate based on NMOC sampling and analysis, must be submitted, following the procedures in [paragraph \(i\)\(2\)](#) of this section, within 180 days of the first calculated exceedance of 34 megagrams per year.

(ii) If the owner or operator elects to recalculate the NMOC emission rate after determining a site-specific methane generation rate constant  $k$ , as provided in Tier 3 in [§ 60.764\(a\)\(4\)](#), and the resulting NMOC emission rate is less than 34 Mg/yr, annual periodic reporting must be resumed. The resulting site-specific methane generation rate constant  $k$  must be used in the emission rate calculation until such time as the emissions rate calculation results in an exceedance. The revised NMOC emission rate report based on the provisions of [§ 60.764\(a\)\(4\)](#) and the resulting site-specific methane generation rate constant  $k$  must be submitted, following the procedure specified in [paragraph \(i\)\(2\)](#) of this section, to the Administrator within 1 year of the first calculated emission rate equaling or exceeding 34 megagrams per year.

(iii) If the owner or operator elects to demonstrate that site-specific surface methane emissions are below 500 parts per million methane, based on the provisions of [§ 60.764\(a\)\(6\)](#), then the owner or operator must submit annually a Tier 4 surface emissions report as specified in this paragraph following the procedure specified in [paragraph \(i\)\(2\)](#) of this section until a surface emissions readings of 500 parts per million methane or greater is found. If the Tier 4 surface emissions report shows no surface emissions readings of 500 parts per million methane or greater for four consecutive quarters at a closed landfill, then the landfill owner or operator may reduce Tier 4 monitoring from a quarterly to an annual frequency. The Administrator may request such additional information as may be necessary to verify the reported instantaneous surface emission readings. The Tier 4 surface emissions report must clearly identify the location, date and time (to nearest second), average wind speeds including wind gusts, and reading (in parts per million) of any value 500 parts per million methane or greater, other than non-repeatable, momentary readings. For location, you must determine the latitude and longitude coordinates using an instrument with an accuracy of at least 4 meters. The coordinates must be in decimal degrees with at least five decimal places. The Tier 4 surface emission report must also include the results of the most recent Tier 1 and Tier 2 results in order to verify that the landfill does not exceed 50 Mg/yr of NMOC.

(A) The initial Tier 4 surface emissions report must be submitted annually, starting within 30 days of completing the fourth quarter of Tier 4 surface emissions monitoring that demonstrates that site-specific surface methane emissions are below 500 parts per million methane, and following the procedure specified in [paragraph \(i\)\(2\)](#) of this section.

(B) The Tier 4 surface emissions report must be submitted within 1 year of the first measured surface exceedance of 500 parts per million methane, following the procedure specified in [paragraph \(i\)\(2\)](#) of this section.

(5) The landfill owner or operator must notify the Administrator that the design plan is completed and submit a copy of the plan's signature page. The Administrator has 90 days to decide whether the design plan should be submitted for review. If the Administrator chooses to review the plan, the approval process continues as described in [paragraph \(c\)\(6\)](#) of this section. However, if the Administrator indicates that submission is not required or does not respond within 90 days, the landfill owner or operator can continue to implement the plan with the recognition that the owner or operator is proceeding at their own risk. In the event that the design plan is required to be modified to obtain approval, the owner or operator must take any steps necessary to conform any prior actions to the approved design plan and any failure to do so could result in an enforcement action.

(6) Upon receipt of an initial or revised design plan, the Administrator must review the information submitted under [paragraphs \(c\)\(1\)](#) through [\(3\)](#) of this section and either approve it, disapprove it, or request that additional information be submitted. Because of the many site-specific factors involved with landfill gas system design, alternative systems may be necessary. A wide variety of system designs are possible, such as vertical wells, combination horizontal and vertical collection systems, or horizontal trenches only, leachate collection components, and passive systems. If the Administrator does not approve or disapprove the design plan, or does not request that additional information be submitted within 90 days of receipt, then the owner or operator may continue with implementation of the design plan, recognizing they would be proceeding at their own risk.

(7) If the owner or operator chooses to demonstrate compliance with the emission control requirements of this subpart using a treatment system as defined in this subpart, then the owner or operator must prepare a site-specific treatment system monitoring plan as specified in [§ 60.768\(b\)\(5\)](#).

(d) ***Revised design plan.*** The owner or operator who has already been required to submit a design plan under [paragraph \(c\)](#) of this section, [subpart WWW of this part](#), or a Federal plan or EPA-approved and effective state plan or tribal plan that implements [subparts Cc](#) or [Cf of this part](#), must submit a revised design plan to the Administrator for approval as follows:

(1) At least 90 days before expanding operations to an area not covered by the previously approved design plan.

(2) Prior to installing or expanding the gas collection system in a way that is not consistent with the design plan that was submitted to the Administrator according to [paragraph \(c\)](#) of this section.



(e) **Closure report.** Each owner or operator of a controlled landfill must submit a closure report to the Administrator within 30 days of waste acceptance cessation. The Administrator may request additional information as may be necessary to verify that permanent closure has taken place in accordance with the requirements of [40 CFR 258.60](#). If a closure report has been submitted to the Administrator, no additional wastes may be placed into the landfill without filing a notification of modification as described under [§ 60.7\(a\)\(4\)](#).

(f) **Equipment removal report.** Each owner or operator of a controlled landfill must submit an equipment removal report to the Administrator 30 days prior to removal or cessation of operation of the control equipment.

(1) The equipment removal report must contain all of the following items:

(i) A copy of the closure report submitted in accordance with [paragraph \(e\)](#) of this section;

(ii) A copy of the initial performance test report demonstrating that the 15-year minimum control period has expired, unless the report of the results of the performance test has been submitted to the EPA via the EPA's CDX, or information that demonstrates that the GCCS will be unable to operate for 15 years due to declining gas flows. In the equipment removal report, the process unit(s) tested, the pollutant(s) tested, and the date that such performance test was conducted may be submitted in lieu of the performance test report if the report has been previously submitted to the EPA's CDX; and

(iii) Dated copies of three successive NMOC emission rate reports demonstrating that the landfill is no longer producing 34 megagrams or greater of NMOC per year, unless the NMOC emission rate reports have been submitted to the EPA via the EPA's CDX. If the NMOC emission rate reports have been previously submitted to the EPA's CDX, a statement that the NMOC emission rate reports have been submitted electronically and the dates that the reports were submitted to the EPA's CDX may be submitted in the equipment removal report in lieu of the NMOC emission rate reports.

(2) The Administrator may request such additional information as may be necessary to verify that all of the conditions for removal in [§ 60.762\(b\)\(2\)\(v\)](#) have been met.

(g) **Annual report.** The owner or operator of a landfill seeking to comply with [§ 60.762\(b\)\(2\)](#) using an active collection system designed in accordance with [§ 60.762\(b\)\(2\)\(ii\)](#) must submit to the Administrator, following the procedure specified in [paragraph \(i\)\(2\)](#) of this section, annual reports of the recorded information in [paragraphs \(g\)\(1\)](#) through [\(7\)](#) of this section. The initial annual report must be submitted within 180 days of installation and startup of the collection and control system and must include the initial performance test report required under [§ 60.8](#), as applicable, unless the report of the results of the performance test has been submitted to the EPA via the EPA's CDX. In the initial annual report, the process unit(s) tested, the pollutant(s) tested, and the date that such performance test was conducted may be submitted in lieu of the



performance test report if the report has been previously submitted to the EPA's CDX. For enclosed combustion devices and flares, reportable exceedances are defined under [§ 60.768\(c\)](#). If complying with the operational provisions of [§§ 63.1958, 63.1960, and 63.1961 of this chapter](#), as allowed at [§ 60.762\(b\)\(2\)\(iv\)](#), the owner or operator must follow the semi-annual reporting requirements in [§ 63.1981\(h\) of this chapter](#) in lieu of this paragraph.

(1) Value and length of time for exceedance of applicable parameters monitored under [§ 60.766\(a\), \(b\), \(c\), \(d\), and \(g\)](#).

(2) Description and duration of all periods when the gas stream was diverted from the control device or treatment system through a bypass line or the indication of bypass flow as specified under [§ 60.766](#).

(3) Description and duration of all periods when the control device or treatment system was not operating and length of time the control device or treatment system was not operating.

(4) All periods when the collection system was not operating.

(5) The location of each exceedance of the 500 parts per million methane concentration as provided in [§ 60.763\(d\)](#) and the concentration recorded at each location for which an exceedance was recorded in the previous month. For location, you must determine the latitude and longitude coordinates using an instrument with an accuracy of at least 4 meters. The coordinates must be in decimal degrees with at least five decimal places.

(6) The date of installation and the location of each well or collection system expansion added pursuant to [§ 60.765\(a\)\(3\), \(a\)\(5\), \(b\), and \(c\)\(4\)](#).

(7) For any corrective action analysis for which corrective actions are required in [§ 60.765\(a\)\(3\) or \(5\)](#) and that take more than 60 days to correct the exceedance, the root cause analysis conducted, including a description of the recommended corrective action(s), the date for corrective action(s) already completed following the positive pressure or elevated temperature reading, and, for action(s) not already completed, a schedule for implementation, including proposed commencement and completion dates.

(h) **Initial performance test report.** Each owner or operator seeking to comply with [§ 60.762\(b\)\(2\)\(iii\)](#) must include the following information with the initial performance test report required under [§ 60.8](#):

(1) A diagram of the collection system showing collection system positioning including all wells, horizontal collectors, surface collectors, or other gas extraction devices, including the locations of any areas excluded from collection and the proposed sites for the future collection system expansion;

(2) The data upon which the sufficient density of wells, horizontal collectors, surface collectors, or other gas extraction devices and the gas mover equipment sizing are based;

(3) The documentation of the presence of asbestos or nondegradable material for each area from which collection wells have been excluded based on the presence of asbestos or nondegradable material;

(4) The sum of the gas generation flow rates for all areas from which collection wells have been excluded based on nonproductivity and the calculations of gas generation flow rate for each excluded area; and

(5) The provisions for increasing gas mover equipment capacity with increased gas generation flow rate, if the present gas mover equipment is inadequate to move the maximum flow rate expected over the life of the landfill; and

(6) The provisions for the control of off-site migration.

(i) **Electronic reporting.** The owner or operator must submit reports electronically according to [paragraphs \(i\)\(1\) and \(2\)](#) of this section.

(1) Within 60 days after the date of completing each performance test (as defined in [§ 60.8](#)), the owner or operator must submit the results of each performance test according to the following procedures:

(i) For data collected using test methods supported by the EPA's Electronic Reporting Tool (ERT) as listed on the EPA's ERT Web site ([https://www3.epa.gov/ttn/chief/ert/ert\\_info.html](https://www3.epa.gov/ttn/chief/ert/ert_info.html)) at the time of the test, you must submit the results of the performance test to the EPA via the Compliance and Emissions Data Reporting Interface (CEDRI). CEDRI can be accessed through the EPA's Central Data Exchange (CDX) (<https://cdx.epa.gov/>). Performance test data must be submitted in a file format generated through the use of the EPA's ERT or an alternative file format consistent with the extensible markup language (XML) schema listed on the EPA's ERT Web site, once the XML schema is available. If you claim that some of the performance test information being submitted is confidential business information (CBI), you must submit a complete file generated through the use of the EPA's ERT or an alternate electronic file consistent with the XML schema listed on the EPA's ERT Web site, including information claimed to be CBI, on a compact disc, flash drive or other commonly used electronic storage media to the EPA. The electronic media must be clearly marked as CBI and mailed to U.S. EPA/OAQPS/CORE CBI Office, Attention: Group Leader, Measurement Policy Group, MD C404-02, 4930 Old Page Rd., Durham, NC 27703. The same ERT or alternate file with the CBI omitted must be submitted to the EPA via the EPA's CDX as described earlier in this paragraph.

(ii) For data collected using test methods that are not supported by the EPA's ERT as listed on the EPA's ERT Web site at the time of the test, you must submit the results of the performance test to the Administrator at the appropriate address listed in [§ 60.4](#).

(2) Each owner or operator required to submit reports following the procedure specified in this paragraph must submit reports to the EPA via the CEDRI. (CEDRI can be accessed through the EPA's CDX.) The owner or operator must use the appropriate electronic report in CEDRI for this subpart or an alternate electronic file format consistent with the XML schema listed on the CEDRI Web site (<https://www3.epa.gov/ttn/chief/cedri/index.html>). If the reporting form specific to this subpart is not available in CEDRI at the time that the report is due, the owner or operator must submit the report to the Administrator at the appropriate address listed in [§ 60.4](#). Once the form has been available in CEDRI for 90 calendar days, the owner or operator must begin submitting all subsequent reports via CEDRI. The reports must be submitted by the deadlines specified in this subpart, regardless of the method in which the reports are submitted.

(j) ***Corrective action and the corresponding timeline.*** The owner or operator must submit according to [paragraphs \(j\)\(1\) and \(2\)](#) of this section. If complying with the operational provisions of [§§ 63.1958, 63.1960, and 63.1961 of this chapter](#), as allowed at [§ 60.762\(b\)\(2\)\(iv\)](#), the owner or operator must follow the corrective action and the corresponding timeline requirements in [§ 63.1981\(j\) of this chapter](#) in lieu of this paragraph.

(1) For corrective action that is required according to [§ 60.765\(a\)\(3\)\(iii\)](#) or [\(a\)\(5\)\(iii\)](#) and is expected to take longer than 120 days after the initial exceedance to complete, you must submit the root cause analysis, corrective action analysis, and corresponding implementation timeline to the Administrator as soon as practicable but no later than 75 days after the first measurement of positive pressure or temperature monitoring value of 55 degrees Celsius (131 degrees Fahrenheit). The Administrator must approve the plan for corrective action and the corresponding timeline.

(2) For corrective action that is required according to [§ 60.765\(a\)\(3\)\(iii\)](#) or [\(a\)\(5\)\(iii\)](#) and is not completed within 60 days after the initial exceedance, you must submit a notification to the Administrator as soon as practicable but no later than 75 days after the first measurement of positive pressure or temperature exceedance.

(k) ***Liquids addition.*** The owner or operator of an affected landfill with a design capacity equal to or greater than 2.5 million megagrams and 2.5 million cubic meters that has employed leachate recirculation or added liquids based on a Research, Development, and Demonstration permit (issued through Resource Conservation and Recovery Act, subtitle D, part 258) within the last 10 years must submit to the Administrator, annually, following the procedure specified in [paragraph \(i\)\(2\)](#) of this section, the following information:

(1) Volume of leachate recirculated (gallons per year) and the reported basis of those estimates (records or engineering estimates).

- (2) Total volume of all other liquids added (gallons per year) and the reported basis of those estimates (records or engineering estimates).
- (3) Surface area (acres) over which the leachate is recirculated (or otherwise applied).
- (4) Surface area (acres) over which any other liquids are applied.
- (5) The total waste disposed (megagrams) in the areas with recirculated leachate and/or added liquids based on on-site records to the extent data are available, or engineering estimates and the reported basis of those estimates.
- (6) The annual waste acceptance rates (megagrams per year) in the areas with recirculated leachate and/or added liquids, based on on-site records to the extent data are available, or engineering estimates.
- (7) The initial report must contain items in [paragraph \(k\)\(1\)](#) through [\(6\)](#) of this section per year for the initial annual reporting period as well as for each of the previous 10 years, to the extent historical data are available in on-site records, and the report must be submitted no later than:
- (i) September 27, 2017, for landfills that commenced construction, modification, or reconstruction after July 17, 2014 but before August 29, 2016 containing data for the first 12 months after August 29, 2016; or
  - (ii) Thirteen (13) months after the date of commenced construction, modification, or reconstruction for landfills that commence construction, modification, or reconstruction after August 29, 2016 containing data for the first 12 months after August 29, 2016.
- (8) Subsequent annual reports must contain items in [paragraph \(k\)\(1\)](#) through [\(6\)](#) of this section for the 365-day period following the 365-day period included in the previous annual report, and the report must be submitted no later than 365 days after the date the previous report was submitted.
- (9) Landfills may cease annual reporting of items in [paragraphs \(k\)\(1\)](#) through [\(7\)](#) of this section once they have submitted the closure report in [paragraph \(e\)](#) of this section.
- (1) ***Tier 4 notification.***
- (1) The owner or operator of an affected landfill with a design capacity equal to or greater than 2.5 million megagrams and 2.5 million cubic meters must provide a notification of the date(s) upon which it intends to demonstrate site-specific surface methane emissions are below 500 parts per million methane, based on the Tier 4 provisions of [§ 60.764\(a\)\(6\)](#). The landfill must also include a description of the wind barrier to be used during the SEM in the notification. Notification must be postmarked not less than 30 days prior to such date.

(2) If there is a delay to the scheduled Tier 4 SEM date due to weather conditions, including not meeting the wind requirements in [§ 60.764\(a\)\(6\)\(iii\)\(A\)](#), the owner or operator of a landfill shall notify the Administrator by email or telephone no later than 48 hours before any delay or cancellation in the original test date, and arrange an updated date with the Administrator by mutual agreement.

(m) Each owner or operator that chooses to comply with the provisions in [§§ 63.1958, 63.1960, and 63.1961](#), as allowed at [§ 60.762\(b\)\(2\)\(iv\)](#), must submit the 24-hour high temperature report according to [§ 63.1981\(k\) of this chapter](#).

[[81 FR 59368](#), Aug. 29, 2016, as amended at [85 FR 17261](#), Mar. 26, 2020; [87 FR 8203](#), Feb. 14, 2022]

### **§ 60.768 Recordkeeping requirements.**

(a) Except as provided in [§ 60.767\(c\)\(2\)](#), each owner or operator of an MSW landfill subject to the provisions of [§ 60.762\(b\)\(2\)\(ii\)](#) and [\(iii\)](#) must keep for at least 5 years up-to-date, readily accessible, on-site records of the design capacity report that triggered [§ 60.762\(b\)](#), the current amount of solid waste in-place, and the year-by-year waste acceptance rate. Off-site records may be maintained if they are retrievable within 4 hours. Either paper copy or electronic formats are acceptable.

(b) Except as provided in [§ 60.767\(c\)\(2\)](#), each owner or operator of a controlled landfill must keep up-to-date, readily accessible records for the life of the control system equipment of the data listed in [paragraphs \(b\)\(1\) through \(5\)](#) of this section as measured during the initial performance test or compliance determination. Records of subsequent tests or monitoring must be maintained for a minimum of 5 years. Records of the control device vendor specifications must be maintained until removal.

(1) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with [§ 60.762\(b\)\(2\)\(ii\)](#):

(i) The maximum expected gas generation flow rate as calculated in [§ 60.765\(a\)\(1\)](#). The owner or operator may use another method to determine the maximum gas generation flow rate, if the method has been approved by the Administrator.

(ii) The density of wells, horizontal collectors, surface collectors, or other gas extraction devices determined using the procedures specified in [§ 60.769\(a\)\(1\)](#).

(2) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with [§ 60.762\(b\)\(2\)\(iii\)](#) through use of an enclosed combustion device other than a boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts:

- (i) The average temperature measured at least every 15 minutes and averaged over the same time period of the performance test.
- (ii) The percent reduction of NMOC determined as specified in [§ 60.762\(b\)\(2\)\(iii\)\(B\)](#) achieved by the control device.
- (3) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with [§ 60.762\(b\)\(2\)\(iii\)\(B\)\(I\)](#) through use of a boiler or process heater of any size: A description of the location at which the collected gas vent stream is introduced into the boiler or process heater over the same time period of the performance testing.
- (4) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with [§ 60.762\(b\)\(2\)\(iii\)\(A\)](#) through use of a non-enclosed flare, the flare type (*i.e.*, steam-assisted, air-assisted, or nonassisted), all visible emission readings, heat content determination, flow rate or bypass flow rate measurements, and exit velocity determinations made during the performance test as specified in [§ 60.18](#); continuous records of the flare pilot flame or flare flame monitoring and records of all periods of operations during which the pilot flame of the flare flame is absent.
- (5) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with [§ 60.762\(b\)\(2\)\(iii\)](#) through use of a landfill gas treatment system:
  - (i) ***Bypass records.*** Records of the flow of landfill gas to, and bypass of, the treatment system.
  - (ii) ***Site-specific treatment monitoring plan,*** to include:
    - (A) Monitoring records of parameters that are identified in the treatment system monitoring plan and that ensure the treatment system is operating properly for each intended end use of the treated landfill gas. At a minimum, records should include records of filtration, de-watering, and compression parameters that ensure the treatment system is operating properly for each intended end use of the treated landfill gas.
    - (B) Monitoring methods, frequencies, and operating ranges for each monitored operating parameter based on manufacturer's recommendations or engineering analysis for each intended end use of the treated landfill gas.
    - (C) Documentation of the monitoring methods and ranges, along with justification for their use.
    - (D) Identify who is responsible (by job title) for data collection.
    - (E) Processes and methods used to collect the necessary data.
    - (F) Description of the procedures and methods that are used for quality assurance, maintenance, and repair of all continuous monitoring systems.

(c) Except as provided in [§ 60.767\(c\)\(2\)](#), each owner or operator of a controlled landfill subject to the provisions of this subpart must keep for 5 years up-to-date, readily accessible continuous records of the equipment operating parameters specified to be monitored in [§ 60.766](#) as well as up-to-date, readily accessible records for periods of operation during which the parameter boundaries established during the most recent performance test are exceeded.

(1) The following constitute exceedances that must be recorded and reported under [§ 60.767\(g\)](#):

(i) For enclosed combustors except for boilers and process heaters with design heat input capacity of 44 megawatts (150 million British thermal units per hour) or greater, all 3-hour periods of operation during which the average temperature was more than 28 degrees Celsius (82 degrees Fahrenheit) below the average combustion temperature during the most recent performance test at which compliance with [§ 60.762\(b\)\(2\)\(iii\)](#) was determined.

(ii) For boilers or process heaters, whenever there is a change in the location at which the vent stream is introduced into the flame zone as required under [paragraph \(b\)\(3\)](#) of this section.

(2) Each owner or operator subject to the provisions of this subpart must keep up-to-date, readily accessible continuous records of the indication of flow to the control system and the indication of bypass flow or records of monthly inspections of car-seals or lock-and-key configurations used to seal bypass lines, specified under [§ 60.766](#).

(3) Each owner or operator subject to the provisions of this subpart who uses a boiler or process heater with a design heat input capacity of 44 megawatts or greater to comply with [§ 60.762\(b\)\(2\)\(iii\)](#) must keep an up-to-date, readily accessible record of all periods of operation of the boiler or process heater. (Examples of such records could include records of steam use, fuel use, or monitoring data collected pursuant to other state, local, tribal, or federal regulatory requirements.)

(4) Each owner or operator seeking to comply with the provisions of this subpart by use of a non-enclosed flare must keep up-to-date, readily accessible continuous records of the flame or flare pilot flame monitoring specified under [§ 60.766\(c\)](#), and up-to-date, readily accessible records of all periods of operation in which the flame or flare pilot flame is absent.

(5) Each owner or operator of a landfill seeking to comply with [§ 60.762\(b\)\(2\)](#) using an active collection system designed in accordance with [§ 60.762\(b\)\(2\)\(ii\)](#) must keep records of periods when the collection system or control device is not operating.

(d) Except as provided in [§ 60.767\(c\)\(2\)](#), each owner or operator subject to the provisions of this subpart must keep for the life of the collection system an up-to-date, readily accessible plot map showing each existing and planned collector in the system and providing a unique identification location label for each collector.



(1) Each owner or operator subject to the provisions of this subpart must keep up-to-date, readily accessible records of the installation date and location of all newly installed collectors as specified under [§ 60.765\(b\)](#).

(2) Each owner or operator subject to the provisions of this subpart must keep readily accessible documentation of the nature, date of deposition, amount, and location of asbestos-containing or nondegradable waste excluded from collection as provided in [§ 60.769\(a\)\(3\)\(i\)](#) as well as any nonproductive areas excluded from collection as provided in [§ 60.769\(a\)\(3\)\(ii\)](#).

(e) Except as provided in [§ 60.767\(c\)\(2\)](#), each owner or operator subject to the provisions of this subpart must keep for at least 5 years up-to-date, readily accessible records of the items in [paragraphs \(e\)\(1\) through \(5\)](#) of this section. Each owner or operator that chooses to comply with the provisions in [§§ 63.1958, 63.1960, and 63.1961 of this chapter](#), as allowed at [§ 60.762\(b\)\(2\)\(iv\)](#), must keep the records in [paragraph \(e\)\(6\)](#) of this section and must keep records according to [§§ 63.1983\(e\)\(1\) through \(5\) of this chapter](#) in lieu of [paragraphs \(e\)\(1\) through \(5\)](#) of this section.

(1) All collection and control system exceedances of the operational standards in [§ 60.763](#), the reading in the subsequent month whether or not the second reading is an exceedance, and the location of each exceedance.

(2) Each owner or operator subject to the provisions of this subpart must also keep records of each wellhead temperature monitoring value of 55 degrees Celsius (131 degrees Fahrenheit) or above, each wellhead nitrogen level at or above 20 percent, and each wellhead oxygen level at or above 5 percent.

(3) For any root cause analysis for which corrective actions are required in [§ 60.765\(a\)\(3\)\(i\)](#) or [\(a\)\(5\)\(i\)](#), keep a record of the root cause analysis conducted, including a description of the recommended corrective action(s) taken, and the date(s) the corrective action(s) were completed.

(4) For any root cause analysis for which corrective actions are required in [§ 60.765\(a\)\(3\)\(ii\)](#) or [\(a\)\(5\)\(ii\)](#), keep a record of the root cause analysis conducted, the corrective action analysis, the date for corrective action(s) already completed following the positive pressure reading or high temperature reading, and, for action(s) not already completed, a schedule for implementation, including proposed commencement and completion dates.

(5) For any root cause analysis for which corrective actions are required in [§ 60.765\(a\)\(3\)\(iii\)](#) or [\(a\)\(5\)\(iii\)](#), keep a record of the root cause analysis conducted, the corrective action analysis, the date for corrective action(s) already completed following the positive pressure reading or high temperature reading, for action(s) not already completed, a schedule for implementation, including proposed commencement and completion dates, and a copy of any comments or final approval on the corrective action analysis or schedule from the regulatory agency.



(6) Each owner or operator that chooses to comply with the provisions in [§§ 63.1958, 63.1960, and 63.1961 of this chapter](#), as allowed at [§ 60.762\(b\)\(2\)\(iv\)](#), must keep records of the date upon which the owner or operator started complying with the provisions in [§§ 63.1958, 63.1960, and 63.1961](#).

(f) Landfill owners or operators who convert design capacity from volume to mass or mass to volume to demonstrate that landfill design capacity is less than 2.5 million megagrams or 2.5 million cubic meters, as provided in the definition of “design capacity”, must keep readily accessible, on-site records of the annual recalculation of site-specific density, design capacity, and the supporting documentation. Off-site records may be maintained if they are retrievable within 4 hours. Either paper copy or electronic formats are acceptable.

(g) Landfill owners or operators seeking to demonstrate that site-specific surface methane emissions are below 500 parts per million by conducting surface emission monitoring under the Tier 4 procedures specified in [§ 60.764\(a\)\(6\)](#) must keep for at least 5 years up-to-date, readily accessible records of all surface emissions monitoring and information related to monitoring instrument calibrations conducted according to sections 8 and 10 of Method 21 of [appendix A of this part](#), including all of the following items:

(1) Calibration records:

(i) Date of calibration and initials of operator performing the calibration.

(ii) Calibration gas cylinder identification, certification date, and certified concentration.

(iii) Instrument scale(s) used.

(iv) A description of any corrective action taken if the meter readout could not be adjusted to correspond to the calibration gas value.

(v) If an owner or operator makes their own calibration gas, a description of the procedure used.

(2) Digital photographs of the instrument setup, including the wind barrier. The photographs must be time and date-stamped and taken at the first sampling location prior to sampling and at the last sampling location after sampling at the end of each sampling day, for the duration of the Tier 4 monitoring demonstration.

(3) Timestamp of each surface scan reading:

(i) Timestamp should be detailed to the nearest second, based on when the sample collection begins.

(ii) A log for the length of time each sample was taken using a stopwatch (*e.g.*, the time the probe was held over the area).

- (4) Location of each surface scan reading. The owner or operator must determine the coordinates using an instrument with an accuracy of at least 4 meters. Coordinates must be in decimal degrees with at least five decimal places.
- (5) Monitored methane concentration (parts per million) of each reading.
- (6) Background methane concentration (parts per million) after each instrument calibration test.
- (7) Adjusted methane concentration using most recent calibration (parts per million).
- (8) For readings taken at each surface penetration, the unique identification location label matching the label specified in [paragraph \(d\)](#) of this section.
- (9) Records of the operating hours of the gas collection system for each destruction device.
- (h) Except as provided in [§ 60.767\(c\)\(2\)](#), each owner or operator subject to the provisions of this subpart must keep for at least 5 years up-to-date, readily accessible records of all collection and control system monitoring data for parameters measured in [§ 60.766\(a\)\(1\)](#), [\(2\)](#), and [\(3\)](#).
- (i) Any records required to be maintained by this subpart that are submitted electronically via the EPA's CDX may be maintained in electronic format.
- (j) For each owner or operator reporting leachate or other liquids addition under [§ 60.767\(k\)](#), keep records of any engineering calculations or company records used to estimate the quantities of leachate or liquids added, the surface areas for which the leachate or liquids were applied, and the estimates of annual waste acceptance or total waste in place in the areas where leachate or liquids were applied.

[[81 FR 59368](#), Aug. 29, 2016, as amended at [85 FR 17261](#), Mar. 26, 2020]

#### **§ 60.769 Specifications for active collection systems.**

(a) Each owner or operator seeking to comply with [§ 60.762\(b\)\(2\)\(i\)](#) must site active collection wells, horizontal collectors, surface collectors, or other extraction devices at a sufficient density throughout all gas producing areas using the following procedures unless alternative procedures have been approved by the Administrator as provided in [§ 60.767\(c\)\(2\)](#) and [\(3\)](#):

(1) The collection devices within the interior must be certified to achieve comprehensive control of surface gas emissions by a professional engineer. The following issues must be addressed in the design: Depths of refuse, refuse gas generation rates and flow characteristics, cover properties, gas system expandability, leachate and condensate management, accessibility, compatibility with filling operations, integration with closure end use, air intrusion control, corrosion resistance, fill settlement, resistance to the refuse decomposition heat, and ability to isolate individual components or sections for repair or troubleshooting without shutting down entire collection system.

(2) The sufficient density of gas collection devices determined in [paragraph \(a\)\(1\)](#) of this section must address landfill gas migration issues and augmentation of the collection system through the use of active or passive systems at the landfill perimeter or exterior.

(3) The placement of gas collection devices determined in [paragraph \(a\)\(1\)](#) of this section must control all gas producing areas, except as provided by [paragraphs \(a\)\(3\)\(i\)](#) and [\(ii\)](#) of this section.

(i) Any segregated area of asbestos or nondegradable material may be excluded from collection if documented as provided under [§ 60.768\(d\)](#). The documentation must provide the nature, date of deposition, location and amount of asbestos or nondegradable material deposited in the area, and must be provided to the Administrator upon request.

(ii) Any nonproductive area of the landfill may be excluded from control, provided that the total of all excluded areas can be shown to contribute less than 1 percent of the total amount of NMOC emissions from the landfill. The amount, location, and age of the material must be documented and provided to the Administrator upon request. A separate NMOC emissions estimate must be made for each section proposed for exclusion, and the sum of all such sections must be compared to the NMOC emissions estimate for the entire landfill.

(A) The NMOC emissions from each section proposed for exclusion must be computed using Equation 7:

$$Q_i = 2 \ k \ L_o M_i (e^{-kt_i}) \ (C_{NMOC}) \ (3.6 \times 10^{-9}) \quad (\text{Eq. 7})$$

Where:

$Q_i$  = NMOC emission rate from the  $i^{\text{th}}$  section, megagrams per year.

$k$  = Methane generation rate constant,  $\text{year}^{-1}$ .

$L_o$  = Methane generation potential, cubic meters per megagram solid waste.

$M_i$  = Mass of the degradable solid waste in the  $i^{\text{th}}$  section, megagram.

$t_i$  = Age of the solid waste in the  $i^{\text{th}}$  section, years.

$C_{NMOC}$  = Concentration of nonmethane organic compounds, parts per million by volume.

$3.6 \times 10^{-9}$  = Conversion factor.

(B) If the owner/operator is proposing to exclude, or cease gas collection and control from, nonproductive physically separated (*e.g.*, separately lined) closed areas that already have gas collection systems, NMOC emissions from each physically separated closed area must be computed using either Equation 3 in [§ 60.764\(b\)](#) or Equation 7 in [paragraph \(a\)\(3\)\(ii\)\(A\)](#) of this section.

(iii) The values for  $k$  and  $C_{NMOC}$  determined in field testing must be used if field testing has been performed in determining the NMOC emission rate or the radii of influence (this distance from the well center to a point in the landfill where the pressure gradient applied by the blower or compressor approaches zero). If field testing has not been performed, the default values for  $k$ ,  $L_0$  and  $C_{NMOC}$  provided in [§ 60.764\(a\)\(1\)](#) or the alternative values from [§ 60.764\(a\)\(5\)](#) must be used. The mass of nondegradable solid waste contained within the given section may be subtracted from the total mass of the section when estimating emissions provided the nature, location, age, and amount of the nondegradable material is documented as provided in [paragraph \(a\)\(3\)\(i\)](#) of this section.

(b) Each owner or operator seeking to comply with [§ 60.762\(b\)\(2\)\(ii\)\(A\)](#) construct the gas collection devices using the following equipment or procedures:

(1) The landfill gas extraction components must be constructed of polyvinyl chloride (PVC), high density polyethylene (HDPE) pipe, fiberglass, stainless steel, or other nonporous corrosion resistant material of suitable dimensions to: Convey projected amounts of gases; withstand installation, static, and settlement forces; and withstand planned overburden or traffic loads. The collection system must extend as necessary to comply with emission and migration standards. Collection devices such as wells and horizontal collectors must be perforated to allow gas entry without head loss sufficient to impair performance across the intended extent of control. Perforations must be situated with regard to the need to prevent excessive air infiltration.

(2) Vertical wells must be placed so as not to endanger underlying liners and must address the occurrence of water within the landfill. Holes and trenches constructed for piped wells and horizontal collectors must be of sufficient cross-section so as to allow for their proper construction and completion including, for example, centering of pipes and placement of gravel backfill. Collection devices must be designed so as not to allow indirect short circuiting of air into the cover or refuse into the collection system or gas into the air. Any gravel used around pipe perforations should be of a dimension so as not to penetrate or block perforations.

(3) Collection devices may be connected to the collection header pipes below or above the landfill surface. The connector assembly must include a positive closing throttle valve, any necessary seals and couplings, access couplings and at least one sampling port. The collection devices must be constructed of PVC, HDPE, fiberglass, stainless steel, or other nonporous material of suitable thickness.

(c) Each owner or operator seeking to comply with [§ 60.762\(b\)\(2\)\(iii\)](#) must convey the landfill gas to a control system in compliance with [§ 60.762\(b\)\(2\)\(iii\)](#) through the collection header pipe(s). The gas mover equipment must be sized to handle the maximum gas generation flow rate expected over the intended use period of the gas moving equipment using the following procedures:

(1) For existing collection systems, the flow data must be used to project the maximum flow rate. If no flow data exists, the procedures in [paragraph \(c\)\(2\)](#) of this section must be used.

(2) For new collection systems, the maximum flow rate must be in accordance with [§ 60.765\(a\)\(1\)](#).

**Appendix B**

**40 C.F.R. Part 63 Subpart AAAA**

*National Emissions Standards for Hazardous Air Pollutants: Municipal Solid Waste Landfills*

## **Subpart AAAA—National Emission Standards for Hazardous Air Pollutants: Municipal Solid Waste Landfills**

**Source:**[85 FR 17261](#), Mar. 26, 2020, unless otherwise noted.

### **What This Subpart Covers**

#### **§ 63.1930 What is the purpose of this subpart?**

This subpart establishes national emission standards for hazardous air pollutants for existing and new municipal solid waste (MSW) landfills.

(a) Before September 28, 2021, all landfills described in [§ 63.1935](#) must meet the requirements of [40 CFR part 60, subpart WWW](#), or an approved state or federal plan that implements [40 CFR part 60, subpart Cc](#), and requires timely control of bioreactors and additional reporting requirements. Landfills must also meet the startup, shutdown, and malfunction (SSM) requirements of the general provisions as specified in Table 1 to [subpart AAAA of this part](#) and must demonstrate compliance with the operating conditions by parameter monitoring results that are within the specified ranges. Specifically, landfills must meet the following requirements of this subpart that apply before September 28, 2021, as set out in: [§§ 63.1955\(a\)](#), [63.1955\(b\)](#), [63.1965\(a\)](#), [63.1965\(c\)](#), [63.1975](#), [63.1981\(a\)](#), [63.1981\(b\)](#), and [63.1982](#), and the definitions of “Controlled landfill” and “Deviation” in [§ 63.1990](#).

(b) Beginning no later than September 27, 2021, all landfills described in [§ 63.1935](#) must meet the requirements of this subpart. A landfill may choose to meet the requirements of this subpart rather than the requirements identified in [§ 63.1930\(a\)](#) at any time before September 27, 2021. The requirements of this subpart apply at all times, including during periods of SSM, and the SSM requirements of the General Provisions of this part do not apply.

#### **§ 63.1935 Am I subject to this subpart?**

You are subject to this subpart if you meet the criteria in [paragraph \(a\)](#) or [\(b\)](#) of this section.

(a) You are subject to this subpart if you own or operate an MSW landfill that has accepted waste since November 8, 1987, or has additional capacity for waste deposition and meets any one of the three criteria in [paragraphs \(a\)\(1\)](#) through [\(3\)](#) of this section:

(1) Your MSW landfill is a major source as defined in [§ 63.2](#) of subpart A.

(2) Your MSW landfill is collocated with a major source as defined in [§ 63.2](#) of subpart A.

(3) Your MSW landfill is an area source landfill that has a design capacity equal to or greater than 2.5 million megagrams (Mg) and 2.5 million cubic meters (m<sup>3</sup>) and has estimated uncontrolled emissions equal to or greater than 50 megagrams per year (Mg/yr) NMOC as calculated according to [§ 63.1959](#).

(b) You are subject to this subpart if you own or operate an MSW landfill that has accepted waste since November 8, 1987, or has additional capacity for waste deposition, that includes a bioreactor, as defined in [§ 63.1990](#), and that meets any one of the criteria in [paragraphs \(b\)\(1\) through \(3\)](#) of this section:

(1) Your MSW landfill is a major source as defined in [§ 63.2](#) of subpart A.

(2) Your MSW landfill is collocated with a major source as defined in [§ 63.2](#) of subpart A.

(3) Your MSW landfill is an area source landfill that has a design capacity equal to or greater than 2.5 million Mg and 2.5 million m<sup>3</sup> and that is not permanently closed as of January 16, 2003.

#### **§ 63.1940 What is the affected source of this subpart?**

(a) An affected source of this subpart is an MSW landfill, as defined in [§ 63.1990](#), that meets the criteria in [§ 63.1935\(a\)](#) or [\(b\)](#). The affected source includes the entire disposal facility in a contiguous geographic space where household waste is placed in or on land, including any portion of the MSW landfill operated as a bioreactor.

(b) A new affected source of this subpart is an affected source that commenced construction or reconstruction after November 7, 2000. An affected source is reconstructed if it meets the definition of reconstruction in [§ 63.2](#) of subpart A.

(c) An affected source of this subpart is existing if it is not new.

#### **§ 63.1945 When do I have to comply with this subpart?**

(a) If your landfill is a new affected source, you must comply with this subpart by January 16, 2003, or at the time you begin operating, whichever is later.

(b) If your landfill is an existing affected source, you must comply with this subpart by January 16, 2004.

#### **§ 63.1947 When do I have to comply with this subpart if I own or operate a bioreactor?**

You must comply with this subpart by the dates specified in [§ 63.1945\(a\)](#) or [\(b\)](#). If you own or operate a bioreactor located at a landfill that is not permanently closed as of January 16, 2003, and has a design capacity equal to or greater than 2.5 million Mg and 2.5 million m<sup>3</sup>, then you must install and operate a collection and control system that meets the criteria in [§ 63.1959\(b\)\(2\)](#) according to the schedule specified in [paragraph \(a\)](#), [\(b\)](#), or [\(c\)](#) of this section.

(a) If your bioreactor is at a new affected source, then you must meet the requirements in [paragraphs \(a\)\(1\) and \(2\)](#) of this section:



(1) Install the gas collection and control system for the bioreactor before initiating liquids addition.

(2) Begin operating the gas collection and control system within 180 days after initiating liquids addition or within 180 days after achieving a moisture content of 40 percent by weight, whichever is later. If you choose to begin gas collection and control system operation 180 days after achieving a 40-percent moisture content instead of 180 days after liquids addition, use the procedures in [§§ 63.1982\(c\)](#) and [\(d\)](#) to determine when the bioreactor moisture content reaches 40 percent.

(b) If your bioreactor is at an existing affected source, then you must install and begin operating the gas collection and control system for the bioreactor by January 17, 2006, or by the date your bioreactor is required to install a gas collection and control system under [40 CFR part 60, subpart WWW](#); a federal plan; or an EPA-approved and effective state plan or tribal plan that applies to your landfill, whichever is earlier.

(c) If your bioreactor is at an existing affected source and you do not initiate liquids addition to your bioreactor until later than January 17, 2006, then you must meet the requirements in [paragraphs \(c\)\(1\)](#) and [\(2\)](#) of this section:

(1) Install the gas collection and control system for the bioreactor before initiating liquids addition.

(2) Begin operating the gas collection and control system within 180 days after initiating liquids addition or within 180 days after achieving a moisture content of 40 percent by weight, whichever is later. If you choose to begin gas collection and control system operation 180 days after achieving a 40-percent moisture content instead of 180 days after liquids addition, use the procedures in [§§ 63.1982\(c\)](#) and [\(d\)](#) to determine when the bioreactor moisture content reaches 40 percent.

[[85 FR 17261](#), Mar. 26, 2020, as amended at [85 FR 64400](#), Oct. 13, 2020]

#### **§ 63.1950 When am I no longer required to comply with this subpart?**

You are no longer required to comply with the requirements of this subpart when your landfill meets the collection and control system removal criteria in [§ 63.1957\(b\)](#).

#### **§ 63.1952 When am I no longer required to comply with the requirements of this subpart if I own or operate a bioreactor?**

If you own or operate a landfill that includes a bioreactor, you are no longer required to comply with the requirements of this subpart for the bioreactor provided you meet the conditions of either [paragraph \(a\)](#) or [\(b\)](#) of this section.

(a) Your affected source meets the control system removal criteria in [§ 63.1950](#) or the bioreactor meets the criteria for a nonproductive area of the landfill in [§ 63.1962\(a\)\(3\)\(ii\)](#).

(b) The bioreactor portion of the landfill is a closed landfill as defined in [§ 63.1990](#), you have permanently ceased adding liquids to the bioreactor, and you have not added liquids to the bioreactor for at least 1 year. A closure report for the bioreactor must be submitted to the Administrator as provided in [§ 63.1981\(g\)](#).

## **Standards**

### **§ 63.1955 What requirements must I meet?**

(a) Before September 28, 2021, if alternatives to the operational standards, test methods, procedures, compliance measures, monitoring, recordkeeping, or reporting provisions have already been approved under [40 CFR part 60, subpart WWW](#); subpart XXX; a federal plan; or an EPA-approved and effective state or tribal plan, these alternatives can be used to comply with this subpart, except that all affected sources must comply with the SSM requirements in [subpart A of this part](#) as specified in Table 1 of this subpart and all affected sources must submit compliance reports every 6 months as specified in [§ 63.1981\(h\)](#), including information on all deviations that occurred during the 6-month reporting period. Deviations for continuous emission monitors or numerical continuous parameter monitors must be determined using a 3-hour monitoring block average. Beginning no later than September 28, 2021, the collection and control system design plan may include for approval collection and control systems that include any alternatives to the operational standards, test methods, procedures, compliance measures, monitoring, recordkeeping, or reporting provisions, as provided in [§ 63.1981\(d\)\(2\)](#).

(b) If you own or operate a bioreactor that is located at an MSW landfill that is not permanently closed and has a design capacity equal to or greater than 2.5 million Mg and 2.5 million m<sup>3</sup>, then you must meet the requirements of this subpart, including requirements in [paragraphs \(b\)\(1\) and \(2\)](#) of this section.

(1) You must comply with this subpart starting on the date you are required to install the gas collection and control system.

(2) You must extend the collection and control system into each new cell or area of the bioreactor prior to initiating liquids addition in that area.

(c) At all times, beginning no later than September 27, 2021, the owner or operator must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require the owner or operator to make any further efforts to reduce emissions if the requirements of this subpart have been achieved. Determination of whether a source is operating in compliance with

operation and maintenance requirements will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

**§ 63.1957 Requirements for gas collection and control system installation and removal.**

(a) **Operation.** Operate the collection and control device in accordance with the provisions of §§ [63.1958](#), [63.1960](#), and [63.1961](#).

(b) **Removal criteria.** The collection and control system may be capped, removed, or decommissioned if the following criteria are met:

(1) The landfill is a closed landfill (as defined in [§ 63.1990](#)). A closure report must be submitted to the Administrator as provided in [§ 63.1981\(f\)](#);

(2) The gas collection and control system has been in operation a minimum of 15 years or the landfill owner or operator demonstrates that the gas collection and control system will be unable to operate for 15 years due to declining gas flow; and

(3) Following the procedures specified in [§ 63.1959\(c\)](#), the calculated NMOC emission rate at the landfill is less than 50 Mg/yr on three successive test dates. The test dates must be no less than 90 days apart, and no more than 180 days apart.

**§ 63.1958 Operational standards for collection and control systems.**

Each owner or operator of an MSW landfill with a gas collection and control system used to comply with the provisions of [§ 63.1957](#) must:

(a) Operate the collection system such that gas is collected from each area, cell, or group of cells in the MSW landfill in which solid waste has been in place for:

(1) 5 years or more if active; or

(2) 2 years or more if closed or at final grade;

(b) Operate the collection system with negative pressure at each wellhead except under the following conditions:

(1) A fire or increased well temperature. The owner or operator must record instances when positive pressure occurs in efforts to avoid a fire. These records must be submitted with the semi-annual reports as provided in [§ 63.1981\(h\)](#);

(2) Use of a geomembrane or synthetic cover. The owner or operator must develop acceptable pressure limits in the design plan;

(3) A decommissioned well. A well may experience a static positive pressure after shut down to accommodate for declining flows. All design changes must be approved by the Administrator as specified in [§ 63.1981\(d\)\(2\)](#);

(c) Operate each interior wellhead in the collection system as specified in [40 CFR 60.753\(c\)](#), until the landfill owner or operator elects to meet the operational standard for temperature in [paragraph \(c\)\(1\)](#) of this section.

(1) Beginning no later than September 27, 2021, operate each interior wellhead in the collection system with a landfill gas temperature less than 62.8 degrees Celsius (145 degrees Fahrenheit).

(2) The owner or operator may establish a higher operating temperature value at a particular well. A higher operating value demonstration must be submitted to the Administrator for approval and must include supporting data demonstrating that the elevated parameter neither causes fires nor significantly inhibits anaerobic decomposition by killing methanogens. The demonstration must satisfy both criteria in order to be approved (*i.e.*, neither causing fires nor killing methanogens is acceptable).

(d)

(1) Operate the collection system so that the methane concentration is less than 500 parts per million (ppm) above background at the surface of the landfill. To determine if this level is exceeded, the owner or operator must conduct surface testing around the perimeter of the collection area and along a pattern that traverses the landfill at no more than 30-meter intervals and where visual observations indicate elevated concentrations of landfill gas, such as distressed vegetation and cracks or seeps in the cover. The owner or operator may establish an alternative traversing pattern that ensures equivalent coverage. A surface monitoring design plan must be developed that includes a topographical map with the monitoring route and the rationale for any site-specific deviations from the 30-meter intervals. Areas with steep slopes or other dangerous areas may be excluded from the surface testing.

(2) Beginning no later than September 27, 2021, the owner or operator must:

(i) Conduct surface testing using an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications provided in [§ 63.1960\(d\)](#).

(ii) Conduct surface testing at all cover penetrations. Thus, the owner or operator must monitor any cover penetrations that are within an area of the landfill where waste has been placed and a gas collection system is required.

(iii) Determine the latitude and longitude coordinates of each exceedance using an instrument with an accuracy of at least 4 meters. The coordinates must be in decimal degrees with at least five decimal places.

(e) Operate the system as specified in [§ 60.753\(e\) of this chapter](#), except:

(1) Beginning no later than September 27, 2021, operate the system in accordance to [§ 63.1955\(c\)](#) such that all collected gases are vented to a control system designed and operated in compliance with [§ 63.1959\(b\)\(2\)\(iii\)](#). In the event the collection or control system is not operating:

(i) The gas mover system must be shut down and all valves in the collection and control system contributing to venting of the gas to the atmosphere must be closed within 1 hour of the collection or control system not operating; and

(ii) Efforts to repair the collection or control system must be initiated and completed in a manner such that downtime is kept to a minimum, and the collection and control system must be returned to operation.

(2) [Reserved]

(f) Operate the control system at all times when the collected gas is routed to the system.

(g) If monitoring demonstrates that the operational requirements in [paragraph \(b\)](#), [\(c\)](#), or [\(d\)](#) of this section are not met, corrective action must be taken as specified in [§ 63.1960\(a\)\(3\)](#) and [\(5\)](#) or [\(c\)](#). If corrective actions are taken as specified in [§ 63.1960](#), the monitored exceedance is not a deviation of the operational requirements in this section.

[[85 FR 17261](#), Mar. 26, 2020, as amended at [85 FR 64400](#), Oct. 13, 2020]

### **§ 63.1959 NMOC calculation procedures.**

(a) Calculate the NMOC emission rate using the procedures specified in [§ 60.754\(a\) of this chapter](#), except:

(1) **NMOC emission rate.** Beginning no later than September 27, 2021 the landfill owner or operator must calculate the NMOC emission rate using either Equation 1 provided in [paragraph \(a\)\(1\)\(i\)](#) of this section or Equation 2 provided in [paragraph \(a\)\(1\)\(ii\)](#) of this section. Both Equation 1 and Equation 2 may be used if the actual year-to-year solid waste acceptance rate is known, as specified in [paragraph \(a\)\(1\)\(i\)](#) of this section, for part of the life of the landfill and the actual year-to-year solid waste acceptance rate is unknown, as specified in [paragraph \(a\)\(1\)\(ii\)](#) of this section, for part of the life of the landfill. The values to be used in both Equation 1 and Equation 2 are 0.05 per year for k, 170 cubic meters per megagram (m<sup>3</sup>/Mg) for L<sub>0</sub>, and 4,000 parts per million by volume (ppmv) as hexane for the C<sub>NMOC</sub>. For landfills located in geographical areas with a 30-year annual average precipitation of less than 25 inches, as measured at the nearest representative official meteorologic site, the k value to be used is 0.02 per year.

(i)

(A) Equation 1 must be used if the actual year-to-year solid waste acceptance rate is known.

$$M_{\text{NMOC}} = \sum_{i=1}^n 2 k L_o M_i (e^{-k t_i}) (C_{\text{NMOC}}) (3.6 \times 10^{-9}) \text{ (Eq. 1)}$$

Where:

$M_{\text{NMOC}}$  = Total NMOC emission rate from the landfill, Mg/yr.

$k$  = Methane generation rate constant, year<sup>-1</sup>.

$L_o$  = Methane generation potential, m<sup>3</sup>/Mg solid waste.

$M_i$  = Mass of solid waste in the  $i$ th section, Mg.

$t_i$  = Age of the  $i$ th section, years.

$C_{\text{NMOC}}$  = Concentration of NMOC, ppmv as hexane.

$3.6 \times 10^{-9}$  = Conversion factor.

(B) The mass of nondegradable solid waste may be subtracted from the total mass of solid waste in a particular section of the landfill when calculating the value for  $M_i$  if documentation of the nature and amount of such wastes is maintained.

(ii)

(A) Equation 2 must be used if the actual year-to-year solid waste acceptance rate is unknown.

$$M_{\text{NMOC}} = 2 L_o R (e^{-k c} - e^{-k t}) C_{\text{NMOC}} (3.6 \times 10^{-9}) \text{ (Eq. 2)}$$

Where:

$M_{\text{NMOC}}$  = Mass emission rate of NMOC, Mg/yr.

$L_o$  = Methane generation potential, m<sup>3</sup>/Mg solid waste.

$R$  = Average annual acceptance rate, Mg/yr.

$k$  = Methane generation rate constant, year<sup>-1</sup>.

$t$  = Age of landfill, years.

$C_{\text{NMOC}}$  = Concentration of NMOC, ppmv as hexane.

$c$  = Time since closure, years; for active landfill  $c=0$  and  $e^{-k c} = 1$ .

$3.6 \times 10^{-9}$  = Conversion factor.

(B) The mass of nondegradable solid waste may be subtracted from the total mass of solid waste in a particular section of the landfill when calculating the value of R, if documentation of the nature and amount of such wastes is maintained.

(2) **Tier 1.** The owner or operator must compare the calculated NMOC mass emission rate to the standard of 50 Mg/yr.

(i) If the NMOC emission rate calculated in [paragraph \(a\)\(1\)](#) of this section is less than 50 Mg/yr, then the landfill owner or operator must submit an NMOC emission rate report according to [§ 63.1981\(c\)](#) and must recalculate the NMOC mass emission rate annually as required under [paragraph \(b\)](#) of this section.

(ii) If the calculated NMOC emission rate as calculated in [paragraph \(a\)\(1\)](#) of this section is equal to or greater than 50 Mg/yr, then the landfill owner must either:

(A) Submit a gas collection and control system design plan within 1 year as specified in [§ 63.1981\(d\)](#) and install and operate a gas collection and control system within 30 months of the first annual report in which the NMOC emission rate equals or exceeds 50 Mg/yr, according to [paragraphs \(b\)\(2\)\(ii\)](#) and [\(iii\)](#) of this section;

(B) Determine a site-specific NMOC concentration and recalculate the NMOC emission rate using the Tier 2 procedures provided in [paragraph \(a\)\(3\)](#) of this section; or

(C) Determine a site-specific methane generation rate constant and recalculate the NMOC emission rate using the Tier 3 procedures provided in [paragraph \(a\)\(4\)](#) of this section.

(3) **Tier 2.** The landfill owner or operator must determine the site-specific NMOC concentration using the following sampling procedure. The landfill owner or operator must install at least two sample probes per hectare, evenly distributed over the landfill surface that has retained waste for at least 2 years. If the landfill is larger than 25 hectares in area, only 50 samples are required. The probes should be evenly distributed across the sample area. The sample probes should be located to avoid known areas of nondegradable solid waste. The owner or operator must collect and analyze one sample of landfill gas from each probe to determine the NMOC concentration using EPA Method 25 or 25C of appendix A-7 to part 60. Taking composite samples from different probes into a single cylinder is allowed; however, equal sample volumes must be taken from each probe. For each composite, the sampling rate, collection times, beginning and ending cylinder vacuums, or alternative volume measurements must be recorded to verify that composite volumes are equal. Composite sample volumes should not be less than one liter unless evidence can be provided to substantiate the accuracy of smaller volumes. Terminate compositing before the cylinder approaches ambient pressure where measurement accuracy diminishes. If more than the required number of samples are taken, all samples must be used in the analysis. The landfill owner or operator must divide the NMOC concentration from EPA Method 25 or 25C of appendix A-7 to part 60 by 6 to convert from  $C_{\text{NMOC}}$  as carbon to  $C_{\text{NMOC}}$  as

hexane. If the landfill has an active or passive gas removal system in place, EPA Method 25 or 25C samples may be collected from these systems instead of surface probes provided the removal system can be shown to provide sampling as representative as the two sampling probe per hectare requirement. For active collection systems, samples may be collected from the common header pipe. The sample location on the common header pipe must be before any gas moving, condensate removal, or treatment system equipment. For active collection systems, a minimum of three samples must be collected from the header pipe.

(i) Within 60 days after the date of completing each performance test (as defined in [§ 63.7](#) of subpart A), the owner or operator must submit the results according to [§ 63.1981\(l\)\(1\)](#).

(ii) The landfill owner or operator must recalculate the NMOC mass emission rate using Equation 1 or Equation 2 provided in [paragraph \(a\)\(1\)\(i\)](#) or [\(ii\)](#) of this section and use the average site-specific NMOC concentration from the collected samples instead of the default value provided in [paragraph \(a\)\(1\)](#) of this section.

(iii) If the resulting NMOC mass emission rate is less than 50 Mg/yr, then the owner or operator must submit a periodic estimate of NMOC emissions in an NMOC emission rate report according to [§ 63.1981\(c\)](#) and must recalculate the NMOC mass emission rate annually as required under [paragraph \(b\)](#) of this section. The site-specific NMOC concentration must be retested every 5 years using the methods specified in this section.

(iv) If the NMOC mass emission rate as calculated using the Tier 2 site-specific NMOC concentration is equal to or greater than 50 Mg/yr, the landfill owner or operator must either:

(A) Submit a gas collection and control system design plan within 1 year as specified in [§ 63.1981\(d\)](#) and install and operate a gas collection and control system within 30 months according to [paragraphs \(b\)\(2\)\(ii\)](#) and [\(iii\)](#) of this section; or

(B) Determine a site-specific methane generation rate constant and recalculate the NMOC emission rate using the site-specific methane generation rate using the Tier 3 procedures specified in [paragraph \(a\)\(4\)](#) of this section.

(4) **Tier 3.** The site-specific methane generation rate constant must be determined using the procedures provided in EPA Method 2E of appendix A-1 to [part 60 of this chapter](#). The landfill owner or operator must estimate the NMOC mass emission rate using Equation 1 or Equation 2 in [paragraph \(a\)\(1\)\(i\)](#) or [\(ii\)](#) of this section and using a site-specific methane generation rate constant, and the site-specific NMOC concentration as determined in [paragraph \(a\)\(3\)](#) of this section instead of the default values provided in [paragraph \(a\)\(1\)](#) of this section. The landfill owner or operator must compare the resulting NMOC mass emission rate to the standard of 50 Mg/yr.



(i) If the NMOC mass emission rate as calculated using the Tier 2 site-specific NMOC concentration and Tier 3 site-specific methane generation rate is equal to or greater than 50 Mg/yr, the owner or operator must:

(A) Submit a gas collection and control system design plan within 1 year as specified in [§ 63.1981\(d\)](#) and install and operate a gas collection and control system within 30 months of the first annual report in which the NMOC emission rate equals or exceeds 50 Mg/yr, according to [paragraphs \(b\)\(2\)\(ii\)](#) and [\(iii\)](#) of this section.

(B) [Reserved]

(ii) If the NMOC mass emission rate is less than 50 Mg/yr, then the owner or operator must recalculate the NMOC mass emission rate annually using Equation 1 or Equation 2 in [paragraph \(a\)\(1\)](#) of this section and using the site-specific Tier 2 NMOC concentration and Tier 3 methane generation rate constant and submit a periodic NMOC emission rate report as provided in [§ 63.1981\(c\)](#). The calculation of the methane generation rate constant is performed only once, and the value obtained from this test must be used in all subsequent annual NMOC emission rate calculations.

(5) **Other methods.** The owner or operator may use other methods to determine the NMOC concentration or a site-specific methane generation rate constant as an alternative to the methods required in [paragraphs \(a\)\(3\)](#) and [\(4\)](#) of this section if the method has been approved by the Administrator.

(b) Each owner or operator of an affected source having a design capacity equal to or greater than 2.5 million Mg and 2.5 million m<sup>3</sup> must either comply with [paragraph \(b\)\(2\)](#) of this section or calculate an NMOC emission rate for the landfill using the procedures specified in [paragraph \(a\)](#) of this section. The NMOC emission rate must be recalculated annually, except as provided in [§ 63.1981\(c\)\(1\)\(ii\)\(A\)](#).

(1) If the calculated NMOC emission rate is less than 50 Mg/yr, the owner or operator must:

(i) Submit an annual NMOC emission rate emission report to the Administrator, except as provided for in [§ 63.1981\(c\)\(1\)\(ii\)](#); and

(ii) Recalculate the NMOC emission rate annually using the procedures specified in [paragraph \(a\)\(1\)](#) of this section until such time as the calculated NMOC emission rate is equal to or greater than 50 Mg/yr, or the landfill is closed.

(A) If the calculated NMOC emission rate, upon initial calculation or annual recalculation required in [paragraph \(b\)](#) of this section, is equal to or greater than 50 Mg/yr, the owner or operator must either: comply with [paragraph \(b\)\(2\)](#) of this section or calculate NMOC emissions using the next higher tier in [paragraph \(a\)](#) of this section.

(B) If the landfill is permanently closed, a closure report must be submitted to the Administrator as provided for in [§ 63.1981\(f\)](#).

(2) If the calculated NMOC emission rate is equal to or greater than 50 Mg/yr using Tier 1, 2, or 3 procedures, the owner or operator must either:

(i) Submit a collection and control system design plan prepared by a professional engineer to the Administrator within 1 year as specified in [§ 63.1981\(d\)](#) or calculate NMOC emissions using the next higher tier in [paragraph \(a\)](#) of this section. The collection and control system must meet the requirements in [paragraphs \(b\)\(2\)\(ii\)](#) and [\(iii\)](#) of this section.

(ii) Collection system. Install and start up a collection and control system that captures the gas generated within the landfill as required by [paragraphs \(b\)\(2\)\(ii\)\(B\)](#) or [\(C\)](#) and [\(b\)\(2\)\(iii\)](#) of this section within 30 months after:

(A) The first annual report in which the NMOC emission rate equals or exceeds 50 Mg/yr, unless Tier 2 or Tier 3 sampling demonstrates that the NMOC emission rate is less than 50 Mg.

(B) An active collection system must:

(1) Be designed to handle the maximum expected gas flow rate from the entire area of the landfill that warrants control over the intended use period of the gas control system equipment;

(2) Collect gas from each area, cell, or group of cells in the landfill in which the initial solid waste has been placed for a period of 5 years or more if active; or 2 years or more if closed or at final grade;

(3) Collect gas at a sufficient extraction rate; and

(4) Be designed to minimize off-site migration of subsurface gas.

(C) A passive collection system must:

(1) Comply with the provisions specified in [paragraphs \(b\)\(2\)\(ii\)\(B\)\(1\)](#), [\(2\)](#), and [\(3\)](#) of this section; and

(2) Be installed with liners on the bottom and all sides in all areas in which gas is to be collected. The liners must be installed as required under [§ 258.40 of this chapter](#).

(iii) Control system. Route all the collected gas to a control system that complies with the requirements in either [paragraph \(b\)\(2\)\(iii\)\(A\)](#), [\(B\)](#), or [\(C\)](#) of this section.

(A) A non-enclosed flare designed and operated in accordance with the parameters established in [§ 63.11\(b\)](#) except as noted in [paragraph \(e\)](#) of this section; or

(B) A control system designed and operated to reduce NMOC by 98 weight-percent, or, when an enclosed combustion device is used for control, to either reduce NMOC by 98 weight-percent or reduce the outlet NMOC concentration to less than 20 ppmv, dry basis as hexane at 3-percent oxygen. The reduction efficiency or ppmv must be established by an initial performance test to be completed no later than 180 days after the initial startup of the approved control system using the test methods specified in [paragraph \(e\)](#) of this section. The performance test is not required for boilers and process heaters with design heat input capacities equal to or greater than 44 megawatts that burn landfill gas for compliance with this subpart.

(1) If a boiler or process heater is used as the control device, the landfill gas stream must be introduced into the flame zone.

(2) The control device must be operated within the parameter ranges established during the initial or most recent performance test. The operating parameters to be monitored are specified in [§§ 63.1961\(b\)](#) through [\(e\)](#);

(C) A treatment system that processes the collected gas for subsequent sale or beneficial use such as fuel for combustion, production of vehicle fuel, production of high-British thermal unit (Btu) gas for pipeline injection, or use as a raw material in a chemical manufacturing process. Venting of treated landfill gas to the ambient air is not allowed. If the treated landfill gas cannot be routed for subsequent sale or beneficial use, then the treated landfill gas must be controlled according to either [paragraph \(b\)\(2\)\(iii\)\(A\)](#) or [\(B\)](#) of this section.

(D) All emissions from any atmospheric vent from the gas treatment system are subject to the requirements of [paragraph \(b\)\(2\)\(iii\)\(A\)](#) or [\(B\)](#) of this section. For purposes of this subpart, atmospheric vents located on the condensate storage tank are not part of the treatment system and are exempt from the requirements of [paragraph \(b\)\(2\)\(iii\)\(A\)](#) or [\(B\)](#) of this section.

(c) After the installation and startup of a collection and control system in compliance with this subpart, the owner or operator must calculate the NMOC emission rate for purposes of determining when the system can be capped, removed, or decommissioned as provided in [§ 63.1957\(b\)\(3\)](#), using Equation 3:

$$M_{NMOC} = 1.89 \times 10^{-3} Q_{LFG} C_{NMOC} \text{ (Eq. 3)}$$

Where:

$M_{NMOC}$  = Mass emission rate of NMOC, Mg/yr.

$Q_{LFG}$  = Flow rate of landfill gas, m<sup>3</sup> per minute.

$C_{NMOC}$  = Average NMOC concentration, ppmv as hexane.

$1.89 \times 10^{-3}$  = Conversion factor.

(1) The flow rate of landfill gas,  $Q_{LFG}$ , must be determined by measuring the total landfill gas flow rate at the common header pipe that leads to the control system using a gas flow measuring device calibrated according to the provisions of section 10 of EPA Method 2E of appendix A-1 of part 60.

(2) The average NMOC concentration,  $C_{NMOC}$ , must be determined by collecting and analyzing landfill gas sampled from the common header pipe before the gas moving or condensate removal equipment using the procedures in EPA Method 25 or 25C of appendix A-7 to [part 60 of this chapter](#). The sample location on the common header pipe must be before any condensate removal or other gas refining units. The landfill owner or operator must divide the NMOC concentration from EPA Method 25 or 25C of appendix A-7 to part 60 by 6 to convert from  $C_{NMOC}$  as carbon to  $C_{NMOC}$  as hexane.

(3) The owner or operator may use another method to determine landfill gas flow rate and NMOC concentration if the method has been approved by the Administrator.

(i) Within 60 days after the date of completing each performance test (as defined in [§ 63.7](#)), the owner or operator must submit the results of the performance test, including any associated fuel analyses, according to [§ 63.1981\(d\)\(1\)](#).

(ii) [Reserved]

(d) For the performance test required in [§ 63.1959\(b\)\(2\)\(iii\)\(B\)](#), EPA Method 25 or 25C (EPA Method 25C of appendix A-7 to [part 60 of this chapter](#) may be used at the inlet only) of [appendix A of this part](#) must be used to determine compliance with the 98 weight-percent efficiency or the 20- ppmv outlet concentration level, unless another method to demonstrate compliance has been approved by the Administrator as provided by [§ 63.1981\(d\)\(2\)](#). EPA Method 3, 3A, or 3C of appendix A-7 to part 60 must be used to determine oxygen for correcting the NMOC concentration as hexane to 3 percent. In cases where the outlet concentration is less than 50 ppm NMOC as carbon (8 ppm NMOC as hexane), EPA Method 25A should be used in place of EPA Method 25. EPA Method 18 may be used in conjunction with EPA Method 25A on a limited basis (compound specific, *e.g.*, methane) or EPA Method 3C may be used to determine methane. The methane as carbon should be subtracted from the EPA Method 25A total hydrocarbon value as carbon to give NMOC concentration as carbon. The landowner or operator must divide the NMOC concentration as carbon by 6 to convert from the  $C_{NMOC}$  as carbon to  $C_{NMOC}$  as hexane. Equation 4 must be used to calculate efficiency:

$$\text{Control Efficiency} = (NMOC_{in} - NMOC_{out}) / (NMOC_{in}) \quad (\text{Eq. 4})$$

Where:

$NMOC_{in}$  = Mass of NMOC entering control device.

$NMOC_{out}$  = Mass of NMOC exiting control device.

(e) For the performance test required in [§ 63.1959\(b\)\(2\)\(iii\)\(A\)](#), the net heating value of the combusted landfill gas as determined in [§ 63.11\(b\)\(6\)\(ii\)](#) is calculated from the concentration of methane in the landfill gas as measured by EPA Method 3C of appendix A to [part 60 of this chapter](#). A minimum of three 30-minute EPA Method 3C samples are determined. The measurement of other organic components, hydrogen, and carbon monoxide is not applicable. EPA Method 3C may be used to determine the landfill gas molecular weight for calculating the flare gas exit velocity under [§ 63.11\(b\)\(7\)](#) of subpart A.

(1) Within 60 days after the date of completing each performance test (as defined in [§ 63.7](#)), the owner or operator must submit the results of the performance tests, including any associated fuel analyses, required by [§ 63.1959\(c\)](#) or [\(e\)](#) according to [§ 63.1981\(l\)\(1\)](#).

(2) [Reserved]

(f) The performance tests required in [§§ 63.1959\(b\)\(2\)\(iii\)\(A\)](#) and [\(B\)](#), must be conducted under such conditions as the Administrator specifies to the owner or operator based on representative performance of the affected source for the period being tested. Representative conditions exclude periods of startup and shutdown unless specified by the Administrator. The owner or operator may not conduct performance tests during periods of malfunction. The owner or operator must record the process information that is necessary to document operating conditions during the test and include in such record an explanation to support that such conditions represent normal operation. Upon request, the owner or operator shall make available to the Administrator such records as may be necessary to determine the conditions of performance tests.

[[85 FR 17261](#), Mar. 26, 2020, as amended at [85 FR 64400](#), Oct. 13, 2020]

#### **§ 63.1960 Compliance provisions.**

(a) Except as provided in [§ 63.1981\(d\)\(2\)](#), the specified methods in [paragraphs \(a\)\(1\)](#) through [\(5\)](#) of this section must be used to determine whether the gas collection system is in compliance with [§ 63.1959\(b\)\(2\)\(ii\)](#).

(1) For the purposes of calculating the maximum expected gas generation flow rate from the landfill to determine compliance with [§ 63.1959\(b\)\(2\)\(ii\)\(C\)\(1\)](#), either Equation 5 or Equation 6 must be used. The owner or operator may use another method to determine the maximum gas generation flow rate, if the method has been approved by the Administrator. The methane generation rate constant (k) and methane generation potential ( $L_0$ ) kinetic factors should be those published in the most recent *Compilation of Air Pollutant Emission Factors* (AP-42) or other site-specific values demonstrated to be appropriate and approved by the Administrator. If k has been determined as specified in [§ 63.1959\(a\)\(4\)](#), the value of k determined from the test must be used. A value of no more than 15 years must be used for the intended use period of the gas mover equipment. The active life of the landfill is the age of the landfill plus the estimated number of years until closure.

(i) For sites with unknown year-to-year solid waste acceptance rate:

$$Q_m = 2L_o R (e^{-kc} - e^{-kt}) \text{ (Eq. 5)}$$

Where:

$Q_m$  = Maximum expected gas generation flow rate,  $m^3/yr$ .

$L_o$  = Methane generation potential,  $m^3/Mg$  solid waste.

$R$  = Average annual acceptance rate,  $Mg/yr$ .

$k$  = Methane generation rate constant,  $year^{-1}$ .

$t$  = Age of the landfill at equipment installation plus the time the owner or operator intends to use the gas mover equipment or active life of the landfill, whichever is less. If the equipment is installed after closure,  $t$  is the age of the landfill at installation, years.

$c$  = Time since closure, years (for an active landfill  $c = 0$  and  $e^{-kc} = 1$ ).

$2$  = Constant.

(ii) For sites with known year-to-year solid waste acceptance rate:

$$Q_M = \sum_{i=1}^n 2kL_o M_i (e^{-kt_i}) \text{ (Eq. 6)}$$

Where:

$Q_m$  = Maximum expected gas generation flow rate,  $m^3/yr$ .

$k$  = Methane generation rate constant,  $year^{-1}$ .

$L_o$  = Methane generation potential,  $m^3/Mg$  solid waste.

$M_i$  = Mass of solid waste in the  $i$ th section,  $Mg$ .

$t_i$  = Age of the  $i$ th section, years.

(iii) If a collection and control system has been installed, actual flow data may be used to project the maximum expected gas generation flow rate instead of, or in conjunction with, Equation 5 or Equation 6 in [paragraphs \(a\)\(1\)\(i\) and \(ii\)](#) of this section. If the landfill is still accepting waste, the actual measured flow data will not equal the maximum expected gas generation rate, so calculations using Equation 5 or Equation 6 in [paragraph \(a\)\(1\)\(i\) or \(ii\)](#) of this section or other methods must be used to predict the maximum expected gas generation rate over the intended period of use of the gas control system equipment.

(2) For the purposes of determining sufficient density of gas collectors for compliance with [§ 63.1959\(b\)\(2\)\(ii\)\(B\)\(2\)](#), the owner or operator must design a system of vertical wells, horizontal collectors, or other collection devices, satisfactory to the Administrator, capable of controlling and extracting gas from all portions of the landfill sufficient to meet all operational and performance standards.

(3) For the purpose of demonstrating whether the gas collection system flow rate is sufficient to determine compliance with [§ 63.1959\(b\)\(2\)\(ii\)\(B\)\(3\)](#), the owner or operator must measure gauge pressure in the gas collection header applied to each individual well monthly. Any attempted corrective measure must not cause exceedances of other operational or performance standards. An alternative timeline for correcting the exceedance may be submitted to the Administrator for approval. If a positive pressure exists, follow the procedures as specified in [§ 60.755\(a\)\(3\)](#), except:

(i) Beginning no later than September 27, 2021, if a positive pressure exists, action must be initiated to correct the exceedance within 5 days, except for the three conditions allowed under [§ 63.1958\(b\)](#).

(A) If negative pressure cannot be achieved without excess air infiltration within 15 days of the first measurement of positive pressure, the owner or operator must conduct a root cause analysis and correct the exceedance as soon as practicable, but no later than 60 days after positive pressure was first measured. The owner or operator must keep records according to [§ 63.1983\(e\)\(3\)](#).

(B) If corrective actions cannot be fully implemented within 60 days following the positive pressure measurement for which the root cause analysis was required, the owner or operator must also conduct a corrective action analysis and develop an implementation schedule to complete the corrective action(s) as soon as practicable, but no more than 120 days following the positive pressure measurement. The owner or operator must submit the items listed in [§ 63.1981\(h\)\(7\)](#) as part of the next semi-annual report. The owner or operator must keep records according to [§ 63.1983\(e\)\(4\)](#).

(C) If corrective action is expected to take longer than 120 days to complete after the initial exceedance, the owner or operator must submit the root cause analysis, corrective action analysis, and corresponding implementation timeline to the Administrator, according to [§ 63.1981\(j\)](#). The owner or operator must keep records according to [§ 63.1983\(e\)\(5\)](#).

(ii) [Reserved]

(4) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the temperature and nitrogen or oxygen operational standards in introductory paragraph [§ 63.1958\(c\)](#), for the purpose of identifying whether excess air infiltration into the



landfill is occurring, the owner or operator must follow the procedures as specified in [§ 60.755\(a\)\(5\) of this chapter](#), except:

(i) Once an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the operational standard for temperature in [§ 63.1958\(c\)\(1\)](#), the owner or operator must monitor each well monthly for temperature for the purpose of identifying whether excess air infiltration exists. If a well exceeds the operating parameter for temperature as provided in [§ 63.1958\(c\)\(1\)](#), action must be initiated to correct the exceedance within 5 days. Any attempted corrective measure must not cause exceedances of other operational or performance standards.

(A) If a landfill gas temperature less than or equal to 62.8 degrees Celsius (145 degrees Fahrenheit) cannot be achieved within 15 days of the first measurement of landfill gas temperature greater than 62.8 degrees Celsius (145 degrees Fahrenheit), the owner or operator must conduct a root cause analysis and correct the exceedance as soon as practicable, but no later than 60 days after a landfill gas temperature greater than 62.8 degrees Celsius (145 degrees Fahrenheit) was first measured. The owner or operator must keep records according to [§ 63.1983\(e\)\(3\)](#).

(B) If corrective actions cannot be fully implemented within 60 days following the temperature measurement for which the root cause analysis was required, the owner or operator must also conduct a corrective action analysis and develop an implementation schedule to complete the corrective action(s) as soon as practicable, but no more than 120 days following the measurement of landfill gas temperature greater than 62.8 degrees Celsius (145 degrees Fahrenheit). The owner or operator must submit the items listed in [§ 63.1981\(h\)\(7\)](#) as part of the next semi-annual report. The owner or operator must keep records according to [§ 63.1983\(e\)\(4\)](#).

(C) If corrective action is expected to take longer than 120 days to complete after the initial exceedance, the owner or operator must submit the root cause analysis, corrective action analysis, and corresponding implementation timeline to the Administrator, according to [§ 63.1981\(h\)\(7\)](#) and [\(j\)](#). The owner or operator must keep records according to [§ 63.1983\(e\)\(5\)](#).

(D) If a landfill gas temperature measured at either the wellhead or at any point in the well is greater than or equal to 76.7 degrees Celsius (170 degrees Fahrenheit) and the carbon monoxide concentration measured, according to the procedures in [§ 63.1961\(a\)\(5\)\(vi\)](#) is greater than or equal to 1,000 ppmv the corrective action(s) for the wellhead temperature standard (62.8 degrees Celsius or 145 degrees Fahrenheit) must be completed within 15 days.

(5) An owner or operator seeking to demonstrate compliance with [§ 63.1959\(b\)\(2\)\(ii\)\(B\)\(4\)](#) through the use of a collection system not conforming to the specifications provided in [§ 63.1962](#) must provide information satisfactory to the Administrator as specified in [§ 63.1981\(d\)\(3\)](#) demonstrating that off-site migration is being controlled.



(b) For purposes of compliance with [§ 63.1958\(a\)](#), each owner or operator of a controlled landfill must place each well or design component as specified in the approved design plan as provided in [§ 63.1981\(d\)](#). Each well must be installed no later than 60 days after the date on which the initial solid waste has been in place for a period of:

- (1) 5 years or more if active; or
- (2) 2 years or more if closed or at final grade.

(c) The following procedures must be used for compliance with the surface methane operational standard as provided in [§ 63.1958\(d\)](#).

(1) After installation and startup of the gas collection system, the owner or operator must monitor surface concentrations of methane along the entire perimeter of the collection area and along a pattern that traverses the landfill at 30 meter intervals (or a site-specific established spacing) for each collection area on a quarterly basis using an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications provided in [paragraph \(d\)](#) of this section.

(2) The background concentration must be determined by moving the probe inlet upwind and downwind outside the boundary of the landfill at a distance of at least 30 meters from the perimeter wells.

(3) Surface emission monitoring must be performed in accordance with [section 8.3.1](#) of EPA Method 21 of appendix A-7 of [part 60 of this chapter](#), except that the probe inlet must be placed within 5 to 10 centimeters of the ground. Monitoring must be performed during typical meteorological conditions.

(4) Any reading of 500 ppm or more above background at any location must be recorded as a monitored exceedance and the actions specified in [paragraphs \(c\)\(4\)\(i\) through \(v\)](#) of this section must be taken. As long as the specified actions are taken, the exceedance is not a violation of the operational requirements of [§ 63.1958\(d\)](#).

(i) The location of each monitored exceedance must be marked and the location and concentration recorded. Beginning no later than September 27, 2021, the location must be recorded using an instrument with an accuracy of at least 4 meters. The coordinates must be in decimal degrees with at least five decimal places.

(ii) Cover maintenance or adjustments to the vacuum of the adjacent wells to increase the gas collection in the vicinity of each exceedance must be made and the location must be re-monitored within 10 days of detecting the exceedance.

(iii) If the re-monitoring of the location shows a second exceedance, additional corrective action must be taken and the location must be monitored again within 10 days of the second

exceedance. If the re-monitoring shows a third exceedance for the same location, the action specified in [paragraph \(c\)\(4\)\(v\)](#) of this section must be taken, and no further monitoring of that location is required until the action specified in [paragraph \(c\)\(4\)\(v\)](#) of this section has been taken.

(iv) Any location that initially showed an exceedance but has a methane concentration less than 500 ppm methane above background at the 10-day re-monitoring specified in [paragraph \(c\)\(4\)\(ii\)](#) or [\(iii\)](#) of this section must be re-monitored 1 month from the initial exceedance. If the 1-month re-monitoring shows a concentration less than 500 ppm above background, no further monitoring of that location is required until the next quarterly monitoring period. If the 1-month re-monitoring shows an exceedance, the actions specified in [paragraph \(c\)\(4\)\(iii\)](#) or [\(v\)](#) of this section must be taken.

(v) For any location where monitored methane concentration equals or exceeds 500 ppm above background three times within a quarterly period, a new well or other collection device must be installed within 120 days of the initial exceedance. An alternative remedy to the exceedance, such as upgrading the blower, header pipes or control device, and a corresponding timeline for installation may be submitted to the Administrator for approval.

(5) The owner or operator must implement a program to monitor for cover integrity and implement cover repairs as necessary on a monthly basis.

(d) Each owner or operator seeking to comply with the provisions in [paragraph \(c\)](#) of this section must comply with the following instrumentation specifications and procedures for surface emission monitoring devices:

(1) The portable analyzer must meet the instrument specifications provided in section 6 of EPA Method 21 of appendix A of [part 60 of this chapter](#), except that “methane” replaces all references to “VOC”.

(2) The calibration gas must be methane, diluted to a nominal concentration of 500 ppm in air.

(3) To meet the performance evaluation requirements in [section 8.1](#) of EPA Method 21 of appendix A of [part 60 of this chapter](#), the instrument evaluation procedures of [section 8.1](#) of EPA Method 21 of appendix A of part 60 must be used.

(4) The calibration procedures provided in sections 8 and 10 of EPA Method 21 of appendix A of [part 60 of this chapter](#) must be followed immediately before commencing a surface monitoring survey.

(e)

(1) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the operational standards in introductory paragraph [§ 63.1958\(e\)](#), the provisions

of this subpart apply at all times, except during periods of SSM, provided that the duration of SSM does not exceed 5 days for collection systems and does not exceed 1 hour for treatment or control devices. You must comply with the provisions in Table 1 to subpart AAAA that apply before September 28, 2021.

(2) Once an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the operational standard in [§ 63.1958\(e\)\(1\)](#), the provisions of this subpart apply at all times, including periods of SSM. During periods of SSM, you must comply with the work practice requirement specified in [§ 63.1958\(e\)](#) in lieu of the compliance provisions in [§ 63.1960](#).

[[85 FR 17261](#), Mar. 26, 2020, as amended at [85 FR 64400](#), Oct. 13, 2020; [87 FR 8203](#), Feb. 14, 2022]

### **§ 63.1961 Monitoring of operations.**

Except as provided in [§ 63.1981\(d\)\(2\)](#):

(a) Each owner or operator seeking to comply with [§ 63.1959\(b\)\(2\)\(ii\)\(B\)](#) for an active gas collection system must install a sampling port and a thermometer, other temperature measuring device, or an access port for temperature measurements at each wellhead and:

(1) Measure the gauge pressure in the gas collection header on a monthly basis as provided in [§ 63.1960\(a\)\(3\)](#); and

(2) Monitor nitrogen or oxygen concentration in the landfill gas on a monthly basis as follows:

(i) The nitrogen level must be determined using EPA Method 3C of appendix A-2 to [part 60 of this chapter](#), unless an alternative test method is established as allowed by [§ 63.1981\(d\)\(2\)](#).

(ii) Unless an alternative test method is established as allowed by [§ 63.1981\(d\)\(2\)](#), the oxygen level must be determined by an oxygen meter using EPA Method 3A or 3C of appendix A-2 to [part 60 of this chapter](#) or ASTM D6522-11 (incorporated by reference, see [§ 63.14](#)). Determine the oxygen level by an oxygen meter using EPA Method 3A or 3C of appendix A-2 to part 60 or ASTM D6522-11 (if sample location is prior to combustion) except that:

(A) The span must be set between 10- and 12-percent oxygen;

(B) A data recorder is not required;

(C) Only two calibration gases are required, a zero and span;

(D) A calibration error check is not required; and

(E) The allowable sample bias, zero drift, and calibration drift are  $\pm 10$  percent.

(iii) A portable gas composition analyzer may be used to monitor the oxygen levels provided:

(A) The analyzer is calibrated; and

(B) The analyzer meets all quality assurance and quality control requirements for EPA Method 3A of appendix A-2 to [part 60 of this chapter](#) or ASTM D6522-11 (incorporated by reference, see [§ 63.14](#)).

(3) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the temperature and nitrogen or oxygen operational standards in introductory paragraph [§ 63.1958\(c\)](#), the owner or operator must follow the procedures as specified in [§ 60.756\(a\)\(2\)](#) and [\(3\) of this chapter](#). Monitor temperature of the landfill gas on a monthly basis as provided in [§ 63.1960\(a\)\(4\)](#). The temperature measuring device must be calibrated annually using the procedure in [Section 10.3](#) of EPA Method 2 of appendix A-1 to [part 60 of this chapter](#).

(4) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the operational standard for temperature in [§ 63.1958\(c\)\(1\)](#), monitor temperature of the landfill gas on a monthly basis as provided in [§ 63.1960\(a\)\(4\)](#). The temperature measuring device must be calibrated annually using the procedure in [Section 10.3](#) of EPA Method 2 of appendix A-1 to [part 60 of this chapter](#). Keep records specified in [§ 63.1983\(e\)](#).

(5) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the operational standard for temperature in [§ 63.1958\(c\)\(1\)](#), unless a higher operating temperature value has been approved by the Administrator under this subpart or under [40 CFR part 60, subpart WWW](#); [40 CFR part 60, subpart XXX](#); or a federal plan or EPA-approved and effective state plan or tribal plan that implements either [40 CFR part 60, subpart Cc](#) or [40 CFR part 60, subpart Cf](#), you must initiate enhanced monitoring at each well with a measurement of landfill gas temperature greater than 62.8 degrees Celsius (145 degrees Fahrenheit) as follows:

(i) Visual observations for subsurface oxidation events (smoke, smoldering ash, damage to well) within the radius of influence of the well.

(ii) Monitor oxygen concentration as provided in [paragraph \(a\)\(2\)](#) of this section;

(iii) Monitor temperature of the landfill gas at the wellhead as provided in [paragraph \(a\)\(4\)](#) of this section.

(iv) Monitor temperature of the landfill gas every 10 vertical feet of the well as provided in [paragraph \(a\)\(6\)](#) of this section.

(v) Monitor the methane concentration with a methane meter using EPA Method 3C of appendix A-6 to part 60, EPA Method 18 of appendix A-6 to [part 60 of this chapter](#), or a portable gas composition analyzer to monitor the methane levels provided that the analyzer is calibrated and

the analyzer meets all quality assurance and quality control requirements for EPA Method 3C or EPA Method 18.

(vi) Monitor and determine carbon monoxide concentrations, as follows:

(A) Collect the sample from the wellhead sampling port in a passivated canister or multi-layer foil gas sampling bag (such as the Cali-5-Bond Bag) and analyze that sample using EPA Method 10 of appendix A-4 to [part 60 of this chapter](#), or an equivalent method with a detection limit of at least 100 ppmv of carbon monoxide in high concentrations of methane; or

(B) Collect and analyze the sample from the wellhead using EPA Method 10 of appendix A-4 to part 60 to measure carbon monoxide concentrations.

(C) When sampling directly from the wellhead, you must sample for 5 minutes plus twice the response time of the analyzer. These values must be recorded. The five 1-minute averages are then averaged to give you the carbon monoxide reading at the wellhead.

(D) When collecting samples in a passivated canister or multi-layer foil sampling bag, you must sample for the period of time needed to assure that enough sample is collected to provide five (5) consecutive, 1-minute samples during the analysis of the canister or bag contents, but no less than 5 minutes plus twice the response time of the analyzer. The five (5) consecutive, 1-minute averages are then averaged together to give you a carbon monoxide value from the wellhead.

(vii) The enhanced monitoring described in this [paragraph \(a\)\(5\)](#) must begin 7 calendar days after the first measurement of landfill gas temperature greater than 62.8 degrees Celsius (145 degrees Fahrenheit); and

(viii) The enhanced monitoring in this [paragraph \(a\)\(5\)](#) must be conducted on a weekly basis. If four consecutive weekly carbon monoxide readings are under 100 ppmv, then enhanced monitoring may be decreased to monthly. However, if carbon monoxide readings exceed 100 ppmv again, the landfill must return to weekly monitoring.

(ix) The enhanced monitoring in this [paragraph \(a\)\(5\)](#) can be stopped once a higher operating value is approved, at which time the monitoring provisions issued with the higher operating value should be followed, or once the measurement of landfill gas temperature at the wellhead is less than or equal to 62.8 degrees Celsius (145 degrees Fahrenheit).

(6) For each wellhead with a measurement of landfill gas temperature greater than or equal to 73.9 degrees Celsius (165 degrees Fahrenheit), annually monitor temperature of the landfill gas every 10 vertical feet of the well. This temperature can be monitored either with a removable thermometer, or using temporary or permanent thermocouples installed in the well.

(b) Each owner or operator seeking to comply with [§ 63.1959\(b\)\(2\)\(iii\)](#) using an enclosed combustor must calibrate, maintain, and operate according to the manufacturer's specifications, the following equipment:

(1) A temperature monitoring device equipped with a continuous recorder and having a minimum accuracy of  $\pm 1$  percent of the temperature being measured expressed in degrees Celsius or  $\pm 0.5$  degrees Celsius, whichever is greater. A temperature monitoring device is not required for boilers or process heaters with design heat input capacity equal to or greater than 44 megawatts.

(2) A device that records flow to the control device and bypass of the control device (if applicable). The owner or operator must:

(i) Install, calibrate, and maintain a gas flow rate measuring device that must record the flow to the control device at least every 15 minutes; and

(ii) Secure the bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. A visual inspection of the seal or closure mechanism must be performed at least once every month to ensure that the valve is maintained in the closed position and that the gas flow is not diverted through the bypass line.

(c) Each owner or operator seeking to comply with [§ 63.1959\(b\)\(2\)\(iii\)](#) using a non-enclosed flare must install, calibrate, maintain, and operate according to the manufacturer's specifications the following equipment:

(1) A heat sensing device, such as an ultraviolet beam sensor or thermocouple, at the pilot light or the flame itself to indicate the continuous presence of a flame; and

(2) A device that records flow to the flare and bypass of the flare (if applicable). The owner or operator must:

(i) Install, calibrate, and maintain a gas flow rate measuring device that records the flow to the control device at least every 15 minutes; and

(ii) Secure the bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. A visual inspection of the seal or closure mechanism must be performed at least once every month to ensure that the valve is maintained in the closed position and that the gas flow is not diverted through the bypass line.

(d) Each owner or operator seeking to demonstrate compliance with [§ 63.1959\(b\)\(2\)\(iii\)](#) using a device other than a non-enclosed flare or an enclosed combustor or a treatment system must provide information satisfactory to the Administrator as provided in [§ 63.1981\(d\)\(2\)](#) describing the operation of the control device, the operating parameters that would indicate proper performance, and appropriate monitoring procedures. The Administrator must review the

information and either approve it, or request that additional information be submitted. The Administrator may specify additional appropriate monitoring procedures.

(e) Each owner or operator seeking to install a collection system that does not meet the specifications in [§ 63.1962](#) or seeking to monitor alternative parameters to those required by [§§ 63.1958](#) through [63.1961](#) must provide information satisfactory to the Administrator as provided in [§ 63.1981\(d\)\(2\)](#) and [\(3\)](#) describing the design and operation of the collection system, the operating parameters that would indicate proper performance, and appropriate monitoring procedures. The Administrator may specify additional appropriate monitoring procedures.

(f) Each owner or operator seeking to demonstrate compliance with the 500-ppm surface methane operational standard in [§ 63.1958\(d\)](#) must monitor surface concentrations of methane according to the procedures in [§ 63.1960\(c\)](#) and the instrument specifications in [§ 63.1960\(d\)](#). If you are complying with the 500-ppm surface methane operational standard in [§ 63.1958\(d\)\(2\)](#), for location, you must determine the latitude and longitude coordinates of each exceedance using an instrument with an accuracy of at least 4 meters and the coordinates must be in decimal degrees with at least five decimal places. In the semi-annual report in [§ 63.1981\(h\)](#), you must report the location of each exceedance of the 500-ppm methane concentration as provided in [§ 63.1958\(d\)](#) and the concentration recorded at each location for which an exceedance was recorded in the previous month. Any closed landfill that has no monitored exceedances of the operational standard in three consecutive quarterly monitoring periods may skip to annual monitoring. Any methane reading of 500 ppm or more above background detected during the annual monitoring returns the frequency for that landfill to quarterly monitoring.

(g) Each owner or operator seeking to demonstrate compliance with [§ 63.1959\(b\)\(2\)\(iii\)\(C\)](#) using a landfill gas treatment system must calibrate, maintain, and operate according to the manufacturer's specifications a device that records flow to the treatment system and bypass of the treatment system (if applicable). Beginning no later than September 27, 2021, each owner or operator must maintain and operate all monitoring systems associated with the treatment system in accordance with the site-specific treatment system monitoring plan required in [§ 63.1983\(b\)\(5\)\(ii\)](#). The owner or operator must:

(1) Install, calibrate, and maintain a gas flow rate measuring device that records the flow to the treatment system at least every 15 minutes; and

(2) Secure the bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. A visual inspection of the seal or closure mechanism must be performed at least once every month to ensure that the valve is maintained in the closed position and that the gas flow is not diverted through the bypass line.

(h) The monitoring requirements of [paragraphs \(a\), \(b\), \(c\), \(d\), and \(g\)](#) of this section apply at all times the affected source is operating, except for periods of monitoring system malfunctions, repairs associated with monitoring system malfunctions, and required monitoring system quality



assurance or quality control activities. A monitoring system malfunction is any sudden, infrequent, not reasonably preventable failure of the monitoring system to provide valid data. Monitoring system failures that are caused in part by poor maintenance or careless operation are not malfunctions. You are required to complete monitoring system repairs in response to monitoring system malfunctions and to return the monitoring system to operation as expeditiously as practicable. Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the temperature and nitrogen or oxygen operational standards in introductory paragraph [§ 63.1958\(c\)\(1\)](#), [\(d\)\(2\)](#), and [\(e\)\(1\)](#), the standards apply at all times.

[[85 FR 17261](#), Mar. 26, 2020, as amended at [85 FR 64401](#), Oct. 13, 2020; [87 FR 8203](#), Feb. 14, 2022]

### **§ 63.1962 Specifications for active collection systems.**

(a) Each owner or operator seeking to comply with [§ 63.1959\(b\)\(2\)\(i\)](#) must site active collection wells, horizontal collectors, surface collectors, or other extraction devices at a sufficient density throughout all gas producing areas using the following procedures unless alternative procedures have been approved by the Administrator as provided in [§ 63.1981\(d\)\(2\)](#) and [\(3\)](#):

(1) The collection devices within the interior must be certified to achieve comprehensive control of surface gas emissions by a professional engineer. The following issues must be addressed in the design: Depths of refuse, refuse gas generation rates and flow characteristics, cover properties, gas system expandability, leachate and condensate management, accessibility, compatibility with filling operations, integration with closure end use, air intrusion control, corrosion resistance, fill settlement, resistance to the refuse decomposition heat, and ability to isolate individual components or sections for repair or troubleshooting without shutting down entire collection system.

(2) The sufficient density of gas collection devices determined in [paragraph \(a\)\(1\)](#) of this section must address landfill gas migration issues and augmentation of the collection system through the use of active or passive systems at the landfill perimeter or exterior.

(3) The placement of gas collection devices determined in [paragraph \(a\)\(1\)](#) of this section must control all gas producing areas, except as provided by [paragraphs \(a\)\(3\)\(i\)](#) and [\(ii\)](#) of this section.

(i) Any segregated area of asbestos or nondegradable material may be excluded from collection if documented as provided under [§ 63.1983\(d\)](#). The documentation must provide the nature, date of deposition, location and amount of asbestos or nondegradable material deposited in the area and must be provided to the Administrator upon request.

(ii) Any nonproductive area of the landfill may be excluded from control, provided that the total of all excluded areas can be shown to contribute less than 1 percent of the total amount of



NMOC emissions from the landfill. The amount, location, and age of the material must be documented and provided to the Administrator upon request. A separate NMOC emissions estimate must be made for each section proposed for exclusion, and the sum of all such sections must be compared to the NMOC emissions estimate for the entire landfill.

(A) The NMOC emissions from each section proposed for exclusion must be computed using Equation 7:

$$Q_i = 2 k L_o M_i (e^{-kt_i}) (C_{NMOC}) (3.6 \times 10^{-9}) \text{ (Eq. 7)}$$

Where:

$Q_i$  = NMOC emission rate from the  $i$ th section, Mg/yr.

$k$  = Methane generation rate constant, year<sup>-1</sup>.

$L_o$  = Methane generation potential, m<sup>3</sup>/Mg solid waste.

$M_i$  = Mass of the degradable solid waste in the  $i$ th section, Mg.

$t_i$  = Age of the solid waste in the  $i$ th section, years.

$C_{NMOC}$  = Concentration of NMOC, ppmv.

$3.6 \times 10^{-9}$  = Conversion factor.

(B) If the owner/operator is proposing to exclude, or cease gas collection and control from, nonproductive physically separated (*e.g.*, separately lined) closed areas that already have gas collection systems, NMOC emissions from each physically separated closed area must be computed using either Equation 3 in [§ 63.1959\(c\)](#) or Equation 7 in [paragraph \(a\)\(3\)\(ii\)\(A\)](#) of this section.

(iii) The values for  $k$  and  $C_{NMOC}$  determined in field testing must be used if field testing has been performed in determining the NMOC emission rate or the radii of influence (the distance from the well center to a point in the landfill where the pressure gradient applied by the blower or compressor approaches zero). If field testing has not been performed, the default values for  $k$ ,  $L_o$  and  $C_{NMOC}$  provided in [§ 63.1959\(a\)\(1\)](#) or the alternative values from [§ 63.1959\(a\)\(5\)](#) must be used. The mass of nondegradable solid waste contained within the given section may be subtracted from the total mass of the section when estimating emissions provided the nature, location, age, and amount of the nondegradable material is documented as provided in [paragraph \(a\)\(3\)\(i\)](#) of this section.

(b) Each owner or operator seeking to comply with [§ 63.1959\(b\)\(2\)\(ii\)](#) must construct the gas collection devices using the following equipment or procedures:

(1) The landfill gas extraction components must be constructed of polyvinyl chloride (PVC), high density polyethylene (HDPE) pipe, fiberglass, stainless steel, or other nonporous corrosion resistant material of suitable dimensions to: Convey projected amounts of gases; withstand installation, static, and settlement forces; and withstand planned overburden or traffic loads. The collection system must extend as necessary to comply with emission and migration standards. Collection devices such as wells and horizontal collectors must be perforated to allow gas entry without head loss sufficient to impair performance across the intended extent of control. Perforations must be situated with regard to the need to prevent excessive air infiltration.

(2) Vertical wells must be placed so as not to endanger underlying liners and must address the occurrence of water within the landfill. Holes and trenches constructed for piped wells and horizontal collectors must be of sufficient cross-section so as to allow for their proper construction and completion including, for example, centering of pipes and placement of gravel backfill. Collection devices must be designed so as not to allow indirect short circuiting of air into the cover or refuse into the collection system or gas into the air. Any gravel used around pipe perforations should be of a dimension so as not to penetrate or block perforations.

(3) Collection devices may be connected to the collection header pipes below or above the landfill surface. The connector assembly must include a positive closing throttle valve, any necessary seals and couplings, access couplings and at least one sampling port. The collection devices must be constructed of PVC, HDPE, fiberglass, stainless steel, or other nonporous material of suitable thickness.

(c) Each owner or operator seeking to comply with [§ 63.1959\(b\)\(2\)\(iii\)](#) must convey the landfill gas to a control system in compliance with [§ 63.1959\(b\)\(2\)\(iii\)](#) through the collection header pipe(s). The gas mover equipment must be sized to handle the maximum gas generation flow rate expected over the intended use period of the gas moving equipment using the following procedures:

(1) For existing collection systems, the flow data must be used to project the maximum flow rate. If no flow data exists, the procedures in [paragraph \(c\)\(2\)](#) of this section must be used.

(2) For new collection systems, the maximum flow rate must be in accordance with [§ 63.1960\(a\)\(1\)](#).

## **General and Continuing Compliance Requirements**

### **§ 63.1964 How is compliance determined?**

Compliance is determined using performance testing, collection system monitoring, continuous parameter monitoring, and other credible evidence. In addition, continuous parameter monitoring data collected under [§ 63.1961\(b\)\(1\)](#), [\(c\)\(1\)](#), and [\(d\)](#) are used to demonstrate compliance with the operating standards for control systems. If a deviation occurs, you have failed to meet the control

device operating standards described in this subpart and have deviated from the requirements of this subpart.

(a) Before September 28, 2021, you must develop a written SSM plan according to the provisions in [§ 63.6\(e\)\(3\)](#) of subpart A. A copy of the SSM plan must be maintained on site. Failure to write or maintain a copy of the SSM plan is a deviation from the requirements of this subpart.

(b) After September 27, 2021, the SSM provisions of [§ 63.6\(e\)](#) of subpart A no longer apply to this subpart and the SSM plan developed under [paragraph \(a\)](#) of this section no longer applies. Compliance with the emissions standards and the operating standards of [§ 63.1958 of this subpart](#) is required at all times.

### **§ 63.1965 What is a deviation?**

A deviation is defined in [§ 63.1990](#). For the purposes of the landfill monitoring and SSM plan requirements, deviations include the items in [paragraphs \(a\)](#) through [\(c\)](#) of this section.

(a) A deviation occurs when the control device operating parameter boundaries described in [§ 63.1983\(c\)\(1\)](#) are exceeded.

(b) A deviation occurs when 1 hour or more of the hours during the 3-hour block averaging period does not constitute a valid hour of data. A valid hour of data must have measured values for at least three 15-minute monitoring periods within the hour.

(c) Before September 28, 2021, a deviation occurs when a SSM plan is not developed or maintained on site and when an affected source fails to meet any emission limitation, (including any operating limit), or work practice requirement in this subpart during SSM, regardless of whether or not such failure is permitted by this subpart.

### **§ 63.1975 How do I calculate the 3-hour block average used to demonstrate compliance?**

Before September 28, 2021, averages are calculated in the same way as they are calculated in [§ 60.758\(b\)\(2\)\(i\) of this subchapter](#) for average combustion temperature and [§ 60.758\(c\)](#) for 3-hour average combustion temperature for enclosed combustors, except that the data collected during the events listed in [paragraphs \(a\)](#) through [\(d\)](#) of this section are not to be included in any average computed under this subpart. Beginning no later than September 27, 2021, averages are calculated according to [§ 63.1983\(b\)\(2\)\(i\)](#) for average combustion temperature and [§ 63.1983\(c\)\(1\)\(i\)](#) for 3-hour average combustion temperature for enclosed combustors, except that the data collected during the event listed in [paragraph \(a\)](#) of this section are not to be included in any average computed under this subpart.

(a) Monitoring system breakdowns, repairs, calibration checks, and zero (low-level) and high-level adjustments.

- (b) Startups.
- (c) Shutdowns.
- (d) Malfunctions.

[[85 FR 17261](#), Mar. 26, 2020, as amended at [87 FR 8204](#), Feb. 14, 2022]

## Notifications, Records, and Reports

### § 63.1981 What reports must I submit?

You must submit the reports specified in this section and the reports specified in Table 1 to this subpart. If you have previously submitted a design capacity report, amended design capacity report, initial NMOC emission rate report, initial or revised collection and control system design plan, closure report, equipment removal report, or initial performance test under [40 CFR part 60, subpart WWW](#); [40 CFR part 60, subpart XXX](#); or a federal plan or EPA-approved and effective state plan or tribal plan that implements either [40 CFR part 60, subpart Cc](#) or [40 CFR part 60, subpart Cf](#), then that submission constitutes compliance with the design capacity report in [paragraph \(a\)](#) of this section, the amended design capacity report in [paragraph \(b\)](#) of this section, the initial NMOC emission rate report in [paragraph \(c\)](#) of this section, the initial collection and control system design plan in [paragraph \(d\)](#) of this section, the revised design plan in [paragraph \(e\)](#) of this section, the closure report in [paragraph \(f\)](#) of this section, the equipment removal report in [paragraph \(g\)](#) of this section, and the initial performance test report in [paragraph \(i\)](#) of this section. You do not need to re-submit the report(s). However, you must include a statement certifying prior submission of the respective report(s) and the date of submittal in the first semi-annual report required in this section.

(a) **Initial design capacity report.** The initial design capacity report must contain the information specified in [§ 60.757\(a\)\(2\) of this chapter](#), except beginning no later than September 28, 2021, the report must contain:

- (1) A map or plot of the landfill, providing the size and location of the landfill, and identifying all areas where solid waste may be landfilled according to the permit issued by the state, local, or tribal agency responsible for regulating the landfill.
- (2) The maximum design capacity of the landfill. Where the maximum design capacity is specified in the permit issued by the state, local, or tribal agency responsible for regulating the landfill, a copy of the permit specifying the maximum design capacity may be submitted as part of the report. If the maximum design capacity of the landfill is not specified in the permit, the maximum design capacity must be calculated using good engineering practices. The calculations must be provided, along with the relevant parameters as part of the report. The landfill may calculate design capacity in either Mg or m<sup>3</sup> for comparison with the exemption values. If the owner or operator chooses to convert the design capacity from volume to mass or from mass to

volume to demonstrate its design capacity is less than 2.5 million Mg or 2.5 million m<sup>3</sup>, the calculation must include a site-specific density, which must be recalculated annually. Any density conversions must be documented and submitted with the design capacity report. The state, tribal, local agency or Administrator may request other reasonable information as may be necessary to verify the maximum design capacity of the landfill.

(b) ***Amended design capacity report.*** An amended design capacity report must be submitted to the Administrator providing notification of an increase in the design capacity of the landfill, within 90 days of an increase in the maximum design capacity of the landfill to meet or exceed 2.5 million Mg and 2.5 million m<sup>3</sup>. This increase in design capacity may result from an increase in the permitted volume of the landfill or an increase in the density as documented in the annual recalculation required in [§ 63.1983\(f\)](#).

(c) ***NMOC emission rate report.*** Each owner or operator subject to the requirements of this subpart must submit a copy of the latest NMOC emission rate report that was submitted according to [§ 60.757\(b\) of this chapter](#) or submit an NMOC emission rate report to the Administrator initially and annually thereafter, except as provided for in [paragraph \(c\)\(1\)\(ii\)\(A\)](#) of this section. The Administrator may request such additional information as may be necessary to verify the reported NMOC emission rate. If you have submitted an annual report under [40 CFR part 60, subpart WWW](#); [40 CFR part 60, subpart XXX](#); or a Federal plan or EPA-approved and effective state plan or tribal plan that implements either [40 CFR part 60, subpart Cc](#) or [40 CFR part 60, subpart Cf](#), then that submission constitutes compliance with the annual NMOC emission rate report in this paragraph. You do not need to re-submit the annual report for the current year. Beginning no later than September 27, 2021, the report must meet the following requirements:

(1) The NMOC emission rate report must contain an annual or 5-year estimate of the NMOC emission rate calculated using the formula and procedures provided in [§ 63.1959\(a\)](#) or [\(b\)](#), as applicable.

(i) The initial NMOC emission rate report must be submitted no later than 90 days after the date of commenced construction, modification, or reconstruction for landfills that commence construction, modification, or reconstruction on or after March 12, 1996.

(ii) Subsequent NMOC emission rate reports must be submitted annually thereafter, except as provided for in [paragraph \(c\)\(1\)\(ii\)\(A\)](#) of this section.

(A) If the estimated NMOC emission rate as reported in the annual report to the Administrator is less than 50 Mg/yr in each of the next 5 consecutive years, the owner or operator may elect to submit, an estimate of the NMOC emission rate for the next 5-year period in lieu of the annual report. This estimate must include the current amount of solid waste-in-place and the estimated waste acceptance rate for each year of the 5 years for which an NMOC emission rate is estimated. All data and calculations upon which this estimate is based must be provided to the

Administrator. This estimate must be revised at least once every 5 years. If the actual waste acceptance rate exceeds the estimated waste acceptance rate in any year reported in the 5-year estimate, a revised 5-year estimate must be submitted to the Administrator. The revised estimate must cover the 5-year period beginning with the year in which the actual waste acceptance rate exceeded the estimated waste acceptance rate.

(B) The report must be submitted following the procedure specified in [paragraph \(1\)\(2\)](#) of this section.

(2) The NMOC emission rate report must include all the data, calculations, sample reports and measurements used to estimate the annual or 5-year emissions.

(3) Each owner or operator subject to the requirements of this subpart is exempted from the requirements to submit an NMOC emission rate report, after installing a collection and control system that complies with [§ 63.1959\(b\)\(2\)](#), during such time as the collection and control system is in operation and in compliance with [§§ 63.1958](#) and [63.1960](#).

(d) ***Collection and control system design plan.*** Each owner or operator subject to the provisions of [§ 63.1959\(b\)\(2\)](#) must submit a collection and control system design plan to the Administrator for approval according to [§ 60.757\(c\) of this chapter](#) and the schedule in [§ 60.757\(c\)\(1\)](#) and [\(2\)](#). Beginning no later than September 27, 2021, each owner or operator subject to the provisions of [§ 63.1959\(b\)\(2\)](#) must submit a collection and control system design plan to the Administrator according to [paragraphs \(d\)\(1\)](#) through [\(6\)](#) of this section. The collection and control system design plan must be prepared and approved by a professional engineer.

(1) The collection and control system as described in the design plan must meet the design requirements in [§ 63.1959\(b\)\(2\)](#).

(2) The collection and control system design plan must include any alternatives to the operational standards, test methods, procedures, compliance measures, monitoring, recordkeeping or reporting provisions of [§§ 63.1957](#) through [63.1983](#) proposed by the owner or operator.

(3) The collection and control system design plan must either conform with specifications for active collection systems in [§ 63.1962](#) or include a demonstration to the Administrator's satisfaction of the sufficiency of the alternative provisions to [§ 63.1962](#).

(4) Each owner or operator of an MSW landfill affected by this subpart must submit a collection and control system design plan to the Administrator for approval within 1 year of becoming subject to this subpart.

(5) The landfill owner or operator must notify the Administrator that the design plan is completed and submit a copy of the plan's signature page. The Administrator has 90 days to decide whether the design plan should be submitted for review. If the Administrator chooses to review the plan, the approval process continues as described in [paragraph \(d\)\(6\)](#) of this section.

In the event that the design plan is required to be modified to obtain approval, the owner or operator must take any steps necessary to conform any prior actions to the approved design plan and any failure to do so could result in an enforcement action.

(6) Upon receipt of an initial or revised design plan, the Administrator must review the information submitted under [paragraphs \(d\)\(1\) through \(3\)](#) of this section and either approve it, disapprove it, or request that additional information be submitted. Because of the many site-specific factors involved with landfill gas system design, alternative systems may be necessary. A wide variety of system designs are possible, such as vertical wells, combination horizontal and vertical collection systems, or horizontal trenches only, leachate collection components, and passive systems.

(e) **Revised design plan.** Beginning no later than September 27, 2021, the owner or operator who has already been required to submit a design plan under [paragraph \(d\)](#) of this section must submit a revised design plan to the Administrator for approval as follows:

- (1) At least 90 days before expanding operations to an area not covered by the previously approved design plan.
- (2) Prior to installing or expanding the gas collection system in a way that is not consistent with the design plan that was submitted to the Administrator according to [paragraph \(d\)](#) of this section.

(f) **Closure report.** Each owner or operator of a controlled landfill must submit a closure report to the Administrator within 30 days of waste acceptance cessation. The Administrator may request additional information as may be necessary to verify that permanent closure has taken place in accordance with the requirements of [§ 258.60 of this chapter](#). If a closure report has been submitted to the Administrator, no additional wastes may be placed into the landfill without filing a notification of modification as described under [§ 63.9\(b\)](#) of subpart A.

(g) **Equipment removal report.** Each owner or operator of a controlled landfill must submit an equipment removal report as provided in [§ 60.757\(e\) of this chapter](#). Each owner or operator of a controlled landfill must submit an equipment removal report to the Administrator 30 days prior to removal or cessation of operation of the control equipment.

(1) Beginning no later than September 27, 2021, the equipment removal report must contain all of the following items:

- (i) A copy of the closure report submitted in accordance with [paragraph \(f\)](#) of this section;
- (ii) A copy of the initial performance test report demonstrating that the 15-year minimum control period has expired, or information that demonstrates that the gas collection and control system will be unable to operate for 15 years due to declining gas flows. In the equipment removal report, the process unit(s) tested, the pollutant(s) tested, and the date that such performance test



was conducted may be submitted in lieu of the performance test report if the report has been previously submitted to the EPA's Central Data Exchange (CDX); and

(iii) Dated copies of three successive NMOC emission rate reports demonstrating that the landfill is no longer producing 50 Mg or greater of NMOC per year. If the NMOC emission rate reports have been previously submitted to the EPA's CDX, a statement that the NMOC emission rate reports have been submitted electronically and the dates that the reports were submitted to the EPA's CDX may be submitted in the equipment removal report in lieu of the NMOC emission rate reports.

(2) The Administrator may request such additional information as may be necessary to verify that all of the conditions for removal in [§ 63.1957\(b\)](#) have been met.

(h) ***Semi-annual report.*** The owner or operator of a landfill seeking to comply with [§ 63.1959\(b\)\(2\)](#) using an active collection system designed in accordance with [§ 63.1959\(b\)\(2\)\(ii\)](#) must submit to the Administrator semi-annual reports. Beginning no later than September 27, 2021, you must submit the report, following the procedure specified in [paragraph \(l\)](#) of this section. The initial report must be submitted within 180 days of installation and startup of the collection and control system and must include the initial performance test report required under [§ 63.7](#) of subpart A, as applicable. In the initial report, the process unit(s) tested, the pollutant(s) tested, and the date that such performance test was conducted may be submitted in lieu of the performance test report if the report has been previously submitted to the EPA's CDX. For enclosed combustion devices and flares, reportable exceedances are defined under [§ 63.1983\(c\)](#). The semi-annual reports must contain the information in [paragraphs \(h\)\(1\)](#) through [\(8\)](#) of this section.

(1) Number of times that applicable parameters monitored under [§ 63.1958\(b\)](#), [\(c\)](#), and [\(d\)](#) were exceeded and when the gas collection and control system was not operating under [§ 63.1958\(e\)](#), including periods of SSM. For each instance, report the date, time, and duration of each exceedance.

(i) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the temperature and nitrogen or oxygen operational standards in introductory paragraph [§ 63.1958\(c\)](#), provide a statement of the wellhead operational standard for temperature and oxygen you are complying with for the period covered by the report. Indicate the number of times each of those parameters monitored under [§ 63.1961\(a\)\(3\)](#) were exceeded. For each instance, report the date, time, and duration of each exceedance.

(ii) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the operational standard for temperature in [§ 63.1958\(c\)\(1\)](#), provide a statement of the wellhead operational standard for temperature and oxygen you are complying with for the period covered by the report. Indicate the number of times each of those parameters monitored



under [§ 63.1961\(a\)\(4\)](#) were exceeded. For each instance, report the date, time, and duration of each exceedance.

(iii) Beginning no later than September 27, 2021, number of times the parameters for the site-specific treatment system in [§ 63.1961\(g\)](#) were exceeded.

(2) Description and duration of all periods when the gas stream was diverted from the control device or treatment system through a bypass line or the indication of bypass flow as specified under [§ 63.1961](#).

(3) Description and duration of all periods when the control device or treatment system was not operating and length of time the control device or treatment system was not operating.

(4) All periods when the collection system was not operating.

(5) The location of each exceedance of the 500-ppm methane concentration as provided in [§ 63.1958\(d\)](#) and the concentration recorded at each location for which an exceedance was recorded in the previous month. Beginning no later than September 27, 2021, for location, you record the latitude and longitude coordinates of each exceedance using an instrument with an accuracy of at least 4 meters. The coordinates must be in decimal degrees with at least five decimal places.

(6) The date of installation and the location of each well or collection system expansion added pursuant to [§ 63.1960\(a\)\(3\)](#) and [\(4\)](#), [\(b\)](#), and [\(c\)\(4\)](#).

(7) For any corrective action analysis for which corrective actions are required in [§ 63.1960\(a\)\(3\)\(i\)](#) or [\(a\)\(5\)](#) and that take more than 60 days to correct the exceedance, the root cause analysis conducted, including a description of the recommended corrective action(s), the date for corrective action(s) already completed following the positive pressure or high temperature reading, and, for action(s) not already completed, a schedule for implementation, including proposed commencement and completion dates.

(8) Each owner or operator required to conduct enhanced monitoring in [§§ 63.1961\(a\)\(5\)](#) and [\(6\)](#) must include the results of all monitoring activities conducted during the period.

(i) For each monitoring point, report the date, time, and well identifier along with the value and units of measure for oxygen, temperature (wellhead and downwell), methane, and carbon monoxide.

(ii) Include a summary trend analysis for each well subject to the enhanced monitoring requirements to chart the weekly readings over time for oxygen, wellhead temperature, methane, and weekly or monthly readings over time, as applicable for carbon monoxide.

(iii) Include the date, time, staff person name, and description of findings for each visual observation for subsurface oxidation event.

(i) **Initial performance test report.** Each owner or operator seeking to comply with [§ 63.1959\(b\)\(2\)\(iii\)](#) must include the following information with the initial performance test report required under [§ 63.7](#) of subpart A:

- (1) A diagram of the collection system showing collection system positioning including all wells, horizontal collectors, surface collectors, or other gas extraction devices, including the locations of any areas excluded from collection and the proposed sites for the future collection system expansion;
- (2) The data upon which the sufficient density of wells, horizontal collectors, surface collectors, or other gas extraction devices and the gas mover equipment sizing are based;
- (3) The documentation of the presence of asbestos or nondegradable material for each area from which collection wells have been excluded based on the presence of asbestos or nondegradable material;
- (4) The sum of the gas generation flow rates for all areas from which collection wells have been excluded based on nonproductivity and the calculations of gas generation flow rate for each excluded area;
- (5) The provisions for increasing gas mover equipment capacity with increased gas generation flow rate, if the present gas mover equipment is inadequate to move the maximum flow rate expected over the life of the landfill; and
- (6) The provisions for the control of off-site migration.

(j) **Corrective action and the corresponding timeline.** The owner or operator must submit information regarding corrective actions according to [paragraphs \(j\)\(1\) and \(2\)](#) of this section.

(1) For corrective action that is required according to [§ 63.1960\(a\)\(3\)](#) or [\(4\)](#) and is not completed within 60 days after the initial exceedance, you must submit a notification to the Administrator as soon as practicable but no later than 75 days after the first measurement of positive pressure or temperature exceedance.

(2) For corrective action that is required according to [§ 63.1960\(a\)\(3\)](#) or [\(4\)](#) and is expected to take longer than 120 days after the initial exceedance to complete, you must submit the root cause analysis, corrective action analysis, and corresponding implementation timeline to the Administrator as soon as practicable but no later than 75 days after the first measurement of positive pressure or temperature monitoring value of 62.8 degrees Celsius (145 degrees Fahrenheit) or above unless a higher operating temperature value has been approved by the Administrator for the well under this subpart or under [40 CFR part 60, subpart WWW](#); [40 CFR part 60, subpart XXX](#); or a Federal plan or EPA approved and effective state plan or tribal plan that implements either [40 CFR part 60, subpart Cc](#) or [40 CFR part 60, subpart Cf](#). The Administrator must approve the plan for corrective action and the corresponding timeline.

(k) **24-hour high temperature report.** Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the operational standard for temperature in [§ 63.1958\(c\)\(1\)](#) and a landfill gas temperature measured at either the wellhead or at any point in the well is greater than or equal to 76.7 degrees Celsius (170 degrees Fahrenheit) and the carbon monoxide concentration measured is greater than or equal to 1,000 ppmv, then you must report the date, time, well identifier, temperature and carbon monoxide reading via email to the Administrator within 24 hours of the measurement unless a higher operating temperature value has been approved by the Administrator for the well under this subpart or under [40 CFR part 60, subpart WWW](#); [40 CFR part 60, subpart XXX](#); or a Federal plan or EPA approved and effective state plan or tribal plan that implements either [40 CFR part 60, subpart Cc](#) or [40 CFR part 60, subpart Cf](#).

(l) **Electronic reporting.** Beginning no later than September 27, 2021, the owner or operator must submit reports electronically according to [paragraphs \(l\)\(1\)](#) and [\(2\)](#) of this section.

(1) Within 60 days after the date of completing each performance test required by this subpart, you must submit the results of the performance test following the procedures specified in [paragraphs \(l\)\(1\)\(i\)](#) through [\(iii\)](#) of this section.

(i) Data collected using test methods supported by the EPA's Electronic Reporting Tool (ERT) as listed on the EPA's ERT website (<https://www.epa.gov/electronic-reporting-air-emissions/electronic-reporting-tool-ert>) at the time of the test. Submit the results of the performance test to the EPA via the Compliance and Emissions Data Reporting Interface (CEDRI), which can be accessed through the EPA's CDX (<https://cdx.epa.gov/>). The data must be submitted in a file format generated through the use of the EPA's ERT. Alternatively, you may submit an electronic file consistent with the extensible markup language (XML) schema listed on the EPA's ERT website.

(ii) Data collected using test methods that are not supported by the EPA's ERT as listed on the EPA's ERT website at the time of the test. The results of the performance test must be included as an attachment in the ERT or an alternate electronic file consistent with the XML schema listed on the EPA's ERT website. Submit the ERT generated package or alternative file to the EPA via CEDRI.

(iii) Confidential business information (CBI). If you claim some of the information submitted under [paragraph \(a\)](#) of this section is CBI, you must submit a complete file, including information claimed to be CBI, to the EPA. The file must be generated through the use of the EPA's ERT or an alternate electronic file consistent with the XML schema listed on the EPA's ERT website. Submit the file on a compact disc, flash drive, or other commonly used electronic storage medium and clearly mark the medium as CBI. Mail the electronic medium to U.S. EPA/OAQPS/CORE CBI Office, Attention: Group Leader, Measurement Policy Group, MD

C404-02, 4930 Old Page Rd., Durham, NC 27703. The same file with the CBI omitted must be submitted to the EPA via the EPA's CDX as described in [paragraph \(1\)\(1\)\(i\)](#) of this section.

(2) Each owner or operator required to submit reports following the procedure specified in this paragraph must submit reports to the EPA via CEDRI. CEDRI can be accessed through the EPA's CDX. The owner or operator must use the appropriate electronic report in CEDRI for this subpart or an alternate electronic file format consistent with the XML schema listed on the CEDRI website (<https://www.epa.gov/electronic-reporting-air-emissions/compliance-and-emissions-data-reporting-interface-cedri>). Once the spreadsheet template upload/forms for the reports have been available in CEDRI for 90 days, the owner or operator must begin submitting all subsequent reports via CEDRI. The reports must be submitted by the deadlines specified in this subpart, regardless of the method in which the reports are submitted. The NMOC emission rate reports, semi-annual reports, and bioreactor 40-percent moisture reports should be electronically reported as a spreadsheet template upload/form to CEDRI. If the reporting forms specific to this subpart are not available in CEDRI at the time that the reports are due, the owner or operator must submit the reports to the Administrator at the appropriate address listed in [§ 63.13](#) of subpart A.

(m) ***Claims of EPA system outage.*** Beginning no later than September 27, 2021, if you are required to electronically submit a report through CEDRI in the EPA's CDX, you may assert a claim of EPA system outage for failure to comply timely with the reporting requirement. To assert a claim of EPA system outage, you must meet the following requirements:

- (1) You must have been or will be precluded from accessing CEDRI and submitting a required report within the time prescribed due to an outage of either the EPA's CEDRI or CDX systems.
- (2) The outage must have occurred within the period of time beginning 5 business days prior to the date that the submission is due.
- (3) The outage may be planned or unplanned.
- (4) You must submit notification to the Administrator in writing as soon as possible following the date you first knew, or through due diligence should have known, that the event may cause or has caused a delay in reporting.
- (5) You must provide to the Administrator a written description identifying:
  - (i) The date(s) and time(s) when CDX or CEDRI was accessed and the system was unavailable;
  - (ii) A rationale for attributing the delay in reporting beyond the regulatory deadline to EPA system outage;
  - (iii) Measures taken or to be taken to minimize the delay in reporting; and

(iv) The date by which you propose to report, or if you have already met the reporting requirement at the time of the notification, the date you reported.

(6) The decision to accept the claim of EPA system outage and allow an extension to the reporting deadline is solely within the discretion of the Administrator.

(7) In any circumstance, the report must be submitted electronically as soon as possible after the outage is resolved.

(n) ***Claims of force majeure.*** Beginning no later than September 27, 2021, if you are required to electronically submit a report through CEDRI in the EPA's CDX, you may assert a claim of force majeure for failure to comply timely with the reporting requirement. To assert a claim of force majeure, you must meet the following requirements:

(1) You may submit a claim if a force majeure event is about to occur, occurs, or has occurred or there are lingering effects from such an event within the period of time beginning 5 business days prior to the date the submission is due. For the purposes of this section, a force majeure event is defined as an event that will be or has been caused by circumstances beyond the control of the affected facility, its contractors, or any entity controlled by the affected facility that prevents you from complying with the requirement to submit a report electronically within the time period prescribed. Examples of such events are acts of nature (*e.g.*, hurricanes, earthquakes, or floods), acts of war or terrorism, or equipment failure or safety hazard beyond the control of the affected facility (*e.g.*, large scale power outage).

(2) You must submit notification to the Administrator in writing as soon as possible following the date you first knew, or through due diligence should have known, that the event may cause or has caused a delay in reporting.

(3) You must provide to the Administrator:

(i) A written description of the force majeure event;

(ii) A rationale for attributing the delay in reporting beyond the regulatory deadline to the force majeure event;

(iii) Measures taken or to be taken to minimize the delay in reporting; and

(iv) The date by which you propose to report, or if you have already met the reporting requirement at the time of the notification, the date you reported.

(4) The decision to accept the claim of force majeure and allow an extension to the reporting deadline is solely within the discretion of the Administrator.

(5) In any circumstance, the reporting must occur as soon as possible after the force majeure event occurs.

[[85 FR 17261](#), Mar. 26, 2020, as amended at [87 FR 8204](#), Feb. 14, 2022]

**§ 63.1982 What records and reports must I submit and keep for bioreactors or liquids addition other than leachate?**

Submit reports as specified in this section and [§ 63.1981](#). Keep records as specified in this section and [§ 63.1983](#).

- (a) For bioreactors at new affected sources you must submit the initial semi-annual compliance report and performance test results described in [§ 63.1981\(h\)](#) within 180 days after the date you are required to begin operating the gas collection and control system by [§ 63.1947\(a\)\(2\)](#).
- (b) If you must submit a semi-annual compliance report for a bioreactor as well as a semi-annual compliance report for a conventional portion of the same landfill, you may delay submittal of a subsequent semi-annual compliance report for the bioreactor according to [paragraphs \(b\)\(1\) through \(3\)](#) of this section so that the reports may be submitted on the same schedule.
  - (1) After submittal of your initial semi-annual compliance report and performance test results for the bioreactor, you may delay submittal of the subsequent semi-annual compliance report for the bioreactor until the date the initial or subsequent semi-annual compliance report is due for the conventional portion of your landfill.
  - (2) You may delay submittal of your subsequent semi-annual compliance report by no more than 12 months after the due date for submitting the initial semi-annual compliance report and performance test results described in [§ 63.1981\(h\)](#) for the bioreactor. The report must cover the time period since the previous semi-annual report for the bioreactor, which would be a period of at least 6 months and no more than 12 months.
  - (3) After the delayed semi-annual report, all subsequent semi-annual reports for the bioreactor must be submitted every 6 months on the same date the semi-annual report for the conventional portion of the landfill is due.
- (c) If you add any liquids other than leachate in a controlled fashion to the waste mass and do not comply with the bioreactor requirements in [§§ 63.1947, 63.1955\(b\)](#), and [paragraphs \(a\) and \(b\)](#) of this section, you must keep a record of calculations showing that the percent moisture by weight expected in the waste mass to which liquid is added is less than 40 percent. The calculation must consider the waste mass, moisture content of the incoming waste, mass of water added to the waste including leachate recirculation and other liquids addition and precipitation, and the mass of water removed through leachate or other water losses. Moisture level sampling or mass balances calculations can be used. You must document the calculations and the basis of any assumptions. Keep the record of the calculations until you cease liquids addition.
- (d) If you calculate moisture content to establish the date your bioreactor is required to begin operating the collection and control system under [§ 63.1947\(a\)\(2\)](#) or [\(c\)\(2\)](#), keep a record of the

calculations including the information specified in [paragraph \(e\)](#) of this section for 5 years. Within 90 days after the bioreactor achieves 40-percent moisture content, report the results of the calculation, the date the bioreactor achieved 40-percent moisture content by weight, and the date you plan to begin collection and control system operation to the Administrator. Beginning no later than September 27, 2021, the reports should be submitted following the procedure specified in [§ 63.1981\(l\)\(2\)](#).

### **§ 63.1983 What records must I keep?**

You must keep records as specified in this subpart. You must also keep records as specified in the general provisions of [40 CFR part 63](#) as shown in Table 1 to this subpart.

(a) Except as provided in [§ 63.1981\(d\)\(2\)](#), each owner or operator of an MSW landfill subject to the provisions of [§ 63.1959\(b\)\(2\)\(ii\)](#) and [\(iii\) of this chapter](#) must keep for at least 5 years up-to-date, readily accessible, on-site records of the design capacity report that triggered [§ 63.1959\(b\)](#), the current amount of solid waste in-place, and the year-by-year waste acceptance rate. Off-site records may be maintained if they are retrievable within 4 hours. Either paper copy or electronic formats are acceptable.

(b) Except as provided in [§ 63.1981\(d\)\(2\)](#), each owner or operator of a controlled landfill must keep up-to-date, readily accessible records for the life of the control system equipment of the data listed in [paragraphs \(b\)\(1\)](#) through [\(5\)](#) of this section as measured during the initial performance test or compliance determination. Records of subsequent tests or monitoring must be maintained for a minimum of 5 years. Records of the control device vendor specifications must be maintained until removal.

(1) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with [§ 63.1959\(b\)\(2\)\(ii\)](#):

(i) The maximum expected gas generation flow rate as calculated in [§ 63.1960\(a\)\(1\)](#).

(ii) The density of wells, horizontal collectors, surface collectors, or other gas extraction devices determined using the procedures specified in [§ 63.1962\(a\)\(1\)](#) and [\(2\)](#).

(2) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with [§ 63.1959\(b\)\(2\)\(iii\)](#) through use of an enclosed combustion device other than a boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts:

(i) The average temperature measured at least every 15 minutes and averaged over the same time period of the performance test.

(ii) The percent reduction of NMOC determined as specified in [§ 63.1959\(b\)\(2\)\(iii\)\(B\)](#) achieved by the control device.



(3) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with [§ 63.1959\(b\)\(2\)\(iii\)\(B\)\(I\)](#) through use of a boiler or process heater of any size: A description of the location at which the collected gas vent stream is introduced into the boiler or process heater over the same time period of the performance testing.

(4) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with [§ 63.1959\(b\)\(2\)\(iii\)\(A\)](#) through use of a non-enclosed flare, the flare type (*i.e.*, steam-assisted, air-assisted, or nonassisted), all visible emission readings, heat content determination, flow rate or bypass flow rate measurements, and exit velocity determinations made during the performance test as specified in [§ 63.11](#); continuous records of the flare pilot flame or flare flame monitoring and records of all periods of operations during which the pilot flame or the flare flame is absent.

(5) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with [§ 63.1959\(b\)\(2\)\(iii\)\(C\)](#) through use of a landfill gas treatment system:

(i) ***Bypass records.*** Records of the flow of landfill gas to, and bypass of, the treatment system.

(ii) ***Site-specific treatment monitoring plan.*** Beginning no later than September 27, 2021, the owner or operator must prepare a site-specific treatment monitoring plan to include:

(A) Monitoring records of parameters that are identified in the treatment system monitoring plan and that ensure the treatment system is operating properly for each intended end use of the treated landfill gas. At a minimum, records should include records of filtration, de-watering, and compression parameters that ensure the treatment system is operating properly for each intended end use of the treated landfill gas.

(B) Monitoring methods, frequencies, and operating ranges for each monitored operating parameter based on manufacturer's recommendations or engineering analysis for each intended end use of the treated landfill gas.

(C) Documentation of the monitoring methods and ranges, along with justification for their use.

(D) List of responsible staff (by job title) for data collection.

(E) Processes and methods used to collect the necessary data.

(F) Description of the procedures and methods that are used for quality assurance, maintenance, and repair of all continuous monitoring systems (CMS).

(c) Except as provided in [§ 63.1981\(d\)\(2\)](#), each owner or operator of a controlled landfill subject to the provisions of this subpart must keep for 5 years up-to-date, readily accessible continuous records of the equipment operating parameters specified to be monitored in [§ 63.1961](#) as well as up-to-date, readily accessible records for periods of operation during which the parameter boundaries established during the most recent performance test are exceeded.



(1) The following constitute exceedances that must be recorded and reported under [§ 63.1981\(h\)](#):

(i) For enclosed combustors except for boilers and process heaters with design heat input capacity of 44 megawatts (150 million Btu per hour) or greater, all 3-hour periods of operation during which the average temperature was more than 28 degrees Celsius (82 degrees Fahrenheit) below the average combustion temperature during the most recent performance test at which compliance with [§ 63.1959\(b\)\(2\)\(iii\)](#) was determined.

(ii) For boilers or process heaters, whenever there is a change in the location at which the vent stream is introduced into the flame zone as required under [paragraph \(b\)\(3\)](#) of this section.

(2) Each owner or operator subject to the provisions of this subpart must keep up-to-date, readily accessible continuous records of the indication of flow to the control system and the indication of bypass flow or records of monthly inspections of car-seals or lock-and-key configurations used to seal bypass lines, specified under [§ 63.1961\(b\)\(2\)\(ii\)](#), [\(c\)\(2\)\(ii\)](#), and [\(g\)\(2\)](#).

(3) Each owner or operator subject to the provisions of this subpart who uses a boiler or process heater with a design heat input capacity of 44 megawatts or greater to comply with [§ 63.1959\(b\)\(2\)\(iii\)](#) must keep an up-to-date, readily accessible record of all periods of operation of the boiler or process heater. Examples of such records could include records of steam use, fuel use, or monitoring data collected pursuant to other state, local, tribal, or federal regulatory requirements.

(4) Each owner or operator seeking to comply with the provisions of this subpart by use of a non-enclosed flare must keep up-to-date, readily accessible continuous records of the flame or flare pilot flame monitoring specified under [§ 63.1961\(c\)](#), and up-to-date, readily accessible records of all periods of operation in which the flame or flare pilot flame is absent.

(5) Each owner or operator of a landfill seeking to comply with [§ 63.1959\(b\)\(2\)](#) using an active collection system designed in accordance with [§ 63.1959\(b\)\(2\)\(ii\)](#) must keep records of periods when the collection system or control device is not operating.

(6) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the operational standard in [§ 63.1958\(e\)\(1\)](#), the date, time, and duration of each startup and/or shutdown period, recording the periods when the affected source was subject to the standard applicable to startup and shutdown.

(7) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the operational standard in [§ 63.1958\(e\)\(1\)](#), in the event that an affected unit fails to meet an applicable standard, record the information below in this paragraph:

(i) For each failure record the date, time and duration of each failure and the cause of such events (including unknown cause, if applicable).

(ii) For each failure to meet an applicable standard; record and retain a list of the affected sources or equipment.

(iii) Record actions taken to minimize emissions in accordance with the general duty of [§ 63.1955\(c\)](#) and any corrective actions taken to return the affected unit to its normal or usual manner of operation.

(8) Beginning no later than September 27, 2021, in lieu of the requirements specified in [§ 63.8\(d\)\(3\)](#) of subpart A you must keep the written procedures required by [§ 63.8\(d\)\(2\)](#) on record for the life of the affected source or until the affected source is no longer subject to the provisions of this part, to be made available for inspection, upon request, by the Administrator. If the performance evaluation plan is revised, you must keep previous (*i.e.*, superseded) versions of the performance evaluation plan on record to be made available for inspection, upon request, by the Administrator, for a period of 5 years after each revision to the plan. The program of corrective action should be included in the plan required under [§ 63.8\(d\)\(2\)](#).

(d) Except as provided in [§ 63.1981\(d\)\(2\)](#), each owner or operator subject to the provisions of this subpart must keep for the life of the collection system an up-to-date, readily accessible plot map showing each existing and planned collector in the system and providing a unique identification location label for each collector.

(1) Each owner or operator subject to the provisions of this subpart must keep up-to-date, readily accessible records of the installation date and location of all newly installed collectors as specified under [§ 63.1960\(b\)](#).

(2) Each owner or operator subject to the provisions of this subpart must keep readily accessible documentation of the nature, date of deposition, amount, and location of asbestos-containing or nondegradable waste excluded from collection as provided in [§ 63.1962\(a\)\(3\)\(i\)](#) as well as any nonproductive areas excluded from collection as provided in [§ 63.1962\(a\)\(3\)\(ii\)](#).

(e) Except as provided in [§ 63.1981\(d\)\(2\)](#), each owner or operator subject to the provisions of this subpart must keep for at least 5 years up-to-date, readily accessible records of the following:

(1) All collection and control system exceedances of the operational standards in [§ 63.1958](#), the reading in the subsequent month whether or not the second reading is an exceedance, and the location of each exceedance.

(2) Each owner or operator subject to the control provisions of this subpart must keep records of each wellhead temperature monitoring value of greater than 55 degrees Celsius (131 degrees Fahrenheit), each wellhead nitrogen level at or above 20 percent, and each wellhead oxygen level at or above 5 percent, except:

(i) When an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the compliance provisions for wellhead temperature in [§ 63.1958\(c\)\(1\)](#), but no

later than September 27, 2021, the records of each wellhead temperature monitoring value of 62.8 degrees Celsius (145 degrees Fahrenheit) or above instead of values greater than 55 degrees Celsius (131 degrees Fahrenheit).

(ii) Each owner or operator required to conduct the enhanced monitoring provisions in [§ 63.1961\(a\)\(5\)](#), must also keep records of all enhanced monitoring activities.

(iii) Each owner or operator required to submit the *24-hour high temperature report* in [§ 63.1981\(k\)](#), must also keep a record of the email transmission.

(3) For any root cause analysis for which corrective actions are required in [§ 63.1960\(a\)\(3\)\(i\)\(A\)](#) or [\(a\)\(4\)\(i\)\(A\)](#), keep a record of the root cause analysis conducted, including a description of the recommended corrective action(s) taken, and the date(s) the corrective action(s) were completed.

(4) For any root cause analysis for which corrective actions are required in [§ 63.1960\(a\)\(3\)\(i\)\(B\)](#) or [\(a\)\(4\)\(i\)\(B\)](#), keep a record of the root cause analysis conducted, the corrective action analysis, the date for corrective action(s) already completed following the positive pressure reading or high temperature reading, and, for action(s) not already completed, a schedule for implementation, including proposed commencement and completion dates.

(5) For any root cause analysis for which corrective actions are required in [§ 63.1960\(a\)\(3\)\(i\)\(C\)](#) or [\(a\)\(4\)\(i\)\(C\)](#), keep a record of the root cause analysis conducted, the corrective action analysis, the date for corrective action(s) already completed following the positive pressure reading or high temperature reading, for action(s) not already completed, a schedule for implementation, including proposed commencement and completion dates, and a copy of any comments or final approval on the corrective action analysis or schedule from the Administrator.

(f) Landfill owners or operators who convert design capacity from volume to mass or mass to volume to demonstrate that landfill design capacity is less than 2.5 million Mg or 2.5 million m<sup>3</sup>, as provided in the definition of “design capacity,” must keep readily accessible, on-site records of the annual recalculation of site-specific density, design capacity, and the supporting documentation. Off-site records may be maintained if they are retrievable within 4 hours. Either paper copy or electronic formats are acceptable.

(g) Except as provided in [§ 63.1981\(d\)\(2\)](#), each owner or operator subject to the provisions of this subpart must keep for at least 5 years up-to-date, readily accessible records of all collection and control system monitoring data for parameters measured in [§ 63.1961\(a\)\(1\)](#) through [\(6\)](#).

(h) Where an owner or operator subject to the provisions of this subpart seeks to demonstrate compliance with the operational standard for temperature in [§ 63.1958\(c\)\(1\)](#), you must keep the following records.

(1) Records of the landfill gas temperature on a monthly basis as monitored in [§ 63.1960\(a\)\(4\)](#).

(2) Records of enhanced monitoring data at each well with a measurement of landfill gas temperature greater than 62.8 degrees Celsius (145 degrees Fahrenheit) as gathered in [§ 63.1961\(a\)\(5\)](#) and [\(6\)](#).

(i) Any records required to be maintained by this subpart that are submitted electronically via the EPA's CEDRI may be maintained in electronic format. This ability to maintain electronic copies does not affect the requirement for facilities to make records, data, and reports available upon request to a delegated air agency or the EPA as part of an on-site compliance evaluation.

(ii) [Reserved]

[[85 FR 17261](#), Mar. 26, 2020, as amended at [85 FR 64401](#), Oct. 13, 2020]

## **Other Requirements and Information**

### **§ 63.1985 Who enforces this subpart?**

(a) This subpart can be implemented and enforced by the EPA, or a delegated authority such as the applicable state, local, or tribal agency. If the EPA Administrator has delegated authority to a state, local, or tribal agency, then that agency as well as the EPA has the authority to implement and enforce this subpart. Contact the applicable EPA Regional office to find out if this subpart is delegated to a state, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a state, local, or tribal agency under [subpart E of this part](#), the authorities contained in [paragraph \(c\)](#) of this section are retained by the EPA Administrator and are not transferred to the state, local, or tribal agency.

(c) The authorities that will not be delegated to state, local, or tribal agencies are as follows. Approval of alternatives to the emission standards in [§§ 63.1955](#) through [63.1962](#). Where this subpart references [part 60, subpart WWW of this subchapter](#), the cited provisions will be delegated according to the delegation provisions of [part 60, subpart WWW of this subchapter](#). For this subpart, the EPA also retains the authority to approve methods for determining the NMOC concentration in [§ 63.1959\(a\)\(3\)](#) and the method for determining the site-specific methane generation rate constant k in [§ 63.1959\(a\)\(4\)](#).

[[85 FR 17261](#), Mar. 26, 2020, as amended at [87 FR 8204](#), Feb. 14, 2022]

### **§ 63.1990 What definitions apply to this subpart?**

Terms used in this subpart are defined in the Clean Air Act, [40 CFR part 60, subparts A, Cc, Cf, WWW](#), and [XXX](#); [40 CFR part 62, subpart GGG](#), and [subpart A of this part](#), and this section that follows:

*Active collection system* means a gas collection system that uses gas mover equipment.

*Active landfill* means a landfill in which solid waste is being placed or a landfill that is planned to accept waste in the future.

*Bioreactor* means an MSW landfill or portion of an MSW landfill where any liquid other than leachate (leachate includes landfill gas condensate) is added in a controlled fashion into the waste mass (often in combination with recirculating leachate) to reach a minimum average moisture content of at least 40 percent by weight to accelerate or enhance the anaerobic (without oxygen) biodegradation of the waste.

*Closed area* means a separately lined area of an MSW landfill in which solid waste is no longer being placed. If additional solid waste is placed in that area of the landfill, that landfill area is no longer closed. The area must be separately lined to ensure that the landfill gas does not migrate between open and closed areas.

*Closed landfill* means a landfill in which solid waste is no longer being placed, and in which no additional solid wastes will be placed without first filing a notification of modification as prescribed under [§ 63.9\(b\)](#). Once a notification of modification has been filed, and additional solid waste is placed in the landfill, the landfill is no longer closed.

*Closure* means that point in time when a landfill becomes a closed landfill.

*Commercial solid waste* means all types of solid waste generated by stores, offices, restaurants, warehouses, and other nonmanufacturing activities, excluding residential and industrial wastes.

*Controlled landfill* means any landfill at which collection and control systems are required under this subpart as a result of the nonmethane organic compounds emission rate. The landfill is considered controlled at the time a collection and control system design plan is submitted in compliance with [§ 60.752\(b\)\(2\)\(i\) of this chapter](#) or in compliance with [§ 63.1959\(b\)\(2\)\(i\)](#).

*Corrective action analysis* means a description of all reasonable interim and long-term measures, if any, that are available, and an explanation of why the selected corrective action(s) is/are the best alternative(s), including, but not limited to, considerations of cost effectiveness, technical feasibility, safety, and secondary impacts.

*Cover penetration* means a wellhead, a part of a landfill gas collection or operations system, and/or any other object that completely passes through the landfill cover. The landfill cover includes that portion which covers the waste, as well as the portion which borders the waste extended to the point where it is sealed with the landfill liner or the surrounding land mass. Examples of what is not a penetration for purposes of this subpart include but are not limited to: Survey stakes, fencing including litter fences, flags, signs, utility posts, and trees so long as these items do not pass through the landfill cover.

*Design capacity* means the maximum amount of solid waste a landfill can accept, as indicated in terms of volume or mass in the most recent permit issued by the state, local, or tribal agency

responsible for regulating the landfill, plus any in-place waste not accounted for in the most recent permit. If the owner or operator chooses to convert the design capacity from volume to mass or from mass to volume to demonstrate its design capacity is less than 2.5 million Mg or 2.5 million m<sup>3</sup>, the calculation must include a site-specific density, which must be recalculated annually.

*Deviation* before September 28, 2021, means any instance in which an affected source subject to this subpart, or an owner or operator of such a source:

- (1) Fails to meet any requirement or obligation established by this subpart, including, but not limited to, any emissions limitation (including any operating limit) or work practice requirement;
- (2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit; or
- (3) Fails to meet any emission limitation, (including any operating limit), or work practice requirement in this subpart during SSM, regardless of whether or not such failure is permitted by this subpart.

*Deviation beginning no later than September 27, 2021*, means any instance in which an affected source subject to this subpart or an owner or operator of such a source:

- (1) Fails to meet any requirement or obligation established by this subpart including but not limited to any emission limit, or operating limit, or work practice requirement; or
- (2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit.

*Disposal facility* means all contiguous land and structures, other appurtenances, and improvements on the land used for the disposal of solid waste.

*Emissions limitation* means any emission limit, opacity limit, operating limit, or visible emissions limit.

*Enclosed combustor* means an enclosed firebox which maintains a relatively constant limited peak temperature generally using a limited supply of combustion air. An enclosed flare is considered an enclosed combustor.

*EPA approved State plan* means a State plan that EPA has approved based on the requirements in [40 CFR part 60, subpart B](#) to implement and enforce [40 CFR part 60, subparts Cc](#) or [Cf](#). An approved state plan becomes effective on the date specified in the document published in the Federal Register announcing EPA's approval.

*EPA approved Tribal plan* means a plan submitted by a tribal authority pursuant to [40 CFR parts 9, 35, 49, 50, and 81](#) to implement and enforce [40 CFR part 60, subpart Cc](#) or subpart Cf.

*Federal plan* means the EPA plan to implement [40 CFR part 60, subparts Cc](#) or [Cf](#) for existing MSW landfills located in states and Indian country where state plans or tribal plans are not currently in effect. On the effective date of an EPA approved state or tribal plan, the Federal Plan no longer applies. The Federal Plan implementing [40 CFR part 60, subpart Cc](#) is found at [40 CFR part 62, subpart GGG](#).

*Flare* means an open combustor without enclosure or shroud.

*Gas mover equipment* means the equipment (*i.e.*, fan, blower, compressor) used to transport landfill gas through the header system.

*Household waste* means any solid waste (including garbage, trash, and sanitary waste in septic tanks) derived from households (including, but not limited to, single and multiple residences, hotels and motels, bunkhouses, ranger stations, crew quarters, campgrounds, picnic grounds, and day-use recreation areas). Household waste does not include fully segregated yard waste. Segregated yard waste means vegetative matter resulting exclusively from the cutting of grass, the pruning and/or removal of bushes, shrubs, and trees, the weeding of gardens, and other landscaping maintenance activities. Household waste does not include construction, renovation, or demolition wastes, even if originating from a household.

*Industrial solid waste* means solid waste generated by manufacturing or industrial processes that is not a hazardous waste regulated under Subtitle C of the Resource Conservation and Recovery Act, [40 CFR parts 264 and 265](#). Such waste may include, but is not limited to, waste resulting from the following manufacturing processes: Electric power generation; fertilizer/agricultural chemicals; food and related products/by-products; inorganic chemicals; iron and steel manufacturing; leather and leather products; nonferrous metals manufacturing/foundries; organic chemicals; plastics and resins manufacturing; pulp and paper industry; rubber and miscellaneous plastic products; stone, glass, clay, and concrete products; textile manufacturing; transportation equipment; and water treatment. This term does not include mining waste or oil and gas waste.

*Interior well* means any well or similar collection component located inside the perimeter of the landfill waste. A perimeter well located outside the landfilled waste is not an interior well.

*Landfill* means an area of land or an excavation in which wastes are placed for permanent disposal, and that is not a land application unit, surface impoundment, injection well, or waste pile as those terms are defined under [§ 257.2 of this chapter](#).

*Lateral expansion* means a horizontal expansion of the waste boundaries of an existing MSW landfill. A lateral expansion is not a modification unless it results in an increase in the design capacity of the landfill.



*Leachate recirculation* means the practice of taking the leachate collected from the landfill and reapplying it to the landfill by any of one of a variety of methods, including pre-wetting of the waste, direct discharge into the working face, spraying, infiltration ponds, vertical injection wells, horizontal gravity distribution systems, and pressure distribution systems.

*Modification* means an increase in the permitted volume design capacity of the landfill by either lateral or vertical expansion based on its permitted design capacity after November 7, 2000. Modification does not occur until the owner or operator commences construction on the lateral or vertical expansion.

*Municipal solid waste landfill* or *MSW landfill* means an entire disposal facility in a contiguous geographical space where household waste is placed in or on land. An MSW landfill may also receive other types of RCRA Subtitle D wastes ([§ 257.2 of this chapter](#)) such as commercial solid waste, nonhazardous sludge, conditionally exempt small quantity generator waste, and industrial solid waste. Portions of an MSW landfill may be separated by access roads. An MSW landfill may be publicly or privately owned. An MSW landfill may be a new MSW landfill, an existing MSW landfill, or a lateral expansion.

*Municipal solid waste landfill emissions* or *MSW landfill emissions* means gas generated by the decomposition of organic waste deposited in an MSW landfill or derived from the evolution of organic compounds in the waste.

*NMOC* means nonmethane organic compounds, as measured according to the provisions of [§ 63.1959](#).

*Nondegradable waste* means any waste that does not decompose through chemical breakdown or microbiological activity. Examples are, but are not limited to, concrete, municipal waste combustor ash, and metals.

*Passive collection system* means a gas collection system that solely uses positive pressure within the landfill to move the gas rather than using gas mover equipment.

*Root cause analysis* means an assessment conducted through a process of investigation to determine the primary cause, and any other contributing causes, of an exceedance of a standard operating parameter at a wellhead.

*Segregated yard waste* means vegetative matter resulting exclusively from the cutting of grass, the pruning and/or removal of bushes, shrubs, and trees, the weeding of gardens, and other landscaping maintenance activities.

*Sludge* means the term sludge as defined in [§ 258.2 of this chapter](#).

*Solid waste* means the term solid waste as defined in [§ 258.2 of this chapter](#).



*Sufficient density* means any number, spacing, and combination of collection system components, including vertical wells, horizontal collectors, and surface collectors, necessary to maintain emission and migration control as determined by measures of performance set forth in this subpart.

*Sufficient extraction rate* means a rate sufficient to maintain a negative pressure at all wellheads in the collection system without causing air infiltration, including any wellheads connected to the system as a result of expansion or excess surface emissions, for the life of the blower.

*Treated landfill gas* means landfill gas processed in a treatment system as defined in this subpart.

*Treatment system* means a system that filters, de-waters, and compresses landfill gas for sale or beneficial use.

*Untreated landfill gas* means any landfill gas that is not treated landfill gas.

*Work practice requirement* means any design, equipment, work practice, or operational standard, or combination thereof, that is promulgated pursuant to section 112(h) of the Clean Air Act.

**Table 1 to Subpart AAAA of Part 63—Applicability of NESHAP General Provisions to Subpart AAAA**

As specified in this subpart, you must meet each requirement in the following table that applies to you. The owner or operator may begin complying with the provisions that apply no later than September 27, 2021, any time before that date.

Table 1 to Subpart AAAA of Part 63—Applicability of NESHAP General Provisions to Subpart AAAA				
Part 63 citation	Description	Applicable to subpart AAAA before September 28, 2021	Applicable to subpart AAAA no later than September 27, 2021	Explanation
§ 63.1(a)	Applicability: General applicability of NESHAP in this part	Yes	Yes	
§ 63.1(b)	Applicability determination for stationary sources	Yes	Yes	

Table 1 to Subpart AAAA of Part 63—Applicability of NESHAP General Provisions to Subpart AAAA

<b>Part 63 citation</b>	<b>Description</b>	<b>Applicable to subpart AAAA before September 28, 2021</b>	<b>Applicable to subpart AAAA no later than September 27, 2021</b>	<b>Explanation</b>
§ 63.1(c)	Applicability after a standard has been set	No <sup>1</sup>	Yes	
§ 63.1(e)	Applicability of permit program before relevant standard is set	Yes	Yes	
§ 63.2	Definitions	Yes	Yes	
§ 63.3	Units and abbreviations	No <sup>1</sup>	Yes	
§ 63.4	Prohibited activities and circumvention	Yes	Yes	
§ 63.5(a)	Construction/reconstruction	No <sup>1</sup>	Yes	
§ 63.5(b)	Requirements for existing, newly constructed, and reconstructed sources	Yes	Yes	
§ 63.5(d)	Application for approval of construction or reconstruction	No <sup>1</sup>	Yes	
§ 63.5(e) and (f)	Approval of construction and reconstruction	No <sup>1</sup>	Yes	
§ 63.6(a)	Compliance with standards and maintenance requirements—applicability	No <sup>1</sup>	Yes	

Table 1 to Subpart AAAA of Part 63—Applicability of NESHAP General Provisions to Subpart AAAA

Part 63 citation	Description	Applicable to subpart AAAA before September 28, 2021	Applicable to subpart AAAA no later than September 27, 2021	Explanation
§ 63.6(b) and (c)	Compliance dates for new, reconstructed, and existing sources	No <sup>1</sup>	Yes	
§ 63.6(e)(1)(i)-(ii)	Operation and maintenance requirements	Yes	No	See <a href="#">§ 63.1955(c)</a> for general duty requirements.
§ 63.6(e)(3)(i)-(ix)	SSM plan	Yes	No	
§ 63.6(f)(1)	Exemption of nonopacity emission standards during SSM	No	No	
§ 63.6(f)(2) and (3)	Compliance with nonopacity emission standards	Yes	Yes	
§ 63.6(g)	Use of an alternative nonopacity standard	No <sup>1</sup>	Yes	
§ 63.6(h)	Compliance with opacity and visible emission standards	No <sup>1</sup>	No	Subpart AAAA does not prescribe opacity or visible emission standards.
§ 63.6(i)	Extension of compliance with emission standards	No <sup>1</sup>	Yes	

Table 1 to Subpart AAAA of Part 63—Applicability of NESHAP General Provisions to Subpart AAAA

Part 63 citation	Description	Applicable to subpart AAAA before September 28, 2021	Applicable to subpart AAAA no later than September 27, 2021	Explanation
§ 63.6(j)	Exemption from compliance with emission standards	No <sup>1</sup>	Yes	
§ 63.7	Performance testing	No <sup>1</sup>	Yes	
§ 63.7(e)(1)	Conditions for performing performance tests	No <sup>1</sup>	No	<a href="#">40 CFR 63.1959(f)</a> specifies the conditions for performing performance tests.
§ 63.8(a) and (b)	Monitoring requirements—Applicability and conduct of monitoring	No <sup>1</sup>	Yes	
§ 63.8(c)(1)	Operation and Maintenance of continuous emissions monitoring system	No <sup>1</sup>	Yes	
§ 63.8(c)(1)(i)	Operation and Maintenance Requirements	No <sup>1</sup>	No	Unnecessary due to the requirements of <a href="#">§ 63.8(c)(1)</a> and the requirements for a quality control plan for monitoring equipment in <a href="#">§ 63.8(d)(2)</a> .
§ 63.8(c)(1)(ii)	Operation and Maintenance Requirements	No <sup>1</sup>	No	

Table 1 to Subpart AAAA of Part 63—Applicability of NESHAP General Provisions to Subpart AAAA

<b>Part 63 citation</b>	<b>Description</b>	<b>Applicable to subpart AAAA before September 28, 2021</b>	<b>Applicable to subpart AAAA no later than September 27, 2021</b>	<b>Explanation</b>
§ 63.8(c)(1)(iii)	SSM plan for monitors	No <sup>1</sup>	No	
§ 63.8(c)(2)-(8)	Monitoring requirements	No <sup>1</sup>	Yes	
§ 63.8(d)(1)	Quality control for monitors	No <sup>1</sup>	Yes	
§ 63.8(d)(2)	Quality control for monitors	No <sup>1</sup>	Yes	
§ 63.8(d)(3)	Quality control records	No <sup>1</sup>	No	See <a href="#">§ 63.1983(c)(8)</a> .
§ 63.9(a), (c), and (d)	Notifications	No <sup>1</sup>	Yes	
§ 63.9(b)	Initial notifications	No <sup>1</sup>	Yes <sup>2</sup>	
§ 63.9(e)	Notification of performance test	No <sup>1</sup>	Yes <sup>2</sup>	
§ 63.9(f)	Notification of visible emissions/opacity test	No <sup>1</sup>	No	Subpart AAAA does not prescribe opacity or visible emission standards.
§ 63.9(g)	Notification when using CMS	No <sup>1</sup>	Yes <sup>2</sup>	
§ 63.9(h)	Notification of compliance status	No <sup>1</sup>	Yes <sup>2</sup>	
§ 63.9(i)	Adjustment of submittal deadlines	No <sup>1</sup>	Yes	

Table 1 to Subpart AAAA of Part 63—Applicability of NESHAP General Provisions to Subpart AAAA

Part 63 citation	Description	Applicable to subpart AAAA before September 28, 2021	Applicable to subpart AAAA no later than September 27, 2021	Explanation
§ 63.9(j)	Change in information already provided	No <sup>1</sup>	Yes	
§ 63.10(a)	Recordkeeping and reporting—general	No <sup>1</sup>	Yes	
§ 63.10(b)(1)	General recordkeeping	No <sup>1</sup>	Yes	
§ 63.10(b)(2)(i)	Startup and shutdown records	Yes	No	See <a href="#">§ 63.1983(c)(6)</a> for recordkeeping for periods of startup and shutdown.
§ 63.10(b)(2)(ii)	Recordkeeping of failures to meet a standard	Yes	No	See <a href="#">§ 63.1983(c)(6)-(7)</a> for recordkeeping for any exceedance of a standard.
§ 63.10(b)(2)(iii)	Recordkeeping of maintenance on air pollution control equipment	Yes	Yes	
§ 63.10(b)(2)(iv)-(v)	Actions taken to minimize emissions during SSM	Yes	No	See <a href="#">§ 63.1983(c)(7)</a> for recordkeeping of corrective actions to restore compliance.
§ 63.10(b)(2)(vi)	Recordkeeping for CMS malfunctions	No <sup>1</sup>	Yes	

Table 1 to Subpart AAAA of Part 63—Applicability of NESHAP General Provisions to Subpart AAAA

Part 63 citation	Description	Applicable to subpart AAAA before September 28, 2021	Applicable to subpart AAAA no later than September 27, 2021	Explanation
§ 63.10(b)(2)(vii)-(xiv)	Other Recordkeeping of compliance measurements	No <sup>1</sup>	Yes	
§ 63.10(c)	Additional recordkeeping for sources with CMS	No <sup>1</sup>	No	See <a href="#">§ 63.1983</a> for required CMS recordkeeping.
§ 63.10(d)(1)	General reporting	No <sup>1</sup>	Yes	
§ 63.10(d)(2)	Reporting of performance test results	No <sup>1</sup>	Yes	
§ 63.10(d)(3)	Reporting of visible emission observations	No <sup>1</sup>	No	
§ 63.10(d)(4)	Progress reports for compliance date extensions	No <sup>1</sup>	Yes	
§ 63.10(d)(5)	SSM reporting	Yes	No	All exceedances must be reported in the semi-annual report required by <a href="#">§ 63.1981(h)</a> .
§ 63.10(e)	Additional reporting for CMS systems	No <sup>1</sup>	Yes	
§ 63.10(f)	Recordkeeping/reporting waiver	No <sup>1</sup>	Yes	

Table 1 to Subpart AAAA of Part 63—Applicability of NESHAP General Provisions to Subpart AAAA

Part 63 citation	Description	Applicable to subpart AAAA before September 28, 2021	Applicable to subpart AAAA no later than September 27, 2021	Explanation
§ 63.11	Control device requirements/flares	No <sup>1</sup>	Yes	§ 60.18 is required before September 27, 2021. However, <a href="#">§ 60.18</a> and <a href="#">63.11</a> are equivalent.
§ 63.12(a)	State authority	Yes	Yes	
§ 63.12(b)-(c)	State delegations	No <sup>1</sup>	Yes	
§ 63.13	Addresses	No <sup>1</sup>	Yes	
§ 63.14	Incorporation by reference	No <sup>1</sup>	Yes	
§ 63.15	Availability of information and confidentiality	Yes	Yes	

<sup>1</sup> Before September 28, 2021, this subpart requires affected facilities to follow [40 CFR part 60, subpart WWW](#), which incorporates the General Provisions of [40 CFR part 60](#).

<sup>2</sup> If an owner or operator has complied with requirements that are parallel to the requirements of the part 63 citation of this table under [40 CFR part 60, subpart WWW](#) or subpart XXX, or a state or federal plan that implements [40 CFR part 60, subpart Cc](#) or [Cf](#), [then](#) additional notification for that requirement is not required.

[[85 FR 17261](#), Mar. 26, 2020, as amended at [85 FR 64401](#), Oct. 13, 2020; [87 FR 8204](#), Feb. 14, 2022]



**Appendix C**

**40 C.F.R. Part 63 Subpart CCCCCC**

***National Emissions Standards for Hazardous Air Pollutants for Source Category: Gasoline  
Dispensing Facilities***

## **Subpart CCCCCC—National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Dispensing Facilities**

**Source:** [73 FR 1945](#), Jan. 10, 2008, unless otherwise noted.

### **What This Subpart Covers**

#### **§ 63.11110 What is the purpose of this subpart?**

This subpart establishes national emission limitations and management practices for hazardous air pollutants (HAP) emitted from the loading of gasoline storage tanks at gasoline dispensing facilities (GDF). This subpart also establishes requirements to demonstrate compliance with the emission limitations and management practices.

#### **§ 63.11111 Am I subject to the requirements in this subpart?**

- (a) The affected source to which this subpart applies is each GDF that is located at an area source. The affected source includes each gasoline cargo tank during the delivery of product to a GDF and also includes each storage tank.
- (b) If your GDF has a monthly throughput of less than 10,000 gallons of gasoline, you must comply with the requirements in [§ 63.11116](#).
- (c) If your GDF has a monthly throughput of 10,000 gallons of gasoline or more, you must comply with the requirements in [§ 63.11117](#).
- (d) If your GDF has a monthly throughput of 100,000 gallons of gasoline or more, you must comply with the requirements in [§ 63.11118](#).
- (e) An affected source shall, upon request by the Administrator, demonstrate that their monthly throughput is less than the 10,000-gallon or the 100,000-gallon threshold level, as applicable. For new or reconstructed affected sources, as specified in [§ 63.11112\(b\)](#) and [\(c\)](#), recordkeeping to document monthly throughput must begin upon startup of the affected source. For existing sources, as specified in [§ 63.11112\(d\)](#), recordkeeping to document monthly throughput must begin on January 10, 2008. For existing sources that are subject to this subpart only because they load gasoline into fuel tanks other than those in motor vehicles, as defined in [§ 63.11132](#), recordkeeping to document monthly throughput must begin on January 24, 2011. Records required under this paragraph shall be kept for a period of 5 years.
- (f) If you are an owner or operator of affected sources, as defined in [paragraph \(a\)](#) of this section, you are not required to obtain a permit under [40 CFR part 70](#) or [40 CFR part 71](#) as a result of being subject to this subpart. However, you must still apply for and obtain a permit under [40 CFR part 70](#) or [40 CFR part 71](#) if you meet one or more of the applicability criteria found in [40 CFR 70.3\(a\)](#) and [\(b\)](#) or [40 CFR 71.3\(a\)](#) and [\(b\)](#).

(g) The loading of aviation gasoline into storage tanks at airports, and the subsequent transfer of aviation gasoline within the airport, is not subject to this subpart.

(h) Monthly throughput is the total volume of gasoline loaded into, or dispensed from, all the gasoline storage tanks located at a single affected GDF. If an area source has two or more GDF at separate locations within the area source, each GDF is treated as a separate affected source.

(i) If your affected source's throughput ever exceeds an applicable throughput threshold, the affected source will remain subject to the requirements for sources above the threshold, even if the affected source throughput later falls below the applicable throughput threshold.

(j) The dispensing of gasoline from a fixed gasoline storage tank at a GDF into a portable gasoline tank for the on-site delivery and subsequent dispensing of the gasoline into the fuel tank of a motor vehicle or other gasoline-fueled engine or equipment used within the area source is only subject to [§ 63.11116 of this subpart](#).

(k) For any affected source subject to the provisions of this subpart and another Federal rule, you may elect to comply only with the more stringent provisions of the applicable subparts. You must consider all provisions of the rules, including monitoring, recordkeeping, and reporting. You must identify the affected source and provisions with which you will comply in your Notification of Compliance Status required under [§ 63.11124](#). You also must demonstrate in your Notification of Compliance Status that each provision with which you will comply is at least as stringent as the otherwise applicable requirements in this subpart. You are responsible for making accurate determinations concerning the more stringent provisions, and noncompliance with this rule is not excused if it is later determined that your determination was in error, and, as a result, you are violating this subpart. Compliance with this rule is your responsibility and the Notification of Compliance Status does not alter or affect that responsibility.

[[73 FR 1945](#), Jan. 10, 2008, as amended at [76 FR 4181](#), Jan. 24, 2011]

#### **§ 63.11112 What parts of my affected source does this subpart cover?**

(a) The emission sources to which this subpart applies are gasoline storage tanks and associated equipment components in vapor or liquid gasoline service at new, reconstructed, or existing GDF that meet the criteria specified in [§ 63.11111](#). Pressure/Vacuum vents on gasoline storage tanks and the equipment necessary to unload product from cargo tanks into the storage tanks at GDF are covered emission sources. The equipment used for the refueling of motor vehicles is not covered by this subpart.

(b) An affected source is a new affected source if you commenced construction on the affected source after November 9, 2006, and you meet the applicability criteria in [§ 63.11111](#) at the time you commenced operation.

(c) An affected source is reconstructed if you meet the criteria for reconstruction as defined in [§ 63.2](#).

(d) An affected source is an existing affected source if it is not new or reconstructed.

**§ 63.11113 When do I have to comply with this subpart?**

(a) If you have a new or reconstructed affected source, you must comply with this subpart according to [paragraphs \(a\)\(1\)](#) and [\(2\)](#) of this section, except as specified in [paragraph \(d\)](#) of this section.

(1) If you start up your affected source before January 10, 2008, you must comply with the standards in this subpart no later than January 10, 2008.

(2) If you start up your affected source after January 10, 2008, you must comply with the standards in this subpart upon startup of your affected source.

(b) If you have an existing affected source, you must comply with the standards in this subpart no later than January 10, 2011.

(c) If you have an existing affected source that becomes subject to the control requirements in this subpart because of an increase in the monthly throughput, as specified in [§ 63.11111\(c\)](#) or [§ 63.11111\(d\)](#), you must comply with the standards in this subpart no later than 3 years after the affected source becomes subject to the control requirements in this subpart.

(d) If you have a new or reconstructed affected source and you are complying with Table 1 to this subpart, you must comply according to [paragraphs \(d\)\(1\)](#) and [\(2\)](#) of this section.

(1) If you start up your affected source from November 9, 2006 to September 23, 2008, you must comply no later than September 23, 2008.

(2) If you start up your affected source after September 23, 2008, you must comply upon startup of your affected source.

(e) The initial compliance demonstration test required under [§ 63.11120\(a\)\(1\)](#) and [\(2\)](#) must be conducted as specified in [paragraphs \(e\)\(1\)](#) and [\(2\)](#) of this section.

(1) If you have a new or reconstructed affected source, you must conduct the initial compliance test upon installation of the complete vapor balance system.

(2) If you have an existing affected source, you must conduct the initial compliance test as specified in [paragraphs \(e\)\(2\)\(i\)](#) or [\(e\)\(2\)\(ii\)](#) of this section.

(i) For vapor balance systems installed on or before December 15, 2009, you must test no later than 180 days after the applicable compliance date specified in [paragraphs \(b\)](#) or [\(c\)](#) of this section.

(ii) For vapor balance systems installed after December 15, 2009, you must test upon installation of the complete vapor balance system.

(f) If your GDF is subject to the control requirements in this subpart only because it loads gasoline into fuel tanks other than those in motor vehicles, as defined in [§ 63.11132](#), you must comply with the standards in this subpart as specified in [paragraphs \(f\)\(1\)](#) or [\(f\)\(2\)](#) of this section.

(1) If your GDF is an existing facility, you must comply by January 24, 2014.

(2) If your GDF is a new or reconstructed facility, you must comply by the dates specified in [paragraphs \(f\)\(2\)\(i\)](#) and [\(ii\)](#) of this section.

(i) If you start up your GDF after December 15, 2009, but before January 24, 2011, you must comply no later than January 24, 2011.

(ii) If you start up your GDF after January 24, 2011, you must comply upon startup of your GDF.

[[73 FR 1945](#), Jan. 10, 2008, as amended at [73 FR 35944](#), June 25, 2008; [76 FR 4181](#), Jan. 24, 2011]

## **Emission Limitations and Management Practices**

### **§ 63.11115 What are my general duties to minimize emissions?**

Each owner or operator of an affected source under this subpart must comply with the requirements of [paragraphs \(a\)](#) and [\(b\)](#) of this section.

(a) You must, at all times, operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

(b) You must keep applicable records and submit reports as specified in [§ 63.11125\(d\)](#) and [§ 63.11126\(b\)](#).

[[76 FR 4182](#), Jan. 24, 2011]

### **§ 63.11116 Requirements for facilities with monthly throughput of less than 10,000 gallons of gasoline.**

(a) You must not allow gasoline to be handled in a manner that would result in vapor releases to the atmosphere for extended periods of time. Measures to be taken include, but are not limited to, the following:

(1) Minimize gasoline spills;

(2) Clean up spills as expeditiously as practicable;

(3) Cover all open gasoline containers and all gasoline storage tank fill-pipes with a gasketed seal when not in use;

(4) Minimize gasoline sent to open waste collection systems that collect and transport gasoline to reclamation and recycling devices, such as oil/water separators.

(b) You are not required to submit notifications or reports as specified in [§ 63.11125](#), [§ 63.11126](#), or [subpart A of this part](#), but you must have records available within 24 hours of a request by the Administrator to document your gasoline throughput.

(c) You must comply with the requirements of this subpart by the applicable dates specified in [§ 63.11113](#).

(d) Portable gasoline containers that meet the requirements of [40 CFR part 59, subpart F](#), are considered acceptable for compliance with [paragraph \(a\)\(3\)](#) of this section.

[[73 FR 1945](#), Jan. 10, 2008, as amended at [76 FR 4182](#), Jan. 24, 2011]

**§ 63.11117 Requirements for facilities with monthly throughput of 10,000 gallons of gasoline or more.**

(a) You must comply with the requirements in section [§ 63.11116\(a\)](#).

(b) Except as specified in [paragraph \(c\)](#) of this section, you must only load gasoline into storage tanks at your facility by utilizing submerged filling, as defined in [§ 63.11132](#), and as specified in [paragraphs \(b\)\(1\)](#), [\(b\)\(2\)](#), or [\(b\)\(3\)](#) of this section. The applicable distances in paragraphs (b)(1) and (2) shall be measured from the point in the opening of the submerged fill pipe that is the greatest distance from the bottom of the storage tank.

(1) Submerged fill pipes installed on or before November 9, 2006, must be no more than 12 inches from the bottom of the tank.

(2) Submerged fill pipes installed after November 9, 2006, must be no more than 6 inches from the bottom of the tank.

(3) Submerged fill pipes not meeting the specifications of [paragraphs \(b\)\(1\)](#) or [\(b\)\(2\)](#) of this section are allowed if the owner or operator can demonstrate that the liquid level in the tank is always above the entire opening of the fill pipe. Documentation providing such demonstration

must be made available for inspection by the Administrator's delegated representative during the course of a site visit.

(c) Gasoline storage tanks with a capacity of less than 250 gallons are not required to comply with the submerged fill requirements in [paragraph \(b\)](#) of this section, but must comply only with all of the requirements in [§ 63.11116](#).

(d) You must have records available within 24 hours of a request by the Administrator to document your gasoline throughput.

(e) You must submit the applicable notifications as required under [§ 63.11124\(a\)](#).

(f) You must comply with the requirements of this subpart by the applicable dates contained in [§ 63.11113](#).

[[73 FR 1945](#), Jan. 10, 2008, as amended at [73 FR 12276](#), Mar. 7, 2008; [76 FR 4182](#), Jan. 24, 2011]

**§ 63.11118 Requirements for facilities with monthly throughput of 100,000 gallons of gasoline or more.**

(a) You must comply with the requirements in [§§ 63.11116\(a\)](#) and [63.11117\(b\)](#).

(b) Except as provided in [paragraph \(c\)](#) of this section, you must meet the requirements in either paragraph (b)(1) or [paragraph \(b\)\(2\)](#) of this section.

(1) Each management practice in Table 1 to this subpart that applies to your GDF.

(2) If, prior to January 10, 2008, you satisfy the requirements in both [paragraphs \(b\)\(2\)\(i\)](#) and [\(ii\)](#) of this section, you will be deemed in compliance with this subsection.

(i) You operate a vapor balance system at your GDF that meets the requirements of either paragraph (b)(2)(i)(A) or [paragraph \(b\)\(2\)\(i\)\(B\)](#) of this section.

(A) Achieves emissions reduction of at least 90 percent.

(B) Operates using management practices at least as stringent as those in Table 1 to this subpart.

(ii) Your gasoline dispensing facility is in compliance with an enforceable State, local, or tribal rule or permit that contains requirements of either paragraph (b)(2)(i)(A) or [paragraph \(b\)\(2\)\(i\)\(B\)](#) of this section.

(c) The emission sources listed in [paragraphs \(c\)\(1\)](#) through [\(3\)](#) of this section are not required to comply with the control requirements in [paragraph \(b\)](#) of this section, but must comply with the requirements in [§ 63.11117](#).

- (1) Gasoline storage tanks with a capacity of less than 250 gallons that are constructed after January 10, 2008.
- (2) Gasoline storage tanks with a capacity of less than 2,000 gallons that were constructed before January 10, 2008.
- (3) Gasoline storage tanks equipped with floating roofs, or the equivalent.
- (d) Cargo tanks unloading at GDF must comply with the management practices in Table 2 to this subpart.
- (e) You must comply with the applicable testing requirements contained in [§ 63.11120](#).
- (f) You must submit the applicable notifications as required under [§ 63.11124](#).
- (g) You must keep records and submit reports as specified in [§§ 63.11125](#) and [63.11126](#).
- (h) You must comply with the requirements of this subpart by the applicable dates contained in [§ 63.11113](#).

[[73 FR 1945](#), Jan. 10, 2008, as amended at [73 FR 12276](#), Mar. 7, 2008]

## **Testing and Monitoring Requirements**

### **§ 63.11120 What testing and monitoring requirements must I meet?**

- (a) Each owner or operator, at the time of installation, as specified in [§ 63.11113\(e\)](#), of a vapor balance system required under [§ 63.11118\(b\)\(1\)](#), and every 3 years thereafter, must comply with the requirements in [paragraphs \(a\)\(1\)](#) and [\(2\)](#) of this section.
  - (1) You must demonstrate compliance with the leak rate and cracking pressure requirements, specified in item 1(g) of Table 1 to this subpart, for pressure-vacuum vent valves installed on your gasoline storage tanks using the test methods identified in [paragraph \(a\)\(1\)\(i\)](#) or [paragraph \(a\)\(1\)\(ii\)](#) of this section.
    - (i) California Air Resources Board Vapor Recovery Test Procedure TP-201.1E,—Leak Rate and Cracking Pressure of Pressure/Vacuum Vent Valves, adopted October 8, 2003 (incorporated by reference, see [§ 63.14](#)).
    - (ii) Use alternative test methods and procedures in accordance with the alternative test method requirements in [§ 63.7\(f\)](#).
  - (2) You must demonstrate compliance with the static pressure performance requirement specified in item 1(h) of Table 1 to this subpart for your vapor balance system by conducting a static pressure test on your gasoline storage tanks using the test methods identified in [paragraphs \(a\)\(2\)\(i\)](#), [\(a\)\(2\)\(ii\)](#), or [\(a\)\(2\)\(iii\)](#) of this section.



- (i) California Air Resources Board Vapor Recovery Test Procedure TP-201.3,—Determination of 2-Inch WC Static Pressure Performance of Vapor Recovery Systems of Dispensing Facilities, adopted April 12, 1996, and amended March 17, 1999 (incorporated by reference, see [§ 63.14](#)).
- (ii) Use alternative test methods and procedures in accordance with the alternative test method requirements in [§ 63.7\(f\)](#).
- (iii) Bay Area Air Quality Management District Source Test Procedure ST-30—Static Pressure Integrity Test—Underground Storage Tanks, adopted November 30, 1983, and amended December 21, 1994 (incorporated by reference, *see* [§ 63.14](#)).
- (b) Each owner or operator choosing, under the provisions of [§ 63.6\(g\)](#), to use a vapor balance system other than that described in Table 1 to this subpart must demonstrate to the Administrator or delegated authority under paragraph [§ 63.11131\(a\) of this subpart](#), the equivalency of their vapor balance system to that described in Table 1 to this subpart using the procedures specified in [paragraphs \(b\)\(1\) through \(3\)](#) of this section.
- (1) You must demonstrate initial compliance by conducting an initial performance test on the vapor balance system to demonstrate that the vapor balance system achieves 95 percent reduction using the California Air Resources Board Vapor Recovery Test Procedure TP-201.1,—Volumetric Efficiency for Phase I Vapor Recovery Systems, adopted April 12, 1996, and amended February 1, 2001, and October 8, 2003, (incorporated by reference, see [§ 63.14](#)).
- (2) You must, during the initial performance test required under [paragraph \(b\)\(1\)](#) of this section, determine and document alternative acceptable values for the leak rate and cracking pressure requirements specified in item 1(g) of Table 1 to this subpart and for the static pressure performance requirement in item 1(h) of Table 1 to this subpart.
- (3) You must comply with the testing requirements specified in [paragraph \(a\)](#) of this section.
- (c) Conduct of performance tests. Performance tests conducted for this subpart shall be conducted under such conditions as the Administrator specifies to the owner or operator based on representative performance (*i.e.*, performance based on normal operating conditions) of the affected source. Upon request, the owner or operator shall make available to the Administrator such records as may be necessary to determine the conditions of performance tests.
- (d) Owners and operators of gasoline cargo tanks subject to the provisions of Table 2 to this subpart must conduct annual certification testing according to the vapor tightness testing requirements found in [§ 63.11092\(f\)](#).

[[73 FR 1945](#), Jan. 10, 2008, as amended at [76 FR 4182](#), Jan. 24, 2011]

## **Notifications, Records, and Reports**

### **§ 63.11124 What notifications must I submit and when?**

(a) Each owner or operator subject to the control requirements in [§ 63.11117](#) must comply with [paragraphs \(a\)\(1\)](#) through [\(3\)](#) of this section.

(1) You must submit an Initial Notification that you are subject to this subpart by May 9, 2008, or no later than 120 days after the source becomes subject to this subpart, whichever is later, or at the time you become subject to the control requirements in [§ 63.11117](#), unless you meet the requirements in [paragraph \(a\)\(3\)](#) of this section. If your affected source is subject to the control requirements in [§ 63.11117](#) only because it loads gasoline into fuel tanks other than those in motor vehicles, as defined in [§ 63.11132](#), you must submit the Initial Notification by May 24, 2011, or no later than 120 days after the source becomes subject to this subpart, whichever is later. The Initial Notification must contain the information specified in [paragraphs \(a\)\(1\)\(i\)](#) through [\(iii\)](#) of this section. The notification must be submitted to the applicable EPA Regional office and delegated state authority as specified in [§ 63.13](#).

(i) The name and address of the owner and the operator.

(ii) The address (i.e., physical location) of the GDF.

(iii) A statement that the notification is being submitted in response to this subpart and identifying the requirements in paragraphs (a) through (c) of [§ 63.11117](#) that apply to you.

(2) You must submit a Notification of Compliance Status to the applicable EPA Regional Office and the delegated State authority, as specified in [§ 63.13](#), within 60 days of the applicable compliance date specified in [§ 63.11113](#), unless you meet the requirements in [paragraph \(a\)\(3\)](#) of this section. The Notification of Compliance Status must be signed by a responsible official who must certify its accuracy, must indicate whether the source has complied with the requirements of this subpart, and must indicate whether the facilities' monthly throughput is calculated based on the volume of gasoline loaded into all storage tanks or on the volume of gasoline dispensed from all storage tanks. If your facility is in compliance with the requirements of this subpart at the time the Initial Notification required under [paragraph \(a\)\(1\)](#) of this section is due, the Notification of Compliance Status may be submitted in lieu of the Initial Notification provided it contains the information required under [paragraph \(a\)\(1\)](#) of this section.

(3) If, prior to January 10, 2008, you are operating in compliance with an enforceable State, local, or tribal rule or permit that requires submerged fill as specified in [§ 63.11117\(b\)](#), you are not required to submit an Initial Notification or a Notification of Compliance Status under [paragraph \(a\)\(1\)](#) or [paragraph \(a\)\(2\)](#) of this section.

(b) Each owner or operator subject to the control requirements in [§ 63.11118](#) must comply with [paragraphs \(b\)\(1\)](#) through [\(5\)](#) of this section.

(1) You must submit an Initial Notification that you are subject to this subpart by May 9, 2008, or no later than 120 days after the source becomes subject to this subpart, whichever is later, or at

the time you become subject to the control requirements in [§ 63.11118](#). If your affected source is subject to the control requirements in [§ 63.11118](#) only because it loads gasoline into fuel tanks other than those in motor vehicles, as defined in [§ 63.11132](#), you must submit the Initial Notification by May 24, 2011, or no later than 120 days after the source becomes subject to this subpart, whichever is later. The Initial Notification must contain the information specified in [paragraphs \(b\)\(1\)\(i\)](#) through [\(iii\)](#) of this section. The notification must be submitted to the applicable EPA Regional office and delegated state authority as specified in [§ 63.13](#).

(i) The name and address of the owner and the operator.

(ii) The address (i.e., physical location) of the GDF.

(iii) A statement that the notification is being submitted in response to this subpart and identifying the requirements in paragraphs (a) through (c) of [§ 63.11118](#) that apply to you.

(2) You must submit a Notification of Compliance Status to the applicable EPA Regional Office and the delegated State authority, as specified in [§ 63.13](#), in accordance with the schedule specified in [§ 63.9\(h\)](#). The Notification of Compliance Status must be signed by a responsible official who must certify its accuracy, must indicate whether the source has complied with the requirements of this subpart, and must indicate whether the facility's throughput is determined based on the volume of gasoline loaded into all storage tanks or on the volume of gasoline dispensed from all storage tanks. If your facility is in compliance with the requirements of this subpart at the time the Initial Notification required under [paragraph \(b\)\(1\)](#) of this section is due, the Notification of Compliance Status may be submitted in lieu of the Initial Notification provided it contains the information required under [paragraph \(b\)\(1\)](#) of this section.

(3) If, prior to January 10, 2008, you satisfy the requirements in both [paragraphs \(b\)\(3\)\(i\)](#) and [\(ii\)](#) of this section, you are not required to submit an Initial Notification or a Notification of Compliance Status under [paragraph \(b\)\(1\)](#) or [paragraph \(b\)\(2\)](#) of this subsection.

(i) You operate a vapor balance system at your gasoline dispensing facility that meets the requirements of either [paragraphs \(b\)\(3\)\(i\)\(A\)](#) or [\(b\)\(3\)\(i\)\(B\)](#) of this section.

(A) Achieves emissions reduction of at least 90 percent.

(B) Operates using management practices at least as stringent as those in Table 1 to this subpart.

(ii) Your gasoline dispensing facility is in compliance with an enforceable State, local, or tribal rule or permit that contains requirements of either [paragraphs \(b\)\(3\)\(i\)\(A\)](#) or [\(b\)\(3\)\(i\)\(B\)](#) of this section.

(4) You must submit a Notification of Performance Test, as specified in [§ 63.9\(e\)](#), prior to initiating testing required by [§ 63.11120\(a\)](#) and [\(b\)](#).

(5) You must submit additional notifications specified in [§ 63.9](#), as applicable.

[[73 FR 1945](#), Jan. 10, 2008, as amended at [73 FR 12276](#), Mar. 7, 2008; [76 FR 4182](#), Jan. 24, 2011; [85 FR 73919](#), Nov. 19, 2020]

### **§ 63.11125 What are my recordkeeping requirements?**

(a) Each owner or operator subject to the management practices in [§ 63.11118](#) must keep records of all tests performed under [§ 63.11120\(a\)](#) and [\(b\)](#).

(b) Records required under [paragraph \(a\)](#) of this section shall be kept for a period of 5 years and shall be made available for inspection by the Administrator's delegated representatives during the course of a site visit.

(c) Each owner or operator of a gasoline cargo tank subject to the management practices in Table 2 to this subpart must keep records documenting vapor tightness testing for a period of 5 years. Documentation must include each of the items specified in [§ 63.11094\(b\)\(2\)\(i\)](#) through [\(viii\)](#). Records of vapor tightness testing must be retained as specified in either paragraph (c)(1) or [paragraph \(c\)\(2\)](#) of this section.

(1) The owner or operator must keep all vapor tightness testing records with the cargo tank.

(2) As an alternative to keeping all records with the cargo tank, the owner or operator may comply with the requirements of [paragraphs \(c\)\(2\)\(i\)](#) and [\(ii\)](#) of this section.

(i) The owner or operator may keep records of only the most recent vapor tightness test with the cargo tank, and keep records for the previous 4 years at their office or another central location.

(ii) Vapor tightness testing records that are kept at a location other than with the cargo tank must be instantly available (*e.g.*, via e-mail or facsimile) to the Administrator's delegated representative during the course of a site visit or within a mutually agreeable time frame. Such records must be an exact duplicate image of the original paper copy record with certifying signatures.

(d) Each owner or operator of an affected source under this subpart shall keep records as specified in [paragraphs \(d\)\(1\)](#) and [\(2\)](#) of this section.

(1) Records of the occurrence and duration of each malfunction of operation (*i.e.*, process equipment) or the air pollution control and monitoring equipment.

(2) Records of actions taken during periods of malfunction to minimize emissions in accordance with [§ 63.11115\(a\)](#), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.

[[73 FR 1945](#), Jan. 10, 2008, as amended at [76 FR 4183](#), Jan. 24, 2011]

### **§ 63.11126 What are my reporting requirements?**

(a) Each owner or operator subject to the management practices in [§ 63.11118](#) shall report to the Administrator the results of all volumetric efficiency tests required under [§ 63.11120\(b\)](#). Reports submitted under this paragraph must be submitted within 180 days of the completion of the performance testing.

(b) Each owner or operator of an affected source under this subpart shall report, by March 15 of each year, the number, duration, and a brief description of each type of malfunction which occurred during the previous calendar year and which caused or may have caused any applicable emission limitation to be exceeded. The report must also include a description of actions taken by an owner or operator during a malfunction of an affected source to minimize emissions in accordance with [§ 63.11115\(a\)](#), including actions taken to correct a malfunction. No report is necessary for a calendar year in which no malfunctions occurred.

[[76 FR 4183](#), Jan. 24, 2011]

## **Other Requirements and Information**

### **§ 63.11130 What parts of the General Provisions apply to me?**

Table 3 to this subpart shows which parts of the General Provisions apply to you.

### **§ 63.11131 Who implements and enforces this subpart?**

(a) This subpart can be implemented and enforced by the U.S. EPA or a delegated authority such as the applicable State, local, or tribal agency. If the U.S. EPA Administrator has delegated authority to a State, local, or tribal agency, then that agency, in addition to the U.S. EPA, has the authority to implement and enforce this subpart. Contact the applicable U.S. EPA Regional Office to find out if implementation and enforcement of this subpart is delegated to a State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under [subpart E of this part](#), the authorities contained in [paragraph \(c\)](#) of this section are retained by the Administrator of U.S. EPA and cannot be transferred to the State, local, or tribal agency.

(c) The authorities that cannot be delegated to State, local, or tribal agencies are as specified in [paragraphs \(c\)\(1\)](#) through [\(3\)](#) of this section.

(1) Approval of alternatives to the requirements in [§§ 63.11116](#) through [63.11118](#) and [63.11120](#).

(2) Approval of major alternatives to test methods under [§ 63.7\(e\)\(2\)\(ii\)](#) and [\(f\)](#), as defined in [§ 63.90](#), and as required in this subpart.

(3) Approval of major alternatives to recordkeeping and reporting under [§ 63.10\(f\)](#), as defined in [§ 63.90](#), and as required in this subpart.

### **§ 63.11132 What definitions apply to this subpart?**

As used in this subpart, all terms not defined herein shall have the meaning given them in the Clean Air Act (CAA), or in subparts A and BBBBBB of this part. For purposes of this subpart, definitions in this section supersede definitions in other parts or subparts.

*Dual-point vapor balance system* means a type of vapor balance system in which the storage tank is equipped with an entry port for a gasoline fill pipe and a separate exit port for a vapor connection.

*Gasoline* means any petroleum distillate or petroleum distillate/alcohol blend having a Reid vapor pressure of 27.6 kilopascals or greater, which is used as a fuel for internal combustion engines.

*Gasoline cargo tank* means a delivery tank truck or railcar which is loading or unloading gasoline, or which has loaded or unloaded gasoline on the immediately previous load.

*Gasoline dispensing facility (GDF)* means any stationary facility which dispenses gasoline into the fuel tank of a motor vehicle, motor vehicle engine, nonroad vehicle, or nonroad engine, including a nonroad vehicle or nonroad engine used solely for competition. These facilities include, but are not limited to, facilities that dispense gasoline into on- and off-road, street, or highway motor vehicles, lawn equipment, boats, test engines, landscaping equipment, generators, pumps, and other gasoline-fueled engines and equipment.

*Monthly throughput* means the total volume of gasoline that is loaded into, or dispensed from, all gasoline storage tanks at each GDF during a month. Monthly throughput is calculated by summing the volume of gasoline loaded into, or dispensed from, all gasoline storage tanks at each GDF during the current day, plus the total volume of gasoline loaded into, or dispensed from, all gasoline storage tanks at each GDF during the previous 364 days, and then dividing that sum by 12.

*Motor vehicle* means any self-propelled vehicle designed for transporting persons or property on a street or highway.

*Nonroad engine* means an internal combustion engine (including the fuel system) that is not used in a motor vehicle or a vehicle used solely for competition, or that is not subject to standards promulgated under section 7411 of this title or section 7521 of this title.

*Nonroad vehicle* means a vehicle that is powered by a nonroad engine, and that is not a motor vehicle or a vehicle used solely for competition.

*Submerged filling* means, for the purposes of this subpart, the filling of a gasoline storage tank through a submerged fill pipe whose discharge is no more than the applicable distance specified

in [§ 63.11117\(b\)](#) from the bottom of the tank. Bottom filling of gasoline storage tanks is included in this definition.

*Vapor balance system* means a combination of pipes and hoses that create a closed system between the vapor spaces of an unloading gasoline cargo tank and a receiving storage tank such that vapors displaced from the storage tank are transferred to the gasoline cargo tank being unloaded.

*Vapor-tight* means equipment that allows no loss of vapors. Compliance with vapor-tight requirements can be determined by checking to ensure that the concentration at a potential leak source is not equal to or greater than 100 percent of the Lower Explosive Limit when measured with a combustible gas detector, calibrated with propane, at a distance of 1 inch from the source.

*Vapor-tight gasoline cargo tank* means a gasoline cargo tank which has demonstrated within the 12 preceding months that it meets the annual certification test requirements in [§ 63.11092\(f\) of this part](#).

[[73 FR 1945](#), Jan. 10, 2008, as amended at [76 FR 4183](#), Jan. 24, 2011]

**Table 1 to Subpart CCCCCC of Part 63—Applicability Criteria and Management Practices for Gasoline Dispensing Facilities With Monthly Throughput of 100,000 Gallons of Gasoline or More<sup>1</sup>**

If you own or operate	Then you must
1. A new, reconstructed, or existing GDF subject to <a href="#">§ 63.11118</a>	Install and operate a vapor balance system on your gasoline storage tanks that meets the design criteria in paragraphs (a) through (h).
	(a) All vapor connections and lines on the storage tank shall be equipped with closures that seal upon disconnect.
	(b) The vapor line from the gasoline storage tank to the gasoline cargo tank shall be vapor-tight, as defined in <a href="#">§ 63.11132</a> .
	(c) The vapor balance system shall be designed such that the pressure in the tank truck does not exceed 18 inches water pressure or 5.9 inches water vacuum during product transfer.
	(d) The vapor recovery and product adaptors, and the method of connection with the delivery elbow, shall be designed so as

If you own or operate	Then you must
	to prevent the over-tightening or loosening of fittings during normal delivery operations.
	(e) If a gauge well separate from the fill tube is used, it shall be provided with a submerged drop tube that extends the same distance from the bottom of the storage tank as specified in <a href="#">§ 63.11117(b)</a> .
	(f) Liquid fill connections for all systems shall be equipped with vapor-tight caps.
	(g) Pressure/vacuum (PV) vent valves shall be installed on the storage tank vent pipes. The pressure specifications for PV vent valves shall be: a positive pressure setting of 2.5 to 6.0 inches of water and a negative pressure setting of 6.0 to 10.0 inches of water. The total leak rate of all PV vent valves at an affected facility, including connections, shall not exceed 0.17 cubic foot per hour at a pressure of 2.0 inches of water and 0.63 cubic foot per hour at a vacuum of 4 inches of water.
	(h) The vapor balance system shall be capable of meeting the static pressure performance requirement of the following equation:
	$P_f = 2e^{-500.887/v}$
	Where:
	$P_f$ = Minimum allowable final pressure, inches of water.
	$v$ = Total ullage affected by the test, gallons.
	$e$ = Dimensionless constant equal to approximately 2.718.
	2 = The initial pressure, inches water.
2. A new or reconstructed GDF, or any storage tank(s) constructed after November 9,	Equip your gasoline storage tanks with a dual-point vapor balance system, as defined in <a href="#">§ 63.11132</a> , and comply with the requirements of item 1 in this Table.



If you own or operate	Then you must
2006, at an existing affected facility subject to <a href="#">§ 63.11118</a>	
<sup>1</sup> The management practices specified in this Table are not applicable if you are complying with the requirements in <a href="#">§ 63.11118(b)(2)</a> , except that if you are complying with the requirements in <a href="#">§ 63.11118(b)(2)(i)(B)</a> , you must operate using management practices at least as stringent as those listed in this Table.	

[[73 FR 1945](#), Jan. 10, 2008, as amended at [73 FR 35944](#), June 25, 2008; [76 FR 4184](#), Jan. 24, 2011]

**Table 2 to Subpart CCCCCC of Part 63—Applicability Criteria and Management Practices for Gasoline Cargo Tanks Unloading at Gasoline Dispensing Facilities With Monthly Throughput of 100,000 Gallons of Gasoline or More**

If you own or operate	Then you must
A gasoline cargo tank	Not unload gasoline into a storage tank at a GDF subject to the control requirements in this subpart unless the following conditions are met:
	(i) All hoses in the vapor balance system are properly connected,
	(ii) The adapters or couplers that attach to the vapor line on the storage tank have closures that seal upon disconnect,
	(iii) All vapor return hoses, couplers, and adapters used in the gasoline delivery are vapor-tight,
	(iv) All tank truck vapor return equipment is compatible in size and forms a vapor-tight connection with the vapor balance equipment on the GDF storage tank, and
	(v) All hatches on the tank truck are closed and securely fastened.
	(vi) The filling of storage tanks at GDF shall be limited to unloading from vapor-tight gasoline cargo tanks. Documentation that the cargo tank has met the specifications of EPA Method 27 shall be carried with the cargo tank, as specified in <a href="#">§ 63.11125(c)</a> .

[[73 FR 1945](#), Jan. 10, 2008, as amended at [76 FR 4184](#), Jan. 24, 2011]

**Table 3 to Subpart CCCCCC of Part 63—Applicability of General Provisions**

<b>Citation</b>	<b>Subject</b>	<b>Brief description</b>	<b>Applies to subpart CCCCCC</b>
§ 63.1	Applicability	Initial applicability determination; applicability after standard established; permit requirements; extensions, notifications	Yes, specific requirements given in <a href="#">§ 63.11111</a> .
§ 63.1(c)(2)	Title V Permit	Requirements for obtaining a title V permit from the applicable permitting authority	Yes, <a href="#">§ 63.11111(f)</a> of subpart CCCCCC exempts identified area sources from the obligation to obtain title V operating permits.
§ 63.2	Definitions	Definitions for part 63 standards	Yes, additional definitions in <a href="#">§ 63.11132</a> .
§ 63.3	Units and Abbreviations	Units and abbreviations for part 63 standards	Yes.
§ 63.4	Prohibited Activities and Circumvention	Prohibited activities; Circumvention, severability	Yes.
§ 63.5	Construction/Reconstruction	Applicability; applications; approvals	Yes, except that these notifications are not required for facilities

Citation	Subject	Brief description	Applies to subpart CCCCCC
			subject to <a href="#">§ 63.11116</a>
§ 63.6(a)	Compliance with Standards/Operation & Maintenance—Applicability	General Provisions apply unless compliance extension; General Provisions apply to area sources that become major	Yes.
§ 63.6(b)(1)-(4)	Compliance Dates for New and Reconstructed Sources	Standards apply at effective date; 3 years after effective date; upon startup; 10 years after construction or reconstruction commences for CAA section 112(f)	Yes.
§ 63.6(b)(5)	Notification	Must notify if commenced construction or reconstruction after proposal	Yes.
§ 63.6(b)(6)	[Reserved]		
§ 63.6(b)(7)	Compliance Dates for New and Reconstructed Area Sources That Become Major	Area sources that become major must comply with major source standards immediately upon becoming major, regardless of whether required to comply when they were an area source	No.
§ 63.6(c)(1)-(2)	Compliance Dates for Existing Sources	Comply according to date in this subpart, which must be no later than 3 years after effective date; for CAA section 112(f) standards, comply within 90 days of effective date unless compliance extension	No, <a href="#">§ 63.11113</a> specifies the compliance dates.

Citation	Subject	Brief description	Applies to subpart CCCCCC
§ 63.6(c)(3)-(4)	[Reserved]		
§ 63.6(c)(5)	Compliance Dates for Existing Area Sources That Become Major	Area sources That become major must comply with major source standards by date indicated in this subpart or by equivalent time period (e.g., 3 years)	No.
§ 63.6(d)	[Reserved]		
63.6(e)(1)(i)	General duty to minimize emissions	Operate to minimize emissions at all times; information Administrator will use to determine if operation and maintenance requirements were met.	No. <i>See</i> <a href="#">§ 63.11115</a> for general duty requirement.
63.6(e)(1)(ii)	Requirement to correct malfunctions ASAP	Owner or operator must correct malfunctions as soon as possible.	No.
§ 63.6(e)(2)	[Reserved]		
§ 63.6(e)(3)	Startup, Shutdown, and Malfunction (SSM) Plan	Requirement for SSM plan; content of SSM plan; actions during SSM	No.
§ 63.6(f)(1)	Compliance Except During SSM	You must comply with emission standards at all times except during SSM	No.
§ 63.6(f)(2)-(3)	Methods for Determining Compliance	Compliance based on performance test, operation and maintenance plans, records, inspection	Yes.

Citation	Subject	Brief description	Applies to subpart CCCCCC
§ 63.6(g)(1)-(3)	Alternative Standard	Procedures for getting an alternative standard	Yes.
§ 63.6(h)(1)	Compliance with Opacity/Visible Emission (VE) Standards	You must comply with opacity/VE standards at all times except during SSM	No.
§ 63.6(h)(2)(i)	Determining Compliance with Opacity/VE Standards	If standard does not State test method, use EPA Method 9 for opacity in appendix A of <a href="#">part 60 of this chapter</a> and EPA Method 22 for VE in appendix A of <a href="#">part 60 of this chapter</a>	No.
§ 63.6(h)(2)(ii)	[Reserved]		
§ 63.6(h)(2)(iii)	Using Previous Tests To Demonstrate Compliance With Opacity/VE Standards	Criteria for when previous opacity/VE testing can be used to show compliance with this subpart	No.
§ 63.6(h)(3)	[Reserved]		
§ 63.6(h)(4)	Notification of Opacity/VE Observation Date	Must notify Administrator of anticipated date of observation	No.
§ 63.6(h)(5)(i), (iii)-(v)	Conducting Opacity/VE Observations	Dates and schedule for conducting opacity/VE observations	No.
§ 63.6(h)(5)(ii)	Opacity Test Duration and Averaging Times	Must have at least 3 hours of observation with 30 6-minute averages	No.
§ 63.6(h)(6)	Records of Conditions During Opacity/VE Observations	Must keep records available and allow Administrator to inspect	No.

Citation	Subject	Brief description	Applies to subpart CCCCCC
§ 63.6(h)(7)(i)	Report Continuous Opacity Monitoring System (COMS) Monitoring Data From Performance Test	Must submit COMS data with other performance test data	No.
§ 63.6(h)(7)(ii)	Using COMS Instead of EPA Method 9	Can submit COMS data instead of EPA Method 9 results even if rule requires EPA Method 9 in appendix A of <a href="#">part 60 of this chapter</a> , but must notify Administrator before performance test	No.
§ 63.6(h)(7)(iii)	Averaging Time for COMS During Performance Test	To determine compliance, must reduce COMS data to 6-minute averages	No.
§ 63.6(h)(7)(iv)	COMS Requirements	Owner/operator must demonstrate that COMS performance evaluations are conducted according to <a href="#">§ 63.8(e)</a> ; COMS are properly maintained and operated according to <a href="#">§ 63.8(c)</a> and data quality as <a href="#">§ 63.8(d)</a>	No.
§ 63.6(h)(7)(v)	Determining Compliance with Opacity/VE Standards	COMS is probable but not conclusive evidence of compliance with opacity standard, even if EPA Method 9 observation shows otherwise. Requirements for COMS to be probable evidence-proper maintenance, meeting Performance Specification 1 in appendix B of <a href="#">part 60 of this</a>	No.

Citation	Subject	Brief description	Applies to subpart CCCCCC
		<a href="#">chapter</a> , and data have not been altered	
§ 63.6(h)(8)	Determining Compliance with Opacity/VE Standards	Administrator will use all COMS, EPA Method 9 (in appendix A of <a href="#">part 60 of this chapter</a> ), and EPA Method 22 (in appendix A of <a href="#">part 60 of this chapter</a> ) results, as well as information about operation and maintenance to determine compliance	No.
§ 63.6(h)(9)	Adjusted Opacity Standard	Procedures for Administrator to adjust an opacity standard	No.
§ 63.6(i)(1)-(14)	Compliance Extension	Procedures and criteria for Administrator to grant compliance extension	Yes.
§ 63.6(j)	Presidential Compliance Exemption	President may exempt any source from requirement to comply with this subpart	Yes.
§ 63.7(a)(2)	Performance Test Dates	Dates for conducting initial performance testing; must conduct 180 days after compliance date	Yes.
§ 63.7(a)(3)	CAA Section 114 Authority	Administrator may require a performance test under CAA section 114 at any time	Yes.
§ 63.7(b)(1)	Notification of Performance Test	Must notify Administrator 60 days before the test	Yes.

Citation	Subject	Brief description	Applies to subpart CCCCCC
§ 63.7(b)(2)	Notification of Re-scheduling	If have to reschedule performance test, must notify Administrator of rescheduled date as soon as practicable and without delay	Yes.
§ 63.7(c)	Quality Assurance (QA)/Test Plan	Requirement to submit site-specific test plan 60 days before the test or on date Administrator agrees with; test plan approval procedures; performance audit requirements; internal and external QA procedures for testing	Yes.
§ 63.7(d)	Testing Facilities	Requirements for testing facilities	Yes.
63.7(e)(1)	Conditions for Conducting Performance Tests	Performance test must be conducted under representative conditions	No, <a href="#">§ 63.11120(c)</a> specifies conditions for conducting performance tests.
§ 63.7(e)(2)	Conditions for Conducting Performance Tests	Must conduct according to this subpart and EPA test methods unless Administrator approves alternative	Yes.
§ 63.7(e)(3)	Test Run Duration	Must have three test runs of at least 1 hour each; compliance is based on arithmetic mean of three runs; conditions when	Yes.



Citation	Subject	Brief description	Applies to subpart CCCCCC
		data from an additional test run can be used	
§ 63.7(f)	Alternative Test Method	Procedures by which Administrator can grant approval to use an intermediate or major change, or alternative to a test method	Yes.
§ 63.7(g)	Performance Test Data Analysis	Must include raw data in performance test report; must submit performance test data 60 days after end of test with the Notification of Compliance Status; keep data for 5 years	Yes.
§ 63.7(h)	Waiver of Tests	Procedures for Administrator to waive performance test	Yes.
§ 63.8(a)(1)	Applicability of Monitoring Requirements	Subject to all monitoring requirements in standard	Yes.
§ 63.8(a)(2)	Performance Specifications	Performance Specifications in appendix B of <a href="#">40 CFR part 60</a> apply	Yes.
§ 63.8(a)(3)	[Reserved]		
§ 63.8(a)(4)	Monitoring of Flares	Monitoring requirements for flares in <a href="#">§ 63.11</a> apply	Yes.
§ 63.8(b)(1)	Monitoring	Must conduct monitoring according to standard unless Administrator approves alternative	Yes.

Citation	Subject	Brief description	Applies to subpart CCCCCC
§ 63.8(b)(2)-(3)	Multiple Effluents and Multiple Monitoring Systems	Specific requirements for installing monitoring systems; must install on each affected source or after combined with another affected source before it is released to the atmosphere provided the monitoring is sufficient to demonstrate compliance with the standard; if more than one monitoring system on an emission point, must report all monitoring system results, unless one monitoring system is a backup	No.
§ 63.8(c)(1)	Monitoring System Operation and Maintenance	Maintain monitoring system in a manner consistent with good air pollution control practices	No.
§ 63.8(c)(1)(i)-(iii)	Operation and Maintenance of Continuous Monitoring Systems (CMS)	Must maintain and operate each CMS as specified in <a href="#">§ 63.6(e)(1)</a> ; must keep parts for routine repairs readily available; must develop a written SSM plan for CMS, as specified in <a href="#">§ 63.6(e)(3)</a>	No.
§ 63.8(c)(2)-(8)	CMS Requirements	Must install to get representative emission or parameter measurements; must verify operational status before or at performance test	No.
§ 63.8(d)	CMS Quality Control	Requirements for CMS quality control, including calibration, etc.; must keep quality control plan on record for 5 years; keep	No.

<b>Citation</b>	<b>Subject</b>	<b>Brief description</b>	<b>Applies to subpart CCCCCC</b>
		old versions for 5 years after revisions	
§ 63.8(e)	CMS Performance Evaluation	Notification, performance evaluation test plan, reports	No.
§ 63.8(f)(1)-(5)	Alternative Monitoring Method	Procedures for Administrator to approve alternative monitoring	No.
§ 63.8(f)(6)	Alternative to Relative Accuracy Test	Procedures for Administrator to approve alternative relative accuracy tests for continuous emissions monitoring system (CEMS)	No.
§ 63.8(g)	Data Reduction	COMS 6-minute averages calculated over at least 36 evenly spaced data points; CEMS 1 hour averages computed over at least 4 equally spaced data points; data that cannot be used in average	No.
§ 63.9(a)	Notification Requirements	Applicability and State delegation	Yes.
§ 63.9(b)(1)-(2), (4)-(5)	Initial Notifications	Submit notification within 120 days after effective date, or no later than 120 days after the source becomes subject to this subpart, whichever is later; notification of intent to construct/reconstruct, notification of commencement of construction/reconstruction,	Yes.

<b>Citation</b>	<b>Subject</b>	<b>Brief description</b>	<b>Applies to subpart CCCCCC</b>
		notification of startup; contents of each	
§ 63.9(c)	Request for Compliance Extension	Can request if cannot comply by date or if installed best available control technology or lowest achievable emission rate	Yes.
§ 63.9(d)	Notification of Special Compliance Requirements for New Sources	For sources that commence construction between proposal and promulgation and want to comply 3 years after effective date	Yes.
§ 63.9(e)	Notification of Performance Test	Notify Administrator 60 days prior	Yes.
§ 63.9(f)	Notification of VE/Opacity Test	Notify Administrator 30 days prior	No.
§ 63.9(g)	Additional Notifications when Using CMS	Notification of performance evaluation; notification about use of COMS data; notification that exceeded criterion for relative accuracy alternative	Yes, however, there are no opacity standards.
§ 63.9(h)(1)-(6)	Notification of Compliance Status	Contents due 60 days after end of performance test or other compliance demonstration, except for opacity/VE, which are due 30 days after; when to submit to Federal vs. State authority	Yes, however, there are no opacity standards.

Citation	Subject	Brief description	Applies to subpart CCCCCC
§ 63.9(i)	Adjustment of Submittal Deadlines	Procedures for Administrator to approve change when notifications must be submitted	Yes.
§ 63.9(j)	Change in Previous Information	Must submit within 15 days after the change	Yes.
§ 63.9(k)	Notifications	Electronic reporting procedures	Yes, only as specified in <a href="#">§ 63.9(j)</a> .
§ 63.10(a)	Recordkeeping/Reporting	Applies to all, unless compliance extension; when to submit to Federal vs. State authority; procedures for owners of more than one source	Yes.
§ 63.10(b)(1)	Recordkeeping/Reporting	General requirements; keep all records readily available; keep for 5 years	Yes.
§ 63.10(b)(2)(i)	Records related to SSM	Recordkeeping of occurrence and duration of startups and shutdowns	No.
§ 63.10(b)(2)(ii)	Records related to SSM	Recordkeeping of malfunctions	No. <i>See</i> <a href="#">§ 63.11125(d)</a> for recordkeeping of (1) occurrence and duration and (2) actions taken during malfunction.

<b>Citation</b>	<b>Subject</b>	<b>Brief description</b>	<b>Applies to subpart CCCCCC</b>
§ 63.10(b)(2)(iii)	Maintenance records	Recordkeeping of maintenance on air pollution control and monitoring equipment	Yes.
§ 63.10(b)(2)(iv)	Records Related to SSM	Actions taken to minimize emissions during SSM	No.
§ 63.10(b)(2)(v)	Records Related to SSM	Actions taken to minimize emissions during SSM	No.
§ 63.10(b)(2)(vi)-(xi)	CMS Records	Malfunctions, inoperative, out-of-control periods	No.
§ 63.10(b)(2)(xii)	Records	Records when under waiver	Yes.
§ 63.10(b)(2)(xiii)	Records	Records when using alternative to relative accuracy test	Yes.
§ 63.10(b)(2)(xiv)	Records	All documentation supporting Initial Notification and Notification of Compliance Status	Yes.
§ 63.10(b)(3)	Records	Applicability determinations	Yes.
§ 63.10(c)	Records	Additional records for CMS	No.
§ 63.10(d)(1)	General Reporting Requirements	Requirement to report	Yes.
§ 63.10(d)(2)	Report of Performance Test Results	When to submit to Federal or State authority	Yes.
§ 63.10(d)(3)	Reporting Opacity or VE Observations	What to report and when	No.

Citation	Subject	Brief description	Applies to subpart CCCCCC
§ 63.10(d)(4)	Progress Reports	Must submit progress reports on schedule if under compliance extension	Yes.
§ 63.10(d)(5)	SSM Reports	Contents and submission	No. <a href="#">See § 63.11126(b)</a> for malfunction reporting requirements.
§ 63.10(e)(1)-(2)	Additional CMS Reports	Must report results for each CEMS on a unit; written copy of CMS performance evaluation; two-three copies of COMS performance evaluation	No.
§ 63.10(e)(3)(i)-(iii)	Reports	Schedule for reporting excess emissions	No.
§ 63.10(e)(3)(iv)-(v)	Excess Emissions Reports	Requirement to revert to quarterly submission if there is an excess emissions and parameter monitor exceedances (now defined as deviations); provision to request semiannual reporting after compliance for 1 year; submit report by 30th day following end of quarter or calendar half; if there has not been an exceedance or excess emissions (now defined as deviations), report contents in a statement that there have been no deviations; must submit report containing all of the	No.

Citation	Subject	Brief description	Applies to subpart CCCCCC
		information in <a href="#">§§ 63.8(c)(7)-(8)</a> and <a href="#">63.10(c)(5)-(13)</a>	
§ 63.10(e)(3)(iv)-(v)	Excess Emissions Reports	Requirement to revert to quarterly submission if there is an excess emissions and parameter monitor exceedances (now defined as deviations); provision to request semiannual reporting after compliance for 1 year; submit report by 30th day following end of quarter or calendar half; if there has not been an exceedance or excess emissions (now defined as deviations), report contents in a statement that there have been no deviations; must submit report containing all of the information in <a href="#">§§ 63.8(c)(7)-(8)</a> and <a href="#">63.10(c)(5)-(13)</a>	No, <a href="#">§ 63.11130(K)</a> specifies excess emission events for this subpart.
§ 63.10(e)(3)(vi)-(viii)	Excess Emissions Report and Summary Report	Requirements for reporting excess emissions for CMS; requires all of the information in <a href="#">§§ 63.10(c)(5)-(13)</a> and <a href="#">63.8(c)(7)-(8)</a>	No.
§ 63.10(e)(4)	Reporting COMS Data	Must submit COMS data with performance test data	No.
§ 63.10(f)	Waiver for Recordkeeping/Reporting	Procedures for Administrator to waive	Yes.
§ 63.11(b)	Flares	Requirements for flares	No.



<b>Citation</b>	<b>Subject</b>	<b>Brief description</b>	<b>Applies to subpart CCCCC</b>
§ 63.12	Delegation	State authority to enforce standards	Yes.
§ 63.13	Addresses	Addresses where reports, notifications, and requests are sent	Yes.
§ 63.14	Incorporations by Reference	Test methods incorporated by reference	Yes.
§ 63.15	Availability of Information	Public and confidential information	Yes.

[[73 FR 1945](#), Jan. 10, 2008, as amended at [76 FR 4184](#), Jan. 24, 2011; [85 FR 73919](#), Nov. 19, 2020]