

ADEQ

ARKANSAS
Department of Environmental Quality

November 8, 2006

Mr. David Jurgens, P. E., Water and Wastewater Director
City of Fayetteville
1400 North Fox Hunter Road
Fayetteville, AR 72701

RE: NPDES Permit No. AR0020010, Paul R. Noland WWTP

Dear Mr. Jurgens:

In accordance with 40 CFR 122.63(a), Page 4 of Part III has been modified to reflect the correct monitoring frequency for the toxic pollutants in 40 CFR 122, Appendix D, Tables III and V (Once/Quarter instead of Once/Six months).

Please replace the old page (Page 4 of Part III) of the permit with the enclosed corrected page.

If there are any questions, please contact Allen Gilliam at (501) 682-0625.

Sincerely,



Martin Maner, P.E.
Chief, Water Division

MM:ag

Enclosure

cc: David Ramsey
Frank Esry
Enforcement Administrator
Central File

NPDES PERMIT FILE
NPDES # AR00 20010
AFIN # 72-00102

Permit PN

Correspondence

Technical Backup

Date Scanned
11/27/06 *st*

All specific prohibitions or limits developed under this requirement are deemed to be conditions of this permit. The specific prohibitions set out in 40 CFR Part 403.5(b) shall be enforced by the permittee unless modified under this provision.

- C. The permittee shall analyze the treatment facility influent and effluent for the presence of the toxic pollutants listed in 40 CFR 122 Appendix D (NPDES Application Testing Requirements) Table II at least **once per year** and the toxic pollutants in Table III at least **4/yr (once per quarter)**. If, based upon information available to the permittee, there is reason to suspect the presence of any toxic or hazardous pollutant listed in Table V, or any other pollutant, known or suspected to adversely affect treatment plant operation, receiving water quality, or solids disposal procedures, analysis for those pollutants shall be performed at least **4/yr (once per quarter)** on both the influent and effluent.
1. The influent and effluent samples collected shall be composite samples consisting of at least 12 aliquots collected at approximately equal intervals over a representative 24 hour period and composited according to flow. Sampling and analytical procedures shall be in accordance with guidelines established in 40 CFR 136. Where composite samples are inappropriate, due to sampling, holding time, or analytical constraints, at least four (4) grab samples, taken at equal intervals over a representative 24 hour period, shall be taken.
- D. The permittee shall prepare annually a list of Industrial Users which during the preceding twelve months were in significant noncompliance with applicable pretreatment requirements. For the purposes of this Part, significant noncompliance shall be determined based upon the more stringent of either criteria established at 40 CFR Part 403.8(f)(2)(vii) [rev. 7/24/90] or criteria established in the approved POTW pretreatment program. This list is to be published annually in the largest daily newspaper in the municipality during the month of **May**.

In addition, during the month of **May** the permittee shall submit an updated pretreatment program status report to ADEQ containing the following information:

1. An updated list of all significant industrial users. For each industrial user listed, the following information shall be included:
 - a. Standard Industrial Classification (SIC) code and the North American Industrial Classification System (NAICS) code and categorical determination.
 - b. Control document status. Whether the user has an effective control document, and the date such document was last issued, reissued, or