Facility ID: _____

ARKANSAS DEPARTMENT OF ENVIRONMENTAL QUALITY **UST COMPLIANCE INSPECTION CHECKLIST**

| A. Ownership of Tank(s) | | B. Location of Tank(s) | | | | | | | |
|--|------------------------|---|--------------|---|-----------|--------------------|------------|--|--|
| | | | | (If same as "Owner", check here: \Box) | | | | | |
| Owner Name (Corporation, Individual, Public Agency, or other entity) | | Facility Name or Company Site Identifier, as applicable | | | | | | | |
| | | 1 donity | | | | | | | |
| Street Address | | Street A | ddress or S | State Road, a | s applica | ble | | | |
| County | | County | | | | | | | |
| | | | | | | | | | |
| City, State Zip | | City (ne | arest), Stat | e Zip | | | | | |
| Phone Number | | Phone | Number | — | | | | | |
| Contact Person at UST Location : | | Number | r of Tanks a | at This Locatio | on: | | | | |
| Phone Number: | | | | | | icuous location: | 🗆 Yes 🗌 No | | |
| | C. Tank | | | | a conop | | | | |
| (1) Tank(s) presently in use | Tank # | | Tank # | | Tank | # | Tank # | | |
| (2) If not in use, date last used | | | | | | | | | |
| (3) If emptied, verify 1" or less of product in tank | | | | | | | | | |
| (4) Month and Year Tank Installed (E-estimate or K-known | ו) | | | | | | | | |
| (5) Material of Construction (E-estimate or K-known) | | | | | | | | | |
| (6) Capacity of Tank (in gallons) (E-estimate or K-known) | | | | | | | | | |
| (7) Substance Stored (E-estimate or K-known) | | | | | | | | | |
| D. Release Detection For Tanks | Release dete | ction syste | m must mee | et the performation | nce stand | lards in 280.43 or | 280.44 | | |
| (1) Automatic Tank Gauging | | | | | | | | | |
| (2) Vapor Monitoring | | [| | | | | | | |
| (3) Groundwater Monitoring | | [| | | | | | | |
| (4) Statistical Inventory Reconciliation (SIR) | | [| | | | | | | |
| (5) Secondary Containment With Interstitial Monitoring (repiping installed after July 1, 2007) | equired on | [| | | | | | | |
| (6) Other approved method (write in name of method) | | | | | | | | | |
| E. Release Detection For Piping | Release detec | ction syster | n must mee | t the performa | nce stand | ards in 280.43 or | 280.44 | | |
| (1) Check Type of Piping for each Tank | Pressure Pipe | [| | | | | | | |
| | Suction Pipe | [| | | | | | | |
| (2) FOR PRESSURE PIPING: Automatic Line Leak Detect (check one) | ctors, <u>and</u> | [| | | | | | | |
| (a) Vapor Monitoring | | [| | | | | | | |
| (b) Groundwater Monitoring | | [| | | | | | | |
| (c) Secondary Containment With Interstitial Monito on piping installed after July 1, 2007) | oring (required | [| | | | | | | |
| (d) Line Tightness Testing | | [| | | | | | | |
| (e) Other approved method (write in name of meth | od) | | | | | | | | |

COMPLIANCE INSPECTION CHECKLIST

RELEASE DETECTION FOR PIPING

| Set 1 | Tank # | Tank # | Tank # | Tank # |
|--|--------|--------|--------|--------|
| (1) Automatic Flow Restrictor | | | | |
| (2) Automatic Shut-off Device | | | | |
| (3) Continuous Alarm System | | | | |
| and | | | | |
| Set 2 | | | | |
| (4) Annual Line Tightness Testing | | | | |
| (5) Vapor Monitoring | | | | |
| (6) If Vapor Monitoring, documentation of monthly monitoring is available? | | | | |
| (7) Interstitial Monitoring | | | | |
| (8) If Interstitial Monitoring, documentation of monthly monitoring is available? | | | | |
| (9) Groundwater Monitoring | | | | |
| (10) If Groundwater Monitoring, documentation of monthly monitoring is available? | | | | |
| (11) Other Approved Method (specify in comments) | | | | |
| Suction Piping Indicate date of most recent test. | | | | |
| (12) Line Tightness Testing (required every 3 years) | | | | |
| (13) Vapor Monitoring | | | | |
| (14) Secondary Containment with Interstitial Monitoring | | | | |
| (15) Groundwater Monitoring | | | | |
| (16) Other Approved Method (specify in comments) | | | | |
| (17) No Leak Detection Required? (must answer yes to all of the following questions) | | | | |
| (a) Operates at less than atmospheric pressure | | | | |
| (b) Has only one check valve, which is located directly under pump | | | | |
| (c) Slope of piping allows product to drain back into tank when suction released | | | | |
| (d) All information on suction piping is verifiable | | | | |

RELEASE PREVENTION

| (1) Overfill prevention device present and operational. Image: constraint of the section of the sectin of the section of the sectin of the section of the s | SPILL PREVENTION | Tank # | Tank # | Tank # | _ Tank # _ |
|--|---|--------|--------|--------|------------|
| (3) Spill prevention device has no significant debris or liquid. Image: Spill prevention device is tested at least every three years, or is double walled and pencidcally monitored. Image: Spill prevention device is tested at least every three years, or is double walled and pencidcally monitored. OVERFILL PREVENTION Image: Spill prevention device present and operational. Image: Spill Spill prevention device present and operational. Image: Spill Spill Prevention device present and operational. Image: Spill S | (1) Spill prevention device present and operational. | | | | |
| (4) Spill prevention device is tested at least every three years, or is double walled and periodically monitored. Image: Control of Control o | (2) Spill prevention device in good repair. | | | | |
| and periodically monitored. Image: Constraint of the second s | (3) Spill prevention device has no significant debris or liquid. | | | | |
| A. Automatic shutoff device. Image: Stress of Stre | | | | | |
| A. Automatic shutoff device. Image: Shutoff device is functional and operational. Image: Shutoff device is functional and operational. (2) Automatic shutoff device appropriate for system. Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. (4) Tested every three years. Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. (4) Tested every three years. Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. (1) Present Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. (2) Alarm is functional and operational. Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. (1) Presence verified thru records and/or observation. Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. Image: Shutoff device appropriate for system. (3) Ball float is appropriate for system. Image: Shutoff device appropriste for system system s | . OVERFILL PREVENTION | | | | |
| (1) Verified by observations.Image: Constraint of the system | (1) Overfill prevention device present and operational. | | | | |
| (2) Automatic shutoff device is functional and operational. Image: Constraint of the system. (3) Automatic shutoff device appropriate for system. Image: Constraint of the system. (4) Tested every three years. Image: Constraint of Constratint of Constraint of Constraint of Constraint of Const | A. Automatic shutoff device. | | | | |
| (3) Automatic shutoff device appropriate for system. Image: Constraint of the system of the system. (4) Tested every three years. Image: Constraint of the system of the system. (1) Present Image: Constraint of the system of the system. (2) Alarm is functional and operational. Image: Constraint of the system of the system. (3) Alarm is audible/visible to delivery driver. Image: Constraint of the system. (4) Tested every three years. Image: Constraint of the system. (1) Presence verified thru records and/or observation. Image: Constraint of the system. (2) Ball float is appropriate for system. Image: Constraint of the system. (3) Ball float is appropriate for system. Image: Constraint of the system. (4) Tested every three years. Image: Constraint of the system. (4) Tested every three years. Image: Constraint of the system. (4) Tested every three years. Image: Constraint of the system of the system. (1) Repairs to UST system reprimed according to a recommended practice. Image: Constraint of the system of the system of the system. (1) Repaired UST system repairs. Image: Constraint of the system repairs. Image: Constraint of the system repairs. (5) CP system properly operated and maintained to provide continuous protection. Image: Constraint of the two most is conducting or completed | (1) Verified by observations. | | | | |
| (4) Tested every three years. Image: Constraint of the second | (2) Automatic shutoff device is functional and operational. | | | | |
| B. High level alarm Image: Constraint of the set of t | (3) Automatic shutoff device appropriate for system. | | | | |
| (1) Present Image: Constraint of the second sec | (4) Tested every three years. | | | | |
| (2) Alarm is functional and operational. (3) Alarm is audible/visible to delivery driver. (4) (3) Alarm is audible/visible to delivery driver. (4) Tested every three years. (4) (4) Tested every three years. (4) (4) (2) Ball float valves (2) (2) (1) Presence verified thru records and/or observation. (2) (2) (2) Ball float is operational. (2) (2) (3) Ball float is appropriate for system. (2) (2) (4) Tested every three years. (2) (2) (4) Tested every three years. (2) (2) (1) Presence verified thru records and/or observation. (2) (3) (4) Tested every three years. (2) (2) (1) Repairs to UST system performed according to a recommended practice. (2) (2) (1) Repaired UST system tightness tested within 30 days of repair. (3) (2) (3) (3) CP system tested within 6 months of any CP repair. (4) | B. High level alarm | | | | |
| (3) Alarm is audible/visible to delivery driver. Image: Constraint of the experiment of the | (1) Present | | | | |
| (4) Tested every three years. Image: C. Ball float valves Image: C. Ball float valves (1) Presence verified thru records and/or observation. Image: C. Ball float is operational. Image: C. Ball float is operational. (2) Ball float is operational. Image: C. Ball float is operational. Image: C. Ball float is operational. Image: C. Ball float is operational. (3) Ball float is appropriate for system. Image: C. Ball float is operational. Image: C. Ball float is operational. Image: C. Ball float is operational. (4) Tested every three years. Image: C. Ball float is operational. Image: C. Ball float is operational. Image: C. Ball float is operational. (4) Tested every three years. Image: C. Ball float is operational. Image: C. Ball flo | (2) Alarm is functional and operational. | | | | |
| C. Ball float valves Image: Constraint of the second s | (3) Alarm is audible/visible to delivery driver. | | | | |
| (1) Presence verified thru records and/or observation. Image: Constraint of the constrecent consecutive months, and for 10 of <td>(4) Tested every three years.</td> <td></td> <td></td> <td></td> <td></td> | (4) Tested every three years. | | | | |
| (2) Ball float is operational. (2) Ball float is operational. (3) Ball float is operational. (3) Ball float is operational. (3) Ball float is oppropriate for system. (4) Casted every three years. (4) Tested every three years. (4) Tested every three years. (2) Repaired UST system performed according to a recommended practice. (1) Repairs to UST system tightness tested within 30 days of repair. (2) Repaired UST system tightness tested within 30 days of repair. (2) Repaired UST system tightness tested within 30 days of repair. (3) CP system tested within 6 months of any CP repair. (4) Records of UST system repairs. (5) CP system properly operated and maintained to provide continuous protection. (6) CP system properly operated and maintained to provide continuous protection. (6) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. (7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of (1) CP system conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of | C. Ball float valves | | | | |
| (3) Ball float is appropriate for system.Image: Constraint of the system is appropriate for system.(4) Tested every three years.Image: Constraint of the system is appropriate for system.(1) Repairs to UST system performed according to a recommended practice.Image: Constraint of the system is appropriate for system is appropriate for system.(1) Repairs to UST system performed according to a recommended practice.Image: Constraint of the system.(2) Repaired UST system tightness tested within 30 days of repair.Image: Constraint of the system is appropriate.(3) CP system tested within 6 months of any CP repair.Image: Constraint of the system repairs.(4) Records of UST system repairs.Image: Constraint of the system.(5) CP system properly operated and maintained to provide continuous protection.Image: Constraint of the system.(6) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair.(7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of | (1) Presence verified thru records and/or observation. | | | | |
| (4) Tested every three years. (4) Tested every three years. (1) OPERATION AND MAINTENANCE (1) Repairs to UST system performed according to a recommended practice. (2) Repaired UST system tightness tested within 30 days of repair. (3) CP system tested within 6 months of any CP repair. (4) Records of UST system repairs. (5) CP system properly operated and maintained to provide continuous protection. (6) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. (7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of | (2) Ball float is operational. | | | | |
| II. OPERATION AND MAINTENANCE (1) Repairs to UST system performed according to a recommended practice. (2) Repaired UST system tightness tested within 30 days of repair. (3) CP system tested within 6 months of any CP repair. (4) Records of UST system repairs. (5) CP system properly operated and maintained to provide continuous protection. (6) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. (7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of | (3) Ball float is appropriate for system. | | | | |
| (1) Repairs to UST system performed according to a recommended practice.(2) Repaired UST system tightness tested within 30 days of repair.(3) CP system tested within 6 months of any CP repair.(4) Records of UST system repairs.(5) CP system properly operated and maintained to provide continuous protection.(6) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair.(7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of | (4) Tested every three years. | | | | |
| (2) Repaired UST system tightness tested within 30 days of repair. (2) Repaired UST system tightness tested within 30 days of repair. (3) CP system tested within 6 months of any CP repair. (4) Records of UST system repairs. (4) Records of UST system repairs. (2) CP system properly operated and maintained to provide continuous protection. (5) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. (2) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. (7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of (2) CP system conducted at least every 30 days. | II. OPERATION AND MAINTENANCE | - | | | |
| (3) CP system tested within 6 months of any CP repair. Image: Comparis tested within 6 months of any CP repair. (4) Records of UST system repairs. Image: Comparison of testing of testing of testing of testing of testing of testing of CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. Image: Comparison of testing | (1) Repairs to UST system performed according to a recommended practice. | | | | |
| (4) Records of UST system repairs. (4) Records of UST system repairs. (5) CP system properly operated and maintained to provide continuous protection. (5) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. (6) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. (7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of (7) Use the two most recent consecutive months. | (2) Repaired UST system tightness tested within 30 days of repair. | | | | |
| (5) CP system properly operated and maintained to provide continuous protection. Image: Control operator is continuous protection. (6) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. Image: Control operator is conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of | (3) CP system tested within 6 months of any CP repair. | | | | |
| protection. (6) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. (7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of (7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of | (4) Records of UST system repairs. | | | | |
| system tested within 3 years and operator is conducting or completed repair. (7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of (7) Walkthrough inspections are conducted at least every 30 days. Facility must have records for the two most recent consecutive months, and for 10 of | | | | | |
| must have records for the two most recent consecutive months, and for 10 of | (6) CP system performing adequately based on results of testing, or CP system tested within 3 years and operator is conducting or completed repair. | | | | |
| | | | | | |

| RELEASE PREVENTION (CONTINUED) | | | | | | | | |
|--|--------|--------|----------|--------|----------|--------|--------|--------|
| Check ($$) for compliance; "No" for noncompliance. Leave blank for "N/A". | | | | | | | | |
| IV. CORROSION PROTECTION | System | n# | System # | | System # | | System | # |
| A. Material of Construction (Check all that apply) | Tank | Piping | Tank | Piping | Tank | Piping | Tank | Piping |
| NON-CORRODIBLE | | | | | | | | |
| CORRODIBLE | | | | | | | | |
| B. Internal lining | | | | | | | | |
| (1) Installed according to a recommended practice. | | | | | | | | |
| (2) Inspected in a timely manner and lining is in compliance. | | | | | | | | |
| (3) Inspected according to approved protocol. | | | | | | | | |
| (4) Corrective action taken on failed inspection. | | | | | | | | |
| C. Galvanic (sacrificial) anodes | | | | | | | | |
| (1) Designed by CP expert/specialist. | | | | | | | | |
| (2) Tested in a timely manner. | | | | | | | | |
| (3) Corrective action taken on failed test. | | | | | | | | |
| (4) Metal components (i.e., flex lines, subpumps, etc.) protected as required. | | | | | | | | |
| (5) Operational records available. | | | | | | | | |
| D. Impressed current | | | | | | | | |
| (1) Designed by CP expert/specialist. | | | | | | | | |
| (2) Tested in a timely manner. | | | | | | | | |
| (3) Rectifier is operational. | | | | | | | | |
| (4) Verify records of 60 day check. | | | | | | | | |
| (5) Corrective action taken on failed check. | | | | | | | | |
| (6) Operational records available. | | | | | | | | |
| (7) CP system maintained. | | | | | | | | |
| (8) Metal components (i.e., flex lines, subpumps, etc.) protected as required. | | | | | | | | |
| V. COMPATIBILITY All portions of the system are compatible with product stored. | | | | | | | | |

Comments:

| Facility ID: | AFIN: | Facility Name | : | | | | | |
|--|------------------------------|---------------------------------|------------------------------------|-------------------|------|-------|------|-------|
| | | FINANCIAL | ASSURANCE | | | | | |
| (1) Petroleum Storage Tan | k Trust Fund (PSTTF)? (| check one) 🗌 Yes | □ No □ N/A | | | | | |
| (2) Can PSTTF deductible If No or N/A for PSTTF | | No N/A financial responsibility | ? | | | | | |
| Other SOC | | | | | | | | |
| (1) Implementing agency ha | as been notified of suspec | cted release as require | d. | | | □ Yes | 🗌 No | □ N/A |
| (2) Hazardous substance U approved by the implement | | tion meets requiremen | ts (i.e., either secondarily co | ontained or other | wise | □ Yes | 🗌 No | □ N/A |
| (3) UST systems in tempora (i.e., method present, opera | | - · · · | bliant with release detection red. | requirements | | ☐ Yes | 🗌 No | □ N/A |
| Operator Training/Ce | ertification Require | ments | | | | | | |
| Class A designated operato | or Name | # | | Yes | | | | |
| Class B designated operato | or Name | # | | | | | | |
| Class C designated operate | or (minimum 1 operator pe | er shift) | | □ Yes | | | A | |
| *Unmanned emerger | ncy generator facility (no c | class C required); OR | | □ Yes | | | ,, | |
| *Unmanned facility in | compliance with Arkansa | as State Fire Code (no | class C required); | □ Yes | | | | |
| If "NO", explain in co | omments | | | | | | | |
| Training records maintained | d for all Class A, B, and C | operators | | ☐ Yes | 🗌 No | | | |
| Class A and Class B Opera | ators certified within 30 da | iys of assuming O/M re | esponsibilities | ☐ Yes | 🗌 No | | | |
| Class A and Class B Opera | ators recertified within 45 | days of delivery prohib | ition violation | ☐ Yes | 🗌 No | □ *N/ | A | |
| Class C Operator(s) training | g: | | | | | | | |
| Conducted by AE | DEQ-certified Class A or C | Class B operator | | ☐ Yes | 🗌 No |) | | |
| Specific to facility | / | | | ☐ Yes | 🗌 No | D | | |
| Documented by A | ADEQ provided forms | | | | 🗌 No | D | | |
| Adequately addre | esses delivery controls, m | onitoring of dispensing | and emergency response | ☐ Yes | |) | | |
| Trained prior to a | ssuming Class C respons | sibility | | ☐ Yes | | D | | |
| Comments: | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

5 of 9

| Facility | / ID: |
|----------|-------|
| | |

GROUNDWATER MONITORING

| Monitoring | Performed | by: |
|------------|-----------|-----|
| 0 | | , |

Date GWM System Installed: _____ Number of Wells: _____

Groundwater monitoring well assessment was conducted by: ____

Please answer each question for each well

| | Well # | Well # | Well # | Well # | | | |
|--|------------------------|--------------------------|--------------------|--------|----|--|--|
| (1) Well is clearly marked & secured to avoid unauthorized access or tampering? | | | | | | | |
| (2) Well was opened & presence of water was observed in well at depth of feet? | | | | | | | |
| Check (${\bf v}$) for compliance; "No" for noncompliance. Le | eave blank for " | N/A". | | | | | |
| (3) Wells are used to monitor piping? | | | | | | | |
| (4) Groundwater monitoring well assessment was performed prior to installation of wells? | | | | | | | |
| (5) Documentation of monthly readings is available? | | | | | | | |
| (6) Specific gravity of product is less than one? | | | | | | | |
| (7) Hydraulic conductivity of soil between UST system & monitoring wells According to: | s is not less than 0.0 | 1 cm/sec. | | | | | |
| (8) Groundwater is not more than 20 feet from ground surface? | | | | | | | |
| (9) Wells are sealed from the ground surface to top of filter pack and pro | perly screened? | | | | | | |
| (10) Continuous monitoring device or manual bailing method used can de on top of groundwater in well? | etect the presence o | f at least one-eighth ir | ch of free product | | | | |
| (11) Groundwater is monitored: Manually Automatically | | | | | | | |
| (12) If groundwater is monitored manually : Bailer used is accessible & for | unctional? | | | | | | |
| (13) If groundwater is monitored automatically : Monitoring box is operated | ional? | | | | | | |
| (14) Checked for presence of sensor in monitoring well? | | | | | | | |
| (15) Release detection system is operating properly (i.e., able to detect a release from any portion of the system that routinely contains product). | | | | | | | |
| (16) Tanks and piping are monitored monthly for releases and records ar consecutive months and for 10 months of the last 12 months). | re available (must ha | we records for the two | most recent | YES | NO | | |

Comments:

| Check ($$) the appropriate box: |
|--|
| Facility in compliance at time of inspection. |
| |
| I certify that I have inspected the above named facility on (date/time) |
| Inspector's Signature: |
| IF DELIVERY PROHIBITION IS INVOKED, THE DESIGNATED CLASS A AND CLASS B OPERATOR MUST BE RECERTIFIED WITHIN 45 DAYS OF THE FACILITY BEING RED-TAGGED. IF FUEL DELIVERY PROHIBITION IS NOT IMMEDIATELY IMPLEMENTED, FAILURE TO CORRECT TCR NON-COMPLIANCE ISSUES IN THE TIMEFRAME GIVEN MAY RESULT IN FUEL DELIVERY PROHIBITION. |
| This inspection checklist and summary serve as your Notice of Noncompliance (if violations are indicated). |
| You have until to provide evidence of compliance. Noncompliance issues could result in enforcement actions but not limited to, penalty assessments. Failure to resolve these noncompliance issues within the specified time frame could result in the escalation of enforcement action. |
| Name of Owner/Owner's Representative (Please Print) Signature of Owner/Owner's Representative Date |

| Facility | ID: |
|----------|-----|
| Facility | ID. |
| | |

INSPECTION SUMMARY (CONTINUED)

Comments:

| Facility ID: | |
|--------------|--|
|--------------|--|

AST SITE DIAGRAM