

**Haley Griffith (adpce.ad)**

---

**Subject:** RE: Work Plan for Piezometer Abandonments & Out-of-Waste Extraction Well Relocations, Eco-Vista Class 1 Landfill, Solid Waste Permit No. 0290-S1-R3, AFIN 72-00144

|   |
|---|
| <b>AFIN:</b> 72-00144   |
| <b>PMT#:</b> 0290-S1-R3                                       |
| <b>Received</b><br>By Haley Griffith at 4:01 pm, Jun 19, 2023 |
| <b>DOC ID#:</b> 84235   |
| <b>TO:</b> BS>FILE <HG  |

**From:** Steve Jett <steve.jett@jettenviro.com>  
**Sent:** Monday, June 19, 2023 12:35 PM  
**To:** gwreports <gwreports@adeq.state.ar.us>  
**Cc:** Conrad, David <dconrad@wm.com>; Reynolds, Jodi <jreyno10@wm.com>; Michael Caldwell <mcaldwell@wm.com>; Small, Blake <bsmall@wm.com>; Travis Doll <travis.doll@jettenviro.com>; Travis Atwood (adpce.ad) <travis.atwood@adeq.state.ar.us>  
**Subject:** Work Plan for Piezometer Abandonments & Out-of-Waste Extraction Well Relocations, Eco-Vista Class 1 Landfill, Solid Waste Permit No. 0290-S1-R3, AFIN 72-00144

On behalf of Eco-Vista, LLC, Jett Environmental Consulting is submitting the attached Work Plan for Piezometer Abandonments & Out-of-Waste Extraction Well Relocations for the Eco-Vista Class 1 Landfill.

If you have any questions or comments regarding this submittal, please do not hesitate to contact us.

Sincerely,

**Steve Jett, P.G.**  
**Owner**  
***Jett Environmental Consulting***  
*18 Lexington Oaks Court*  
*Foristell, MO 63348*  
*314-496-4654*  
[steve.jett@jettenviro.com](mailto:steve.jett@jettenviro.com)  
[www.jettenviro.com](http://www.jettenviro.com)



June 19, 2023

*Submitted via Electronic Mail*

Mr. Travis Atwood, Geologist  
Arkansas Department of Energy and Environment  
Division of Environmental Quality  
5301 Northshore Drive  
North Little Rock, AR 72118

**Re: Work Plan for Piezometer Abandonments & Out-of-Waste Extraction Well Relocations  
Eco-Vista, LLC, Class 1 Landfill (Permit No. 0290-S1-R3)  
AFIN: 72-00144**

Dear Mr. Atwood:

On behalf of Eco Vista, LLC, Jett Environmental Consulting is pleased to submit this Work Plan to the Arkansas Department of Energy and Environment, Division of Environmental Quality (ADEQ) for work to be conducted at the Eco-Vista Class 1 Landfill.

The site intends to abandon four piezometers (PZ-1D, PZ-2D, PZ-3S, and PZ-3D) and nine out-of-waste (OW) extraction wells (OW-5 through OW-10, and OW-19 through OW-21) that are in the footprint of the future Class 1 Landfill expansion area (see **Figure 1**).

In addition, the site plans to install up to five new OW wells (OW-204 through OW-208) just northwest of the future Class 1 Landfill expansion area (see **Figure 1**).

### **ABANDONMENT**

The abandonment of the four piezometers and nine OW wells will be performed by an Arkansas-licensed driller. The piezometers will be abandoned in general conformance with American Society for Testing and Materials (ASTM) D5299-99, US Environmental Protection Agency (EPA) (160014-891034), and Arkansas Water Well Construction Commission (AWWCC) guidance documents.

The equipment to be used for abandonment will be cleaned and decontaminated prior to the first piezometer/OW and between decommissioning locations. The protective outer casing, pipe bollards, and concrete pad will be removed. An attempt will be made to remove the inner-casing. The associated annular materials and any remaining inner-casing will attempt to be removed by overdrilling. Each piezometer will be overdrilled to its total installed depth using sonic core barrels, air rotary, or hollow-stem augers fitted with a guide pipe. Once each piezometer has been overdrilled to its total depth, the borehole will be tremie grouted to the ground surface. It is recommended to use bentonite grout to backfill the boreholes due to their location in the future Class 1 cell, where a portion of the backfilled material may have to be removed. Construction logs for each point proposed for abandonment are included in **Attachment 1**.

### **INSTALLATION**

Based on boring logs of the piezometers, existing OW wells, and nearby monitoring wells MW-1N, MW-19 and NE-4, we suspect that the target zone for the screened interval of the new OW wells may be within the epikarst zone, approximately 20 feet above the top of the bedrock. It is estimated that the 20-foot length screened interval will be located at an approximate depth of 40 to 60 feet below ground surface (ft bgs). Actual depths may vary depending on topography and local variations in depth to the target stratum encountered in the field.

The following is a summary of the decision process on where, and how many, new OW wells will be installed. The exact number and locations are to be determined in the field based on subsurface conditions encountered during the pilot borings. The final number of OW wells is contingent on if/where the epikarst zone is encountered. The epikarst zone is the optimal flow zone for potential landfill gas migration and extraction.

The purpose of the existing OW wells (OW-5 through OW-10, and OW-19 through OW-21) was for landfill gas control. According to the site, OW-10, OW-19, OW-20, and OW-21 have consistently exhibited significant amounts of landfill gas, and OW-5 through OW-9 have not had significant amounts of landfill gas. Past investigations have identified possible NW-SE trending lineaments/fractures just west and east of these OW wells. Therefore, extending the NW-SE lineament to the northwest (outside of the Class 1 waste area and the proposed Class 1 waste expansion area) would optimally place additional (i.e., replacement) OW wells in the lineament path towards MW-1N. It is proposed to drill the first OW pilot boring at OW-204, as shown on **Figure 1**.

The target zone for the screened interval of an OW well is the epikarst zone, which generally has consisted of silty/sandy gravel and weathered chert/limestone above competent bedrock. The epikarst zone would be the ideal pathway for landfill gas to migrate, if present.

Step 1: The initial pilot boring (i.e., PB-204) would be drilled in an attempt to encounter the epikarst zone. If encountered, then an OW-well (i.e., OW-204) would be installed within the pilot boring.

Step 2: If the epikarst zone is encountered (Step 1), then the next OW-well would be drilled approximately 100 feet north of OW-204, continuing on 100-foot spacings (i.e., OW-205, OW-206, and OW-207) until OW-208 is reached (see **Figure 1**).

Step 3: If no epikarst zone is encountered (i.e., no silty/sandy/gravelly/cherty weathered zone between the silty/cherty clay and overlying bedrock), then the pilot boring would be terminated, backfilled with grout, and the next pilot boring would be attempted approximately 50 feet north of PB-204 (or any subsequent boring).

Step 4: Upon conclusion of PB-208/OW-208, then the drilling of the pilot borings/wells would be considered complete. The maximum number of OW-wells anticipated is five (OW-204 through OW-208), as shown on **Figure 1**.

Drilling and well installation will be performed by an Arkansas-licensed driller. To install the wells, the driller will advance borings and install the wells using sonic (rotary vibratory), air rotary, or hollow-stem auger drilling methods. Each boring will be logged by either observation of the cuttings or by a continuous sampler. Soils will be logged and classified according to the Unified Soil Classification System by a qualified geologist contracted separately by the facility. The wells will be constructed and developed in general conformance with ASTM D5092 construction protocols and in accordance with EPA 160014-891034 and AWWCC guidance documents.

The equipment to be used for well installation will be cleaned and decontaminated prior to the first boring and between drilling locations.

Each OW well will have the following design components:

- The well borings will be advanced using sonic core barrels, hollow stem augers, or air rotary utilizing a sufficient diameter to maintain a minimum of 2 inches of annular space between the well casing and borehole wall.
- The polyvinyl chloride (PVC) well casing at each well will have a locking cap, which is vented to allow equilibration of water levels with atmospheric pressure.
- The top of casing at each well will be permanently marked, or notched, for future use as a reference point for water-level measurements.
- Each well will be secured at the surface with a locking, protective steel or aluminum casing; concrete pad; and protective pipe bollards. A weep hole will be drilled in the protective casing approximately 6 inches above ground surface to allow for drainage.
- The well identifications will be clearly marked on the outside protective casings.
- Well casings and screens will be constructed of 4-inch-diameter, Schedule 80 PVC with flush-threaded casing; a minimum 20-ft long, 10-slot (i.e., 0.010-inch) well screen; and a bottom end cap.
- A filter pack consisting of well-rounded, 3/8-inch washed pea gravel will be placed in the annular space to a minimum distance of 3 ft above the top of the screen.
- The bentonite seal will be followed by a well-mixed bentonite cement grout filled to the ground surface and installed using a tremie pipe.

Slight adjustments to well construction may be required in the field based on the observed lithology at each well location. Any deviations from well design will conform to recommendations in the above-referenced guidance documents.

### **WELL SURVEY**

An Arkansas-licensed surveyor will survey the horizontal and vertical location of each new monitoring point. The vertical locations of the top of PVC casing will be surveyed to the nearest 0.01 ft, with the horizontal locations surveyed to the nearest 0.1 ft. The vertical locations of the top of concrete and nearest ground surface will be surveyed to the nearest 0.1 ft.

The survey report will include horizontal and vertical coordinates based on the landfill's site-referenced coordinate system, which is based on established site-specific benchmarks.

### **INSTALLATION & ABANDONMENT REPORT**

Within 60 calendar days of completion of the proposed field work, a report will be submitted documenting field activities. The report will be certified by the supervising professional per Regulation 22.1103(f) and will include the following:

- A site map that includes the locations of the abandoned points and surveyed locations of the newly installed monitoring points,
- Boring logs and construction diagrams for the new monitoring points,
- Completed Abandonment Forms for each point,
- Summary of work quality and methods, and
- The certified survey report from an Arkansas-licensed surveyor containing vertical and horizontal location coordinates for the newly installed monitoring points.

If you have any questions or comments, please contact me at [steve.jett@jettenviro.com](mailto:steve.jett@jettenviro.com) or 314-496-4654.

Sincerely,



Steve Jett, P.G. No. 1826  
Owner

*Attachments: Figure 1 – Site Layout & Piezometer/Extraction Well Locations  
Attachment 1 – Boring Logs & As-Builts*

*cc: Jodi Reynolds – WM (PDF via Email)  
Dave Conrad – WM (PDF via Email)  
Michael Caldwell – WM (PDF via Email)*













FTN Project #  
R06820-0100-013

|   |  |  |
|---|--|--|
| PROJECT:<br><b>Eco-Vista, LLC Class 1 Landfill GHI</b>  | BORING ID:<br><b>PZ-1D</b>               | PIEZOMETER ID:<br><b>PZ-1D</b>               |
| LOCATION:<br><b>Eco-Vista, LLC Landfill, Tontitown, AR</b>  | NORTHING, FT SRC:<br><b>664908.0</b>     | EASTING, FT SRC:<br><b>645833.0</b>          |
| DRILLING CONTRACTOR:<br><b>Walker-Hill Environmental, Inc.</b>  | GROUND SURFACE, FT SRE:<br><b>1296.5</b> | TOC MP, FT SRE:<br><b>1299.39</b>            |
| DRILLING EQUIPMENT:<br><b>Versa-Drill VersaSonic</b>  | WELL DEPTH, FT BELOW MP:<br><b>80.3</b>  | INSTALLATION DATES:<br><b>6/29-7/29/2019</b> |
| DRILLING METHOD:<br><b>Sonic with 4x6 in dia. core and case in soils and air rotary in bedrock</b>                  |  |  |
| SAMPLING METHOD:<br><b>Continuous with 10 ft, 4 in dia. core barrel in soil and 10 ft HQ core barrel in bedrock</b> |  |  |
| LOGGED BY:<br><b>AJP</b>  |  |  |


| Depth (feet) | % REC | USCS  | Graphic Log | CALIPER |    |    | GAMMA |    |    | SPR |      |      | Description  | Well Construction   |
|--------------|-------|-------|-------------|---------|----|----|-------|----|----|-----|------|------|--|---|
|              |       |       |             | 9       | 14 | 19 | 24    | 25 | 50 | 75  | 3200 | 3450 |  |   |
| 0            |       |       |             |         |    |    |       |    |    |     |      |      | FILL   | Above ground completion including 2.5x2.5 ft concrete pad, four pipe bollards, and locking outer aluminum casing<br><br>70.1 ft of 2 in dia., Sch. 40 PVC solid riser, including 2.9 ft of stickup<br><br>Cement/bentonite grout from 0 ft bgs to 20.0 ft bgs |
| 60           |       | GC    |             |         |    |    |       |    |    |     |      |      | ASPHALT  |   |
|              |       |       |             |         |    |    |       |    |    |     |      |      | CLAYEY GRAVEL, reddish orange, gravel (<3" dia), stiff, moist.   |   |
|              |       | ML    |             |         |    |    |       |    |    |     |      |      | GRAVELLY SILT, light gray, gravel (<2" dia), moist.  |   |
| 100          |       | GC/GM |             |         |    |    |       |    |    |     |      |      | SILTY GRAVEL to CLAYEY GRAVEL, reddish brown to tan, stiff, moist to almost dry.                               |   |
| 10           |       | CH/CL |             |         |    |    |       |    |    |     |      |      | GRAVELLY LEAN CLAY to FAT CLAY, reddish brown, gravel (<2" dia), moist.  |   |
|              |       |       |             |         |    |    |       |    |    |     |      |      | CHERT, some clay, 13.5-14.2 ft bgs.  |   |
| 100          |       | CL    |             |         |    |    |       |    |    |     |      |      | GRAVELLY LEAN CLAY, orangish brown, decreasing clay with depth, soft, moist.                                   |   |
| 20           |       |       |             |         |    |    |       |    |    |     |      |      | @ 20-23 ft bgs increasing silt content with depth.   |   |
|              |       | ML    |             |         |    |    |       |    |    |     |      |      | SILT with gravel, orange with some clay, medium stiff, moist.  |   |
| 100          |       | ML/CL |             |         |    |    |       |    |    |     |      |      | CHERT, white with oxidation along fractures<br>Gas odor, 24.24.5 ft bgs.                                       |   |
|              |       |       |             |         |    |    |       |    |    |     |      |      | GRAVELLY SILT to GRAVELLY LEAN CLAY, orangish brown with lenses of red clay and tan silt, medium stiff, moist. |   |
| 30           |       | GM    |             |         |    |    |       |    |    |     |      |      | CHERT, white with weathering along fractures<br>28-29 ft bgs.  |   |
|              |       | CL    |             |         |    |    |       |    |    |     |      |      | GRAVELLY SILT, orangish brown, moist.  |   |
|              |       |       |             |         |    |    |       |    |    |     |      |      | LEAN CLAY, tannish orange with black nodules (<3/4" dia), soft, moist.   |   |
| 80           |       | GW-GM |             |         |    |    |       |    |    |     |      |      | CHERT, 31-31.5 ft bgs.   |   |
|              |       |       |             |         |    |    |       |    |    |     |      |      | WELL GRADED GRAVEL with silt, reddish brown with some clay, chert heavily weathered, moist.                    |   |
|              |       |       |             |         |    |    |       |    |    |     |      |      | @ 38-40 ft bgs color changes to tan.   |   |

NOTES: Horizontal and vertical data are based on the Mason Surveying & Consulting, Inc., report dated August 9, 2019. SRE=site referenced elevation, SRC=site referenced coordinates, TOC=top of casing, MP=surveyed measuring point on TOC.



FTN Project #  
R06820-0100-013

|   |  |  |
|---|--|--|
| PROJECT:<br><b>Eco-Vista, LLC Class 1 Landfill GHI</b>  | BORING ID:<br><b>PZ-1D</b>               | PIEZOMETER ID:<br><b>PZ-1D</b>               |
| LOCATION:<br><b>Eco-Vista, LLC Landfill, Tontitown, AR</b>  | NORTHING, FT SRC:<br><b>664908.0</b>     | EASTING, FT SRC:<br><b>645833.0</b>          |
| DRILLING CONTRACTOR:<br><b>Walker-Hill Environmental, Inc.</b>  | GROUND SURFACE, FT SRE:<br><b>1296.5</b> | TOC MP, FT SRE:<br><b>1299.39</b>            |
| DRILLING EQUIPMENT:<br><b>Versa-Drill VersaSonic</b>  | WELL DEPTH, FT BELOW MP:<br><b>80.3</b>  | INSTALLATION DATES:<br><b>6/29-7/29/2019</b> |
| DRILLING METHOD:<br><b>Sonic with 4x6 in dia. core and case in soils and air rotary in bedrock</b>                  |  |  |
| SAMPLING METHOD:<br><b>Continuous with 10 ft, 4 in dia. core barrel in soil and 10 ft HQ core barrel in bedrock</b> |  |  |
| LOGGED BY:<br><b>AJP</b>  |  |  |




NOTES: Horizontal and vertical data are based on the Mason Surveying & Consulting, Inc., report dated August 9, 2019. SRE=site referenced elevation, SRC=site referenced coordinates, TOC=top of casing, MP=surveyed measuring point on TOC.



FTN Project #  
R06820-0100-013

|   |  |  |
|---|--|--|
| PROJECT:<br><b>Eco-Vista, LLC Class 1 Landfill GHI</b>  | BORING ID:<br><b>PZ-2D</b>               | PIEZOMETER ID:<br><b>PZ-2D</b>               |
| LOCATION:<br><b>Eco-Vista, LLC Landfill, Tontitown, AR</b>  | NORTHING, FT SRC:<br><b>664568.4</b>     | EASTING, FT SRC:<br><b>645439.1</b>          |
| DRILLING CONTRACTOR:<br><b>Walker-Hill Environmental, Inc.</b>  | GROUND SURFACE, FT SRE:<br><b>1295.5</b> | TOC MP, FT SRE:<br><b>1294.74</b>            |
| DRILLING EQUIPMENT:<br><b>Versa-Drill VersaSonic</b>  | WELL DEPTH, FT BELOW MP:<br><b>103.1</b> | INSTALLATION DATES:<br><b>7/10-7/29/2019</b> |
| DRILLING METHOD:<br><b>Sonic with 4x6 in dia. core and case in soils and air rotary in bedrock</b>                  |  |  |
| SAMPLING METHOD:<br><b>Continuous with 10 ft, 4 in dia. core barrel in soil and 10 ft HQ core barrel in bedrock</b> |  |  |
| LOGGED BY:<br><b>AJP</b>  |  |  |



NOTES: Horizontal and vertical data are based on the Mason Surveying & Consulting, Inc., report dated August 9, 2019. SRE=site referenced elevation, SRC=site referenced coordinates. TOC=top of casing, MP=surveyed measuring point on TOC.



FTN Project #  
R06820-0100-013

|   |  |  |
|---|--|--|
| PROJECT:<br><b>Eco-Vista, LLC Class 1 Landfill GHI</b>  | BORING ID:<br><b>PZ-2D</b>               | PIEZOMETER ID:<br><b>PZ-2D</b>               |
| LOCATION:<br><b>Eco-Vista, LLC Landfill, Tontitown, AR</b>  | NORTHING, FT SRC:<br><b>664568.4</b>     | EASTING, FT SRC:<br><b>645439.1</b>          |
| DRILLING CONTRACTOR:<br><b>Walker-Hill Environmental, Inc.</b>  | GROUND SURFACE, FT SRE:<br><b>1295.5</b> | TOC MP, FT SRE:<br><b>1294.74</b>            |
| DRILLING EQUIPMENT:<br><b>Versa-Drill VersaSonic</b>  | WELL DEPTH, FT BELOW MP:<br><b>103.1</b> | INSTALLATION DATES:<br><b>7/10-7/29/2019</b> |
| DRILLING METHOD:<br><b>Sonic with 4x6 in dia. core and case in soils and air rotary in bedrock</b>                  |  |  |
| SAMPLING METHOD:<br><b>Continuous with 10 ft, 4 in dia. core barrel in soil and 10 ft HQ core barrel in bedrock</b> |  |  |
| LOGGED BY:<br><b>AJP</b>  |  |  |


| Depth (feet) | % REC | USCS  | Graphic Log | CALIPER |     |   | GAMMA   |    |    | SPR |   |     | Description | Well Construction |
|--------------|-------|-------|-------------|---------|-----|---|---|----|----|-----|---|-----|-------------|-------------------|
|              |       |       |             | 7.2     | 9.2 | 11.2  | 0   | 20 | 40 | 320 | 520   | 720 |             |                   |
| 35           | 90    | CH    |             |         |     |   | FAT CLAY, dark reddish brown, blocky, stiff, moist. |    |    |     | Bentonite chip seal from 30.0 ft bgs to 67.0 ft bgs |     |             |                   |
| 40           |       | CL    |             |         |     | LEAN CLAY, with interbedded gravel and layers of fat blocky clay, medium stiff, moist.  |   |    |    |     |   |     |             |                   |
| 45           | 20    | GM/GC |             |         |     | SILTY GRAVEL to CLAYEY GRAVEL, gravel (<4" dia).  |   |    |    |     |   |     |             |                   |
| 50           |       | CL-GC |             |         |     | WEATHERED CHERT/EPIKARST, chert is weathered into a well-graded gravel with silt, tan, gravel (<3" dia), loose, moist.  |   |    |    |     |   |     |             |                   |
| 55           | 100   | CL-GC |             |         |     | LEAN CLAY with gravel, dark reddish brown, medium stiff to soft, moist.<br>WEATHERED CHERT/EPIKARST, chert is weathered into a well-graded gravel with silt, tan, gravel (<3" dia) moist to dry. @ 54.5 color change to white with reddish brown staining.<br><br>@ 58-60 ft bgs color change to white and tan. |   |    |    |     |   |     |             |                   |
| 60           |       | CL-GC |             |         |     | LEAN CLAY with gravel, dark reddish brown, medium stiff to soft, moist.   |   |    |    |     |   |     |             |                   |
| 65           |       | CL    |             |         |     |   |   |    |    |     |   |     |             |                   |

NOTES: Horizontal and vertical data are based on the Mason Surveying & Consulting, Inc., report dated August 9, 2019. SRE=site referenced elevation, SRC=site referenced coordinates. TOC=top of casing, MP=surveyed measuring point on TOC.



FTN Project #  
R06820-0100-013

|   |  |  |
|---|--|--|
| PROJECT:<br><b>Eco-Vista, LLC Class 1 Landfill GHI</b>  | BORING ID:<br><b>PZ-2D</b>               | PIEZOMETER ID:<br><b>PZ-2D</b>               |
| LOCATION:<br><b>Eco-Vista, LLC Landfill, Tontitown, AR</b>  | NORTHING, FT SRC:<br><b>664568.4</b>     | EASTING, FT SRC:<br><b>645439.1</b>          |
| DRILLING CONTRACTOR:<br><b>Walker-Hill Environmental, Inc.</b>  | GROUND SURFACE, FT SRE:<br><b>1295.5</b> | TOC MP, FT SRE:<br><b>1294.74</b>            |
| DRILLING EQUIPMENT:<br><b>Versa-Drill VersaSonic</b>  | WELL DEPTH, FT BELOW MP:<br><b>103.1</b> | INSTALLATION DATES:<br><b>7/10-7/29/2019</b> |
| DRILLING METHOD:<br><b>Sonic with 4x6 in dia. core and case in soils and air rotary in bedrock</b>                  |  |  |
| SAMPLING METHOD:<br><b>Continuous with 10 ft, 4 in dia. core barrel in soil and 10 ft HQ core barrel in bedrock</b> |  |  |
| LOGGED BY:<br><b>AJP</b>  |  |  |




NOTES: Horizontal and vertical data are based on the Mason Surveying & Consulting, Inc., report dated August 9, 2019. SRE=site referenced elevation, SRC=site referenced coordinates. TOC=top of casing, MP=surveyed measuring point on TOC.





FTN Project #  
R06820-0100-013

|   |  |  |
|---|--|--|
| PROJECT:<br><b>Eco-Vista, LLC Class 1 Landfill GHI</b>                  | BORING ID:<br><b>PZ-3S</b>               | PIEZOMETER ID:<br><b>PZ-3S</b>               |
| LOCATION:<br><b>Eco-Vista, LLC Landfill, Tontitown, AR</b>              | NORTHING, FT SRC:<br><b>664604.5</b>     | EASTING, FT SRC:<br><b>646951.1</b>          |
| DRILLING CONTRACTOR:<br><b>Walker-Hill Environmental, Inc.</b>          | GROUND SURFACE, FT SRE:<br><b>1262.7</b> | TOC MP, FT SRE:<br><b>1265.71</b>            |
| DRILLING EQUIPMENT:<br><b>Versa-Drill VersaSonic</b>                    | WELL DEPTH, FT BELOW MP:<br><b>72.9</b>  | INSTALLATION DATES:<br><b>6/27-7/29/2019</b> |
| DRILLING METHOD:<br><b>Sonic with 4x6 in dia. core and case</b>         |  |  |
| SAMPLING METHOD:<br><b>Continuous with 10 ft, 4 in dia. core barrel</b> |  |  |
| LOGGED BY:<br><b>AJP</b>  |  |  |




NOTES: Horizontal and vertical data are based on the Mason Surveying & Consulting, Inc., report dated August 9, 2019. SRE=site referenced elevation, SRC=site referenced coordinates, TOC=top of casing, MP=surveyed measuring point on TOC.



FTN Project #  
R06820-0100-013

|   |  |  |
|---|--|--|
| PROJECT:<br><b>Eco-Vista, LLC Class 1 Landfill GHI</b>                  | BORING ID:<br><b>PZ-3S</b>               | PIEZOMETER ID:<br><b>PZ-3S</b>               |
| LOCATION:<br><b>Eco-Vista, LLC Landfill, Tontitown, AR</b>              | NORTHING, FT SRC:<br><b>664604.5</b>     | EASTING, FT SRC:<br><b>646951.1</b>          |
| DRILLING CONTRACTOR:<br><b>Walker-Hill Environmental, Inc.</b>          | GROUND SURFACE, FT SRE:<br><b>1262.7</b> | TOC MP, FT SRE:<br><b>1265.71</b>            |
| DRILLING EQUIPMENT:<br><b>Versa-Drill VersaSonic</b>                    | WELL DEPTH, FT BELOW MP:<br><b>72.9</b>  | INSTALLATION DATES:<br><b>6/27-7/29/2019</b> |
| DRILLING METHOD:<br><b>Sonic with 4x6 in dia. core and case</b>         |  |  |
| SAMPLING METHOD:<br><b>Continuous with 10 ft, 4 in dia. core barrel</b> |  |  |
| LOGGED BY:<br><b>AJP</b>  |  |  |




NOTES: Horizontal and vertical data are based on the Mason Surveying & Consulting, Inc., report dated August 9, 2019. SRE=site referenced elevation, SRC=site referenced coordinates, TOC=top of casing, MP=surveyed measuring point on TOC.





water resources / environmental consultants  
 FTN Project #  
 R06820-0100-013

|   |  |  |
|---|--|--|
| PROJECT:<br><b>Eco-Vista, LLC Class 1 Landfill GHI</b>  | BORING ID:<br><b>PZ-3D</b>               | PIEZOMETER ID:<br><b>PZ-3D</b>               |
| LOCATION:<br><b>Eco-Vista, LLC Landfill, Tontitown, AR</b>  | NORTHING, FT SRC:<br><b>664592.8</b>     | EASTING, FT SRC:<br><b>646955.6</b>          |
| DRILLING CONTRACTOR:<br><b>Walker-Hill Environmental, Inc.</b>  | GROUND SURFACE, FT SRE:<br><b>1262.9</b> | TOC MP, FT SRE:<br><b>1265.73</b>            |
| DRILLING EQUIPMENT:<br><b>Versa-Drill VersaSonic</b>  | WELL DEPTH, FT BELOW MP:<br><b>90.8</b>  | INSTALLATION DATES:<br><b>6/25-7/29/2019</b> |
| DRILLING METHOD:<br><b>Sonic with 4x6 in dia. core and case in soils and air rotary in bedrock</b>                  |  |  |
| SAMPLING METHOD:<br><b>Continuous with 10 ft, 4 in dia. core barrel in soil and 10 ft HQ core barrel in bedrock</b> |  |  |
| LOGGED BY:<br><b>AJP</b>  |  |  |




NOTES: Horizontal and vertical data are based on the Mason Surveying & Consulting, Inc., report dated August 9, 2019. SRE=site referenced elevation, SRC=site referenced coordinates. TOC=top of casing, MP=surveyed measuring point on TOC.



FTN Project #  
R06820-0100-013

|   |  |  |
|---|--|--|
| PROJECT:<br><b>Eco-Vista, LLC Class 1 Landfill GHI</b>  | BORING ID:<br><b>PZ-3D</b>               | PIEZOMETER ID:<br><b>PZ-3D</b>               |
| LOCATION:<br><b>Eco-Vista, LLC Landfill, Tontitown, AR</b>  | NORTHING, FT SRC:<br><b>664592.8</b>     | EASTING, FT SRC:<br><b>646955.6</b>          |
| DRILLING CONTRACTOR:<br><b>Walker-Hill Environmental, Inc.</b>  | GROUND SURFACE, FT SRE:<br><b>1262.9</b> | TOC MP, FT SRE:<br><b>1265.73</b>            |
| DRILLING EQUIPMENT:<br><b>Versa-Drill VersaSonic</b>  | WELL DEPTH, FT BELOW MP:<br><b>90.8</b>  | INSTALLATION DATES:<br><b>6/25-7/29/2019</b> |
| DRILLING METHOD:<br><b>Sonic with 4x6 in dia. core and case in soils and air rotary in bedrock</b>                  |  |  |
| SAMPLING METHOD:<br><b>Continuous with 10 ft, 4 in dia. core barrel in soil and 10 ft HQ core barrel in bedrock</b> |  |  |
| LOGGED BY:<br><b>AJP</b>  |  |  |




NOTES: Horizontal and vertical data are based on the Mason Surveying & Consulting, Inc., report dated August 9, 2019. SRE=site referenced elevation, SRC=site referenced coordinates. TOC=top of casing, MP=surveyed measuring point on TOC.



FTN Project #  
R06820-0100-013

|   |  |  |
|---|--|--|
| PROJECT:<br><b>Eco-Vista, LLC Class 1 Landfill GHI</b>  | BORING ID:<br><b>PZ-3D</b>               | PIEZOMETER ID:<br><b>PZ-3D</b>               |
| LOCATION:<br><b>Eco-Vista, LLC Landfill, Tontitown, AR</b>  | NORTHING, FT SRC:<br><b>664592.8</b>     | EASTING, FT SRC:<br><b>646955.6</b>          |
| DRILLING CONTRACTOR:<br><b>Walker-Hill Environmental, Inc.</b>  | GROUND SURFACE, FT SRE:<br><b>1262.9</b> | TOC MP, FT SRE:<br><b>1265.73</b>            |
| DRILLING EQUIPMENT:<br><b>Versa-Drill VersaSonic</b>  | WELL DEPTH, FT BELOW MP:<br><b>90.8</b>  | INSTALLATION DATES:<br><b>6/25-7/29/2019</b> |
| DRILLING METHOD:<br><b>Sonic with 4x6 in dia. core and case in soils and air rotary in bedrock</b>                  |  |  |
| SAMPLING METHOD:<br><b>Continuous with 10 ft, 4 in dia. core barrel in soil and 10 ft HQ core barrel in bedrock</b> |  |  |
| LOGGED BY:<br><b>AJP</b>  |  |  |




NOTES: Horizontal and vertical data are based on the Mason Surveying & Consulting, Inc., report dated August 9, 2019. SRE=site referenced elevation, SRC=site referenced coordinates. TOC=top of casing, MP=surveyed measuring point on TOC.

# Drilling Log

|                                      |                      |                                    |                            |                         |
|--------------------------------------|----------------------|------------------------------------|----------------------------|-------------------------|
| Project Name <i>W/M</i>              |                      | Project Number <i>08201045.00</i>  | Boring Number <i>OW-5</i>  |                         |
| Ground Elevation <i>1294.4</i>       | Location             |                                    | Page <i>1</i>              | of <i>1</i>             |
| Monitoring Equipment                 |                      |                                    | Total Footage <i>73'</i>   |                         |
| Drilling Type <i>Air Rotary</i>      | Hole Size <i>10"</i> | Overburden Footage <i>- 44'</i>    | Bedrock Footage <i>29'</i> | No. Of Samples <i>—</i> |
| Drilling Company <i>Flippin Bros</i> |                      | Driller (s) <i>Marius Flippin</i>  |                            |                         |
| Drilling Rig <i>Schramm</i>          |                      | Type of Sampler <i>—</i>           |                            |                         |
| Date <i>2/22/02</i>                  | To                   | Field Observer (s) <i>Mark Orr</i> |                            |                         |

| Depth (feet) | Description   | Class     | Blow Count | Recov. | Run/Time    | Sample Desig. | PID (ppm) |    |   | Remarks/<br>Water Levels |
|--------------|---|-----------|------------|--------|-------------|---------------|-----------|----|---|--------------------------|
|              |   |           |            |        |             |               | BZ        | BH | S |                          |
| 1            | <i>Clay, w/silt. Trace plasticity. Damp. Abundant chert fragments. Bright orangish-red.</i> | <i>CL</i> |            |        | <i>1615</i> |               |           |    |   |                          |
| 2            |   |           |            |        |             |               |           |    |   |                          |
| 3            |   |           |            |        |             |               |           |    |   |                          |
| 4            | <i>Limestone w/chert fragments</i>  | <i>LS</i> |            |        |             |               |           |    |   |                          |
| 5            |   |           |            |        |             |               |           |    |   |                          |
| 6            |   |           |            |        |             |               |           |    |   |                          |
| 7            | <i>TD = 73' @ 1700</i>  |           |            |        |             |               |           |    |   |                          |
| 8            |   |           |            |        |             |               |           |    |   |                          |
| 9            |   |           |            |        |             |               |           |    |   |                          |
| 10           |   |           |            |        |             |               |           |    |   |                          |
| 11           |   |           |            |        |             |               |           |    |   |                          |
| 12           |   |           |            |        |             |               |           |    |   |                          |
| 14           |   |           |            |        |             |               |           |    |   |                          |




BZ=Breathing Zone    BH=Bore Hole    S=Sample

# Drilling Log

|                                      |            |                                   |                                   |                                    |                   |
|--------------------------------------|------------|-----------------------------------|-----------------------------------|------------------------------------|-------------------|
| Project Name <i>W/M</i>              |            | Project Number <i>DB201045.00</i> |                                   | Boring Number <i>DW-6</i>          |                   |
| Ground Elevation <i>1288.6</i>       |            | Location                          |                                   | Page <i>1</i> of <i>1</i>          |                   |
| Monitoring Equipment                 |            |                                   |                                   | Total Footage <i>67'</i>           |                   |
| Drilling Type                        | Hole Size  | Overburden Footage                | Bedrock Footage                   | No. Of Samples                     | No. Of Core Boxes |
| <i>Air Rotary</i>                    | <i>10"</i> | <i>39'</i>                        | <i>28'</i>                        | <i>—</i>                           | <i>—</i>          |
| Drilling Company <i>Flippin Bros</i> |            |                                   | Driller (s) <i>Marcus Flippin</i> |                                    |                   |
| Drilling Rig <i>Schramm</i>          |            |                                   | Type of Sampler                   |                                    |                   |
| Date <i>2/25/02</i>                  |            | To                                |                                   | Field Observer (s) <i>Mark Orr</i> |                   |

| Depth (feet) | Description  | Class     | Blow Count | Recov. | Run/Time    | Sample Desig. | PID (ppm) |    |   | Remarks/<br>Water Levels |
|--------------|--|-----------|------------|--------|-------------|---------------|-----------|----|---|--------------------------|
|              |  |           |            |        |             |               | BZ        | BH | S |                          |
| 1            | <i>Clay, whitt. Trace plasticity. Damp. Abundant chert fragments, Bright orangish-red.</i> | <i>CL</i> |            |        | <i>0915</i> |               |           |    |   |                          |
| 2            |  |           |            |        |             |               |           |    |   |                          |
| 3            |  |           |            |        |             |               |           |    |   |                          |
| 4            | <i>Limestone w/ chert fragments</i>  | <i>LS</i> |            |        |             |               |           |    |   |                          |
| 5            |  |           |            |        |             |               |           |    |   |                          |
| 6            | <i>TD = 67' @ 1015</i>   |           |            |        |             |               |           |    |   |                          |
| 7            |  |           |            |        |             |               |           |    |   |                          |
| 8            |  |           |            |        |             |               |           |    |   |                          |
| 9            |  |           |            |        |             |               |           |    |   |                          |
| 10           |  |           |            |        |             |               |           |    |   |                          |
| 11           |  |           |            |        |             |               |           |    |   |                          |
| 12           |  |           |            |        |             |               |           |    |   |                          |
| 14           |  |           |            |        |             |               |           |    |   |                          |




BZ=Breathing Zone    BH=Bore Hole    S=Sample

# Drilling Log

|   |                         |                                      |                                      |                                       |                   |
|---|-------------------------|--------------------------------------|--------------------------------------|---------------------------------------|-------------------|
| Project Name<br><i>WIM</i>              |                         | Project Number<br><i>08201045.02</i> |                                      | Boring Number<br><i>0w-7</i>          |                   |
| Ground Elevation<br><i>1291.2</i>       |                         | Location                             |                                      | Page<br><i>1</i> of <i>1</i>          |                   |
| Monitoring Equipment                    |                         |                                      |                                      | Total Footage<br><i>72'</i>           |                   |
| Drilling Type<br><i>Air Rotary</i>      | Hole Size<br><i>10"</i> | Overburden Footage<br><i>28'</i>     | Bedrock Footage<br><i>44'</i>        | No. Of Samples                        | No. Of Core Boxes |
| Drilling Company<br><i>Flippin Bros</i> |                         |                                      | Driller (s)<br><i>Marcus Flippin</i> |                                       |                   |
| Drilling Rig<br><i>Schramm</i>          |                         |                                      | Type of Sampler                      |                                       |                   |
| Date<br><i>2/25/02</i>                  |                         | To                                   |                                      | Field Observer (s)<br><i>Mark Orr</i> |                   |

| Depth (feet) | Description   | Class     | Blow Count       | Recov. | Run/Time    | Sample Desig. | PID (ppm) |    |   | Remarks/<br>Water Levels |
|--------------|---|-----------|------------------|--------|-------------|---------------|-----------|----|---|--------------------------|
|              |   |           |                  |        |             |               | BZ        | BH | S |                          |
| 1            | <i>Clay, w/silt. Trace plasticity. Damp. Abundant chert fragments. Bright orangish-red.</i> | <i>CL</i> |                  |        | <i>110v</i> |               |           |    |   |                          |
| 2            |   |           |                  |        |             |               |           |    |   |                          |
| 3            | <i>0'-28'</i>   |           |                  |        |             |               |           |    |   |                          |
| 4            |   |           |                  |        |             |               |           |    |   |                          |
| 5            | <i>Limestone w/chert fragments</i>  | <i>LS</i> |                  |        |             |               |           |    |   |                          |
| 6            |   |           | <i>28' - 72'</i> |        |             |               |           |    |   |                          |
| 7            | <i>TD = 72' @ 1255</i>  |           |                  |        |             |               |           |    |   |                          |
| 8            |   |           |                  |        |             |               |           |    |   |                          |
| 9            |   |           |                  |        |             |               |           |    |   |                          |
| 10           |   |           |                  |        |             |               |           |    |   |                          |
| 11           |   |           |                  |        |             |               |           |    |   |                          |
| 12           |   |           |                  |        |             |               |           |    |   |                          |
| 14           |   |           |                  |        |             |               |           |    |   |                          |




BZ=Breathing Zone    BH=Bore Hole    S=Sample

# Drilling Log

|                                      |            |                                   |                                    |                                    |                   |
|--------------------------------------|------------|-----------------------------------|------------------------------------|------------------------------------|-------------------|
| Project Name <i>Wm</i>               |            | Project Number <i>DB201045.00</i> |                                    | Boring Number <i>OW-8</i>          |                   |
| Ground Elevation <i>1293.0</i>       |            | Location                          |                                    | Page <i>1</i> of <i>1</i>          |                   |
| Monitoring Equipment                 |            |                                   |                                    | Total Footage <i>74'</i>           |                   |
| Drilling Type                        | Hole Size  | Overburden Footage                | Bedrock Footage                    | No. Of Samples                     | No. Of Core Boxes |
| <i>Air Rotary</i>                    | <i>10"</i> | <i>50'</i>                        | <i>24'</i>                         |                                    |                   |
| Drilling Company <i>Flippin Bros</i> |            |                                   | Driller (s) <i>Marci's Flippin</i> |                                    |                   |
| Drilling Rig <i>Schramm</i>          |            |                                   | Type of Sampler                    |                                    |                   |
| Date <i>2/25/02</i>                  |            | To                                |                                    | Field Observer (s) <i>Mark Orr</i> |                   |

| Depth (feet) | Description   | Class     | Blow Count | Recov. | Run/Time    | Sample Desig. | PID (ppm) |    |   | Remarks/<br>Water Levels |
|--------------|---|-----------|------------|--------|-------------|---------------|-----------|----|---|--------------------------|
|              |   |           |            |        |             |               | BZ        | BH | S |                          |
| 1            | <i>Clay, w/silt. Trace plasticity. Damp. Abundant chert fragments. Bright orangish-red.</i> | <i>CL</i> |            |        | <i>13SD</i> |               |           |    |   |                          |
| 2            |   |           |            |        |             |               |           |    |   |                          |
| 3            |   |           |            |        |             |               |           |    |   |                          |
| 4            |   |           |            |        |             |               |           |    |   |                          |
| 5            | <i>Limestone w/ chert fragments</i>   | <i>LS</i> |            |        |             |               |           |    |   |                          |
| 6            |   |           |            |        |             |               |           |    |   |                          |
| 7            |   |           |            |        |             |               |           |    |   |                          |
| 8            |   |           |            |        |             |               |           |    |   |                          |
| 9            |   |           |            |        |             |               |           |    |   |                          |
| 10           |   |           |            |        |             |               |           |    |   |                          |
| 11           |   |           |            |        |             |               |           |    |   |                          |
| 12           |   |           |            |        |             |               |           |    |   |                          |
| 13           |   |           |            |        |             |               |           |    |   |                          |
| 14           |   |           |            |        |             |               |           |    |   |                          |




BZ=Breathing Zone    BH=Bore Hole    S=Sample



# Drilling Log

|   |                         |                                      |                                      |                                       |                               |
|---|-------------------------|--------------------------------------|--------------------------------------|---------------------------------------|-------------------------------|
| Project Name<br><i>WM</i>               |                         | Project Number<br><i>08201045.00</i> |                                      | Boring Number<br><i>0W-9</i>          |                               |
| Ground Elevation<br><i>1293.9</i>       |                         | Location                             |                                      | Page<br><i>1</i> of <i>1</i>          |                               |
| Monitoring Equipment                    |                         |                                      |                                      | Total Footage<br><i>62'</i>           |                               |
| Drilling Type<br><i>Air Rotary</i>      | Hole Size<br><i>10"</i> | Overburden Footage<br><i>62'</i>     | Bedrock Footage<br><i>—</i>          | No. Of Samples<br><i>—</i>            | No. Of Core Boxes<br><i>—</i> |
| Drilling Company<br><i>Flippin Bros</i> |                         |                                      | Driller (s)<br><i>Maciej Flippin</i> |                                       |                               |
| Drilling Rig<br><i>Schramm</i>          |                         |                                      | Type of Sampler<br><i>—</i>          |                                       |                               |
| Date<br><i>2/25/02</i>                  |                         | To<br><i>2/26/02</i>                 |                                      | Field Observer (s)<br><i>Mark Orr</i> |                               |

| Depth (feet) | Description  | Class     | Blow Count | Recov. | Run/Time | Sample Desig. | PID (ppm) |    |   | Remarks/<br>Water Levels  |
|--------------|--|-----------|------------|--------|----------|---------------|-----------|----|---|---|
|              |  |           |            |        |          |               | BZ        | BH | S |   |
| 1            | <i>Clay, w/silt. Trace plasticity. Damp.<br/>Abundant chert fragments. Bright<br/>orangish-red.</i><br><br><i>0-62'</i><br><br><i>TD=62' @ 0825</i><br><i>No bedrock encountered</i> | <i>CL</i> |            |        |          |               |           |    |   | <br><br><br><i>Lost all circulation @ 62' bgs.<br/>Set well at borehole TD,</i> |
| 2            |  |           |            |        |          |               |           |    |   |   |
| 3            |  |           |            |        |          |               |           |    |   |   |
| 4            |  |           |            |        |          |               |           |    |   |   |
| 5            |  |           |            |        |          |               |           |    |   |   |
| 6            |  |           |            |        |          |               |           |    |   |   |
| 7            |  |           |            |        |          |               |           |    |   |   |
| 8            |  |           |            |        |          |               |           |    |   |   |
| 9            |  |           |            |        |          |               |           |    |   |   |
| 10           |  |           |            |        |          |               |           |    |   |   |
| 11           |  |           |            |        |          |               |           |    |   |   |
| 12           |  |           |            |        |          |               |           |    |   |   |
| 14           |  |           |            |        |          |               |           |    |   |   |



BZ=Breathing Zone    BH=Bore Hole    S=Sample


# Drilling Log

|                                   |  |                                      |  |                               |  |
|-----------------------------------|--|--------------------------------------|--|-------------------------------|--|
| Project Name<br><i>WM</i>         |  | Project Number<br><i>08201045.00</i> |  | Boring Number<br><i>00-10</i> |  |
| Ground Elevation<br><i>1294.6</i> |  | Location                             |  | Page<br><i>1</i> of <i>1</i>  |  |
| Monitoring Equipment              |  |                                      |  | Total Footage<br><i>74'</i>   |  |

| Drilling Type     | Hole Size  | Overburden Footage | Bedrock Footage | No. Of Samples | No. Of Core Boxes |
|-------------------|------------|--------------------|-----------------|----------------|-------------------|
| <i>Air Rotary</i> | <i>10"</i> | <i>74'</i>         |                 |                |                   |

|   |  |                                       |  |
|---|--|---------------------------------------|--|
| Drilling Company<br><i>Flippin Bros</i> |  | Driller (s)<br><i>Marcus Flippin</i>  |  |
| Drilling Rig<br><i>Schramm</i>          |  | Type of Sampler                       |  |
| Date<br><i>2/26/02</i>                  |  | To<br><i>2/27/02</i>                  |  |
|   |  | Field Observer (s)<br><i>Mark Orr</i> |  |

| Depth (feet) | Description   | Class     | Blow Count | Recov. | Run/Time    | Sample Desig. | PID (ppm) |    |   | Remarks/ Water Levels |
|--------------|---|-----------|------------|--------|-------------|---------------|-----------|----|---|-----------------------|
|              |   |           |            |        |             |               | BZ        | BH | S |                       |
| 1            | <i>Clay, w/ silt. Trace plasticity. Damp. Abundant chert fragments. Bright orangish-red.</i><br><br><i>0' - 74'</i><br><br><i>TD = 74' @ 1100</i><br><br><i>No bedrock encountered.</i> | <i>CL</i> |            |        | <i>1105</i> |               |           |    |   |                       |
| 2            |   |           |            |        |             |               |           |    |   |                       |
| 3            |   |           |            |        |             |               |           |    |   |                       |
| 4            |   |           |            |        |             |               |           |    |   |                       |
| 5            |   |           |            |        |             |               |           |    |   |                       |
| 6            |   |           |            |        |             |               |           |    |   |                       |
| 7            |   |           |            |        |             |               |           |    |   |                       |
| 8            |   |           |            |        |             |               |           |    |   |                       |
| 9            |   |           |            |        |             |               |           |    |   |                       |
| 10           |   |           |            |        |             |               |           |    |   |                       |
| 11           |   |           |            |        |             |               |           |    |   |                       |
| 12           |   |           |            |        |             |               |           |    |   |                       |
| 13           |   |           |            |        |             |               |           |    |   |                       |
| 14           |   |           |            |        |             |               |           |    |   |                       |



BZ=Breathing Zone    BH=Bore Hole    S=Sample



**SCS ENGINEERS**

**DRILLING LOG**

|  |                              |                   |                            |
|--|------------------------------|-------------------|----------------------------|
| Boring/Monitoring Well Identification: | OW-19                        | 2 of 2            | Facility: Tontitown LF     |
| Surface Elevation ~                    | 1294                         |                   | Springdale                 |
| Date:                                  | 08/05/03                     | Time: 1300 - 1445 | Project No.: 08203020.00   |
| Sampling Method:                       | Grab from Cuttings           |                   | Driller: Flippin Bros.     |
| Drilling Method:                       | Direct Air w/Downhole Hammer |                   | Geologist: Jerrett Domling |

| Depth In Feet          | Well Construction Detail | Well Construction Materials              | Classification | Rock Formations, Soil, Color and Classifications Observations   |                                     |
|------------------------|--------------------------|--|----------------|---|-------------------------------------|
| Bolt Elevation         |                          |  |                |   |                                     |
| (MSL)                  |                          |  |                |   |                                     |
| TOC Elevation          |                          |  |                | 42'   | Intermittent losses of circulation. |
| (MSL)                  |                          |  |                |   |                                     |
| Ground Water Elevation |                          |  |                |   |                                     |
| (MSL)                  |                          | 51 Sloughed<br>52 Borehole<br>52-53 feet |                | 53' No circulation, drilling suspended.<br>BOH measured at 52' after removal of bit.<br>53' Total depth |                                     |

|   |        |  |  |  |  |  |
|---|--------|--|--|--|--|--|
| OBSERVATIONS<br>WATER (SWL from TOC)<br>Static Water Level Symbol - v | Date:  |  |  |  |  |  |
|   | Level: |  |  |  |  |  |

**SCS ENGINEERS**

**DRILLING LOG**

|  |  |                   |                            |
|--|--|-------------------|----------------------------|
| Boring/Monitoring Well Identification: | OW-20                                  | 1 of 2            | Facility: Tontitown LF     |
| Surface Elevation ~ 1297               |  |                   | Springdale                 |
| Date:                                  | 08/05/03                               | Time: 0815 - 1245 | Project No.: 08203020.00   |
| Sampling Method:                       | Grab from Cuttings                     |                   | Driller: Flippin Bros.     |
| Drilling Method:                       | Direct Air Rotary with Downhole Hammer |                   | Geologist: Jerrett Domling |

| Depth In Feet                               | Well Construction Detail  | Well Construction Materials                                   | Classification | Rock Formations, Soil, Color and Classifications Observations  |
|---|---------------------------|---|----------------|--|
| Bolt Elevation 0                            | Boring: 10"<br>Casing: 4" | +/- 3' Stick-Up<br>0  |                | 0' - 12' Start drilling @ 8:15.<br>Silty clay, moist, chert fragments,<br>2.5 YR 4/6.                        |
| (MSL)<br>TOC<br>Elevation<br>5              |                           | 3/8-inch<br>Chip<br>Bentonite<br>0-20 feet                    |                |  |
| (MSL)<br>Ground<br>Water<br>Elevation<br>10 |                           | 4-inch<br>Schad. 80<br>PVC<br>Solid<br>Riser<br>0-21 feet     |                | 12' Increasing high plastic clay content.  |
| (MSL)<br>20                                 |                           | 20<br>21  |                |  |
| 25  |                           | 3/8-inch<br>Washed<br>Pea<br>Gravel<br>20-46 feet             |                |  |
| 30  |                           | 4-inch<br>Slotted<br>Schad. 80<br>PVC<br>Screen<br>21-46 feet |                | 28' Weathered chert limestone, 2.5 YR 7/4.<br>30' Low cutting return, experiencing problems<br>with fall-in. |
| 35  |                           |   |                | 34' Water added and circulation returns.   |

|   |        |  |  |  |  |  |
|---|--------|--|--|--|--|--|
| OBSERVATIONS<br>WATER (SWL from TOC)<br>Static Water Level Symbol - v | Date:  |  |  |  |  |  |
|   | Level: |  |  |  |  |  |

**SCS ENGINEERS**

**DRILLING LOG**

|  |  |                   |                            |
|--|--|-------------------|----------------------------|
| Boring/Monitoring Well Identification: | OW-20                                  | 2 of 2            | Facility: Tontitown LF     |
| Surface Elevation ~1297                |  |                   | Springdale                 |
| Date:                                  | 08/05/03                               | Time: 0815 - 1245 | Project No.: 08203020.00   |
| Sampling Method:                       | Grab from Cuttings                     |                   | Driller: Flippin Bros.     |
| Drilling Method:                       | Direct Air Rotary with Downhole Hammer |                   | Geologist: Jerrett Domling |

| Depth In Feet                   | Well Construction Detail | Well Construction Materials        | Classification | Rock Formations, Soil, Color and Classifications Observations  |
|---------------------------------|--------------------------|------------------------------------|----------------|--|
| Bolt Elevation<br>(MSL) 40      |                          | 46 Sloughed Borehole<br>46-48 feet |                | 44' Low water/cutting return, increased fracturing of bedrock formation.   |
| TOC Elevation<br>(MSL) 45       |                          |                                    |                | 46' Foam added to increase circulation, drilling suspended at 10:45. Rock pack and bentonite plug placed at 12:45. |
| Ground Water Elevation<br>(MSL) |                          |                                    |                | 48' Total depth  |
|                                 |                          |                                    |                |  |

|   |        |  |  |  |  |  |
|---|--------|--|--|--|--|--|
| OBSERVATIONS<br>WATER (SWL from TOC)<br>Static Water Level Symbol - v | Date:  |  |  |  |  |  |
|   | Level: |  |  |  |  |  |



**SCS ENGINEERS**

**DRILLING LOG**

|  |                              |                          |                         |
|--|------------------------------|--------------------------|-------------------------|
| Boring/Monitoring Well Identification: | OW-21                        | 1 of 2                   | Facility: Tontitown LF  |
| Surface Elevation ~1296                | Springdale                   |                          |                         |
| Date: 07/30/03                         | Time: 0800                   | Project No.: 08203020.00 |                         |
| Sampling Method:                       | Grab from Cuttings           |                          | Driller: Flippin Bros.  |
| Drilling Method:                       | Direct Air w/Downhole Hammer |                          | Geologist: Brett Engard |

| Depth In Feet          | Well Construction Detail | Well Construction Materials         | Classification | Rock Formations, Soil, Color and Classifications Observations   |
|------------------------|--------------------------|-------------------------------------|----------------|---|
| Bolt Elevation         | Boring: 10"              | +/- 3' Stick-Up                     |                | 0'- 28' Silty clay, moist, medium, chert fragments, 2.5 YR 5/8. |
| (MSL)                  | Casing: 4"               | 0                                   |                |   |
| TOC Elevation          |                          | 3/8-inch Chip Bentonite             |                |   |
| (MSL)                  |                          | 0-17 feet                           |                |   |
| Ground Water Elevation |                          | 4-inch Schad. 80 PVC Solid Riser    |                |   |
| (MSL)                  |                          | 0-23 feet                           |                |   |
|                        |                          | 17                                  |                |   |
|                        |                          | 3/8-inch Washed Pea Gravel          |                |   |
|                        |                          | 23 17-43 feet                       |                |   |
|                        |                          | 4-inch Slotted Schad. 80 PVC Screen |                |   |
|                        |                          | 23-43 feet                          |                | 28' Weathered cherty limestone, fossiliferous.                  |


|   |        |  |  |  |  |  |
|---|--------|--|--|--|--|--|
| OBSERVATIONS<br>WATER (SWL from TOC)<br>Static Water Level Symbol - v | Date:  |  |  |  |  |  |
|   | Level: |  |  |  |  |  |



**SCS ENGINEERS**

**DRILLING LOG**

|  |                              |            |                          |
|--|------------------------------|------------|--------------------------|
| Boring/Monitoring Well Identification: | OW-21                        | 2 of 2     | Facility: Tontitown LF   |
| Surface Elevation ~1296                |                              |            | Springdale               |
| Date:                                  | 07/30/03                     | Time: 8:00 | Project No.: 08202035.00 |
| Sampling Method:                       | Grab from Cuttings           |            | Driller: Flippin Bros.   |
| Drilling Method:                       | Direct Air w/Downhole Hammer |            | Geologist: Brett Engard  |

| Depth In Feet          | Well Construction Detail  | Well Construction Materials | Classification | Rock Formations, Soil, Color and Classifications Observations                                 |
|------------------------|---|-----------------------------|----------------|---|
| Bolt Elevation         | 40  |                             |                | Loss of return, added foam to increase circulation, rig down, well set 8/5/03.<br>Total depth |
| (MSL)                  |  |                             |                |   |
| TOC Elevation          |   |                             | 43'            |   |
| (MSL)                  |   |                             |                |   |
| Ground Water Elevation |   |                             |                |   |
| (MSL)                  |   |                             |                |   |

|   |        |  |  |  |  |  |
|---|--------|--|--|--|--|--|
| OBSERVATIONS<br>WATER (SWL from TOC)<br>Static Water Level Symbol - v | Date:  |  |  |  |  |  |
|   | Level: |  |  |  |  |  |